

Scilab Textbook Companion for
Fluid Power Theory & Applications
by J. Sullivan¹

Created by
Kukunuri Venkata Phani Pradeep
Fluid mechanics
Chemical Engineering
IIT Bombay
College Teacher
Parth Goswami
Cross-Checked by
Ganesh R

August 9, 2013

¹Funded by a grant from the National Mission on Education through ICT,
<http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab
codes written in it can be downloaded from the "Textbook Companion Project"
section at the website <http://scilab.in>

Book Description

Title: Fluid Power Theory & Applications

Author: J. Sullivan

Publisher: Reston Publishing Company

Edition: 4

Year: 2007

ISBN: 0137555881

Scilab numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

AP Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

Contents

List of Scilab Codes	4
2 Applying Hydraulic Principles To Single Acting Linear Systems	6
3 Determining the properties of fluids	10
4 applications and testing of seals and packings	15
5 Accounting for the energy in hydraulic systems	17
6 Characteristics of rotary pumps	24
7 Valves in hydraulic transmission control	27
8 Characteristics of Actuators	28
9 Hydraulic system components	34
11 Introduction to Pneumatics	38

List of Scilab Codes

Exa 2.1	chapter 2 example 1	6
Exa 2.2	chapter 2 example 2	6
Exa 2.3	chapter 2 example 3	7
Exa 2.4	chapter 2 example 4	7
Exa 2.5	chapter 2 example 5	8
Exa 2.6	chapter 2 example 6	8
Exa 2.7	chapter 2 example 7	9
Exa 3.1	chapter 3 example 1	10
Exa 3.2	chapter 3 example 2	11
Exa 3.3	chapter 3 example 3	11
Exa 3.4	chapter 3 example 4	12
Exa 3.5	chapter 3 example 5	12
Exa 3.6	chapter 3 example 6	12
Exa 3.7	chapter 3 example 7	13
Exa 3.8	chapter 3 example 8	13
Exa 3.9	chapter 3 example 9	13
Exa 3.11	chapter 3 example 11	14
Exa 4.1	Chapter 4 example 1	15
Exa 4.2	Chapter 4 example 2	15
Exa 4.3	Chapter 4 example 3	16
Exa 5.1	Chapter 5 example 1	17
Exa 5.2	chapter 5 example 2	17
Exa 5.3	chapter 5 example 3	18
Exa 5.4	chapter 5 example 4	18
Exa 5.5	chapter 5 example 5	19
Exa 5.6	chapter 5 example 6	19
Exa 5.7	chapter 5 example 7	20
Exa 5.8	chapter 5 example 8	20

Exa 5.9	chapter 5 example 9	20
Exa 5.10	chapter 5 example 10	21
Exa 5.11	chapter 5 example 11	21
Exa 5.12	chapter 5 example 12	22
Exa 5.13	chapter 5 example 13	22
Exa 6.1	chapter 6 example 1	24
Exa 6.2	chapter 6 example 2	24
Exa 6.3	chapter 6 example 3	25
Exa 6.4	chapter 6 example 4	25
Exa 6.5	chapter 6 example 5	26
Exa 7.1	chapter 7 example1	27
Exa 8.1	chapter 8 example 1	28
Exa 8.2	chapter 8 example 2	28
Exa 8.3	chapter 8 example 3	29
Exa 8.4	chapter 8 example 4	29
Exa 8.5	chapter 8 example 5	30
Exa 8.6	chapter 8 example 6	30
Exa 8.7	chapter 8 example 7	31
Exa 8.8	chapter 8 example 8	31
Exa 8.9	chapter 8 example 9	31
Exa 8.10	chapter 8 example 10	32
Exa 8.11	chapter 8 example 11	32
Exa 8.12	chapter 8 example 12	33
Exa 9.1	chapter 9 example 1	34
Exa 9.2	chapter 9 example 2	34
Exa 9.3	chapter 9 example 3	35
Exa 9.4	chapter 9 example 4	35
Exa 9.5	chapter 9 example 5	36
Exa 9.6	chapter 9 example 6	36
Exa 11.1	chapter 11 example 1	38
Exa 11.2	chapter 11 example 2	38
Exa 11.3	chapter 11 example 3	39
Exa 11.4	chapter 11 example 4	39
Exa 11.5	chapter 11 example 5	40
Exa 11.6	chapter 11 example 6	40
Exa 11.7	chapter 11 example 7	41
Exa 11.8	chapter 11 example 8	41

Chapter 2

Applying Hydraulic Principles To Single Acting Linear Systems

Scilab code Exa 2.1 chapter 2 example 1

```
1 clc
2 //initialisation of variables
3 F= 1500 //lb
4 L= 54 //IN
5 t= 12 //sec
6 //CALCULATIONS
7 hp= F*L/(t*6600)
8 //RESULTS
9 printf ('Horsepower expended at the output = %.2f hp
', hp)
```

Scilab code Exa 2.2 chapter 2 example 2

```
1 clc
```

```
2 //initialisation of variables
3 F= 1500 //lb
4 t1= 10 //sec
5 F1= 1200 //lb
6 //CALCULATIONS
7 t2= F*t1/F1
8 //RESULTS
9 printf ('time required to raise the load = %.1f sec',
, t2)
```

Scilab code Exa 2.3 chapter 2 example 3

```
1 clc
2 //initialisation of variables
3 d= 2 //in
4 F= 1000 //lb
5 t= 10 //sec
6 L= 48 //in
7 S= 24 //in
8 //CALCULATIONS
9 ohp= F*L/(t*6600)
10 Ac= %pi*d^2/4
11 P= ohp*t*6600/(S*Ac)
12 //RESULTS
13 printf ('Pressure within the system = %.f psi ',P)
```

Scilab code Exa 2.4 chapter 2 example 4

```
1 clc
2 //initialisation of variables
3 P= 1000 //psi
4 Q= 3 //gpm
5 //CALCULATIONS
```

```
6 Fhp= P*Q/(1714)
7 //RESULTS
8 printf ('Fluid horsepower = %.2f hp ',Fhp)
```

Scilab code Exa 2.5 chapter 2 example 5

```
1 clc
2 //initialisation of variables
3 Fi= 25 //lb
4 li= 12 //in
5 ni= 30
6 ti= 60 //sec
7 F0= 1000 //lb
8 Lo= 6 //in
9 to= 60 //sec
10 //CALCULATIONS
11 lhp= Fi*li*ni/(ti*6600)
12 Ohp= F0*Lo/(to*6600)
13 eo= Ohp*100/lhp
14 //RESULTS
15 printf ('overall efficiency = %.f percent ',eo)
```

Scilab code Exa 2.6 chapter 2 example 6

```
1 clc
2 //initialisation of variables
3 vp= 0.75 //in^3
4 n= 9 //strokes
5 t= 10 //sec
6 d= 2 //in
7 Sc= 2 //in
8 //CALCULATIONS
9 Qt= vp*n/(t*3.85)
```

```
10 Ac= %pi*d^2/4
11 Qa= Ac*Sc/(t*3.85)
12 s= Qt-Qa
13 s1= (1-(Qa/Qt))*100
14 ev= Qa*100/Qt
15 //RESULTS
16 printf ('Slip = %.3f gpm',s)
17 printf ('\n Slip percentage= %.f percent',s1)
18 printf ('\n volumetric efficiency = %.f perecnt',ev
)
```

Scilab code Exa 2.7 chapter 2 example 7

```
1 clc
2 //initialisation of variables
3 eo= 87
4 em= 94
5 //CALCULATIONS
6 ee= eo*100/em
7 //RESULTS
8 printf ('Electro-mechanical efficiency = %.f percent
',ee)
```

Chapter 3

Determining the properties of fluids

Scilab code Exa 3.1 chapter 3 example 1

```
1  clc
2 //initialisation of variables
3 M= 5 //slug
4 g= 32 //ft/sec^2
5 M1= 10 //kg
6 g1= 9.8 //m/sec^2
7 M2= 15 //gm
8 g2= 980 //cm/sec^2
9 //CALCULATIONS
10 W= M*g
11 W1= M1*g1
12 W2= M2*g2
13 //RESULTS
14 printf ('weight = %.f lb ',w)
15 printf ('\n weight = %.f N ',W1)
16 printf ('\n weight = %.f dyn ',W2)
```

Scilab code Exa 3.2 chapter 3 example 2

```
1 clc
2 //initialisation of variables
3 M= 20 //grams
4 V= 25 //mm^3
5 //CALCULATIONS
6 d= M/V
7 d1= M*0.001/(V*0.000001)
8 d2= M*0.0022/(V*0.00003531)
9 //RESULTS
10 printf ('density = %.2f gm/cm^3 ',d)
11 printf ('\n density = %.f kg/m^3 ',d1)
12 printf ('\n density = %.1f slugs/ft ^3 ',d2)
```

Scilab code Exa 3.3 chapter 3 example 3

```
1 clc
2 //initialisation of variables
3 W= 7200 //lb
4 V= 120 //ft ^3
5 W1= 3600 //lb
6 V1= 50 //m^3
7 W2= 500 //dyn
8 V2= 7000 //cm^3
9 //CALCULATIONS
10 s= W/V
11 s1= W1/V1
12 s2= W2/V2
13 //RESULTS
14 printf ('specific weight = %.f lbs/ft ^3 ',s)
15 printf ('\n specific weight = %.f N/m^3 ',s1)
16 printf ('\n specific weight = %.4f dyn/cm^3 ',s2)
```

Scilab code Exa 3.4 chapter 3 example 4

```
1 clc
2 //initialisation of variables
3 F= 200 //lb
4 A= 4 //in^2
5 //CALCULATIONS
6 P= F/A
7 //RESULTS
8 printf ('Pressure = %.f psi',P)
```

Scilab code Exa 3.5 chapter 3 example 5

```
1 clc
2 //initialisation of variables
3 P= 1500 //psi
4 A= 2 //in^2
5 //CALCULATIONS
6 F= P*A
7 //RESULTS
8 printf ('Force = %.f lb ',F)
```

Scilab code Exa 3.6 chapter 3 example 6

```
1 clc
2 //initialisation of variables
3 s= 0.85
4 h= 50 //ft
5 //CALCULATIONS
```

```
6 P= s*h*0.433
7 //RESULTS
8 printf ('Pressure = %.1f psi ',P)
```

Scilab code Exa 3.7 chapter 3 example 7

```
1 clc
2 //initialisation of variables
3 P= 1500 //psi
4 d= 0.78
5 //CALCULATIONS
6 h= P*2.31/d
7 //RESULTS
8 printf ('head = %.1f ft ',h)
```

Scilab code Exa 3.8 chapter 3 example 8

```
1 clc
2 //initialisation of variables
3 k= 0.1200
4 t= 225 //sec
5 d= 0.82
6 //CALCULATIONS
7 v= t*k
8 u= v*d
9 //RESULTS
10 printf ('kinematic viscosity = %.1f cP ',u)
```

Scilab code Exa 3.9 chapter 3 example 9

```
1 clc
2 //initialisation of variables
3 t= 80 //sec
4 //CALCULATIONS
5 v= 0.226*t-(195/t)
6 v1= 0.00035*t-(0.303/t)
7 //RESULTS
8 printf ('equivalent viscosity = %.2f cst ',v)
9 printf ('\n equivalent viscosity = %.3f newtons ',v1
)
```

Scilab code Exa 3.11 chapter 3 example 11

```
1 clc
2 //initialisation of variables
3 F= 45 //gm
4 L= 20000//gm\
5 r= 7.86
6 s= 1.27
7 //CALCULATIONS
8 CF= (F/L)*(r/s)*2*sqrt(2)
9 //RESULTS
10 printf (' coefficient of friction = %.3f ',CF)
```

Chapter 4

applications and testing of seals and packings

Scilab code Exa 4.1 Chapter 4 example 1

```
1 clc
2 //initialisation of variables
3 d= 4 //in
4 p= 20 //percent
5 d1= 0.140
6 //CALCULATIONS
7 Gd= d-2*((100-20)*d1/100)
8 Gw= d1+2*(p*d1/100)
9 //RESULTS
10 printf ('Groove diameter = %.3f in ',Gd)
11 printf ('\n Groove width = %.3f in ',Gw)
12 printf ('\n outside diameter = %.f in ',d)
```

Scilab code Exa 4.2 Chapter 4 example 2

```
1 clc
```

```
2 // initialisation of variables
3 D= 2 //in
4 S= 10 //in
5 s= 10000 //strokes
6 V= 231 //in^3
7 //CALCULATIONS
8 di= V/(S*s*D*%pi)
9 //RESULTS
10 printf ('thickness = %.7f in ',di)
```

Scilab code Exa 4.3 Chapter 4 example 3

```
1 clc
2 // initialisation of variables
3 d= 0.275 //in
4 p= 15
5 p1= 20
6 p3= 8
7 //CALCULATIONS
8 Fs= (d*p/100)+(d*p1/100)-(d*p3/100)
9 Fs1= Fs*100/d
10 //RESULTS
11 printf ('final available squeeze = %.2f percent ',Fs1)
```

Chapter 5

Accounting for the energy in hydraulic systems

Scilab code Exa 5.1 Chapter 5 example 1

```
1 clc
2 //initialisation of variables
3 Q= 40 //gpm
4 d= 2 //in
5 d1= 4 //in
6 //CALCULATIONS
7 v1= Q*4/(%pi*d^2*3.12)
8 v2= %pi*v1*4/(%pi*d1^2)
9 //RESULTS
10 printf ('velocity of fluid in the conductor = %.2f
           fps ',v1)
11 printf ('\n velocity of fluid in a maniflod = %.2f
           fps ',v2)
```

Scilab code Exa 5.2 chapter 5 example 2

```
1 clc
2 //initialisation of variables
3 Q= 18 //gpm
4 d= 2 //in
5 v2= 10 //fps
6 //CALCULATIONS
7 v1= Q*4/(%pi*d^2*3.12)
8 d2= sqrt(4*Q/(%pi*v2*3.12))
9 //RESULTS
10 printf ('minnimum diameter = %.3f in ',d2)
```

Scilab code Exa 5.3 chapter 5 example 3

```
1 clc
2 //initialisation of variables
3 Q= 10 //gpm
4 d= 1 //in
5 //CALCULATIONS
6 v= Q*4/(%pi*d^2*3.12)
7 //RESULTS
8 printf ('velocity = %.1f fps ',v)
```

Scilab code Exa 5.4 chapter 5 example 4

```
1 clc
2 //initialisation of variables
3 S= 0.91
4 g= 32.2 //ft/sec^2
5 P1= 1000 //psi
6 Q= 500 //gpm
7 d= 3 //in
8 d1= 1 //in
9 //CALCULATIONS
```

```
10 v1= Q*4/(3.12*%pi*d^2)
11 v2= Q*4/(%pi*d1^2*3.12)
12 P2= ((P1*2.31/S)+(v1^2/(2*g))-(v2^2/(2*g)))*(S/2.31)
13 //RESULTS
14 printf ('pressure = %.f psi ',P2-1)
```

Scilab code Exa 5.5 chapter 5 example 5

```
1 clc
2 //initialisation of variables
3 P1= 1000 //psi
4 S= 0.85
5 P2= 350 //psi
6 H1= 679.41 //ft
7 //CALCULATIONS
8 Ha= P1*2.31/S
9 He= Ha-(P2*2.31/S)-H1
10 //RESULTS
11 //RESULTS
12 printf ('energy exctracted from the fluid = %.2f ft ',He)
```

Scilab code Exa 5.6 chapter 5 example 6

```
1 clc
2 //initialisation of variables
3 g= 32 //ft/sec^2
4 h= 40 //ft
5 //CALCULATIONS
6 v= sqrt(2*g*h)
7 //RESULTS
8 printf ('velocity of the fluid = %.1f fps ',v)
```

Scilab code Exa 5.7 chapter 5 example 7

```
1 clc
2 //initialisation of variables
3 Q= 1000 //gpm
4 d= 2 //in
5 S= 0.85
6 dp= 120 //psi
7 //CALCULATIONS
8 Cf= (1/38.06)*(Q*4/(%pi*d^2))*sqrt(S/dp)
9 //RESULTS
10 printf ('friction coefficient for the orifice = %.2f
', Cf)
```

Scilab code Exa 5.8 chapter 5 example 8

```
1 clc
2 //initialisation of variables
3 Q= 100 //gpm
4 d= 1 //in
5 kv= 0.05 //N
6 //CALCULATIONS
7 v= Q*4/(3.12*%pi*d^2)
8 Nr= (12*v*d)/kv
9 //RESULTS
10 printf ('Reynolds number = %.f ', Nr+5)
```

Scilab code Exa 5.9 chapter 5 example 9

```
1 clc
2 //initialisation of variables
3 v= 27 //cp
4 s= 0.85
5 d= 1 //in
6 //CALCULATIONS
7 V= v/s
8 V1= V*0.001552
9 V2= 2000*V1/(12*d)
10 V3= 4000*V1/(12*d)
11 //RESULTS
12 printf ('Critical velocity = %.2f fps ',V3)
```

Scilab code Exa 5.10 chapter 5 example 10

```
1 clc
2 //initialisation of variables
3 Q= 200 //gpm
4 d= 2 //in
5 S= 0.91
6 f= 0.05
7 L= 800 //ft
8 g= 32.2 //ft/sec^2
9 //CALCULATIONS
10 v= Q*4/(%pi*3.12*d^2)
11 h= 2.598*S*f*L*v^2/(2*g)
12 //RESULTS
13 printf ('Pressure drop = %.f psi ',h)
```

Scilab code Exa 5.11 chapter 5 example 11

```
1 clc
2 //initialisation of variables
```

```
3 Q= 15 //gpm
4 d= 1 //in
5 s= 0.85
6 v= 0.08 //N
7 L= 400 //ft
8 //CALCULATIONS
9 V= Q*4/(%pi*d^2*3.12)
10 Nr= 12*V*2*d/v
11 h= .43*s*v*L*V/d^2
12 //RESULTS
13 printf ('Pressure drop = %.2f psi ',h)
```

Scilab code Exa 5.12 chapter 5 example 12

```
1 clc
2 //initialisation of variables
3 Q= 1000 //gpm
4 d= 2 //in
5 V= 0.30 //N
6 L= 500 //ft
7 f= 0.034
8 S= 0.85
9 g= 32.2 //ft/sec^2
10 //CALCULATIONS
11 v= Q*4/(%pi*3.12*d^2)
12 Nr= (12*v*d)/V
13 h= 2.598*S*f*L*v^2/(2*g)
14 //RESULTS
15 printf ('Pressure drop = %.f psi ',h+5)
```

Scilab code Exa 5.13 chapter 5 example 13

```
1 clc
```

```
2 // initialisation of variables
3 Q= 500 //gpm
4 d= 2 //in
5 S= 0.91
6 kv= 0.25 //N
7 r= 0.0012
8 K= 3
9 f= 0.04
10 //CALCULATIONS
11 v= Q*4/(%pi*d^2*3.12)
12 Nr= (v*d*12)/kv
13 Rr= 12*r/d
14 Le= K*d/(f*12)
15 //RESULTS
16 printf ('equivalent length = %.1f ft ',Le)
```

Chapter 6

Characteristics of rotary pumps

Scilab code Exa 6.1 chapter 6 example 1

```
1 clc
2 //initialisation of variables
3 P= 2500 //psi
4 Q= 3 //gpm
5 p= 5 //Bhp
6 N= 1725 //rpm
7 //CALCULATIONS
8 eo= P*Q*100/(1714*p)
9 To= p*5250/N
10 //RESULTS
11 printf ('input torque = %.2f lb-ft ',To)
```

Scilab code Exa 6.2 chapter 6 example 2

```
1 clc
2 //initialisation of variables
3 Q= 52 //gpm
4 v= 3.75 //in^3
```

```
5 N= 3300 //rpm
6 //CALCULATIONS
7 ev= 231*Q*100/(v*N)
8 //RESULTS
9 printf ('volumetric efficiency = %.2f percent ',ev)
```

Scilab code Exa 6.3 chapter 6 example 3

```
1 clc
2 //initialisation of variables
3 eo= 87 //percent
4 ev= 94 //percent
5 p= 10 //bhpi
6 //CALCULATIONS
7 em= eo/ev
8 em1= em*100
9 Fhp= p*(1-em)
10 //RESULTS
11 printf ('frictional horsepower = %.1f hp ',Fhp+0.1)
12 printf ('\n mechanical efficiency = %.2f percent ',em1)
```

Scilab code Exa 6.4 chapter 6 example 4

```
1 clc
2 //initialisation of variables
3 n= 9
4 N= 3000 //rpm
5 s= 0.75 //inch
6 d= 0.5 //inch
7 //CALCULATIONS
8 Q= n*N*s*%pi*d^2/(4*231)
9 //RESULTS
```

```
10 printf ('volume flow rate = %.1f gpm' ,Q)
```

Scilab code Exa 6.5 chapter 6 example 5

```
1 clc
2 //initialisation of variables
3 d= 6 //in
4 N= 120 //in
5 Q= 5 //gpm
6 //CALCULATIONS
7 Vc= %pi*d^2*N/(4*231)
8 //RESULTS
9 printf ('minimum size of the reservoir = %.2f gpm' ,
Vc)
```

Chapter 7

Valves in hydraulic transmission control

Scilab code Exa 7.1 chapter 7 example1

```
1 clc
2 //initialisation of variables
3 Q= 30 //gpm
4 dp= 300 //psi
5 S= .85
6 Cv= 5.41 //
7 //CALCULATIONS
8 Cv1= Q/(sqrt(dp/S))
9 dp1= S*Q^2/Cv^2
10 //RESULTS
11 printf ('flow coefficient = %.3f gpm',Cv1)
12 printf ('\n pressure drop = %.f psi ',dp1)
```

Chapter 8

Characteristics of Actuators

Scilab code Exa 8.1 chapter 8 example 1

```
1 clc
2 //initialisation of variables
3 F= 80000 //lbs
4 P= 1600 //psi
5 //CALCULATIONS
6 db= sqrt(4*F/(%pi*P))
7 //RESULTS
8 printf ('size of the cylinder postion = %.f in ',db)
```

Scilab code Exa 8.2 chapter 8 example 2

```
1 clc
2 //Initialization ogf variables
3 Q=25 //gpm
4 A=.533 //in^2
5 //Calculations
6 nu=Q*19.25/(A*60) //Fluid velocity
7 nucylinder=Q*19.25/12.56 //Cylinder velocity
```

```
8 //Results
9 printf ('Fluid velocity = %.2f',nu)
10 printf ('\n Cylinder velocity = %.2f',nucylinder)
```

Scilab code Exa 8.3 chapter 8 example 3

```
1 clc
2 //initialisation of variables
3 d= 3 //in
4 P= 2000 //psi
5 s= 20 //strokes
6 //CALCULATIONS
7 C1= s*d/2
8 F= P*%pi*d^2/4
9 st1= (C1-40)/10
10 //RESULTS
11 printf ('length of the stop tube= %.f in ',C1)
12 printf ('\n thrust on the rod= %.f lb ',F+3)
13 printf ('\n Stop Tube length= %.f st1 ',st1)
```

Scilab code Exa 8.4 chapter 8 example 4

```
1 clc
2 //initialisation of variables
3 v= 120 //ft/min
4 S= 1.5 //in
5 w= 8000 //lb
6 //CALCULATIONS
7 ga= v^2*0.0000517/S
8 F= w*ga
9 //RESULTS
10 printf ('total force decessary to decelarate the
load= %.f lb ',F-3)
```

Scilab code Exa 8.5 chapter 8 example 5

```
1 clc
2 //initialisation of variables
3 P= 750 //psi
4 d= 3 //in
5 w= 1500 //lb
6 ga= 0.172
7 f= 0.12
8 v= 50 //ft/min
9 s= 0.75 //in
10 //CALCULATIONS
11 Fa= P*%pi*d^2/4
12 F= w*(ga-f)+Fa
13 //RESULTS
14 printf ('total force decessary to decelarate the
load= %.f lb ',F-2)
```

Scilab code Exa 8.6 chapter 8 example 6

```
1 clc
2 //initialisation of variables
3 d= 3 //in
4 d1= 1.5 //in
5 F= 7500 //lb
6 //CALCULATIONS
7 A1= (%pi/4)*(d^2-d1^2)
8 P= F/A1
9 //RESULTS
10 printf ('pressure in the cylinder = %.f psi ',P-1)
```

Scilab code Exa 8.7 chapter 8 example 7

```
1 clc
2 //initialisation of variables
3 P= 2000 //psi
4 Vm= 0.5 //in^3
5 //CALCULATIONS
6 T= P*Vm*0.16
7 //RESULTS
8 printf ('Theotrical torque = %.f lb-in ',T)
```

Scilab code Exa 8.8 chapter 8 example 8

```
1 clc
2 //initialisation of variables
3 Q= 7.5 //gpm
4 Vm= 2 //in^3
5 //CALCULATIONS
6 N= 231*Q/Vm
7 //RESULTS
8 printf ('Theotrical speed of fluid power = %.f rpm ',N)
```

Scilab code Exa 8.9 chapter 8 example 9

```
1 clc
2 //initialisation of variables
3 Vm= 0.55 //in^3
4 N= 3400 //rpm
```

```
5 //CALCULATIONS
6 Q= Vm*N/231
7 //RESULTS
8 printf ('effective flow rate = %.2f gpm',Q)
```

Scilab code Exa 8.10 chapter 8 example 10

```
1 clc
2 //initialisation of variables
3 T= 32 //lb-ft
4 N= 1200 //rpm
5 P= 2000 //psi
6 Q= 7.5 //gpm
7 //CALCULATIONS
8 eo= T*N*100/(P*Q*3.06)
9 //RESULTS
10 printf ('overall efficiency = %.f percent',eo)
```

Scilab code Exa 8.11 chapter 8 example 11

```
1 clc
2 //initialisation of variables
3 Vm= 0.6 //in^3
4 N= 2400 //rpm
5 Qa= 6.5 //gpm
6 p= 50
7 //CALCULATIONS
8 ev= Vm*N*100/(Qa*231)
9 Tf= (100-ev)*Qa/100
10 C1= p*Tf/100
11 //RESULTS
12 printf ('Case drain loss = %.3f gpm',C1)
```

Scilab code Exa 8.12 chapter 8 example 12

```
1 clc
2 //initialisation of variables
3 eo= 88 //percent
4 ev= 97 //percent
5 //CALCULATIONS
6 em= eo*100/ev
7 //RESULTS
8 printf ('mechanical efficiency = %.2f percent ',em)
```

Chapter 9

Hydraulic system components

Scilab code Exa 9.1 chapter 9 example 1

```
1 clc
2 //initialisation of variables
3 t= 4 //hr
4 Ihp= 8 //ihp
5 Ohp= 5 //hp
6 //CALCULATIONS
7 Hl= t*2544*(Ihp-Ohp)
8 //RESULTS
9 printf ('total Btu heat loss over a period of 4hr =
% .f Btu ',Hl)
```

Scilab code Exa 9.2 chapter 9 example 2

```
1 clc
2 //initialisation of variables
3 t= 1 //sec
4 P= 1000 //psi
5 Q= 3 //gpm
```

```
6 Sg= 0.85
7 s= 0.42
8 //CALCULATIONS
9 H1= 2544*t*P*Q/1714
10 Wf= 62.4*Q*60*Sg
11 Tr= H1/(Wf*s)
12 //RESULTS
13 printf ('rise in temperature of the fluid = %.2f F', Tr)
```

Scilab code Exa 9.3 chapter 9 example 3

```
1 clc
2 //initialisation of variables
3 P= 1500 //psi
4 d= 12 //in
5 V= 50 //gal
6 //CALCULATIONS
7 F= P*(%pi*d^2/4)
8 S= V*231*4/(%pi*d^2)
9 //RESULTS
10 printf ('Weight = %.f lb ',F)
11 printf ('Stroke length = %.1f in ',S)
```

Scilab code Exa 9.4 chapter 9 example 4

```
1 clc
2 //initialisation of variables
3 P= 1500 //psig
4 V= 5 //gal
5 P1= 3000 //psig
6 P2= 2000 //psig
7 //CALCULATIONS
```

```
8 V2= V*231*(P2+14.7)/(P1-P2)
9 V1= V2*(P1+14.7)/((P+14.7)*231)
10 //RESULTS
11 printf ('Size of accumulator = %.2f gal ',V1)
```

Scilab code Exa 9.5 chapter 9 example 5

```
1 clc
2 //Initialization of variables
3 beta=1.4
4 p3=2000+14.7 //non guage
5 p2=3000+14.7 //non guage
6 p1=1500+14.7 //non guage
7 deltav=1155
8 //Calculations
9 v2=(p3/p2)^(1/beta)*(deltav)/(1-(p3/p2)^(1/beta))
10 v1=v2*(p2/p1)^(1/beta)
11 perdiff=(v1-4627.25)*100/v1
12 //Results
13 printf('volume 2 = %.1f ',v2)
14 printf('\n volume 1 = %.1f ',v1)
15 printf('\n percentage difference in volume = %.2f ',
perdiff)
```

Scilab code Exa 9.6 chapter 9 example 6

```
1 clc
2 //initialisation of variables
3 Fr= 20 //gpm
4 P= 2500 //psi
5 sf= 4
6 Ts= 55000 //psi
7 V= 15 //fps
```

```
8 //CALCULATIONS
9 A= Fr*0.3208/V
10 ID= 2*sqrt(A/%pi)
11 Wt= P*ID/(2*(Ts-P))
12 Wt1= Wt*sf
13 //RESULTS
14 printf ('Wall thickness = %.3f in ',Wt1)
```

Chapter 11

Introduction to Pneumatics

Scilab code Exa 11.1 chapter 11 example 1

```
1 clc
2 //initialisation of variables
3 V1= 20 //gal
4 P1= 20 //psi
5 n= 2
6 //CALCULATIONS
7 V2= V1/n
8 P2= (P1+14.7)*V1*231/(V2*231)
9 P3= P2-14.7
10 //RESULTS
11 printf ('Guage pressure = %.1f psi ',P3)
```

Scilab code Exa 11.2 chapter 11 example 2

```
1 clc
2 //initialisation of variables
3 V1= 1500 //in^3
4 T= 80 //F
```

```
5 T1= 200 //F
6 //CALCULATIONS
7 V2= V1*(460+T1)/(T+460)
8 //RESULTS
9 printf ('volume the heated gas will occupy = %.1f in
^3 ',V2)
```

Scilab code Exa 11.3 chapter 11 example 3

```
1 clc
2 //initialisation of variables
3 P1= 2000 //in^3
4 T= 80 //F
5 T1= 250 //F
6 //CALCULATIONS
7 P2= (P1+14.7)*(460+T1)/(T+460)
8 P3= P2-14.7
9 //RESULTS
10 printf ('guage pressure = %.f psi ',P3)
```

Scilab code Exa 11.4 chapter 11 example 4

```
1 clc
2 //initialisation of variables
3 P1= 2000//psi
4 V1= 1500 //in^3
5 T2= 250 //F
6 T1= 75 //F
7 V2= 1000 //in^3
8 //CALCULATIONS
9 P2= (P1+14.7)*V1*(T2+460)/((T1+460)*V2)
10 P3= P2-14.7
11 //RESULTS
```

```
12 printf ('guage pressure = %.f psi ',P3)
```

Scilab code Exa 11.5 chapter 11 example 5

```
1 clc
2 //initialisation of variables
3 s= 10 //stroke
4 d= 2 //in
5 r= 40 //cpm
6 P1= 80 //psi
7 //CALCULATIONS
8 V1= %pi*d^2*s*r/(4*1728)
9 V2= (P1+14.7)*V1/14.7
10 //RESULTS
11 printf ('air consumption in cfm of free air = %.2f
           cfm free air ',V2)
```

Scilab code Exa 11.6 chapter 11 example 6

```
1 clc
2 //initialisation of variables
3 V= 650 //cfm
4 Cr= 250 //psi
5 d= 2 //in
6 L= 500 //ft
7 //CALCULATIONS
8 CR= (Cr+14.7)/14.7
9 pf= 0.1025*L*(V/60)^2/(CR*d^(5.31))
10 //RESULTS
11 printf ('Pressure drop = %.f psi ',pf-1)
```

Scilab code Exa 11.7 chapter 11 example 7

```
1 clc
2 //initialisation of variables
3 d= 1 //in
4 P= 100 //psi
5 C= 1
6 T= 70 //F
7 s= 0.07494 //lb/ft ^3
8 //CALCULATIONS
9 Qw= (0.5303*pi*d^2*(P+14.7))/(4*sqrt(T+460))
10 Qv= Qw*60/s
11 //RESULTS
12 printf ('Amount of air passing thorugh orifice = %.1
f cfm ',Qv)
```

Scilab code Exa 11.8 chapter 11 example 8

```
1 clc
2 //initialisation of variables
3 t= 5 //min
4 qr= 10 //cfm
5 P1= 125 //psi
6 P2= 100 //psi
7 //CALCULATIONS
8 Vr= qr*t*14.7/(P1-P2)
9 //RESULTS
10 printf ('Size of reservoir = %.1f ft ^3 ',Vr)
```
