Scilab Textbook Companion for Electrical Engineering Materials by R. K. Shukla and A. Singh[1]

Created by
Chanagam Saikomal
B.tech
Electronics Engineering
SASTRA UNIVERSITY
College Teacher
NA
Cross-Checked by
Spandana

April 21, 2015

[1]Funded by a grant from the National Mission on Education through ICT, http://spoken-tutorial.org/NMEICT-Intro. This Textbook Companion and Scilab codes written in it can be downloaded from the "Textbook Companion Project" section at the website http://scilab.in

Book Description

Title: Electrical Engineering Materials

Author: R. K. Shukla and A. Singh

Publisher: Tata McGraw-Hill, New Delhi

Edition: 1

Year: 2012

ISBN: 9781259029745

Scilab numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

AP Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

Contents

List of Scilab Codes 4

1 Crystal structure Bonding and Defects in solids 9

2 Band Theory of Solids 25

3 Magnetic properties of Materials 31

4 Behaviour of Dielectric Materials in ac and dc fields 49

5 Conductivity of metals and superconductivity 66

6 Electrical Conducting and Insulating materials 103

7 Junction Resistor Transistors and Devices 121

8 Mechanism of Conduction in Semiconductors 136

9 Mechanical Properties of Materials 156

10 Mechanical Properties of Materials 160

List of Scilab Codes

Exa 1.1 To find lattice constant 9
Exa 1.2 To find interplanar distances 10
Exa 1.3 To find miller indices 11
Exa 1.4 To find miller indices 12
Exa 1.5 To find miller indices 13
Exa 1.6 To find miller indices 14
Exa 1.8 To find interplanar distance 16
Exa 1.9 To find interplanar spacing 17
Exa 1.10 To find distance between atoms 18
Exa 1.11 To find wavelength 18
Exa 1.12 To find spacing between planes 19
Exa 1.13 To find lattice constant 20
Exa 1.14 To find angle 21
Exa 1.15 To find wavelength 22
Exa 1.16 To find lattice parameters 23
Exa 2.1 To find three lowest permissible quantum energies . . 25
Exa 2.2 To find energy differences between two states 26
Exa 2.3 comment on first three energy levels of an electron . . 27
Exa 2.4 To find lowest allowed energy bandwidth 28
Exa 2.5 T find energy of free electron for first Brillouin Zone . 29
Exa 3.1 To find magnetic moment and bohr magneton 31
Exa 3.2 To find the magnetic moment of the rod 32
Exa 3.3 To find the magnetic moment of the rod 33
Exa 3.4 To find change in magnetic moment 33
Exa 3.6 To find temperate must the substance cooled 34
Exa 3.7 To find magnetisation vector and flux density 35
Exa 3.8 To find increase in percentage 35
Exa 3.9 To find magnetisation vector and flux density 36

Exa 3.10	To find permeability and relative permeability	37
Exa 3.11	To find absolute and relative permeability	38
Exa 3.12	To find relative permeability and magnetic susceptibility	38
Exa 3.13	To find diamagnetic susceptability of He	39
Exa 3.14	To find permiability and susceptibility	40
Exa 3.15	To find susceptability	41
Exa 3.16	To find number ampere turns	43
Exa 3.17	To find current to be sent into solenoid	44
Exa 3.18	To find number of turns	44
Exa 3.19	To find permeability and susceptibility	45
Exa 3.20	To find loss of energy per hour	46
Exa 3.21	To find hysteresis loss per cycle	47
Exa 4.1	To find dielectric constant of argon at NTP	49
Exa 4.2	To estimate the shift of the electron cloud	50
Exa 4.3	To find local field acting on a given molecule	51
Exa 4.4	To find polarisabilities of benzene and water	52
Exa 4.5	To find polarisation of plates	53
Exa 4.6	To find percentage contribution of ionic polarisability	54
Exa 4.7	To find separation between positive and negative charges	55
Exa 4.8	To find orientational polarisation at room temperature	56
Exa 4.9	To find relative dielectric constant	57
Exa 4.10	To find ratio between electronic and ionic polarisability	58
Exa 4.11	To find dielectric constant and electrical susceptibility	59
Exa 4.12	To find the polarisation	60
Exa 4.13	To find dielectric susceptibility	61
Exa 4.14	To find free charge and polarisation and displacement	62
Exa 4.15	To find capacitance and charge stored and displacement vector and polarisation vector	63
Exa 4.16	To find phase difference	64
Exa 5.1	To find average drift velocity of free electron	66
Exa 5.2	To find drift velocity	67
Exa 5.3	To find current density and drift velocity of electrons	68
Exa 5.4	To find resistivity of the material	69
Exa 5.5	To find mobility and relaxation time of electrons	70
Exa 5.6	To find mobility of conduction electrons	71
Exa 5.7	To find relaxation time	72
Exa 5.9	To find thermal conductivity for a metal	73
Exa 5.10	To find energy difference between two states	74

Exa 5.11 To find fermi energy 75
Exa 5.12 To find fermi energy 76
Exa 5.13 To find fermi energy 77
Exa 5.14 To find number of electrons 78
Exa 5.15 To find electron density 79
Exa 5.16 To find average energy and temperature 80
Exa 5.17 To find average energy and speed of electron 81
Exa 5.18 To find average energy and speed of electron 82
Exa 5.19 To find fermi energy and fermi velocity 83
Exa 5.20 To find efficiency of transmission and percentage voltage drop 84
Exa 5.21 To find value of constants 85
Exa 5.23 To find neutral temperature and temperature of inversion 86
Exa 5.24 To find resistivity of an alloy 87
Exa 5.25 To find transition temperature 88
Exa 5.26 To find critical temperature 89
Exa 5.27 To find critical temperature 90
Exa 5.28 To find critical magnetic field 91
Exa 5.29 To find critical current density 92
Exa 5.30 To find transition temperature 93
Exa 5.31 To find transition temperature 93
Exa 5.32 To find transition temperature 94
Exa 5.33 To find critical current 95
Exa 5.34 To find current 96
Exa 5.35 To find Londons penetration depth 97
Exa 5.36 To find penetration depth 98
Exa 5.37 To find critical temperature of aluminium 99
Exa 5.38 To find wavelength 100
Exa 5.39 To find energy gap and wavelength 101
Exa 6.1 To find temperature coefficient of resistance 103
Exa 6.2 To find temperature 104
Exa 6.3 Tofind cold resistance and average temperature coefficient 105
Exa 6.4 To find resistivity 106
Exa 6.5 To find percentage conductivity 107
Exa 6.10 To find resistance 108
Exa 6.11 To find resistivity 109
Exa 6.12 To find insulation resistance 110

Exa 6.13 To find capacitance 111
Exa 6.14 To find charge and electric flux and flux density and electric field strength 112
Exa 6.15 To find capacitance 113
Exa 6.16 To find thickness of insulation 114
Exa 6.17 To find area and breakdown voltage 115
Exa 6.18 To find dielectric loss 116
Exa 6.19 To find area 117
Exa 6.20 To find thermal cnductivity 118
Exa 7.2 To find change in temperature 121
Exa 7.3 To find current 122
Exa 7.4 To find diffusion coefficients 123
Exa 7.6 To find resistance of diode 124
Exa 7.7 To find diffusion constant 125
Exa 7.8 To find pinch off voltage 126
Exa 7.9 To find pinch off voltage 127
Exa 7.10 To find transconductance 128
Exa 7.11 To find drain current 129
Exa 7.12 To find transconductance 129
Exa 7.13 To find resistance 130
Exa 7.14 To find transconductance 131
Exa 7.15 To find drain resistance and transconductance and amplification fector 132
Exa 7.16 To find transconductance 134
Exa 8.1 To find kinetic energy and momenta 136
Exa 8.2 To find thermal equilibrium hole concentration 137
Exa 8.3 To find intrinsic carrier concentration 138
Exa 8.4 To find position of intrinsic fermi level 139
Exa 8.5 To find donor binding energy 140
Exa 8.6 To find position of fermi level 141
Exa 8.7 To find electrical conductivity 142
Exa 8.8 To find resistivity 143
Exa 8.9 To find intrinsic carrier density 144
Exa 8.10 To find conductivity 145
Exa 8.11 To find carrier density 146
Exa 8.12 To find drift velocity 147
Exa 8.13 To know about changes in temperature 148
Exa 8.14 To find conductivity 149

Exa 8.15	To find diffusion current density	150
Exa 8.16	To find wavelength	151
Exa 8.17	To find cut off wavelength	151
Exa 8.18	To find energy	152
Exa 8.19	To find hall voltage	153
Exa 8.20	To find current density	154
Exa 8.21	To find hall coefficient	155
Exa 9.1	To find elongation	156
Exa 9.3	To find stress	157
Exa 9.4	To find strain	158
Exa 9.5	To find ductility	158
Exa 10.1	To find wavelength	160
Exa 10.2	To find maximum wavelength of opaque	161
Exa 10.3	To find composition	162
Exa 10.4	To find energy of metastable state	163
Exa 10.5	To find number of optical modes	164
Exa 10.6	To find numerical aperture	165
Exa 10.7	To find critical angle	166

Chapter 1

Crystal structure Bonding and Defects in solids

Scilab code Exa 1.1 To find lattice constant

```

//
================================================================================
// chapter 1 example 1

clc;
clear;

// input data
// FCC structured crystal

 p        = 6250;             // Density of crystal
    in kg/m^3
 N        = 6.023*10^26;      // Avagadros number in
    atoms/kilomole
 M        = 60.2;             // molecular weight per
     mole
 n        = 4;                // No. of atoms per
```

```
    unit cell for FCC

//Calculations

 a        = ((n*M)/(N*p))^(1/3);          //Lattice
    Constant

//Output

mprintf('Lattice Constant a = %3.2f.   ',a/10^-10);
//
  ==========================================================================
```

Scilab code Exa 1.2 To find interplanar distances

```

//
  ==========================================================================

// chapter 1 example 2
clc;
clear;

//input data
h1        = 1;              // miller indice
k1        = 1;              // miller indice
l1        = 1;              // miller indice
h0        = 0;              // miller indice
k0        = 0;              // miller indice
l0        = 0;              // miller indice
p        = 1980;                // Density of KCl in kg/
  m^3
N        = 6.023*10^26;        // Avagadros number in
   atoms/kilomole
```

```
M        = 74.5;                // molecular weight of
    KCl
n        = 4;                   // No. of atoms per unit
     cell for FCC

// calculations
a        = ((n*M)/(N*p))^(1/3);

// dhkl     = a/sqrt((h^2)+(k^2)+(l^2)); //
    interplanar distance
d100     = a/sqrt((h1^2)+(k0^2)+(l0^2)); //
    interplanar distance
d110     = a/sqrt((h1^2)+(k1^2)+(l0^2)); //
    interplanar distance
d111     = a/sqrt((h1^2)+(k1^2)+(l1^2)); //
    interplanar distance

// Output
mprintf('d100 = %3.2f   \n d110 = %3.2f   \n d111 =
    %3.2f   ',d100*10^10,d110*10^10,d111*10^10);

//
    ================================================================
```

Scilab code Exa 1.3 To find miller indices

```
//
    ================================================================
// chapter 1 example 3


clc;
clear;
```

```

// Variable Declaration
 h          = 4;                    //miller indices
 k          = 1;                    //miller indices
 l          = 2;                    //miller indices

 //result

v= int32([h k l]);
lc=double(lcm(v));
 //calculation
 h1 =1/h;
 k1 =1/k;
 l1 =1/l;
 a = h1*lc;
 b = k1*lc;
 c = l1*lc;
 //result
 mprintf('miller indices = %d %d %d',a,b,c);

 //
    ==================================================================
```

Scilab code Exa 1.4 To find miller indices

```
// chapter 1 example 4


clc;
clear;

//intercepts given are 3a,4b,2c
//from the law of rational indices
//3a:4b:2c=a/h:b/k:c/l
```

```

// Variable Declaration
 h1          = 3;                //miller indices
 k1          = 4;                //miller indices
 l1          = 2;                //miller indices

 //calculation
v= int32([h1 k1 l1]);
lc=int32(lcm(v));
h = lc*1/h1;
k = lc*1/k1;
l= lc*1/l1;

 //result
 mprintf('miller indices = %d %d %d',h,k,l);
```

Scilab code Exa 1.5 To find miller indices

```
//
//chapter 1 example 5

clc;
clear all;

//intercepts given are a,2b,-3c/2
//from the law of rational indices
//a:2b:-3c/2=a/h:b/k:c/l


//variable declaration
h1 = 1;                //miller indices
k1 = 1/2;                //miller indices
l1 = -2/3;                //miller indices
```

```

//calculation
p = int32([1,2,3]);
l2 = lcm(p);
h=h1*l2;
k=(k1)*double(l2);
l=(l1)*double(l2);

//result
mprintf('miller indices = %d %d %d',h,k,l);

//
    ==============================================================================
```

Scilab code Exa 1.6 To find miller indices

```
//
    ==============================================================================
//chapter 1 example 6

clc;
clear all;

//intercepts given are 3a,3b,2c
//from the law of rational indices
//3a:3b:2c=a/h:b/k:c/l
//variable declaration

h1 = 1/4;                    //miller indices
k1 = 1/4;                    //miller indices
l1 = 1/2;                    //miller indices
h12 = 1/2;                         //miller indices
k12 = 1;                         //miller indices
```

```
l12 = 1/%inf;                    //miller indices
h13 = 1;
k13 = 2;
l13 = 1;


//calculation
p = int32([4,4,2]);
l2 = lcm(p);
h=h1*double(l2);
k=(k1)*double(l2);
l=(l1)*double(l2);

p1 = int32([2,1,1]);

// 1/%inf = 0  ; (1/2 1/1 0/1) hence lcm is taken for [2 1 1]

l22 = lcm(p1);
h3=h12*double(l22);
k3=(k12)*double(l22);
l3=(l12)*double(l22);

p3 = int32([1,1,1]);
l23 = lcm(p3);
h4=h13*double(l23);
k4=(k13)*double(l23);
l4=(l13)*double(l23);



//result
mprintf('miller indices = %d %d %d\n',h,k,l);
mprintf('Note:printing mistake of miller indices in textbook \n');
mprintf('\nmiller indices = %d %d %d\n',h3,k3,l3);
mprintf('\nmiller indices = %d %d %d\n',h4,k4,l4);
mprintf('Note:calculation mistake in textbook\n');
```

```


//
```

Scilab code Exa 1.8 To find interplanar distance

```
//

//chapter 1 example 8

clc;
clear all;

//intercepts given are a,2b,-3c/2
//from the law of rational indices
//a:2b:-3c/2=a/h:b/k:c/l


//variable declaration
h12 = 1;                //miller indices
k12 = 1/2;                //miller indices
l12 = 1/%inf;                //miller indices
a = 10*10^-9;
//calculation

p1 = int32([2,1,1]);
// 1/%inf = 0  ; (1/2 1/1 0/1) hence lcm is taken
   for [2 1 1]

l22 = lcm(p1);
h=h12*double(l22);
k=(k12)*double(l22);
```

```
l=(l12)*double(l22);
d=a/double(((h^2)+(k^2)+(l^2))^(1/2));


//result
mprintf('miller indices = %d %d %d',h,k,l);
mprintf('interplanar distance is =%e   ',d);
//
```

Scilab code Exa 1.9 To find interplanar spacing

```
//

// chapter 1 example 9


clc;
clear;

// Variable Declaration

r       = 0.175*10^-9;                  //radius in m
h       = 2;                            //miller indices
k       = 3;                            //miller indices
l       = 1;                            //miller indices

//calculation
 a      = (4*r)/sqrt(2);
 dhkl   = a/sqrt((h^2)+(k^2)+(l^2));

 //result
  mprintf('inter planar spacing =%3.2e m\n',dhkl);
```

```
mprintf('Note : calculation mistake in textbook in calculating dhkl value ');

//
```

Scilab code Exa 1.10 To find distance between atoms

```
//

// chapter 1 example 10

clc;
clear;

//input data
a        = 4;                //lattice constant in

//calculation
d        = (sqrt(3)*a)/4;

//result
mprintf('distance between two atoms =%3.3f.  \n',d);

//
```

Scilab code Exa 1.11 To find wavelength

```
//
=====================================================================
// chapter 1 example 11
clc;
clear;

//input data

 d     = 1.41;           //lattice constant in
 theta  = 8.8;           // angle in degrees
 n      = 1;

//calculation

 lamda  = (2*d*sin(theta*%pi/180))/n;


//result
mprintf('wavelength=%3.2f   \n',lamda);

//
=====================================================================
```

Scilab code Exa 1.12 To find spacing between planes

```
//
=====================================================================
// chapter 1 example 12

clc;
clear;

```

```
//input data
d          = 2.5;                    //spacing in angstroms
theta      = 9;                          //glancing angle in degrees
n1         = 1;
n2         = 2;


//calculation
lamda       = (2*sin(theta*(%pi/180))*d);
theta       = asin((2*lamda)/(2*d));

//result
mprintf('wavelength =%3.4f \n',lamda);
mprintf('glancing angle =%3.1f \n',theta*(180/%pi));

//==================================================================
```

Scilab code Exa 1.13 To find lattice constant

```
//==================================================================
// chapter 1 example 13

clc;
clear;


//input data
lamda       = 2;                         //wavelength in
```

```
angstroms
theta1      = 60;                          //angle in degrees
n           = 1;

//formula
//2*d*sin(theta)=n*lamda;

//calculation
d   = (n*lamda)/(2*sin(theta1*%pi/180));

//result

mprintf('lattice constant=%3.4f   \n',d);
mprint('Note:calulation mistake in textbook)
//==========================================================================
```

Scilab code Exa 1.14 To find angle

```
//==========================================================================
//chapter 1 example 14

clc;
clear;

//input data
lamda       = 1.4*10^-10;                  //wavelength in angstroms
a           = 2*10^-10;                    //lattice parameter in angstroms
h           = 1;                    //miller indices
k           = 1;                    //miller indices
```

```
 l           = 1;                   //miller indices
 n          = 1;
//formula
//2*d*sin(theta)=n*lamda

//calculation

dhkl        = a/sqrt((h^2)+(k^2)+(l^2));          //
   inter planar spacing
theta       = asin((n*lamda)/(2*dhkl));

//result
mprintf('angle=%3.2f.\n',theta*(180/%pi));

//
  ==================================================================================
```

Scilab code Exa 1.15 To find wavelength

```
//
  ==================================================================================

// Chapter 1 example 15
clc;
clear;

// input data
 d      = 3.84 *10^-10;        //spacing between
    planes in m
 theta      = 45;              //glancing angle in
    degrees
 m      = 1.67*10^-27;         //mass ef electron
 h      = 6.62*10^-34;         // planck's constant
 n      = 1;                  //braggg reflextion
```

```
 v      = 5.41*10^-10;

//calculation
//lamda = 2*d*(1/sqrt(2));
lamda = h/(m*v);

//result
 mprintf('wavelength of neutron =%3.2e m\n',lamda);
 mprintf(' Note:calculation mistake in text book in calculating wavelength ')
//==================================================================
```

Scilab code Exa 1.16 To find lattice parameters

```
//==================================================================
// chapter 1 example 16
clc;
clear;

//input data
 m       = 9.1*10^-31;        // mass of electron in kilograms
 e       = 1.6*10^-19;        //charge of  electron in coulombs
 n       = 1;                //bragg's reflection
 h1      = 6.62*10^-34;       //planck's constant J.s
 n      = 1;                  //bragg reflecton
 V       = 200;               //voltage in V
 theta   = 22;                //observed reflection

 //calculation
```

```
lamda       = h1/sqrt(2*m*e*V);
dhkl        = (n*lamda)/(2*sin(theta*%pi/180));
a          = dhkl*sqrt(3);

//result

mprintf('lattice parameter =%3.0f.  \n',a*10^10);
//
```

Chapter 2

Band Theory of Solids

Scilab code Exa 2.1 To find three lowest permissible quantum energies

```
// Chapter 2 example 1

clc;
clear;

// Variable declaration
h   = 6.63*10^-34;          // plancks constant in J.s
m   = 9.1*10^-31;           // mass of electron in kg
a   = 2.5*10^-10;           // width of infinite square well
e   = 1.6*10^-19;           // charge of electron coulombs
n2  = 2;                    //number of permiissable quantum
n3  = 3;                    //number of permiissable quantum

// Calculations
E1  = (h^2)/(8*m*a^2*e);      // first lowest
```

```
permissable quantum energy  in eV
E2  = n2^2 *E1;                   // second lowest permissable quantum energy in eV
E3  = n3^2 *E1;                   // second lowest permissable quantum energy in eV

// Result
mprintf('Lowest three permissable quantum energies are \n E1 = %d eV\n E2 = %d eV\n E3 = %d eV',E1,E2,E3);
```

Scilab code Exa 2.2 To find energy differences between two states

```
// Chapter 2 example 2

clc;
clear;

// Variable declaration
 h   = 6.63*10^-34;           // plancks constant in J.s
 m   = 9.1*10^-31;            // mass of electron in kg
 a   = 10^-10;            // width of infinite square well in m
 e   = 1.6*10^-19;            // charge of electron in coulombs
 n1  = 1;                      //energy level constant
 n2  = 2;                        //energy level constant

// calculations
 E1  = ((n1^2)*(h^2))/(8*m*(a^2)*e);      // ground state energy in eV
```

```
E2  = ((n2^2)*(h^2))/(8*m*(a^2)*e);      // first excited state in energy in eV
dE  = E2-E1                             // difference between first excited and ground state(E2 - E1)

// Result
mprintf('Energy Difference = %3.2f eV',dE);
```

Scilab code Exa 2.3 comment on first three energy levels of an electron

```
// Chapter 2 example 3
clc;
clear;

// Variable declaration
h   = 6.63*10^-34;          // plancks constant in J.s
m   = 9.1*10^-31;           // mass of electron in kg
a   = 5*10^-10;             // width of infinite potential well in m
e   = 1.6*10^-19;            // charge of electron in coulombs
n1  = 1;                      // energy level constant
n2  = 2;                      // energy level constant
n3  = 3;                      // energy level constant

// Calculations
E1  = ((n1^2)*(h^2))/(8*m*(a^2)*e);       // first energy level in eV
E2  = ((n2^2)*(h^2))/(8*m*(a^2)*e);      // second energy level in eV
```

```
E3  = ((n3^2)*(h^2))/(8*m*(a^2)*e);      // third energy level in eV

// Result
mprintf('First Three Energy levels are \n E1 = %3.2f eV\n E2 = %3.2f eV\n E3 = %3.2f eV',E1,E2,E3);
mprintf('\n Above calculation shows that the energy of the bound electron cannot be continuous')
```

Scilab code Exa 2.4 To find lowest allowed energy bandwidth

```
// Chapter 2 example 4
clc;
clear;

// Variable declaration
h   = 1.054*10^-34;          //plancks constant in J.s
m   = 9.1*10^-31;            // mass of electron in kg
a   = 5*10^-10;              // width of infinite potential well in m
e   = 1.6*10^-19;            // charge of electron coulombs

// Calculations
//cos(ka) = ((Psin(alpha*a))/(alpha*a)) + cos(alpha*a)
//to find the lowest allowed energy bandwidth,we have to find the difference in  a values, as ka changes from 0 to
// for ka = 0 in above eq becomes
// 1 = 10*sin( a))/( a)) + cos( a)
// This gives  a = 2.628 rad
// ka =   ,  a =
```

```
// sqrt((2*m*E2)/h^2)*a =
E2   = ((%pi*%pi) *h^2)/(2*m*a^2*e);          //energy in eV
E1   = ((2.628^2) *h^2)/(2*m*a^2*e)   // for   a = 2.628 rad energy in eV
dE   = E2 - E1;                           //lowest energy bandwidth in eV

// Result
mprintf('Lowest energy bandwidth = %3.3f eV',dE);
```

Scilab code Exa 2.5 T find energy of free electron for first Brillouin Zone

```
// Chapter 2 example 5
clc;
clear;

// Variable declaration
a    = 3*10^-10;              // side of 2d square lattice in m
h    = 6.63*10^-34;           // plancks constant in J.s
e    = 1.6*10^-19             // charge of electron in coulombs
m    = 9.1*10^-31;            // mass of electron in kg

// calculations
//p    = h*k                    // momentum of the electron
k    = %pi/a;                   // first Brillouin zone
p    = (h/(2*%pi))*(%pi/a);           //momentum of electron
E    = (p^2)/(2*m*e)                   // Energyin eV
```

```
// Result
mprintf('Electron Momentum for first Brillouin zone
   appearance = %g\n Energy of free electron with
   this momentum = %4.1feV',p,E);
mprintf(" \n Note: in Textbook Momentum value is
   wrongly printed as 1.1*10^-10')
```

Chapter 3

Magnetic properties of Materials

Scilab code Exa 3.1 To find magnetic moment and bohr magneton

```
// Chapter 3 example 1
clc;
clear;

// Variable declaration
r   = 0.53*10^-10;          // orbit radius m
n   = 6.6*10^15;            // frequency of revolution of electronHz
e   = 1.6*10^-19           // charge of electron in coulombs
h   = 6.63*10^-34;          // plancks constant in J.s
m   = 9.1*10^-31;           // mass of electron in kg

// Calculations
i   = e*n                     // current produced due to electron
A   = %pi*r*r                 // Area in m^2
```

```
u    = i*A;                      // magnetic moment A*m^2
ub   = (e*h)/(4*%pi*m)           // Bohr magneton in J/T

// Output
mprintf('Magnetic moment = %3.3e Am^2\n Bohr magneton = %3.2e J/T',u,ub);
```

Scilab code Exa 3.2 To find the magnetic moment of the rod

```
// Chapter 3 example 2
clc;
clear;

// Variable declaration
ur   = 1150;            // relative permeability
n    = 500;             // turns per m
V    = 10^-3;          // volume of iron rod in m^3
i    = 0.5;            // current in amp

// Calculations
// B = uo(H+M)
// B = uH, u/uo = ur
// M = (ur - 1)H
// if current is flowing through a solenoid having n turns/l then H = ni
 M = (ur - 1)*n*i       // magnetisation
 m = M*V;              // magnetic moment

 // Output
 mprintf('Magnetic moment = %3.2e A-m^2',m);
 mprintf('\n Note: Instead of 2.87*10^2, 2.87*10^-2 is printed in textbook');
```

Scilab code Exa 3.3 To find the magnetic moment of the rod

```
// Chapter 3 example 3
clc;
clear;

// Variable declaration
ur  = 90;               // relative permeability
n   = 300;                // turns per m
i   = 0.5;               // current in amp
d   = 10*10^-3;          // diameter of iron rod
l   = 2;                 // length of iron rod

// Calculations
V   = %pi*(d/2)^2 * l        // volume of rod
M   = (ur - 1)*n*i             // magnetisation
m   = M*V                      // magnetic moment

// Output
mprintf('Magnetic Moment of the rod = %3.3g A-m^2\n
   ',m);
mprintf('Note: In textbook length of iron rod given
   as 2m whereas in calculation it is wrongly taken
   as 0.2m' )
```

Scilab code Exa 3.4 To find change in magnetic moment

```
// Chapter 3 example 4
clc;
clear;

// Variable declaration
```

```
Bo   = 2;                 // magnetic field in tesla
r    = 5.29*10^-11        // radius in m
m    = 9.1*10^-31;             // mass of electron in
   kg
e    = 1.6*10^-19            // charge of electron

// calculations
du   = (e^2 * Bo * r^2)/(4*m)         // change in
   magnetic moment

// output
mprintf('Change in magnetic moment = %3.1e J/T',du);
```

Scilab code Exa 3.6 To find temperate must the substance cooled

```
// Chapter 3 example 6
clc;
clear;

// Variable declaration
u1   = 3.3;            // magnetic dipole moment
u    = 9.24*10^-24;
B    = 5.2;            // magnetic field in tesla
k    = 1.38*10^-23;    // boltzmann constant

// calculations
T    = (u*u1*B)/(1.5*k);      // Temperature in Kelvin

// Output
mprintf('Temperature to which substance to be cooled
    = %3.1f K\n ',T);
mprintf('Note:Values given in question B = 52, u =
   924*10^-24.Values substituted in calculation B =
   5.2, u = 9.24*10^-24');
```

Scilab code Exa 3.7 To find magnetisation vector and flux density

```
// Chapter 3 example 7
clc;
clear;

// Variable declaration
xm       = -4.2*10^-6;            // magnetic
   susceptibility in A.m^-1
H        = 1.15*10^5;             // magnetic field in
    A.m^-1

// Calculations
uo       = 4*%pi*10^-7;           // magnetic
   permeability  N A^-2
M        = xm*H                   // magnetisation in
   A.m^-1
B        = uo*(H + M)             // flux density in T
ur       = 1+(M/H)                // relative
   permeability

// Output
mprintf('Magnetisation = %3.2f A/m\n flux density =
   %g Tesla\n relative permeability = %g',M,B,ur);
```

Scilab code Exa 3.8 To find increase in percentage

```
// Chapter 3 example 8
clc;
clear;

// Variable declaration
```

```
xm       = 1.4*10^-5;          // magnetic
    susceptibility
// B     = uoH
// B'    = uruoH
// ur    = 1+xm
// from above equations
//B'     = (1+xm)B
// percentage increase in magnetic induction = ((B'-
   B)/B)*100
//       = (((1+xm)B - B)/B)*100
PI     = xm*100;        // percentage increase

// Output
mprintf('Percentage increase = %3.4f percent',PI);
```

Scilab code Exa 3.9 To find magnetisation vector and flux density

```
// Chapter 3 example 9
clc;
clear;

// Variable declaration
xm       = -0.2*10^-5;         // magnetic
    susceptability in A.m^-1
H        = 10^4;               // magnetic field in A/m


// Calculations
uo       = 4*%pi*10^-7;            // magnetic
    permeability
M        = xm*H                // magnetisation in A/m
B        = uo*(H+M);           // magnetic flux density
     in T

// Output
```

```
mprintf('magnetisation = %3.2f A/m\n Magnetic flux density = %3.4f T',M,B);
```

Scilab code Exa 3.10 To find permeability and relative permeability

```
//

// chapter 3 example 10


clc;
clear;


//input data
 sighem         = 2.1*10^-5;                //magnetic susceptability
 u0             = 4*%pi*10^-7;


//calculation
ur              = 1+(sighem);
u               = u0*ur;

//result
 mprintf('permeability =%3.6f\n',ur);
 mprintf('relative permeability =%3.4e.N/A^2\n',u);

 //
```

Scilab code Exa 3.11 To find absolute and relative permeability

```
//
// chapter 3 example 11


clc;
clear;


//input data
 sighem          = 0.084;                //magnetic susceptability
 u0              = 4*%pi*10^-7;


//calculation
ur               = 1+(sighem);
u                = u0*ur;

//result
 mprintf('permieability =%3.6f\n',ur);
 mprintf('relative permiability =%3.4e.N/A^2\n',u);

 //
```

Scilab code Exa 3.12 To find relative permeability and magnetic susceptibility

```
//
```

```
// chpter 3 example 12


clc;
clear;


//input data
u               = 0.126;                //permiability in N/A^2
u0              = 4*%pi*10^-7;

//calculation
ur                = u/u0
sighe           = ur-1;             //magnetic susceptability

//result
mprintf('relative permiability =%3.5e\n',sighe);
mprintf(' Note:Calculation mistake in textbook in calculating sighe by taking ur as 10^5 instead of 100318.4')

//
```

Scilab code Exa 3.13 To find diamagnetic susceptibility of He

```
//

// chapter 3 example 13

```

```

clc;
clear;

//input data
//diamagnetic susceptability of He
 R          = 0.6*10^-10;               //mean radius of atom in m
 N          = 28*10^26;                //avagadro number in per m^3
 e          = 1.6*10^-19;                //charge of electron in coulombs
 m          = 9.1*10^-31;                  //mass of electron in kilograms
  Z          = 2;                            //atomic number

 //calculation
 u0         = 4*%pi*10^-7;              //atomic number
 si         = -(u0*Z*(e^2)*N*(R^2))/(6*m);        //susceptability of diamagnetic material

//result
 mprintf('susceptability of diamagnetic material = %3.4e\n',si);

//
```

Scilab code Exa 3.14 To find permiability and susceptibility

```
//
```

```
// chpter 3 example 14


clc;
clear;

//input data
 phi         = 2*10^-5;          //magnetic flux in Wb/m^2
 H           = 2*10^3;              //in A/m
 A           = 0.2*10^-4;         //area  in m^2



//calculation
 u0          = 4*%pi*10^-7;
 B       = phi/A;                  //magnetic flux density in Wb/m^2
 u       = B/H;                    //permiability in /A^2
 sighem = (u/u0)-1;
///result
 mprintf('permiability =%3.2e.N/A^2\n',u);
 mprintf('susceptability =%4f\n',sighem);
 mprintf('Note:answer of permiability is wrong in textbook\n');
 mprintf(' Note: calcuation mistake in textbook in sighem');


//
```

Scilab code Exa 3.15 To find susceptability

```
//
=====================================================================
// chpter 3 example 15


clc;
clear;

//input data
 N          = 6.5*10^25;            //number of atoms
    in atoms per m^3
 e          = 1.6*10^-19;            //charge of
    electron in coulombs
 m          = 9.1*10^-31;            //mass of
    electron inilograms
 h          = 6.6*10^-34;           //planck's
    constant in J.s
 T          = 300;                  //temperature in K
  k          = 1.38*10^-23;           //boltzman
     constant in J*(K^-1)
  n          = 1;                     //constant


//calculation
 u0         = 4*%pi*10^-7;
 M               = n*((e*h)/(4*%pi*m));
                       //magnetic moment in A*m^2
 sighe           = (u0*N*(M^2))/(3*k*T);
    //susceptability of diamagnetic material

//result
 mprintf('susceptability of diamagnetic material =
    %3.2e\n',sighe);

//
=====================================================================
```

Scilab code Exa 3.16 To find number ampere turns

```
//==========================================================================

// chpter 3 example 16


clc;
clear;

//input data
L        = 2.0;                      //length in m
A        = 4*10^-4;                  //cross section sq.
   m
u        = 50*10^-4;                //permiability in H*
   m^-1
phi        = 4*10^-4;               //magnetic flux in
   Wb

//calculation
 B       =  phi/A;                  //magnetic flux
    density in Wb/m^2
 NI      = B/u;                     //ampere turn in A/m

 //result
 mprintf('ampere turn =%3.2f.A/m\n',NI);

 //==========================================================================
```

Scilab code Exa 3.17 To find current to be sent into solenoid

```
//
// chapter 3 example 17


clc;
clear;

//input data
 H           = 5*10^3;              //corecivity in A/m
 l           = 10^-1;                  //length in m
 n           = 500;                 //number of turns

//calculation
 N       = n/l;                     // number of turns per m
 i       = H/N;                    //current in A

//result
 mprintf('current =%1d A\n',i);

//
```

Scilab code Exa 3.18 To find number of turns

```
//
// chapter 3 example 18

```

```

clc;
clear;

//input data
 A          = 6*10^-4;                   //area in m^2
 l          = 0.5;                      //length in m
 u          = 65*10^-4;                 //permiability in H/m
 phi        = 4*10^-5;                  // magnetic flux in Wb


//calculation
 B          = phi/A;
 H          = B/u;
 N          = H*l;

//result
 mprintf('number of turns =%1f\n',N);
 mprintf(' Note: calculation mistake in textbook in calculattig H by taking B value as 0.06 instead of 0.0666');

//
```

Scilab code Exa 3.19 To find permeability and susceptibility

```
//
// chpter 3 example 19

```

```

clc;
clear;

//input data
 A           = 0.2*10^-4;                    //area in m^2
 H           = 500;                           //magnetising field in A.m^-1
 phi          = 2.4*10^-5;                   // magnetic flux in Wb

 //calculation
 u0          = 4*%pi*10^-7;
 B       = phi/A;                             //magnetic flux density in N*A^-1 *m^-1
 u       = B/H;                               //permiability in N/m
 fm      = (u/u0)-1;                          //susceptability

//result
 mprintf('susceptability =%3.2d\n',fm);


//
```

Scilab code Exa 3.20 To find loss of energy per hour

```
//
// chapter 3 example 20

```

```
clc;
clear;

//input data
f       = 50;                       //number of reversals /s in Hz
W       = 50;                       //weight in kg
d       = 7500;                     //density in kg/m^3
A       = 200;                      //area in  joules /m^3

//calculation

V       = 1/d;                //volume of 1 kg iron
E       = A*V;                  //loss of energy per kg
L       = f*E;                //hysteresisloss/s in Joule/second
Lh      = L*60*60;              //loss per hour

//calculation
mprintf('loss of energy per hour =%3.2f\n',Lh);
mprintf('calculation mistake in textbook in calculating Lh');

//
```

Scilab code Exa 3.21 To find hysteresis loss per cycle

```
//
// chpter 3 example 21
```

```
clc;
clear;

//input data
f        = 50;                  //frequency in Hz
Bm       = 1.1;                 //magnetic flux in Wb/m^2
t        = 0.0005;              //thickness of sheet
p        = 30*10^-8*7800;              //resistivity in ohms m
d        = 7800;                       //density in kg/m^3
Hl       = 380;                        //hysteresis loss per cycle in W-S/m^2

//calculation
 Pl      = ((%pi^2)*(f^2)*(Bm^2)*(t^2))/(6*p);     // eddy current loss
 Hel      = (Hl*f)/d;                              // hysteresis loss
 Tl       = Pl+Hel;                                 // total iron loss

 //result
 mprintf('total iron loss =%3.2f watt/kg \n',Tl);
```

Chapter 4

Behaviour of Dielectric Materials in ac and dc fields

Scilab code Exa 4.1 To find dielectric constant of argon at NTP

```
//

// chapter 4 example 1

clc;
clear;

//input data
 alpha       = 1.8*10^-40;            //polarisability of argon in Fm^2
 e0          = 8.85*10^-12;           //dielectric constant F/m
 N1          = 6.02*10^23;            //avagadro number in mol^-1
 x           = 22.4*10^3;             //volume in m^3

//formula
//er-1=N*p/e0*E=(N/e0)*alpha
```

```
//calculation
 N           = N1/double(x);                  //number of argon atoms in per unit volume in cm^3
 N2          = N*10^6;                        //number of argon atoms in per unit volume in m^3
 er      = 1+((N2/e0))*alpha;                 //dielectric constant F/m


//result
mprintf('dielectric constant of argon=%3.7f\n',er);
//==================================================================
```

Scilab code Exa 4.2 To estimate the shift of the electron cloud

```
//==================================================================
// chapter 4 example 2

clc;
clear;


//input dta
 alpha        = 1.8*10^-40;        //polarisability of argon in F*m^2
 E            = 2*10^5;            // in V/m
 z            = 18;
 e            = 1.6*10^-19;


//formula
```

```
//p=18*e*x
//calculation
 p       = alpha*E;
 x       = p/(18*e);      //shift of electron in m


//result
 mprintf('displacement=%3.2e.m\n',x);

//==========
```

Scilab code Exa 4.3 To find local field acting on a given molecule

```
//==========
// chapter 4 example 3

clc;
clear;


//input data
 E0     = 300*10^2;                    //local field in
     V/m
 P1   = 3.398*10^-7;                   //dipole moment
     Coulomb/m
 P2   = 2.124*10^-5;                   //dipole moment
     Coulomb/m
 e0   = 8.85*10^-12;                   //permittivity
     in F/m


```

```
//formula
//E10Ci=E0-(2*Pi/3*e0)
//calculation
 E10C1  = E0-((2*P1)/(3*e0));       //local field of benzene in V/m
 E10C2  = E0-((2*P2)/(3*e0));      //local field of water in V/m

 //result
 mprintf('local field of benzene=%3.2e.V/m\n',E10C1);
 mprintf('local field of water=%3.2e.V/m\n',E10C2);

//==================================================================
```

Scilab code Exa 4.4 To find polarisabilities of benzene and water

```
//==================================================================
// chapter 4 example 4

clc;
clear;

//input data
 p1 = 5.12*10^-34;        //p of benzene kg/m^3
 p2 = 6.34*10^-34;      //p of water kg/m^3
 e10C1  = 4.4*10^3;        //local field of benzene in V/m
 e10C2  = 1570*10^3;        //local field of water in V/m

```

```
//formula
//p=alphai*e10Ci
//calculation
alpha1 = p1/e10C1;        //polarisability of benzene in F*m^2
alpha2 = p2/e10C2;      //polarisability of water in F*m^2


//result
mprintf('polarisability of benzene=%3.2e.F*m^2\n',alpha1);
mprintf('polarisability of water=%3.2e.F*m^2\n',alpha2);
mprintf('Note: mistake in textbok,alpha1 value is printed as 1.16*10^-38 instead of 1.16*10^-37');

//
```

Scilab code Exa 4.5 To find polarisation of plates

```
//
//chapter 4 example 5

clc;
clear;


//input data
e0      = 8.85*10^-12;            //abslute
```

```
permitivity in (m^-3)*(kg^-1)*(s^4)*(A^2)
E      = 600*10^2;               //strength in V/cm
er1    = 2.28;            //dielectric constant of benzene in coulomb/m
er2    = 81;             //dielectric constant of water in coulomb/m


//fomula
//p=e0*E*(er-1)
//calculation
pB     = e0*E*(er1-1);      //polarisation of benzene in c/m^2
pW     = e0*E*(er2-1);         //polarisation of water in c/m^2


//result
mprintf('polarisation of benzene=%3.2e.c/m^2\n',pB);
mprintf('polarisation of water=%3.2e.c/m^2\n',pW);

//
```

Scilab code Exa 4.6 To find percentage contribution of ionic polarisability

```
//
// chapter 4 example 6

clc;
clear;
```

```
//input data
er0   = 5.6;        //static dielectric cnstant of NaCl
n    = 1.5;           //optical index of refraction


//calculation
er = er0-n^2;
d  = (er/er0*100);

//result
mprintf('percentage contribution from ionic polaristion=%3.2f percent\n',d);

//==================================================================================
```

Scilab code Exa 4.7 To find separation between positive and negative charges

```
//==================================================================================
// chaoter 4 example 7
clc;
clear;


//input data
alpha        = 0.18*10^-40;       //polarisability of He in F *m^2
E            = 3*10^5;                  // constant in V/m
```

```
N            = 2.6*10^25;              //number of atoms in per m^3
e            = 1.6*10^-19;


//formula
//P=N*p
//charge of He=2*electron charge
//p=2(e*d)
//calculation
P       = N*alpha*E;              //in coul/m^2
p       = P/N;                    //polarisation of He in coul.m
d       = p/(2*e);                //separation between charges in m


//result
mprintf('separation=%3.2e.m\n',d);

//==================================================================
```

Scilab code Exa 4.8 To find orientational polarisation at room temperature

```
//==================================================================
// chapter 4 example 8
clc;
clear;

//input data
```

```
N      = 10^27;                    //number of HCl
   molecules in molecules/m^3
E      = 10^5;                     //electric field
   in V/m
P      = 1.04*3.33*10^-30;        //permanent dipole
    moment in coul.m
T      = 300;                     //temperature in
   kelvin
K      = 1.38*10^-23;


//calculation
P0     = (N*P^2*E)/(3*K*T);        //oriental
   polarisation in coul/m^2


//result
mprintf('oriental polarisation=%3.2e.coul/m^2\n',P0
   );

//
   ==================================================
```

Scilab code Exa 4.9 To find relative dielectric constant

```
//
   ==================================================
// chapter 4 example 9

clc;
clear;

//input data
```

```
N       = 6.023*10^26;        //avagadro number   (lb-mol)^-1
alpha   = 3.28*10^-40;        //polarisability in F*m^2
M       = 32;                 //molecular weight in kilograms
p       = 2.08*10^3;          //density of sulphur in g/cm^3
e0      = 8.85*10^12;         //permitivity in F/m

//calculation
er = ((2*N*p*alpha)+(3*M*e0))/((3*M*e0)-(N*p*alpha));

//result

mprintf('relative dielectric constant =%3.1f\n',er);
mprintf(' Note: calculation mistake in text book in calculating relative dielectric constant');
//
```

Scilab code Exa 4.10 To find ratio between electronic and ionic polarisability

```
//

// chapter 4 example 10

clc;
clear;

```

```

//input data
 er          = 4.94;
 n           = 1.64;


//calculatio
//(alphae)/(alphai) =x
 x        = ((er-1)/(er+2))*(((n^2)+2)/((n^2)-1));


//result
 mprintf('ratio of electronic and ionic
    probabilities =%6f\n',x);

//
   ==================================================================
```

Scilab code Exa 4.11 To find dielectric constant and electrical susceptibility

```
//
   ==================================================================

// chapter 4 example 11


clc;
clear;


//input data
 E      = 1.46*10^-10;              //permitivity in
    c^2*N^-1*m^-2
```

```
 E0       = 8.885*10^-12;             // permitivity in c^2*N^-1*m^-2


//calculation
 Er          = E/E0;
 sighe       = E0*(Er-1);           //electrical suseptbility in c^2*N^-1*M^-2


//result
 mprintf('dielectric constant=%3.2f.\n',Er);
 mprintf('electrical suseptibility=%3.4e.c^2*N^-1*M^-2\n',sighe);

//==================================================================
```

Scilab code Exa 4.12 To find the polarisation

```
//==================================================================
// chapter 4 example 12

clc;
clear;

//input data
 r        = 0.1;                        //radius in  m
 pw       = 1;                         //density of water in  g/ml
 Mw       = 18;                        // molecular mass of water
```

```
E        = 6.0*10^-30;              //dipole moment of water in cm
N        = 6.0*10^26;              //avagadro constant in (lb-mol)  1


//calculation
n   = N*(4*(%pi)*(r^3)*pw)/(Mw*3)        //number of water molecules in a water drop
p   = n*E;                               //polarisation in cm^2


//result
mprintf('polarisation=%3.1e.cm^2\n',p);

//==================================================================
```

Scilab code Exa 4.13 To find dielectric susceptibility

```
//==================================================================
// chapter 4 example 13

clc;
clear;

//input data
Er      = 1.000074;                    //dielectric constant for a gas at 0 C


```

```
//calculation
sighe      = Er-1;


//result
mprintf('dielectric susceptibility=%3.6f\n',sighe);

//
```

Scilab code Exa 4.14 To find free charge and polarisation and displacement

```
//

// chapter 4 example 14


clc;
clear;


//input data
E        = 10^6;                //dielectric in volts/s
er       = 3;                   //dielectric in mm
e0       = 8.85*10^-12;


//calculation
E0      = er*E;                  //electric field in V/m
sigma   = e0*E0;                 //free charge in
```

```
    Coul/m^2
 P        = e0*(er-1)*E0;          //polarisation in
    coul/m
 D        = e0*er*E0;              //displacement in in
     dielectric


//result
 mprintf('free charge=%3.2e.Coul/m^2\n',sigma);
 mprintf('polarisation=%3.2e.Coul/m\n',P);
 mprintf('displacement=%3.2e\n',D);

//
    ==================================================================
```

Scilab code Exa 4.15 To find capacitance and charge stored and displacement vector and polarisation vector

```
//
    ==================================================================

// chapter 4 example 15

clc;
clear;

//input data
 d      = 1.0*10^-3;               //separation between
     plates in m
 A      = 6.45*10^-4;             // surface area in m
    ^2
 e0      = 8.85*10^-12;            //permitivity of
    electron in (m^-3)*(kg^-1)*(s^4)*(A^2)
 er     = 6.0;                     //relative
```

```
    permitivity in (m^-3)*(kg^-1)*(s^4)*(A^2)
V     = 10;                          //voltage in V
E     = 10;


//calculation
C      = (e0*er*A)/d;                //capacitance in Farad
q      = C*V;                        //charge in coulomb
D      = (e0*er*E)/(10^-3);          //displacement vector in c/m^2
P      = D-(e0*E/(10^-3));                 //polarisation vector in c/m^2


//result
mprintf('capacitance = %3.2e,Farad\n',C);
mprintf('charge =%3.2e.coulomb\n',q);
mprintf('displacement =%3.2e.c/m^2\n',D);
mprintf('polarisation =%3.2e.c/m^2\n',P);
mprintf('Note:error in calculation of P,E value is taken as 5000 instead of 10^4\n');

//
```

Scilab code Exa 4.16 To find phase difference

```

//
// chapter 4 example 16
```

```


clc;
clear;


//input data
 t        = 18*10^-6;              //relaxation time in s
 er1      = 1;                     //permitivity in F/m
 er       = 1;                     //permitivity in F/m
 t        = 18*10^-6;              //relaxation time in s

 //calculation
 f                =   1/(2*%pi*t);                //frequency in Hz
 theta_c              = atan(er1/er);
 theta_c_deg           = theta_c*(180/%pi);
 phi                  = 90-theta_c_deg;            //phase difference in degrees


 //result
 mprintf('frequency = %3.2f KHz\n',(f/10^3));
 mprintf('phase difference =%3.2f  \n',phi);

 //
```

Chapter 5

Conductivity of metals and superconductivity

Scilab code Exa 5.1 To find average drift velocity of free electron

```
//
// chapter 5 example 1
clc;
clear;

//input data
 d       = 2*10^-3;                //diameter in m
 I       = 5*10^-3;                //current in A
 e       = 1.6*10^-19;             //charge of
    electron in coulombs
 a       = 3.61*10^-10;            //side of cube in
    m
 N       = 4;                      //number of atoms
     in per unit cell


//formula
```

```
//J=n*v*e

//calculation
r        = d/2;                    //radius in m
n        = N/(a^3);                //number of atoms per unit volume in atoms/m^3
A        = %pi*(r^2);              //area in m^2
J        = I/A;                    //current density in Amp/m^2
v        = J/(n*e);               //average drift velocity in m/s

//result
mprintf('velocity=%3.2e.m/s\n',v);

//==================================================================
```

Scilab code Exa 5.2 To find drift velocity

```
//==================================================================
// chapter 5 example 2

clc;
clear;


//input data
I        = 6;                        //current in A
d        = 1*10^-3;                 //diameter in m
n        = 4.5*10^28;              //electrons available in electron/m^3
```

```
e       = 1.6*10^-19;            //charge of  electron in coulombs


//calculation
r      = d/2;                  //radius in m
A      = %pi*(r^2);           //area in m^2
J      = I/A;                //current density in A/m^3
vd     = J/(n*e);           //density in m/s


//result
 mprintf('velocity=%3.2e.m/s\n',vd);

//==================================================================================
```

Scilab code Exa 5.3 To find current density and drift velocity of electrons

```
//==================================================================================
//chapter 5 exmple 3

clc;
clear;

//input data

V        = 63.5;                 //atomic weight in kg
d        = 8.92*10^3;            //density of copper in kg/m^3
r        = 0.7*10^-3;            //radius in m
I        = 10;                   //current in A
```

```
 e          = 1.6*10^-19;             //charge of
    electronin coulomb
 h          = 6.02*10^28;             //planck's constant
    in (m^2)*kg/s


//calculation
A           = %pi*(r^2);            // area in m^2
N           = h*d;
n           = N/V;
J           = I/A;                  //current density in m/
   s
vd          = J/(n*e);              //drift velocity in m/s

//result
 mprintf('velocity=%2e.m/s\n',vd);

//
   ====================================================================
```

Scilab code Exa 5.4 To find resistivity of the material

```
//
   ====================================================================

// chapter 5 example 4

clc;
clear;


//input data
 R           = 0.182;                //resistance in ohm
 l          = 1;                    //length in m
```

```
A        = 0.1*10^-6;           //area in m^2

//formula
//R=(p*l)/A

//calculation
p       = (R*A)/l;                    //resistivity in ohm m


//result
mprintf('restivity=%3.2e.ohm m\n',p);

//==============================================================================
```

Scilab code Exa 5.5 To find mobility and relaxation time of electrons

```
//==============================================================================

// chapter 5 example 5

clc;
clear;

//input data
n         = 5.8*10^28;                    //number of silver electrons in electrond/m^3
p         = 1.45*10^-8;                  //resistivity in ohm m
E         = 10^2;                       //electric field in V/m
e         = 1.6*10^-19;
```

```


//formula
//sigma  = n*e*u
//sigma=//p
//calculation
 u       = 1/(n*e*p);
 vd      = u*E;                       //drift  velocity in m/s

//result
 mprintf('velocity=%3.2f.m/s\n',vd);

//==============================================================================
```

Scilab code Exa 5.6 To find mobility of conduction electrons

```
//==============================================================================
// chapter 5 example 6

clc;
clear;

//input data
 W            = 107.9;                 //atomic weight
 p            = 10.5*10^3;             //density in kg/m^3
 sigma        =6.8*10^7;              //conductivity in ohm^-1.m^-1
 e            =1.6*10^-19;            //charge of electron in coulombs
```

```
N              = 6.02*10^26;          //avagadro number
    in mol^-1


//calculation
n        = (N*p)/W;                //number of atoms
    per unit volume
u        = sigma/(n*e);            //density of
    electron in m^2.V^-1.s^-1


//result
mprintf('density=%3.2e.m^2.V^-1.s^-1\n',u);

//
    ==================================================================
```

Scilab code Exa 5.7 To find relaxation time

```
//
    ==================================================================

// chapter 5 example 7

clc;
clear;

//input data
//for common metal copper
n              = 8.5*10^28;               //number of
    atoms in m^-3
sigma          = 6*10^7;                  //sigma  in
    ohm^-1m^-1
m              = 9.1*10^-31;              //mass of
```

```
    electron in kilogram
e            = 1.6*10^-19;                //charge of electron in coulombs

//calculation
t   = (m*sigma)/(n*(e^2));         //relaxation time in s

//result
mprintf('time=%3.2e.s\n',t);

//==========================================================================
```

Scilab code Exa 5.9 To find thermal conductivity for a metal

```
//==========================================================================
// chapter 5 example 9

clc;
clear;

//input data
t        = 3.0*10^-14;                  //time in s
n        = 2.5*10^22;                   //in electrons per m^3
m        = 9.1*10^-31;                  //mass of electron in kilograms
e        = 1.6*10^-19;                  //charge of electron in coulombs
T        = 3.25;                        //temperature in K

```

```

//formula
//K/(sigma*T)=2.44*10^-8    from wiedemann Franz law
//calculation
 sigma     = (n*(e^2)*t)/(m*10^-6);              //conductivity in m^3
 K         = (2.44*10^-8)*sigma*T;                //thermalconductivity in W/m-K


//result
 mprintf('thermal conductivity=%3.4f.W/m-K\n',K);
 mprintf(' Note: calculation mistake in textbook in calculating K as T value is taken 325 instead of 3.25');

//==================================================================================
```

Scilab code Exa 5.10 To find energy difference between two states

```
//==================================================================================
// chapter 5 example 10

clc;
clear;

//input data
 a        = 10^-10;                      //one dimension in m
 m        = 9.1*10^-31;
 h        = 6.62*10^-34;
```

```
//formula
//En    = ((n^2)*(h^2))/(8*m*(a^2))
//calculation
E1       = (h^2)/(8*m*(a^2));
E2       = (4*(h^2))/(8*m*(a^2));
dE        = (3*(h^2))/(8*m*(a^2));


//result
mprintf('energy diefference=%3.2e.J\n',dE);

//==================================================================
```

Scilab code Exa 5.11 To find fermi energy

```
//==================================================================
// chapter 5 example 11

clc;
clear;

//input data
N          =6.02*10^23;            //avagadro number in atoms /mole
h         = 6.63*10^-34;           //planck's constant in joule-s
m         = 9.11*10^-31;          //mass in kg
M         = 23;                  //atomic weight in grams /mole
```

```
p          = 0.971;                //density in gram/cm
    ^3


//formula
//x=N/V=(N*p)/M
//calculation
 x        = (N*p)/M;
 x1       = x*10^6;
 eF       = (((h^2)/(2*m)))*(((3*x1)/(8*%pi))^(2/3));
              //Fermi energy
 eF1      = (eF)/(1.6*10^-19);
//result
 mprintf('fermi energy=%3.2f.eV\n',eF1);

 //
    ==================================================
```

Scilab code Exa 5.12 To find fermi energy

```
//
   ==================================================
// chapter 5 example 12

clc;
clear;


//input data
 x        = 2.54*10^28;            //number of
    electrons in per m^2
 h        = 6.63*10^-34;           // planck's
    constant in joule-s
```

```
m        = 9.11*10^-31;          // mass in kg
p        = 0.971;                //density in grams/cm^3
k        = 1.38*10^-23;


//calculation
//x        = (N*p)/M;
eF       = (((h^2)/(2*m)))*(((3*x)/(8*%pi))^(2/3));   //Fermi energy
eF1      = (eF)/(1.6*10^-19);
vF       = sqrt((2*eF)/m);
TF       = eF/k;


//result
mprintf('fermi energy =%3.2f.eV\n',eF1);
mprintf('fermi velocit =%3.2e.m/s\n',vF);
mprintf('femi temperature =%3.2e.K\n',TF);

//
```

Scilab code Exa 5.13 To find fermi energy

```
//
// chapter 5 example 13

clc;
clear;


```

```
//input data
M       = 65.4;                //atomic weight
p       = 7.13;                //density
h       = 6.62*10^-34;        // planck's constant
m       = 7.7*10^-31;         // mass
v       = 6.02*10^23;


//calculation
//x =N/V
V       = M/p;   //volume of one atom in cm^3
n       = v/V;   // number of Zn atoms in volume v
x       = 2*n*(10^6);   //number of free electrons in unit volume iper m^2
eF      = ((h^2)/(2*m))*(((3*x)/(8*%pi))^(2/3));   // fermi energy in J
eF1     = eF/(1.6*(10^-19));


//result
mprintf('fermi energy =%3.2d.eV\n',eF1);

//
```

Scilab code Exa 5.14 To find number of electrons

```
//
// chapter 5 example 14

```

```
clc;
clear;


//input data
eF      = 4.27;              // fermi energy in eV
m       = 9.11*10^-31;       // mass of electron in kg
h       = 6.63*10^-34;       // planck's constant in J.s


//formula
//x= N/V
//calculation
eF1     = eF*1.6*10^-19;                          // fermi energy in eV
x       = (((2*m*eF1)/(h^2))^(3/2))*((8*%pi)/3);    //number of electrons per unit volume


//result
mprintf('number of electrons per unit volume =%4.0e./m^3\n',x);

//
```

Scilab code Exa 5.15 To find electron density

```
//
// chapter 5 example 15
```

```

clc;
clear;


//input data
 eF1         = 4.70;               // fermi energy in eV
 eF2         = 2.20;               // fermi energy in eV
 x1          = 4.6*10^28;          // electron density
    of lithium per m^3


//formula
//N/V = (((2*m*eF1)/(h^2))^(3/2))*((8*%pi)/3);
//N/V = k*(eF^3/2)
//N/V = x
//calculation
 x2       = x1*((eF2/eF1)^(3/2));              //
    electron density for metal in per m^3


//result
 mprintf('electron density  for a metal =%4.2e per m
    ^3\n',x2);

 //
    ================================================================
```

Scilab code Exa 5.16 To find average energy and temperature

```
//
   ================================================================

// chapter 5 example 16
```

```
clc;
clear;


//input data
 eF      = 5.4;                              //fermi
    energy in eV
 k       = 1.38*10^-23;                      // k in
    joule/K


//calculation
 e0      = (3*eF)/5;                            //average
     energy in eV
 T       = (e0*(1.6*10^-19)*2)/(3*k);              //
    temperature in K


//result
 mprintf('average energy =%3.2f.eV\n',e0);
 mprintf('temperature =%3.2e.K\n',T);

//
    ================================================================
```

Scilab code Exa 5.17 To find average energy and speed of electron

```
//
    ================================================================
// chapter 5 example 17

clc;
```

```
clear;


//input data
 EF          = 15;                         //fermi energy
     in eV
 m           = 9.1*10^-31;               //mass of
    electron in kilogarams


//calculation
 E0          = (3*EF)/5;                         //
    average energy en eV
 v           =sqrt((2*E0*1.6*10^-19)/m);
    //speed of electron in m/s


//result
 mprintf('average energy =%3.2f.eV\n',E0);
 mprintf('speed =%3.2e.m/s\n',v);

//
   ==================================================
```

Scilab code Exa 5.18 To find average energy and speed of electron

```
//
   ==================================================
// chapter 5 example 18

clc;
clear;

```

```
//input data
EF          = 7.5;                          //fermi energy in eV
m           = 9.1*10^-31;                   //mass of electron in kilograms

//calculation

E0          = (3*EF)/5;                     //average energy en eV
v=sqrt((2*E0*1.6*10^-19)/m);                //speed in m

//result
mprintf('average energy =%3.2f.eV\n',E0);
mprintf(' speed =%3.2e.m/s\n',v);

//==================================================================================
```

Scilab code Exa 5.19 To find fermi energy and fermi velocity

```
//==================================================================================

// chapter 5 example 19

clc;
clear;

//input data
m       = 9.1*10^-31;           //mass of electron in kg
h       = 6.62*10^-34;          //planck's constant in (m^2)*kg/s

```

```

//formula
//x=N/V
 x       = 2.5*10^28;

//calculation
 EF        = ((h^2)/(8*(%pi^2)*m))*((3*(%pi^2)*x)^(2/3));                    //fermi energy in J
 EF1       = EF/(1.6*10^-19);                                                //fermi energy in eV
 vF        = (h/(2*m*%pi))*((3*(%pi^2)*x)^(1/3));                  //fermi velocity in m/s


//result
 mprintf('energy=%3.2e.eV\n',EF1);
 mprintf(' speed= =%3.2e.m/s\n',vF);

//==================================================================
```

Scilab code Exa 5.20 To find efficiency of transmission and percentage voltage drop

```
//==================================================================
// chapter 5 example 20

clc;
clear;

 //input data
```

```
Ps       = 10^7;
V       = 33*10^3;
R       = 2;

//calculation
I       = Ps/V;
Pd      = (I^2*R)/1000;
n       = ((Ps-Pd)/Ps)*100;
v       = I*R;
Vd      = (v/V)*100;               //percentage voltage drop

//result
mprintf('efficiency =%0f percent\n',n);
mprintf('voltage drop =%3.2f percent\n',Vd);
```

Scilab code Exa 5.21 To find value of constants

```
//==================================================================

// chapter 5 example 21

clc;
clear;

//input data
a1   = 2.76;                //a1 in uv/ C
a2  =16.6;               //a2 in uv/ C
b1  = 0.012;               //b1 in uv/ C
b2  = -0.03;               //b2 in uv/ C

//calculation
//aFe,Pb   =a1
//aCu,Pb   = a2
```

```
//bCu,Fe    = b1
//bFe,Pb    = b2

//calculation
 a3     = a1-a2;                    //a3 in uv/ C
 b3     = b1-b2;                    //b3 in uv/( C)^2

//result
 mprintf('aCu,Fe =%3.2f.uV/ C\n',a3);
 mprintf(' bCu,Fe =%3.3f.uV/( C)^2\n',b3);

//
    ================================================================
```

Scilab code Exa 5.23 To find neutral temperature and temperature of inversion

```
//
    ================================================================
// chapter 5 example 23

clc;
clear;

//input data
 a        = 15;                    //a in uv/ C
 b        = -1/30;                    //b in uv/ C

//E = at+bt^2
//dE/dT =a+2*b*t
//t=tn
//dE/dT =0
//calculation
```

```
tn      = -(a/(2*(b)))                    //neutral
   temperature in  C
//t1+t2  = 2*t2;
t2     = 2*tn                  //inversion temperature
   in  C

//result
mprintf('neutral temperature =%3.2d  C\n',tn);
mprintf('temperature of inversin =%3.2d  C\n',t2);

//
  =====================================================================
```

Scilab code Exa 5.24 To find resistivity of an alloy

```
//
  =====================================================================

// chapter 5 example 23

clc;
clear;

//input data
p2          =  2.75;          //resistivity of alloy 1
     percent of Ni in uohm-cm
p1               =  1.42;     //resistivity of pure
   copper in uohm-cm
p3             = 1.98;        //resistivity of alloy 3
     percent of silver in uohm-cm

//p(Ni+Cu) =p1
//pCu =p2
//p(Cu+silver)=p3
```

```
//calculation
pNi        = p2-p1;
p4    = (p3-p1)/3;
palloy      = p1+(2*pNi)+(2*p4);        //resistivity of alloy 2 percent of silver and 2 percent of nickel in uohm-cm

//result
mprintf('resistivity of alloy =%3.4f.uohm-cm\n',palloy);
```

Scilab code Exa 5.25 To find transition temperature

```
//==============================================================================

// chapter 5 example 25

clc;
clear;


//input data
 M1        = 202;             //mass number
 M2        = 200;            // mass number
 Tc1       = 4.153;         // temperature in K
 alpha     = 0.5;


//formula
//m^alpha*(Tc)= conatant
// calculation
 Tc2    = ((M1^alpha)*Tc1)/(M2^alpha);


```

```
//result
mprintf('transition temperature =%3.2f.K\n',Tc2);

//
```

Scilab code Exa 5.26 To find critical temperature

```
//

// chapter 5 example 26

clc;
clear;

//input data
Tc1      = 2.1;                    //temperature in
   K
M1       = 26.91;
M2       =32.13;


//formula
//Tc*(M1^2) = constant
//calculation
Tc2        = (Tc1*(M1^(1/2)))/(M2^(1/2));


//result
mprintf('critical temperature =%3.2f.K\n',Tc2);

//
```

Scilab code Exa 5.27 To find critical temperature

```
//
// chapter 5 example 27

clc;
clear;

//input data
Hc1          =  1.41*10^5;        //critical fields in amp/m
Hc2          = 4.205*10^5;        // critical fields in amp/m
T1           = 14.1;              //temperature in K
T2           = 12.9;              // temperature in K
T3           = 4.2;               //temperature in K


//formula
//Hcn =Hc*((1-((T/Tc)^4)))
//calculation
Tc          =(((((Hc2*(T1^2))-(Hc1*(T2^2)))/(Hc2-Hc1)))^(1/2));           //temperature in K
Hc0         = Hc1/(1-((T1/Tc)^2));                           //critical field in A/m
Hc2         = Hc0*(1-(T3/Tc)^2);                             //critical field in A/m


```

```
//result
 mprintf('transition temperature =%3.2f K\n',Tc);
 mprintf('critical field  =%3.2e.A/m\n',Hc2);

//
  ==================================================================
```

Scilab code Exa 5.28 To find critical magnetic field

```
//
  ==================================================================

// Chapter 5 example 28


clc;
clear;


// input data
 Hc0          = 700000;        //critical field at 0 K
 T            = 4;         //temperature in K
 Tc           = 7.26;       //temperature in K


//calculation
  Hc    = Hc0*(1-(T/Tc)^2);


//result
 mprintf('critical field =%3.4e.A/m\n',Hc);
  mprintf(' Note: calculation mistake in texttbook
     in calculating Hc')

```

```
//
```

Scilab code Exa 5.29 To find critical current density

```
//
// Chapter 5 example 29

clc;
clear;


// input data
 Hc0          = 8*10^4;        //critical field
 T            = 4.5;           //temperature in K
 Tc           = 7.2;           //temperature in K
 D            = 1*10^-3;       //diameter in m


 //calculation
  Hc     = Hc0*(1-(T/Tc)^2);
  r      = D/2;       //radius in m
 Ic      = 2*%pi*r*Hc;


//result
 mprintf('critical current =%3.2f.A\n',Ic);

//
```

Scilab code Exa 5.30 To find transition temperature

```
//
   ==========================================================================
// Chapter 5 example 30

clc;
clear;


// input data
 Hc0        = 0.0306;        //critical field at 0 K
 T          = 2;        //temperature in K
 Tc         = 3.7;      //temperature in K


 //calculation
  Hc    = Hc0*(1-(T/Tc)^2);


//result
 mprintf('critical field =%3.4f tesla\n',Hc);

 //
   ==========================================================================
```

Scilab code Exa 5.31 To find transition temperature

```
//
   ==========================================================================
```

```
// Chapter 5 example 31

clc;
clear;


// input data
HcT        = 1.5*10^5;      // critical field for niobium at 0 K
Hc0        = 2*10^5;        // critical field for nobium at 0 K
T          = 8;             // temperature in K


//calculation
Tc     = T/((1-(HcT/Hc0))^0.5);


//result
mprintf('transition temperature =%3.2f.K\n',Tc);

//==============================================================
```

Scilab code Exa 5.32 To find transition temperature

```
//==============================================================
// chapter 5 example 32

clc;
clear;
```

```
//input data
 Hc1         =  0.176;        //critical fields
 Hc2         = 0.528;        // critical fields
 T1          = 14;         //temperature in K
 T2          = 13;        // temperature in K
 T3          = 4.2;

//formula
//Hcn =Hc*((1-((T/Tc)^4)))
//calculation
 Tc     =(((((Hc2*(T1^2))-(Hc1*(T2^2)))/(Hc2-Hc1)))
    ^(1/2));
 Hc0    = Hc1/(1-((T1/Tc)^2));
 Hc2    = Hc0*(1-((T3/Tc)^2));


//result
 mprintf('transition temperature =%3.2f K\n',Tc);
 mprintf(' critical field  =%3.2f.T\n',Hc2);

//
  ==================================================================
```

Scilab code Exa 5.33 To find critical current

```
//
  ==================================================================
//chapter 5 example 33

clc;
clear;
```

```
//input data
Hc          = 7900;            //magnetic field in A/m
r           = 2.0*10^-3;       //radius of super condutor in m


//calculation
I           = 2*%pi*r*Hc;      //critical current in A

//result
mprintf('critical current =%4f.A\n',I);
mprintf('Note: calculation mistake in textbook in calculation of I');

//==================================================================
```

Scilab code Exa 5.34 To find current

```
//==================================================================
//chapter 5 example 34

clc;
clear;


//input data
d            = 10^-3;             //diameter in m
```

```
 Bc           = 0.0548;           // Bc in T


 //calculation
 u0           = 4*%pi*10^-7;          //permiability m^2
 r            = d/2;                   //radius in m
 Ic           = (2*%pi*r*Bc)/u0;       //current in Amp

//result
mprintf('current =%3.2d Amp\n',Ic);

//==================================================================
```

Scilab code Exa 5.35 To find Londons penetration depth

```
//==================================================================
// chapter 5 example 35

clc;
clear;


//input data
 D           =8.5*10^3;                //density in kg/m^3
 W           =93;                      //atomic weight
 m           =9.1*10^-31;              //mass of electron in kilograms
 e           =2*1.6*10^-19;             //charge of
```

```
electron in coulombs
N           =6.023*10^26;           //avagadro number in (lb-mol)  1


//calculation
u0          =4*%pi*10^-7;
ns          =(D*N)/W;                        //in per m^3
lamdaL      =(m/(u0*ns*e^2))^(1/2);      //London's penetration depth in nm

//result
mprintf('penetration depth=%3.2f.nm\n',lamdaL/10^-9);

//==========================================================================
```

Scilab code Exa 5.36 To find penetration depth

```
//==========================================================================
// chapter 5 example 36

clc;
clear;


//input data
Tc      =7.2;   //temperature in K
lamda   =380;   //penetration depth in
T       =5.5;   //temperature in K

```

```

//calculation
lamdaT=lamda*((1-((T/Tc)^4))^(-1/2));  //penetration depth in

//result
mprintf('penetration depth=%3.1f.  \n',lamdaT);
mprintf(' Note: calculation mistake in textbook in calculating lamdaT');

//==================================================================================
```

Scilab code Exa 5.37 To find critical temperature of aluminium

```
//==================================================================================
// chapter 5 example 37

clc;
clear;


//input data
lamda1      = 16;       //penetration depth in nm
lamda2      = 96;       // penetration depth in nm
T1          = 2.18;      //temperature in K
T2          = 8.1;       // temperature in K

//formula
//lamdaT =lamda0*((1-((T/Tc)^4))^(-1/4))
//calculation
Tc          = ((((lamda2*(T2^4))-(lamda1*(T1^4)))/(
```

```
    lamda2-lamda1))^(1/4));


//result
 mprintf('critical temperature =%3.2f K\n',Tc);

 //
  ====================================================================
```

Scilab code Exa 5.38 To find wavelength

```
//
  ====================================================================
// chapter 5 example 38

clc;
clear;


//input data
 Eg      =30.5*1.6*10^-23;        //energy gap in eV
 h       =6.6*10^-34;             //planck's constant
    in (m^2)*kg/s
 c       =3.0*10^8;               //velocity of light
    in m


//formula
//Eg=h*v
//calculation
 v       = Eg/h;                  //velocity in m
 lamda   = c/v;                  //wavelength in m

```

```
//result
 mprintf('wavelength=%2e.m\n',lamda);

//
```

Scilab code Exa 5.39 To find energy gap and wavelength

```
//
//chapter 5 example 39

clc;
clear;


//input data
 k   =1.38*10^-23;
 Tc   =4.2;                //tempetrature in K
 h   =6.6*10^-34;          //planck's constant in (m
    ^2)*kg/s
 c   =3*10^8;              // velocity of light in m


//calculation
 Eg=(3*k*Tc);        //energy gap in eV
 lamda=h*c/Eg;        //wavelngth in m

//result
 mprintf('region of electromagnetic spectrum=%3.2e.m
    \n',lamda);

 //
```

Chapter 6

Electrical Conducting and Insulating materials

Scilab code Exa 6.1 To find temperature coefficient of resistance

```
//
// chapter 6 example 1

clc;
clear;

//input data

 R75    = 57.2;      //resistance at 75 C in ohm
 R25    = 55;        //resistance at 25 C in ohm
 t1     = 25;        //temperature in C
 t2     = 75         // temperature in C

//formula
//Rt = R0*(1+(alpha*t))
//calculation
 alpha  = (R25-R75)/((25*R75)-(75*R25));         //
```

```
temperature cofficient


//result
 mprintf('temperature coefficient =%3.5f.K^-1',alpha);

//
```

Scilab code Exa 6.2 To find temperature

```
//
// chapter 6 example 2

clc;
clear;

//input data
 R1     = 50;           //resistance in ohm at temperature 15 C
 R2     = 60;           // resistance in ohm temperature 15 C
 t1     = 15;           //temperature in  C
 alpha  = 0.00425;      //temperature coefficient of resistance


//formula
//Rt = R0*(1+(alpha*t))
//Rt1/Rt2 = R0*(1+(alpha*t1))/R0*(1+(alpha*t2))
//calculation
```

```
R           = R2/R1;
X           = 1+(alpha*t1);
t2          = ((R*X)-1)/alpha;



//result
mprintf('temperature coefficient of resistance =%3.2f C\n',t2);

//==================================================================================
```

Scilab code Exa 6.3 Tofind cold resistance and average temperature coefficient

```
//==================================================================================
// chapter 6 example 3

clc;
clear;

//input data
t1          = 20;                // temperature in C
alpha       = 5*10^-3;           //average temperature coefficient at 20 C
R1          = 8;                 //resistance in ohm
R2          = 140;               //resistaance in ohm


//calculation
```

```
t2      = t1+((R2-R1)/(R1*alpha));         //
    temperature in C

//result
mprintf('Hence temperature under normal condition
    is %3.2f C\n',t2);

//
```

Scilab code Exa 6.4 To find resistivity

```
//

//chapter 6 example 4
clc;
clear;


//input data
l      = 100;                          //length in cm
d      = 0.008;                       //diameter of wire
     in cm
R      = 95.5;                       //resistance in ohm
A     = %pi*0.004*0.004;          //cross-sectional
    area


//formula
//R=p*l/A
//calculation
p   = R*A/l;                       //;resistivity of
    wire in ohm-cm
```

```
//result
mprintf('resistivity=%3.2e ohm-m\n',p);

//
```

Scilab code Exa 6.5 To find percentage conductivity

```
//
//chapter 6 example 5

clc;
clear;


//input data
 R0       =17.5;              //resistance at 0 degree c in ohm
 alpha    =0.00428;           //temperature coefficient of copper in per degree c
 t        =16;                //temperature in degree


//formula
 Rt      = R0*(1+(alpha*t));           //resistance at 16 degree  C
 P        = (R0/Rt)*100;                             //percentage conductivity at 16 degree C


```

```
//result
mprintf('percentage conductivity=%3.2f.percent\n',P);

//
```

Scilab code Exa 6.10 To find resistance

```
//
// chapter 6 example 10
clc;
clear;


//input data
 l          = 60;                   //length in m
 r2         = 38/2;                // radius of outer cylinder in m
 r1         = 18/2;                //radius of inner cylinder in m
 p          = 8000;                //specific resistance in ohm-m

//calculation
 R  = (p/(2*%pi*l))*log(r2/r1);      //insulation resistance of liquid resistor  in ohm

//result
mprintf('insulation resistance=%3.0f ohm\n',R);

//
```

Scilab code Exa 6.11 To find resistivity

```
//
//chapter 6 example 11
clc;
clear;


//input data
 d1  =0.0018;// inner diameter  in m
 d2  =0.005;//outer diameter in m
 R   =1820*10^6;//insulation resistance in ohm
 l   =3000;//length in m


//formula
 r1  =d1/2;//inner radius  in m
 r2  =d2/2;//outer radius in m

//calculation
 p=2*%pi*l*R/log(r2/r1);//resistivity of dielectric
    in ohm-m

//result
 mprintf('resistivity=%3.3e.ohm-m\n',p);

//
```

Scilab code Exa 6.12 To find insulation resistance

```
//
    ===============================================================

// chapter 6 example 12
clc;
clear;


//input data
 d1 = 0.05;       //inner diametr in m
 d2 = 0.07;       //outer diameter in m
 l  = 2000;       //length in m
 p  = 6*10^12;     //specific resistance in ohm-m


//formula
 r1 = d1/2;       //radius in m
 r2 = d2/2;       //radius in m

//calculation
 R = (p/(2*%pi*l))*(log(r2/r1))        //insulation
    resistance

//result
 mprintf('insulation resistance =%1e.ohm\n',R);
 mprintf(' Note: calculation mistake in textbook in
    calculating insulating resistance');

//
    ===============================================================
```

Scilab code Exa 6.13 To find capacitance

```
//
   ==========================================================

// chapter 6 example 13

clc;
clear;


//input data
 a      = 110*10^-3;                          //area in m^2
 d      = 2;                                 //thickness in
     mm
 er     = 5;                                //relative
     permitivity
 E      = 12.5*10^3;                        //electric field
     strength in V/mm
 e0     = 8.854*10^-12;                      //charge of
     electron in coulombs


//calculations
 A      = a*a;                                  //area in m
     ^2
 C      = e0*((er*A)/(d*10^-3))                 //
     capacitance in F
 V      = E*(d);
 Q      = (C)*(V)                           //charge on
     capacitor in C

// result
 mprintf('capacitance =%3.2e.F\n',C);
```

```
mprintf(' charge=%3.4e C\n',Q);

//
```

Scilab code Exa 6.14 To find charge and electric flux and flux density and electric field strength

```
//
// chapter 6 example 14


clc;
clear;


//input data
I        = 15*10^-3;                //current in A
t        = 5;                        //time in s
A        = 120*10^-3*120*10^-3;     //area in m^2
V        = 1000;                    //voltage in
   volts
d        = 10^-3;                   //thickness in m

//calculation
Q       = I*t;                      //charge on
   capacitor in C
//since charge and electric field are equal
phi      = Q;                        //electric flux
    in mc
D       = Q/A;                      //electric flux
   density in c/m^2
```

```
 E       = V/d;                          //electric field strength in dielectric

//result
mprintf('charge=%3.2e.C\n',Q);
mprintf(' electric flux=%4.3f.mc\n',phi);
mprintf(' electric flux density=%3.4f.c/m^2\n',D);
mprintf(' electric field strength=%2.3e.V/m\n',E);

//
```

Scilab code Exa 6.15 To find capacitance

```
//
// chapter 6 example 15

clc;
clear;


//input data
 n         = 12;                        //number of plates
 er        = 4;                         //relative permitivty
 d         = 1.0*10^-3;                 //distance between plates in m
 A        = 120*150*10^-6;              //area in m^2
 e0       = 8.854*10^-12;               // in F/m

//calculation
 c       = (n-1)*e0*er*A/d;             //capacitance in
```

```
F

//result
mprintf('capacitance=%3.4e.F\n',c);

//
```

Scilab code Exa 6.16 To find thickness of insulation

```
//

// chpter 6 example 16

clc;
clear;


//input data
e0     = 40000;          //dielectric strength  in volts/m
d      = 33000;          //thickness in kV
t      = d/e0;           //required thickness of insulation in mm

//result
mprintf('thickness=%4f.mm\n',t);

//
```

Scilab code Exa 6.17 To find area and breakdown voltage

```
//
    ========================================================================
// chapter 6 example 17


clc;
clear;


//input data
 C      = 0.03*10^-6;           //capacitance in F
 d      = 0.001;               //thickness in m
 er     = 2.6;                 //dielectric constant
 e0     = 8.85*10^-12;         //dielectric strength
 E0     = 1.8*10^7

//formula
//C=e0*er*A/d
//e0=v/d
//calculation
 A      = (C*d)/(e0*er);        //area of dielectric
     needed in m^2
 Vb      = E0*d;                //breakdown voltage
    in m

//result
mprintf('area=%3.2f.m^2\n',A);
mprintf(' breakdown voltage=%3.1e.V\n',Vb);

//
    ========================================================================
```

Scilab code Exa 6.18 To find dielectric loss

```
//

// chapter 6 example 18


clc;
clear;


//input data
 C        = 0.035*10^-6;                          //capacitance in F
 tangent     = 5*10^-4;                              //power factor
 f        = 25*10^3;                              //frequency in Hz
 I        = 250;                                  //current in A


//calculation
 V        = I/(2*%pi*f*C)                      //voltage across capacitor in volts
 P        = V*I*tangent;                      //dielectric loss in watts

//result
mprintf('dielectric loss=%3.2f.watts\n',P);

//
```

Scilab code Exa 6.19 To find area

```
//
// chapter 6 exmple 19

clc;
clear;

//input data

 Q        = 20*10^-6;                //charge of
    electron in coulomb
 V        = 10*10^3;                 //potential in
    V
 e0       = 8.854*10^-12;           //absolute
    permitivity
 d        = 5*10^-4;                //separation
    between plates in m
 er       = 10;                    //dielectric
    constant

//formula
//Q=CV
//C=er*e0*A/d
 C       = Q/V;
 A       = (C*d)/(er*e0);          //area in m^2

//result
mprintf('area=%1e.m^2\n',A);

```

```
//==========================================================================
```

Scilab code Exa 6.20 To find thermal cnductivity

```
// chapter 6 example 2o

clc;
clear;


//input data
 n  = 3.0*10^28;        //number of electrons per m^3
 t   = 3*10^-14;      //time in s
 m   = 9.1*10^-31;     //mass of electron in kg
 L   = 2.44*10^-8;         //lorentz number in ohm W/K^2
 T  = 330;             //temperature in kelvin
 e   = 1.6*10^-19;         //charge of electron


//calculation
 sigma  = n*e^2*t/m;     //electrical conductivity in (ohm-m)^-1

//result
 mprintf('electrial conductivity=%3.2e.(ohm-m)^-1\n',sigma);
```

```
810
```

```
622
```

Chapter 7

Junction Resistor Transistors and Devices

Scilab code Exa 7.2 To find change in temperature

```
//
// Chapter 7 example 2

clc;
clear;

//variable declaration
//given Is2/Is1 =150
//Is2/Is1 =2^(T2−T1)/10
//dT=10ln(I)/ln(2)
 I  = 150;



// Calculations
dT  = 10*log(I)/log(2);        // increase in
   temperature in  C
```

```

// Result
mprintf('Increase in temperature necessary to increase Is by a factor by 150 is %3.2f  C',dT);

//
```

Scilab code Exa 7.3 To find current

```
//

// Chapter 7 example 3

clc;
clear;

// Variable declaration
Io  = 0.25*10^-6;       // large reverse biased current in A
V   = 0.12;             // applied voltage in V
Vt  = 0.026;            // Volt-equivalent of temperature in V

// Calculations
I   = Io*(exp(V/Vt)-1);     // current in A

// Result
mprintf('Current flowing through germanium diode = %g uA',I*10^6);

//
```

Scilab code Exa 7.4 To find diffusion coefficients

```
//
    ====================================================================
// Chapter 7 example 4

clc;
clear;

// Variable declaration
k    = 1.38*10^-23;          // boltzmann constant (m
   ^2)*(kg)*(s^-2)*(K^-1)
e    = 1.6*10^-19;           // charge of electron in
    coulombs
ue   = 0.19                  // mobility of electron
    in m^2.V^-1.s^-1
uh   = 0.027;                // mobilty of holes in m
   ^2.V^-1.s^-1
T    = 300;                  // temperature in K

// Calculations
Dn   = (k*T/e)*ue;           //diffusion constant of
   electrons in cm^2/s
Dh   = (k*T/e)*uh;           // diffusion constant of
    holes in cm^2/s


// Result
mprintf('Diffusion co-efficients of electrons = %g m
   ^2/s\n Diffusion co-efficients of holes = %g m^2/
   s',Dn,Dh)

```

```
//
```

Scilab code Exa 7.6 To find resistance of diode

```
//

// chapter 7 example 6

clc;
clear;

// Variable declaration
I1  = 20;           // current in ma
V1  = 0.8;          // vtg in volts
V2  = 0.7;          // vtg in volts
I2  = 10;           // current in ma
v3  = -10;
I3  = -1*10^-6;     // current

// Calculations
R   = (V1 - V2)/(I1 - I2);
Vreb  = v3/I3;

// Result
mprintf('a. resistance = %d ohm\n Vreb = %3.1e ohm',
   R*10^3,Vreb);

//
```

Scilab code Exa 7.7 To find diffusion constant

```
//

// Chapter 7 example 7

clc;
clear;

// Variable Declaration
T   = 300;           // temp in kelvin
k   = 1.38*10^-23;   // Boltzmann constant (m^2)*(kg)*(s^-2)*(K^-1)
e   = 1.602*10^-19;  // charge of electron in coulombs
ue  = 3650;          // mobility of electrons
uh  = 1720;          // mobility of holes

// Calculations
De  = (ue*k*T)/e;        // diffusion constant of electrons in cm^2/s
Dh  = (uh*k*T)/e;        // diffusion constant of holes in cm^2/s

// Result
mprintf('Diffusion constant of electrons = %3.1f cm^2/s\n Diffusion constant of electrons = %3.1f cm^2/s',De,Dh);

//
```

Scilab code Exa 7.8 To find pinch off voltage

```
//
    ==========================================================================

// chapter 7 example 8

clc;
clear;

// Variable Declaration
p    = 2;         // resistivity in ohm-m
er   = 16;        // relative dielectrivity of Ge cm
   ^2/s
up   = 1800;       // mobility of holes in cm^2/s
e0   = 8.85*10^-12;       //permitivity in (m^-3)*(kg
   ^-1)*(s^4)*(A^2)
a    = 2*10^-4;       //channel height in m

// Calculations
 qNa   = 1/(up*p);
 e     = e0*er;            //permitivity in F/cm
 Vp    = (qNa*(a^2))/(2*e);        // pinch-off
    voltage in V

// Result
mprintf('Pinch-off voltage = %3.4e V\n',Vp);
mprintf(' Note:calculation mistake in text book ,e
   value is taken as 14.16*10^-12 instead of
   141.6*10^-12');

//
    ==========================================================================
```

Scilab code Exa 7.9 To find pinch off voltage

```
//
//chapter 7 example 9
clc;
clear;


//input data
 a        = 3.5*10^-6;              //channel width in m
 N        = 10^21;                      //number of electrons in electrons/m^3
 q        = 1.6*10^-19;           //charge of electron in coulombs
 er       = 12;                   //dielectric constant F/m
 e0       = 8.85*10^-12;                        //dielectric constant F/m


//calculation
 e       = (e0)*(er);                   //permitivityin F/m
 Vp      = (q*(a^2)*N)/(2*e);          //pinch off voltage in V


//result
 mprintf('pinch off velocity =%2f V\n',Vp);

//
```

Scilab code Exa 7.10 To find transconductance

```
//
//chapter 7 example 10

clc;
clear;


//input data
IDSS        = 10;                   //current in mA
IDS         =2.;                    // current in mA
Vp          = -4.0;                 //pinch off voltage
    in V

//formula
//IDS    = IDSS*((1-(VGS/Vp))^2)
//calculation
VGS         = Vp*(1-(sqrt(IDS/IDSS)));
gm          = ((-2*IDSS)/Vp)*(1-(VGS/Vp));


//result
mprintf('transconductance =%3.2f.m*A/V\n',gm);

//
```

Scilab code Exa 7.11 To find drain current

```
//==================================================================
//chapter 7 example 11

clc;
clear;


//input data
 VGS        = -3;               //pinch off voltage in V
 IDSS         =10*10^-3;                //  current in A
 Vp           =  -5.0;                //pinch off voltage in V


//calculation
IDS    =  IDSS*((1-(VGS/Vp))^2);


//result
 mprintf('current =%3.2f.A\n',IDS/10^-3);

//==================================================================
```

Scilab code Exa 7.12 To find transconductance

```
//
//chapter 7 example 12

clc;
clear;


//input data
 IDS         = 2*10^-3;                  //current in mA
 IDSS        = 8*10^-3;                   // current in mA
 Vp          = -4.5;                //pinch off voltage in V
 VGS1        = -1.902;              //pinch off voltage when IDS =3*10^-3 A

//formula
//IDS    = IDSS*((1-(VGS/Vp))^2)
//calculation
 VGS         = Vp*(1-(sqrt(IDS/IDSS)));
 gm          = ((-2*IDSS)/Vp)*(1-(VGS1/Vp));


//result
 mprintf('transconductance =%3.2f.mS\n',gm/10^-3);

//
```

Scilab code Exa 7.13 To find resistance

```
//
```

```
//chapter 7 example 13


clc;
clear;


//input data
 VGS         = 26;                  //gate source
    voltage in V
 IG          = 1.6*10^-9;         //gate current in A


//calculation
 R           = VGS/IG;            //gate to current
    resistance in ohms


//result
mprintf('resistance =%3.2e.ohms\n',R);

//
```

Scilab code Exa 7.14 To find transconductance

```
//

//chapter 7 example 14

clc;
```

```
clear;


//input data
 ID1            = 1;                   //current in A
 ID2            = 2.1;                    // current in A
 VGS1           = 3.0;                 //pinch off voltage in V
 VGS2           = 3.5;                 //pinch off voltage in V


//calculation
 dID           = ID2-ID1;
 dVGS          = VGS2-VGS1;
 gm            = (dID*10^-3)/dVGS;


//result
 mprintf('transconductance =%3.2e mho\n',gm);
 mprintf('Note:wrong answer in textbook');

//=================================================================
```

Scilab code Exa 7.15 To find drain resistance and transconductance and amplification fector

```
//=================================================================
//chapter 7 example 15

clc;
```

```
clear;


//input data
 ID1          = 8;                          // drain current in mA
 ID2          = 8.3;                        //drain current in mA
 VDS1         = 5;                          //drainn source voltage in V
 VDS2         = 14;                         //drain source voltage in V
 ID3          = 7.1;                        //drain current when VDS constant VGS change
 ID4          = 8.3;                        //drain current when VDS constant VGS change
 VGS1          = 0.1;                       //drain source voltage in V
 VGS2          = 0.4;                       //drain source voltage in V

//calculation
 dID1         = ID2-ID1;
 dVDS         = VDS2-VDS1;
 rd           = dVDS/dID1;                  //ac drain resistance
 dID2         = ID4-ID3;
 dVGS         = VGS2-VGS1;
 gm           = dID2/dVGS;                  //transconductance
 u            = rd*gm;                      //amplification factor


//result
 mprintf('ac drain resistnce =%3.2d.k-ohms\n',rd);
 mprintf('transconductance =%3.2d.u ohms\n',gm/10^-3);
```

```
 mprintf('amplification factor=%3.2f.\n',u);

//
```

Scilab code Exa 7.16 To find transconductance

```
//
// chapter 7 example 16


clc;
clear;

//input data
 u          = 100;              //amplification factor
 rd         = 33*10^3;          //drain resistance in ohms


//calculation
gm          = u/rd;         //transconductance in mhos

//result
 mprintf('transconductance =%3.2f mmhos\n',gm/10^-3);
 printf('Note:transconductance value is wrongly printed in terms of umhos');

//
```

Chapter 8

Mechanism of Conduction in Semiconductors

Scilab code Exa 8.1 To find kinetic energy and momenta

```
//

// chapter 8 example 1

clc;
clear;

// Variable declaration
Ephoton = 1.5;           // energy of photon in eV
Eg      = 1.4;           // energy gap in eV
m       = 9.1*10^-31;    // mass of electron in kg
e       = 1.6*10^-19;       //charge ofelectro in coulombs
me_GaAs = 0.07;              //times of electro mass in kilograms
mh_GaAs = 0.068;              //times of electro mass in kilograms

```

```
// Calculations
Eke      = Ephoton - Eg;                    //energy on eV
pe       = sqrt(2*m*me_GaAs*Eke*e)      // momentum of
    electrons  in kg m/s
ph       = sqrt(2*m*mh_GaAs*Eke*e)      // momentum of
    electrons in kg m/s


// Result
mprintf('Kinetic Energy = %3.1f eV\n Momentum of
   electrons = %3.1e kg m/s\n Momentum of holes = %3
   .1e kg m/s',Eke,pe,ph);

//
   ==========================================================
```

Scilab code Exa 8.2 To find thermal equilibrium hole concentration

```
//
   ==========================================================

// chapter 8 example 2

clc;
clear;

// Variable Declaration
T1   = 300;                  // temperature in kelvin
nv   = 1.04*10^19;          //in cm^-3
T2   = 400;                 //temperature in K
fl   = 0.25;              // fermi level position in eV

// Calculations
Nv   = (1.04*10^19)*(T2/T1)^(3/2);            //Nv at
```

```
400 k in cm^-3
kT  = (0.0259)*(T2/T1);                          //kT in eV
po  = Nv*exp(-(fl)/(kT));                        //hole oncentration in cm^-3


// Result
mprintf('Thermal equilibrium hole concentration = %3.2e cm^-3\n ',po);
mprintf('Note: Calculation mistake in textbook Nv is not multiplied by exponentiation');

//==========================================================================
```

Scilab code Exa 8.3 To find intrinsic carrier concentration

```
//==========================================================================
// Chapter 8 example 3

clc;
clear;

// Variable declaration
Nc  = 3.8*10^17;            //constant in cm^-3
Nv  = 6.5*10^18;           //constant in cm^-3
Eg  = 1.42;                // band gap energy in eV
KT1 = 0.03885;            // kt value at 450K
T1  = 300;                //temperature in K
T2  = 450;                //temperature in K

```

```
// calculation
n1i  = sqrt(Nc*Nv*exp(-Eg/0.0259));           // intrinsic carrier concentration in cm^-3
n2i  = sqrt(Nc*Nv*((T2/T1)^3) *exp(-Eg/KT1));      // intrinsic carrier conc at 450K in cm^-3

// Result
mprintf('Intrinsic Carrier Concentration at 300K = %3.2e cm^-3\n Intrinsic Carrier Concentration at 300K = %3.2e cm^-3',n1i,n2i)
mprintf('\n Note : Calculation mistake in textbook in finding carrier conc. at 450K')


// ==========================================================================
```

Scilab code Exa 8.4 To find position of intrinsic fermi level

```
// ==========================================================================
// Chapter 8 example 4

clc;
clear;

// variable declaration

mh  = 0.56;               //masses interms of m0
me  = 1.08;               //masses interms of m0
t   = 27;                 //temperature in  C
k   = 8.62*10^-5;

```

```
// Calculations
T   = t+273;                        //temperature in K
fl  = (3/4)*k*T*log(mh/me);             //position of
   fermi level in eV

// result
mprintf('The position of Fermi level with respect to
    middle of the bandgap is %3.1f meV',fl/10^-3)

//
   ================================================================
```

Scilab code Exa 8.5 To find donor binding energy

```
//
   ================================================================

// chapter 8 example 5

clc;
clear;

// variable declaration
mo  = 9.11*10^-31;          // mass of electron
   inkilograms
e   = 1.6*10^-19;           // charge of electron in
    coulombs
er  = 13.2;                 //relative permitivity
   in F/m
eo  = 8.85*10^-12;          // permitivity in F/m
h   = 6.63*10^-34;          // plancks constant J.s
me  = 0.067*mo;

```

```
// Calculations

E   = (me*e^4)/(8*(eo*er)^2 * h^2 * e);          // energy in eV

// Result
mprintf('Donor binding energy = %3.4f eV',E);

//
```

Scilab code Exa 8.6 To find position of fermi level

```
//
// Chapter 8 example 6

clc;
clear;

// Variable declaration
no      = 10^17     // doping carrier conc
ni      = 1.5*10^10;         // intrinsic concentration
kT      = 0.0259

// Calculations
po      = (ni^2)/no
fl      = kT*log10(no/ni)

// Result
mprintf('Equlibrium hole concentration = %3.2e cm^-3\n Position of fermi energy level = %3.3f eV',
```

```
    po,fl)

//
```

Scilab code Exa 8.7 To find electrical conductivity

```
//
// Chapter 8 example 7

clc;
clear;

// Variable declaration

k   = 8.62*10^-5;             //in eV/K
Eg  = 1.10;                   //energy in eV
 t1 = 200;                    //temperature in  C
 t2 = 27;                    //temperature in  C
 psi = 2.3*10^3;

// Calculations
// sigma = sigmao*exp(-Eg/(2kT))
// k     = sigma_473/sigma_300;
 t3  = t1+273;                //temperature in K
 t4  = t2+273;                 //temperature in K
 k1        = exp((-Eg)/(2*k*t3));          //
    electrical conductivity in cm^-1.m^-1
 k2        = exp((-Eg)/(2*k*t4));          //
    electrical conductivity in cm^-1.m^-1
 k         = k1/k2;
 pm=      k/psi;
```

```

// Result

mprintf('electrical conductivity of pure silicon = %3.2e.ohm^-1.m^-1\n',k);
mprintf('Note:calculation mistake in electrical conductivity,and units of conductivity');

//
```

Scilab code Exa 8.8 To find resistivity

```
//
// Chapter 8 example 8

clc;
clear;

// Variable declaration
ni  = 2.5*10^19;              // carrier density in per m^3
q   = 1.6*10^-19;             // charge of electron in coulombs
un  = 0.35;                   //mobility of electrons in m^2/V-s
up  = 0.15;                   //mobility of electrons in m^2/V-s

// Calculations
sigma = ni*q*(un + up);            //conductivity in per ohm-m
```

```
p     = 1/sigma;                    //resistivity in ohm-m


// Result
mprintf('Resistivity = %3.1f ohm-m',p);


//
```

Scilab code Exa 8.9 To find intrinsic carrier density

```
//

// chapter 8 example 9

clc;
clear;

// Variable declaration
p  = 3.16*10^3;              // resistivity ohm-m
e  = 1.6*10^-19;             // charge of electron in coulombs
ue = 0.14;                   //mobility of electrons in m^2/V-s
uh = 0.05;                    //mobility of holes in m^2/V-s

// Calculations

n  = 1/((p*e)*(ue + uh));            //carrier density  in perm^3
```

```

// Result
mprintf('Intrinsic Carrier Concentration = %3.2e /m^3',n);

//==========================================================================
```

Scilab code Exa 8.10 To find conductivity

```
//==========================================================================
// chapter 8 example 10

clc;
clear;

// Variable declaration
p   = 5.32*10^3;          // density of germanium
Nav = 6.023*10^26;        // Avagadros number
AW  = 72.59;              // atomic wt
ni  = 1.5*10^19           // carrier density
ue  = 0.36
uh  = 0.18
e   = 1.6*10^-19

// calculations
N   = (p*Nav)/AW          // no of germanium atoms per unit volume
Nd  = N*10^-6             // no of pentavalent impurity atoms/m^3
f   = Nd/ni
nh  = ni^2/Nd             // hole conc
```

```
sigma = e*((Nd*ue)+(nh*uh))

// Result
mprintf('The factor by which the majority conc. is more than the intrinsic carrier conc = %d\n Hole concentration = %3.1e /m^3\n Conductivity = %d /ohm-m',f,nh,sigma)

//
```

Scilab code Exa 8.11 To find carrier density

```
//
// chapter 8 example 11

clc;
clear;

// variable declaration
p   = 5*10^-3;          // resistivity in ohm-m
ue  = 0.3;              // electron mobility m^2/volt-s
uh  = 0.1;              // hole mobility m^2/volt-s
e   = 1.6*10^-19        // charge of electron in coulombs

// calculations
sigma   = 1/p;                      // conductivity in per ohm -m
n       = sigma/(e*(ue + uh));   // carrier density per m^3
```

```

// Result
mprintf('Carrier Density = %3.1e /m^3',n);

//
```

Scilab code Exa 8.12 To find drift velocity

```
//
// chapter 8 example 12

clc;
clear;

// Variable declaration
Jd  = 500;      // current density A/m^2
p   = 0.05      // resistivity in ohm-m
l   = 100*10^-6     // travel length m
ue  = 0.4;          // electron mobility m^2/Vs
e   = 1.6*10^-19;   // charge of electron in coulombs


// Calculations
ne  = 1/(p*e*ue);       //iin per m^3
vd  = Jd/(ne*e);             //drift velocity in m/s
t   = l/vd;                  //time teken in s

// result
mprintf('Drift velocity = %d m/s\n time = %e s',vd,t);
```

```
//
```

Scilab code Exa 8.13 To know about changes in temperature

```
//

// Chapter 8 example 13

clc;
clear;

T         = 300;                    // room temperature
     in K
psi1       =100;                   //
psi2     = 130;



// T+dT = 1/((1/T)-(2k/Eg)log1.3)
// T+dT = 305.9
dT  = 305.9 - 300;


mprintf('Therefore %3.1f K rise in temperature will
   lead to a rise of 30 percent in conductivity',dT)

//
```

Scilab code Exa 8.14 To find conductivity

```
//
// Chapter 8 example 14

clc;
clear;

// variable declaration
v   = 5;            // voltage in volts
r   = 10;           // resistance in k-ohm
J   = 60;           // current density in A/cm^2
E   = 100;          // electric field in V.m^-1
Nd  = 5*10^15;      //in cm^-3
up  = 410;          // approx hole mobility cm^2/V-s
Na  = 1.25*10^16;   // approx in cm^-3
e   = 1.6*10^-19;   // charge of electron in coulombs

// Calculations
I   = v/r;              // total current A
A   = I/J               // cross sectional area cm^2
L   = v/E               // length of resistor cm
sigma = L/(r*A);        //conductivity in (ohm-cm)^-1
sigma_comp = e*up*(Na - Nd);        //conductivity in (ohm-cm)^-1

// Result
mprintf('Conductivity of the compensated p-type semiconductor is %3.3f',sigma_comp);

```

```
//
```

Scilab code Exa 8.15 To find diffusion current density

```
//
// chapter 8 example 15

clc;
clear;

// Variable declaration
e   = 1.6*10^-19;        // charge of electron in coulombs
Dn  = 250;               // electron diffusion co-efficient cm^2/s
n1  = 10^18              // electron conc. in cm^-3
n2  = 7*10^17            // electron conc. in cm^-3
dx  = 0.10               // distance in cm

// Calculations
Jdiff   = e*Dn*((n1-n2)/dx);    // diffusion current density A/cm^2

// Result
mprintf('Diffusion Current Density = %d A/cm^2',Jdiff);

//
```

Scilab code Exa 8.16 To find wavelength

```
//
    ================================================================
// Chapter 8 example 16

clc;
clear;

// Variable declaration
e    = 1.6*10^-19        // charge of electron in
    coulombs
Eg   = 0.75;              // bandgap energy eV
c    = 3*10^8;            // velocity of light in m
h    = 6.62*10^-34        // plancks constant in J.s

// Calculations
lamda   = (h*c)/(Eg*e)      // wavelength in

// Result
mprintf('Wavelength at which Ge starts to absorb
    light = %d   ',lamda*10^10);

//
    ================================================================
```

Scilab code Exa 8.17 To find cut off wavelength

```
//
    ================================================================
```

```
// chapter 8 example 17

clc;
clear;

// Variable Declaration

  Eg         = 1.35*1.6*10^-19;          //energy in eV
  h          = 6.63*10^-34;              //plancks constant in J.s
  c          = 3*10^8;                   //velocity in m

  //calculation
  lamda      = (h*c)/Eg;                 //wavelength in m

  //result
  mprintf('cutoff wavelength =%3.2e m\n',lamda);

  //
```

Scilab code Exa 8.18 To find energy

```
//

// Chapter 8 example 18

clc;
clear;

```

```
// Variable declaration
h    = 6.62*10^-34         // plancks constant J.s
c    = 3*10^8;             // velocity of light in m
lamda = 1771*10^-9;        // wavelengthg in m
e    = 1.6*10^-19          // charge of electron in coulombs

// Calculations
Eg   = (h*c)/(lamda*e);       // bandgap energy eV

// Result
mprintf('bandgap energy = %3.3f eV',Eg);

// ====================================================================
```

Scilab code Exa 8.19 To find hall voltage

```
// ====================================================================
// Chapter 8 example 19

clc;
clear;

// Variable declaration
Nd   = 10^21;          // donar density per in  m^3
H    = 0.6;            // magnetic field in T
J    = 500;            // current density A/m^2
d    = 3*10^-3;        // width in m
e    = 1.6*10^-19          // charge of electron coulombs

```

```
// Calculations
Ey   = (J*H)/(Nd*e)         // field in V/m
vh   = Ey*d;                // hall voltage V

// Result
mprintf('Hall Voltage = %3.1f mV',vh*10^3);

//
```

Scilab code Exa 8.20 To find current density

```
//

// Chapter 8 example 20

clc;
clear;

// Variable declaration
e    = 1.6*10^-19           // charge of electron
Rh   = -0.0125;             // hall co-efficient
ue   = 0.36;                // electron mobility
E    = 80;                  // electric field

// Calculations
n    = -1/(Rh*e)
J    = n*e*ue*E             // current density

// Result
mprintf('Current density = %d Ampere/m^2',J);

//
```

Scilab code Exa 8.21 To find hall coefficient

```
//

// Chapter 8 example 21

clc;
clear;

// Variable declaration
p    = 0.00893;       // resistivity  in ohm-m
Hz   = 0.5;           // field in weber/m^2
Rh   = 3.66*10^-4;    // hall co-efficient hall
   coefficient in m^3

// Calculations

u    = Rh/p;                    //mobility of charge
   cerrier in m^2*(V^-1)*s^-1
theta_h = (atan(u*Hz))*(180/%pi);       // hall angle
    in degrees

// Result
mprintf('Hall angle = %3.4f degrees',theta_h);

//
```

Chapter 9

Mechanical Properties of Materials

Scilab code Exa 9.1 To find elongation

```
//
// chapter 9 example 1
clc
clear

// Variable declaration
F   = 8482;      // Tensile force in newtons
lo  = 0.30;      // length of steel wire in cm
Y   = 207*10^9;  // Youngs modulus of steel Gpa
r   = 3*10^-3;   // radius of steel wire  in m
v   = 0.30;      // poisson ratio

// Calculations

dl  = (F*lo)/(Y*%pi*r^2);        // elongation in mm
e1  = dl/lo                      // longitudanl
   strain
```

```
e2  = v*e1                          // lateral strain
dr  = e2*r;                         // lateral contraction in m

// Result
mprintf('Elongation = %3.3f mm\n Lateral contraction = %3.1f um',dl/10^-3,dr/10^-6);

// ==================================================================
```

Scilab code Exa 9.3 To find stress

```
// ==================================================================
// chapter 9 example 3

clc
clear

// Variable declaration

P   = 400;            // tensile force in newtons
d   = 6*10^-3;        // diameter of steel rod m

// Calculations
r   =d/2;
E_stress = P/((%pi/4)*r*r);         //e_stress in N/m^2

// Result

mprintf('Engineering stress = %3.2f MPa',E_stress
```

```
/10^6);

//
```

Scilab code Exa 9.4 To find strain

```
//

// chapter 9 example 4
clc
clear

// Variable declaration
Lf  = 42.3;          // guage length after strain mm
Lo  = 40;            // guage length in mm

// Calculations
e   = ((Lf - Lo)/Lo)*100      // Engineering Strain
   in percent

// Result
mprintf('Percentage of elongation = %3.2f percent',e
   );

//
```

Scilab code Exa 9.5 To find ductility

```
//
// chapter 9 example 5

clc;
clear;

// Variable declaration

dr  = 12.8       // original diameter of steel wire
   in mm
df  = 10.7;      // diameter at fracture in mm

// Calculations

percent_red = (((%pi*dr*dr) - (%pi*df*df))/(%pi*dr*
   dr))*100;


// Result

mprintf('Percent reduction in area = %3.2f percent',
   percent_red);

//
```

Chapter 10

Mechanical Properties of Materials

Scilab code Exa 10.1 To find wavelength

```
//
// chapter 10 example 1

clc;
clear;

// Variable declaration
 E2      = 5.56*10^-19;          // Higher Energy level in J
 E1      = 2.36*10^-19;          // Lower Energy level in J
 h       = 6.626*10^-34;         // plancks constant in J.s
 c       = 3*10^8;               // velocity of light in m

// Calculations
```

```
 dE    = E2 - E1;                  // Energy difference in J
 lamda = (h*c)/dE;                 // wavelength in m


// Result

mprintf('Wavelength of the photon = %d   \n',lamda/10^-10);
mprintf(' The colour of the photon is red')

//
```

Scilab code Exa 10.2 To find maximum wavelength of opaque

```
//

// chapter 10 example 2
clc
clear

// Variable declaration

 h   = 6.63*10^-34;          // plancks constant in J.s
 c   = 3*10^8;               // velocity of light in m
 E   = 5.6;                  // bandgap in eV
 e   = 1.6*10^-19;           // charge of electron coulombs

// Calculations
```

```
lamda     = (h*c)/(E*e)          // wavelength in m

// output

mprintf('Maximum Wavelength for which diamond is
   opaque is Imax = %d    ',lamda/10^-10);
mprintf('\n Note: Imax is wrongly printed as 220
    in textbook');

//
   ==========================================================================
```

Scilab code Exa 10.3 To find composition

```
//
   ==========================================================================
// chapter 10 example 3

clc;
clear;

// Variable declaration

h    = 6.63*10^-34;              // plancks constant
c    = 3*10^8;                   // velocity of light
lamda = 0.6*10^-6;               // wavelength in m
e    = 1.6*10^-19;               // charge of electron
EGap = 2.25                      // energy in eV
EGas = 1.42                      // energy in eV

// Calculations

```

```
E    = (h*c)/(lamda*e)              // Energy in eV
p_change = (EGap - EGas)/100;       // rate of energy gap
x    = (E-EGas)/p_change            // mol % og GaP to be added to get an energy gap of E

// Result

mprintf('Energy of radiation = %3.4f eV\n Rate of energy gap varies with addition of GaP is %3.5f\n mol percent to be added to get an energy gap of %3.4f eV is %3.1f mol percent',E,p_change,E,x);

// ==================================================================================
```

Scilab code Exa 10.4 To find energy of metastable state

```
// ==================================================================================
// chapter 10 example 4
clc;
clear;

// Variable declaration

h    = 6.63*10^-34;          // plancks constant in J.s
c    = 3*10^8;               // velocity of light in m
lamda = 1.1*10^-6;           // wavelength in m
e    = 1.6*10^-19;           // charge of electron
```

```
    in coulombs
 E2  = 0.4*10^-19;            // energy level in
    joules


// Calculations
 E3  = E2 + (h*c)/(lamda);          //energy in J

// Result
 mprintf('Energy of the metastable state E3 = %3.1e
    J',E3);

// 
   ==========================================================
```

Scilab code Exa 10.5 To find number of optical modes

```
// 
   ==========================================================
// chapter 10 example 5
clc
clear

// Variable declaration
c    = 3*10^8;                // velocity of light in
   m
L    = 1.5;                   //length in m
n    = 1.0204;                // refractive index
BW   = 1.5*10^9;              // Bandwidth in Hz

// Calculations
dV   = c/(2*L*n);              //frequency in Hz
N    = BW/dV;                 // Number of optical
```

```
    nodes

// Result

mprintf('Number of Optical modes = % d',N);

//
```

Scilab code Exa 10.6 To find numerical aperture

```
//
// chapter 10 example 6

clc
clear

// Variable declaration
n1  = 1.55;          // refractive index of core
n2  = 1.53;          // refractive index of cladding


// Calculations

NA  = sqrt(n1^2 - n2^2);


// Result
mprintf('Numerical aperture = %3.3f',NA);

//
```

Scilab code Exa 10.7 To find critical angle

```
//
    ==========================================================================

// chapter 10 example 7
clc
clear

// Variable declaration
 n1      = 1.33;          //refractive index of water
 n2      = 1;             // refractive index of air

// Calculations
 theta_c = asin((n2/n1))
 theta_c_deg = theta_c*(180/%pi);        // radian
    to degree conversion

// Result
mprintf('For angles above %3.2f degrees , there will
    be total internal reflection in water',
   theta_c_deg );

//
    ==========================================================================
```