

Scilab Textbook Companion for
Modern Physics for Engineers
by S. P. Taneja¹

Created by
Piyush Ahuja
B.Tech
Electrical Engineering
NIT kuruKshetra
College Teacher
None
Cross-Checked by
K. V. P. Pradeep

June 15, 2014

¹Funded by a grant from the National Mission on Education through ICT, <http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab codes written in it can be downloaded from the "Textbook Companion Project" section at the website <http://scilab.in>

Book Description

Title: Modern Physics for Engineers

Author: S. P. Taneja

Publisher: R. Chand & Co, New Delhi

Edition: 7

Year: 2011

ISBN: 81-8045-031-7

Scilab numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

AP Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

Contents

List of Scilab Codes	5
1 Interference of Light	9
2 diffraction of light	24
3 polarization of light	34
4 Laser	40
5 Fiber Optics	42
6 oscillatory motion	45
7 electromagnetic waves	50
8 Dielectrics	53
14 crystal structure and x ray diffraction	56
16 difficulties of classical mechanics abd development of wave mechanics	61
17 uncertainty principle and schrodinger equation	65
18 free electron theory	67
19 band theory of solids	69
21 magnetic properties of solids	73

List of Scilab Codes

Exa 1.1	fringe width	9
Exa 1.2	slit separation	9
Exa 1.3	wave length	10
Exa 1.4	position of fringe	10
Exa 1.5	Distance between coherent source	11
Exa 1.6	Fringe width	11
Exa 1.8	Vertex angle	11
Exa 1.9	wavelength	12
Exa 1.10	Fringe width	13
Exa 1.11	distance between coherent sources	13
Exa 1.12	Refractive Index of sheet	13
Exa 1.14	Thickness of plate	14
Exa 1.15	Film Thickness	14
Exa 1.16	Order of interference	15
Exa 1.17	Fringe Width	15
Exa 1.18	Wavelength of light	16
Exa 1.19	Wedge angle	16
Exa 1.20	No of Dark bands	17
Exa 1.21	Radius of lens	17
Exa 1.22	Wavelength of light	18
Exa 1.23	Distance between rings	18
Exa 1.24	Refractive Index of liquid	19
Exa 1.25	Diameter of Ring	19
Exa 1.26	Thickness of film	19
Exa 1.27	Refractive Index	20
Exa 1.28	Thickness of film	20
Exa 1.29	Distance between position of mirrors	21
Exa 1.30	Velocity of Light in liquid	21

Exa 1.31	Film Thickness	22
Exa 1.32	wavelength of light	22
Exa 1.33	diameter of ring	22
Exa 2.1	half angular width of central maxima	24
Exa 1.2	wavelength of light	24
Exa 2.3	slit width	25
Exa 2.4	angular width and linear width of central maxima	25
Exa 2.5	wavelength of light	26
Exa 2.6	No of lines in grating	26
Exa 2.7	order of spectrum	27
Exa 2.8	Angular separation between lines	27
Exa 2.9	lines no of lines in grating	28
Exa 2.10	difference of wavelength	28
Exa 2.11	dispersive power	29
Exa 2.12	resolving power and wavelength	29
Exa 2.13	resolving power	30
Exa 2.14	resolving power	30
Exa 2.15	radius of first half of zone plate	31
Exa 2.16	position of spot	31
Exa 2.17	radii of zones	31
Exa 2.18	focal length of zone	32
Exa 2.19	angular separation	32
Exa 3.1	angle of refraction	34
Exa 3.2	refractive index of glass	34
Exa 3.3	thickness of refracting crystal	35
Exa 3.4	thickness of half wave plate	35
Exa 3.5	thickness of quarter wave plate	36
Exa 3.6	thickness of calcite plate	36
Exa 3.7	amount of optical rotation	37
Exa 3.8	phase retardation	37
Exa 3.9	specific rotation	37
Exa 3.10	strength of solution	38
Exa 3.11	optical thickness of quarter wave plate	38
Exa 4.1	Coherence Length	40
Exa 4.2	Coherence Length	40
Exa 4.3	Degree of Non monochromacity	41
Exa 5.1	Numerical Aperture	42
Exa 5.2	Number of Modes	43

Exa 5.3	Refractive Index	43
Exa 5.4	Numerical Aperture	43
Exa 6.1	Equilibrium position time	45
Exa 6.2	Maximum velocity in SHM	45
Exa 6.3	Period of Oscillation	46
Exa 6.4	period of oscillation	46
Exa 6.6	oscillation time	47
Exa 6.7	Equilibrium position time	47
Exa 6.8	Q factor and half width of power resonance	48
Exa 6.9	amplitude of oscillations and relative phase	48
Exa 7.1	Energy of plane wave	50
Exa 7.2	impedence of medium and peak magnetic field	50
Exa 7.3	wavelength of wave and amplitude of magnetic field	51
Exa 7.4	solar energy	51
Exa 7.5	Dielectric constant	52
Exa 8.1	polarisation and Energy density	53
Exa 8.2	Dipole moment of slab	53
Exa 8.3	electric susceptibility	54
Exa 8.4	Dipole moment	54
Exa 14.4	wavelength and angle	56
Exa 14.5	wavelength and speed of neutron	56
Exa 14.6	spacing	57
Exa 14.7	glancing angle	58
Exa 14.10	Energy to create defect	58
Exa 14.11	Number of defects	59
Exa 14.12	fraction of vacancy sites	59
Exa 16.1	de broglie wavelength	61
Exa 16.2	Energy of Neutrons	61
Exa 16.3	frequency and energy of photon	62
Exa 16.4	de broglie wavelength of neutrons	62
Exa 16.5	de broglie wavelength	63
Exa 16.6	energy of photoelectrons emitted	63
Exa 17.1	Uncertainty in angle of Emergence	65
Exa 17.2	Uncertainty in frequency and uncertainty in velocity	66
Exa 18.1	Fermi Energy	67
Exa 18.2	Energy difference	67
Exa 19.1	density of electrons and holes	69
Exa 19.2	position of fermi level	69

Exa 19.3	position of fermi level	70
Exa 19.4	Hall coefficient and Hall voltage	70
Exa 19.5	energy of electron	71
Exa 21.1	electron spin magnetic dipole moment	73
Exa 21.2	diamagnetic susceptibility	73
Exa 22.1	critical field and transition temperature	75
Exa 22.2	critical temperature	76
Exa 22.3	critical current density	76
Exa 22.4	penetration depth	76

Chapter 1

Interference of Light

Scilab code Exa 1.1 fringe width

```
1 //Example 1.1 // fringe width
2 clear;
3 clc;
4 //given data :
5 d=5D-4;// distance between slits in m
6 w=5890D-10;// wavelength in m
7 D=0.5;//distance between source and screen in m
8 b=D*w/d;//fringes width
9 disp(b,"width of fringes in meter")
```

Scilab code Exa 1.2 slit separation

```
1 //Example 1.2 // double slit separation
2 clear;
3 clc;
4 //given data :
5 w=5100D-10;// wavelength in m
6 D=2;//distance between source and screen in m
```

```

7 n=10; // number of fringes
8 x=0.02; //width of all n fringes in m
9 b=x/n; //fringes width
10 d=D*w/b; //double slit width
11 disp(d,"double slit separation in meter")

```

Scilab code Exa 1.3 wave length

```

1 //Example 1.3 // wavelength of lighth
2 clc;
3 clear;
4 //given data :
5 d=19D-4; // distance between slits in m
6 D=1; //distance between source and screen in m
7 b=.31D-3; //fringes width in m
8 w=b*d/D; // wavelength in m
9 w=w*1D10; // to convert in A
10 disp(w,"wavelength of light in A(angstrom)")

```

Scilab code Exa 1.4 position of fringe

```

1 //Example 1.4 // position of fringe
2 clc;
3 clear;
4 //given data :
5 d=2D-3; // distance between slits in m
6 w=5890D-10; // wavelength in m
7 D=0.04; //distance between source and screen in m
8 n=10; // number of fringe which is to locate
9 x=n*D*w/d; //position of fringe
10 disp(x,"position of nth fringes in meter")

```

Scilab code Exa 1.5 Distance between coherent source

```
1 //Example 1.5 // distance between coherent source
2 clc;
3 //given data :
4 b=9.424D-4;//fringes width in m
5 w=5890D-10;// wavelength in m
6 a=0.05;// distance between source & prism in m
7 c=0.75;// distance between prism & screen in m
8 D=a+c;//distance between source and screen in m
9 d=(D*w)/b;//distance between coherent source
10 disp(d,"distance between coherent source in meter")
```

Scilab code Exa 1.6 Fringe width

```
1 //Example 1.6 // fringe width
2 clc;
3 //given data :
4 a=0.10;// distance between source & prism in m
5 c=1;// distance between prism & screen in m
6 u=1.5;//refractive index of bi-prism
7 al=%pi/180;//angle in radian
8 d=2*a*(u-1)*al;// distance between slits in m
9 w=5900D-10;// wavelength in m
10 D=a+c;//distance between source and screen in m
11 b=D*w/d;//fringes width
12 disp(b,"width of fringes in meter")
```

Scilab code Exa 1.8 Vertex angle

```

1 //Example 1.8 // angle of vertex of biprism
2 clc;
3 clear;
4 //given data :
5 u=1.5;//refractive index of bi-prism
6 b=.2D-3;//fringes width in m
7 al=%pi/180;//angle in radian
8 w=5D-7;// wavelength in m
9 a=0.25;// distance between source & prism in m
10 c=1.75;// distance between prism & screen in m
11 D=a+c;//distance between source and screen in m
12 d=D*w/b;//distance between slits in m
13 a1=d/(2*a*(u-1));// angle in radian
14 al=a1*180/%pi;// angle in degree
15 vert=180-2*a1;// vertex angle
16 disp(vert,"angle of vertex of biprism in degree")

```

Scilab code Exa 1.9 wavelength

```

1 //Example 1.9 // wavelength of lighth
2 clc;
3 clear;
4 //given data :
5 u=1.5;//refractive index of bi-prism
6 a=50;// distance between source & prism in cm
7 c=50;// distance between prism & screen in cm
8 A=179;// angle of bi-prism in degree
9 D=a+c;//distance between source and screen in cm
10 b=.0135;//fringes width in cm
11 al=(180-A)/2;// angle with base in degree
12 al=al*%pi/180;//to convert in radian
13 w=2*al*(u-1)*a*b/D// wavelength in cm
14 disp(w*1D8,"wavelength of light in Angstrom")

```

Scilab code Exa 1.10 Fringe width

```
1 //Example 1.10 // fringe width
2 clc;
3 clear;
4 //given data :
5 b1=0.087;// initally fringe width in mm
6 //when distance given in ratio
7 r=.75;// ratio
8 b=b1/r
9 disp(b,"width of fringes in mm")
```

Scilab code Exa 1.11 distance between coherent sources

```
1 //Example 1.11 // separation between coherent source
2 clc;
3 clear;
4 //given data :
5 u=1.5;//refractive index of bi-prism
6 al=2*%pi/180;//angle in radian
7 a=.1;// distance between source & prism in m
8 d=2*a*(u-1)*al;// distance between slits in m
9 disp(d,"separation between coherent source in meter"
    )
```

Scilab code Exa 1.12 Refractive Index of sheet

```
1 //Example 1.12 // refractive index of sheet
2 clc;
```

```

3 clear;
4 //given data :
5 w=5460D-10; // wavelength in m
6 n=6; // number of fringe shifted
7 t=6.3D-6; //thickness of material
8 u=(n*w)/t +1; // equation for fefractive index
9 disp(u,"refractive index of sheet")

```

Scilab code Exa 1.14 Thickness of plate

```

1 //Example 1.4 // thickness of plate
2 clc;
3 clear;
4 //given data :
5 u=1.5; //refractive index of glass plate
6 r=60; // refraction angle in degree
7 r=r*%pi/180; // to convert in radian
8 w=5890D-10; // wavelength in m
9 //for least thickness
10 t=w/(2*u*cos(r));
11 t=t*1D10; // to convert in angstrom
12 disp(t,"thickness of plate in A")

```

Scilab code Exa 1.15 Film Thickness

```

1 //Example 1.15 // flim thickness
2 clc;
3 clear;
4 //given data :
5 u=1.5; //refractive index of oil
6 i=30; // incident angle in degree
7 i=i*%pi/180; //to convert in radian
8 n=8; //8th dark band

```

```

9 w=5890D-10; // wavelength in m
10 r=sqrt(1-(sin(i)/u)^2); //cos of received angle
11 t=n*w/(2*u*r); //formula of thickness
12 t=t*1D3; //to convert in mm
13 disp(t*1D-3,"flim thickness in m")

```

Scilab code Exa 1.16 Order of interference

```

1 //Example 1.16 // order of dark band
2 clc;
3 clear;
4 //given data :
5 u=4/3; //refractive index of soap flim
6 t=1.5D-6; //thickness of soap flim
7 i=60; //incident angle in degree
8 i=i*%pi/180; // incident angle in radian
9 w=5D-7; // wavelength in m
10 r=sin(i)/u; //sin of refracted angle
11 R=asin(r); //refracted angle in radian
12 n=2*u*t*cos(R)/w
13 n=floor(n)
14 disp(n,"order of dark band")

```

Scilab code Exa 1.17 Fringe Width

```

1 //Example 1.17 // fringe width
2 clc;
3 clear;
4 //given data :
5 x=.15; // air flim base width in m
6 w=6D-7; // wavelength in m
7 ab=0.05D-3; //length wire in m
8 u=1; //refractive index of air

```



```

9 theta=ab/x;
10 b=w/(2*u*theta); //fringes width
11 disp(b,"width of fringes in meter")

```

Scilab code Exa 1.18 Wavelength of light

```

1 //Example 1.18 // wavvlength of light
2 clc;
3 //given data :
4 b=.5D-2; //distace between succesive fringes in m
5 u=1.4; //refractive index of cellophane
6 a=10; //angle of wedge in sec
7 a=a*%pi/(60*60*180); //to convert in radian
8 w=2*u*a*b;
9 w=w*1D10; //to convert in A
10 disp(w,"wavelength of light used in A")
11
12 //note: Pi is taken as 22/7 in the textbook.

```

Scilab code Exa 1.19 Wedge angle

```

1 //Example 1.19 // angle of wedge
2 clc;
3 clear;
4 //given data :
5 x=1D-2; //distace of mth dark band
6 w=6D-7; // wavelength in m
7 m=10; //number of dark band
8 a=m*w/(2*x)
9 disp(a,"angle of wedge in radian")
10 //note: answer in textbook is in seconds

```

Scilab code Exa 1.20 No of Dark bands

```
1 //Example 1.20 // number of dark band
2 clc;
3 clear;
4 //given data :
5 t=0.01;//thickness of oil film
6 t=t*1D-3;//to convert in m
7 u=1.4;//refractive index of oil
8 w1=4D-7;// first wavelength in m
9 w2=5D-7;// second wavelength in m
10 a=%pi/4;//flim placed at angle
11 cosr=sqrt(1-(sin(a)/u)^2);//formula
12 n1=2*u*t*cosr/w1;
13 n2=2*u*t*cosr/w2;
14 n1=floor(n1);//to convert in integer
15 n2=floor(n2);//to convert in integer
16 n=n1-n2;//number of dark band
17 disp(n,"number of dark band")
```

Scilab code Exa 1.21 Radius of lens

```
1 //Example 1.21 // radius of lens
2 clc;
3 clear;
4 //given data :
5 w=5890D-10;//wavelength used in m
6 d=.01;//diameter of dark ring in m
7 r=%pi/6;//angle that light passes in radian
8 n=3;// order of ring
9 u=1;// refractive index of medium between lens and
    plate
```

```

10 R=u*(d^2)*cos(r)/(4*n*w); // radius of lens in m
11 disp(R,"radius of lens in m")

```

Scilab code Exa 1.22 Wavelength of light

```

1 //Example 1.22 // wavelength used
2 clc;
3 clear;
4 //given data :
5 R=3; //radius of lens in m
6 n=8; // order of bright ring
7 D=.72D-2; // diameter of bright ring in m
8 u=1; // refractive index of medium between lens and
    plate
9 w=(D^2)/((2*n-1)*2*R); // wavelength used in m
10 w=w*1D10; //to convert in A
11 disp(w,"wavelength of light used in A")

```

Scilab code Exa 1.23 Distance between rings

```

1 //Example 1.23 // distance between rings
2 clc;
3 clear;
4 //given data :
5 R1=100; //radii of curvature in cm
6 R2=R1; // given
7 w=5400D-8; // wavelength of light in m
8 n1=5; // order of ring for case one
9 r1=sqrt(n1*w/((1/R1)+(1/R2))); //radii of curvature
    in cm
10 n2=15; // order of ring for second case
11 r2=sqrt(n2*w/(1/R1+1/R2)); // radii of curvature in
    cm

```

```
12 d=r2-r1; // distance between rings
13 disp(d,"distance between rings in cm")
```

Scilab code Exa 1.24 Refractive Index of liquid

```
1 //Example 1.24 // refractive index
2 clc;
3 clear;
4 //given data :
5 d1=.3; // diameter of ring in cm
6 d2=.25; //diameter of ring(in cm) after placing in
   medium
7 u=(d1/d2)^2; // refractive index of medium
8 disp(u,"refractive index of medium")
```

Scilab code Exa 1.25 Diameter of Ring

```
1 //Example 1.25 // diameter of bright ring
2 clc;
3 clear;
4 //given data :
5 w=6D-7; // wavelength used in m
6 R1=3; //radius of curvature of convex lens in m
7 R2=4; //radius of curvature of concave lens in m
8 n=13; // order of ring
9 r=sqrt(((2*n-1)*w/(2*(1/R1-1/R2)))); // radius of ring
10 disp(2*r,"diameter of bright ring in m")
```

Scilab code Exa 1.26 Thickness of film

```

1 //Example 1.26 // thickness of flim
2 clc;
3 clear;
4 //given data :
5 u=1.5;// refractive index of flim between lens and
   plate
6 m=10;//no. of fringes shifted in experiment
7 w=5890D-10;// wavelength of light used in m
8 t=m*w/(2*(u-1));// thickness of plastic flim in m
9 t=t*1D9;// to convert in mm
10 disp(t,"thickness of flim in nm(nanometer)")

```

Scilab code Exa 1.27 Refractive Index

```

1 //Example 1.27 // refractive index
2 clc;
3 clear;
4 //given data :
5 n=150;//no. of frnges shifted
6 w=4D-7;// wavelength of light used
7 l=.2;//length of tube in m
8 u=n*w/(2*l) +1
9 disp(u,"refractive index of medium ")

```

Scilab code Exa 1.28 Thickness of film

```

1 //Example 1.28 // thickness of flim
2 clc;
3 clear;
4 //given data :
5 w=589D-9;//wavelength of light used in m
6 u=1.45;// refractive index of medium between lens
   and plate

```

```

7 n=6.5; // fringes shifted
8 t=n*w/(2*(u-1)); // thickness of flim in m
9 t=t*1D9; //to convert in nano meter
10 disp(t,"thickness of flim in nm(nanometer)")

```

Scilab code Exa 1.29 Distance between position of mirrors

```

1 //Example 1.29 // distance between successive
   positions of movable mirror
2 clc;
3 clear;
4 //given data :
5 w1=5896D-8; //one wavelength of light used in cm
6 w2=5890D-8; // second wavelength of light used in cm
7 d=w1*w2/(2*(w1-w2)); // distance between successive
   position of mirror in cm
8 disp(d,"dustance between sucessive position of
   mirror in cm")

```

Scilab code Exa 1.30 Velocity of Light in liquid

```

1 //Example 1.30 // velocity of light in medium
2 clc;
3 clear;
4 //given data :
5 d1=.3; // diameter of ring in cm
6 d2=.25; //diameter of ring(in cm) after placing in
   medium
7 c=3D8; //speed of light in m/s
8 u=(d2/d1)^2; // refractive index of medium
9 v=u*c; // velocity of light in fluid
10 disp(v,"velocity of light in liquid in m/s")

```

Scilab code Exa 1.31 Film Thickness

```
1 //Example 1.31 // thickness of flim
2 clc;
3 clear;
4 //given data :
5 w1=6.1D-5;//wavelength of light fall in cm
6 w2=6D-5;// wavelength of light fall in cm
7 u=1.33;// refractive index soap flim
8 si=4/5;//sine of incident angle
9 t=w1*w2/(2*(w1-w2)*sqrt(u^2-si^2))
10 disp(t,"thickness of flim in cm")
```

Scilab code Exa 1.32 wavelength of light

```
1 //Example 1.32 // wavelength of light
2 clc;
3 //given data :
4 n1=5;//order of ring
5 n2=25;// order of ring
6 m=n2-n1;//difference of ring order
7 R=100;//radius of curvature in cm
8 d1=.3;//diameter of ring n cm
9 d2=.8;//diameter of ring in cm
10 w=(d2^2-d1^2)/(4*R*m);//wavelength in cm
11 disp(w,"wacelength of light in cm")
```

Scilab code Exa 1.33 diameter of ring

```
1 //Example 1.33 // diameter of ring
2 clc
3 clear;
4 //given data :
5 n1=4;//order of ring
6 n2=12;// order of ring
7 m=n2-n1;//difference of ring order
8 n=20;// order of ring to find
9 //let k=4*wavelength**R
10 d1=.4;// diameter of first ring in cm
11 d2=.7;//diameter of second ring in cm
12 k=(d2^2-d1^2)/m;
13 d=sqrt(n*k);// diameter of ring in cm
14 disp(d,"diameter of ring in cm")
15
16 //note: Wrong answer in the textbook.
```

Chapter 2

diffraction of light

Scilab code Exa 2.1 half angular width of central maxima

```
1 //Example 2.1 // Half angular width of diffraction
  pattern
2 clc;
3 clear;
4 //given data :
5 w=6D-7;// wavelength of monochromatic light in m
6 a=12D-7;// slit width in m
7 theta=asin(w/a);//half angular width of central
  bright maxima
8 theta=theta*180/%pi;// to convert in degree
9 disp(theta,"Half angular width of central bright
  maxima in degree")
```

Scilab code Exa 1.2 wavelength of light

```
1 //Example 2.2 // Wavelength of light
2 clc;
3 clear;
```

```

4 //given data :
5 a=.2D-3;//slit width in m
6 D=2;// screen is placed at distance in m
7 x=5D-3;// first minima lies at distance to central
  maxima
8 w=(a*x)/D;// wavelength of light in m
9 w=w*1D10;// to convert in A
10 disp(w,"wavelength of light used in A")

```

Scilab code Exa 2.3 slit width

```

1 //Example 2.3 // slit width
2 clc;
3 clear;
4 //given data :
5 w=6D-7;// wavelength of light used in m
6 D=2;// screen is placed at distance in m
7 x=5D-3;// first minima lies at distance to central
  maxima
8 a=(w*D)/x;//slit width in m
9 disp(a,"slit width in m")

```

Scilab code Exa 2.4 angular width and linear width of central maxima

```

1 //Example 2.4 // Angular width & linear width of
  central maxima
2 clc;
3 clear;
4 //given data :
5 w=589D-9;// wavelength of light used in m
6 D=1;// screen is placed at distance in m
7 a=.1D-3;//slit width in m
8 theta=asin(w/a);//half angular width in radian

```

```

9 angle=2*theta; // angular width in radian
10 disp(angle,"Angular width of central maxima in
    radian")
11 y=D*angle; // linear width of central maxima in m
12 y=y*100; // to convert in cm
13 disp(y,"linear width of central maxima in cm")

```

Scilab code Exa 2.5 wavelength of light

```

1 //Example 2.5 // wavelength of light used
2 clc;
3 clear;
4 //given data :
5 c=1/5000; // grating element
6 theta=%pi/6; //spectral line deviated
7 n=2; //order of spectral line
8 w=(c*sin(theta))/(n); //wavelength in cm
9 w=w*1D8; //to convert in A
10 disp(w,"wavelength of lighth used in A")

```

Scilab code Exa 2.6 No of lines in grating

```

1 //Example 2.6 // minimum number of lines in grating
2 clc;
3 clear;
4 //given data :
5 w1=589D-9; //wavelength of one sodium line
6 w2=5896D-10 //wavelength of second line
7 dw=w2-w1; //change of wavelength
8 w=(w1+w2)/2; // mid wavelength
9 n=1; //order of spectrum
10 N=w/(n*dw); //number of lines in grating
11 N=floor(N); //no. should be integer

```

```
12 disp(N,"number of lines in grating")
```

Scilab code Exa 2.7 order of spectrum

```
1 //Example 2.7 // order of spectrum
2 clc;
3 clear;
4 //given data :
5 w=5D-5;//wavelength of light used in cm
6 c=1/5000;//grating element
7 n=c/w;//order of spectrum
8 disp(n,"order of spectrum")
```

Scilab code Exa 2.8 Angular separation between lines

```
1 //Example 2.8 //angular separation
2 clc;
3 clear;
4 //part a
5 c=1/5000;//grating element
6 w1=5890D-8;// in first case first wavelength used in
   cm
7 n=2;//order of spectrum
8 theta=asin((n*w1)/c);//angular separation in radian
9 theta=theta*180/%pi;//to convert in degree
10 disp(theta,"angular width in degree")
11 //part b
12 w2=5896D-8;// in second case second wavelength used
   in cm
13 n=2;//order of spectrum
14 theta1=asin((n*w2)/c);//angular separation in radian
15 theta1=theta1*180/%pi;//to convert in degree
16 disp(theta1,"angular width in degree")
```

```

17 a=theta1-theta;//angular separation in degree
18 disp(a,"angular separation in degree")
19 //part c
20 w=5893D-8;// mid wavelength
21 dw=w2-w1;// change in wavelength
22 n=2;//order of spectrum
23 N=w/(dw*n);//no. of lines in grating
24 N=floor(N);//N should be integer
25 disp(N,"no. of lines in grating")

```

Scilab code Exa 2.9 lines no of lines in grating

```

1 //Example 2.9 //No. of lines in grating
2 clc;
3 clear;
4 //given data
5 w1=54D-6;// first wavelength used in cm
6 w2=405D-7;// second wavelength used in cm
7 //first wavelength order superimposed on next
  higher order
8 theta=%pi/6;//angle of diffraction in radian
9 c=(w1*w2/(w1-w2))/sin(theta);//grating element
10 N=1/c;// no. of lines per cm
11 N=round(N);// N should be integer
12 disp(N,"No. of lines in grating")

```

Scilab code Exa 2.10 difference of wavelength

```

1 //Example 2.10 //Difference of wavelengths
2 clc;
3 clear;
4 //given data
5 d_theta=.01;// change of diffraction angle

```

```

6 theta=%pi/6;// diffraction angle
7 w=5000;// wavelength used in A
8 dw=w*d_theta*cotg(theta)//change of wavelength in A
9 disp(dw,"difference of wavelength in A")

```

Scilab code Exa 2.11 dispersive power

```

1 //Example 2.11 // Dispersive power
2 clc;
3 clear;
4 //given data :
5 c=1/4000;// grating element
6 w=5D-5;// wavelength of light in cm
7 n=3;// order of spectrum
8 D=n/(c*sqrt(1-((n*w/c)^2)));//dispersive power in
   radian per cm
9 disp(D,"Dispersive power in rad/sec")
10 // in book there is calculation mistake

```

Scilab code Exa 2.12 resolving power and wavelength

```

1 //Example 2.12 //Difference of wavelengths
2 clc;
3 clear;
4 //part a
5 l=5;// length of grating
6 N=16000;// no. of lines per inch on the grating
7 w=6000;// wavelength used in A
8 n=2;// order of spectrum
9 T=N*l;//total no. of lines on grating
10 R=T*n;// resolving power
11 disp(R,"resolving power..")
12 //part b

```

```
13 dw=w/(T*n); // wavelength can be resolved in A
14 disp(dw,"wavelength can be resolved in A")
```

Scilab code Exa 2.13 resolving power

```
1 //Example 2.14 //Resolving power
2 clc;
3 clear;
4 //given data
5 c=12.5D-5; // grating element in cm
6 w=5D-5; // wavelength used in cm
7 N=40000; //no. of lines on grating
8 n=c/w; // order for maximum resolving power
9 n=floor(n); //n should be integer
10 P=n*N; // maximum resolving power
11 disp(P,"Resolving power ")
```

Scilab code Exa 2.14 resolving power

```
1 //Example 2.14 //Resolving power
2 clc;
3 clear;
4 //given data
5 c=12.5D-5; // grating element in cm
6 w=5D-5; // wavelength used in cm
7 N=40000; //no. of lines on grating
8 n=c/w; // order for maximum resolving power
9 n=floor(n); //n should be integer
10 P=n*N; // maximum resolving power
11 disp(P,"Resolving power ")
```

Scilab code Exa 2.15 radius of first half of zone plate

```
1 //Example 2.14 //Radius of half period element
2 clc;
3 clear;
4 //given data
5 f=50;//focal length of convex lens in cm
6 w=5D-5;// wavelength used in cm
7 n=1;// order of principal maxima
8 r=sqrt(n*f*w);// radius of half period element
9 disp(r,"Radius of half period element in cm")
```

Scilab code Exa 2.16 position of spot

```
1 //Example 2.16 //position of brightest spot
2 clc;
3 clear;
4 //given data
5 d=.2;// diameter of ring
6 n=1;//order of ring
7 w=5D-5;//wavelength used in cm
8 r=d/2;// radius of ring
9 f=(r^2)/(w*n);//position of brightest spot
10 disp(f,"position of brightest spot in cm")
```

Scilab code Exa 2.17 radii of zones

```
1 //Example 2.17 //radii of transparent zone
2 clc;
3 clear;
4 //given data
5 f=1;//focal length in m
6 n=1;//order of zone
```



```

7 w=5893D-10; // wavelength used in m
8 r=sqrt(n*f*w); //radius of transparent zone
9 disp(r,"radius of transparent in m")
10 n=3; //next order
11 r=sqrt(n*f*w); //radius of transparent zone
12 disp(r,"radius of transparent in m")
13 n=5; //next order
14 r=sqrt(n*f*w); //radius of transparent zone
15 disp(r,"radius of transparent in m")

```

Scilab code Exa 2.18 focal length of zone

```

1 //Example 2.18 // focal length of zone plate
2 clc;
3 clear;
4 //given data :
5 r=200; // radius of curvature in cm
6 f=r; //principal focal length in cm
7 disp(f,"principal focal length in cm")

```

Scilab code Exa 2.19 angular separation

```

1 //Example 2.19 //Angular separation
2 clc;
3 clear;
4 //given data
5 n=1; // order of spectrum
6 wi=.5; // width of grating in cm
7 N=2500; //total no. of lines
8 c=wi/N; //grating element
9 w1=589D-7; // first wavelength of sodium in cm
10 //part a
11 theta1=asin(n*w1/c) //angular width in radian

```

```

12 theta1=theta1*180/%pi;//angular width in degree
13 disp(theta1,"angular width in degree")
14 w2=5896D-8;//second wavelength of sodium in cm
15 //part b
16 theta2=asin(n*w2/c)//angular width in radian
17 theta2=theta2*180/%pi;//angular width in degree
18 disp(theta2,"angular width in degree")
19 theta=theta2-theta1;//angular separation degree
20 disp(theta,"angular separation in degree")
21 w=(w1+w2)/2;//mid wavelength
22 dw=6D-8;// change of wavelength in cm
23 n=1;//order of spectrum
24 N=w/(n*dw);//no. of lines will appear
25 N=floor(N);// N should be integer
26 if(1/c>N)
27     disp(N,"No. of lines will appear")
28 else
29     disp("they can not be seen differently ")
30 end

```

Chapter 3

polarization of light

Scilab code Exa 3.1 angle of refraction

```
1 //Example 3.1 // Angle of Polarization
2 clc;
3 clear;
4 //given data :
5 u=1.54;//refractive index of glass
6 i=atan(u);//incidence angle in radian
7 r=%pi/2 -i;//refraction angle in radian brewester's
   law
8 r=r*180/%pi;// to convert in degree
9 disp(r,"angle of refraction in degree")
```

Scilab code Exa 3.2 refractive index of glass

```
1 //Example 3.2 // Refractive index of glass
2 clc;
3 clear;
4 //given data :
5 i=%pi/3;// incidence angle in radian
```

```

6 //reflected and refracted rays are perpendicular to
  each other
7 u=tan(i); //Refractive index
8 disp(u,"Refractive index of glass")

```

Scilab code Exa 3.3 thickness of refracting crystal

```

1 //Example 3.3 // Thickness of doubly refracting
  crystal
2 clc;
3 clear;
4 //given data :
5 Uo=1.55; //refractive index for O ray
6 Ue=1.54; //refractive index for E ray
7 w=6D-7; // wavelength of light used in m
8 p=w/2; // path difference in m
9 t=w/(2*(Uo-Ue)); //thickness of in m
10 disp(t*1D2,"thickness of doubly refracting crystal
  in cm")

```

Scilab code Exa 3.4 thickness of half wave plate

```

1 //Example 3.4 // Thickness of half wave plate
2 clc;
3 //given data :
4 Uo=1.54; //Refractive index for Ordinary light
5 r=1.007; //ratio of velocity of ordinary to
  extraordinary
6 Ue=r*Uo; //refractive index for extraordinary light
7 w=5893D-10; // wavelength of light used in m
8 t=w/(2*(Uo-Ue)); // thickness of half wave plate in m
9 t=abs(t); // thickness always positive
10 disp(t,"Thickness of half wave plate in m")

```

Scilab code Exa 3.5 thickness of quarter wave plate

```
1 //Example 3.5 // Thickness of quarter wave plate
2 clc;
3 clear;
4 //given data :
5 Uo=1.652;//refractive index for O ray
6 Ue=1.488;//refractive index for E ray
7 w=546D-9;// wavelength of light used in m
8 p=w/2;// path difference in m
9 t=w/(4*(Uo-Ue));//thickness of in m
10 t=t*100;// to convert in cm
11 disp(t,"thickness of quarter wave plate in cm")
```

Scilab code Exa 3.6 thickness of calcite plate

```
1 //Example 3.6 // Thickness of Calcite plate
2 clc;
3 clear;
4 //given data :
5 Uo=1.658;//refractive index for O ray
6 Ue=1.486;//refractive index for E ray
7 w=589D-9;// wavelength of light used in m
8 n=1;//integer for odd multiples
9 t=(2*n-1)*w/(4*(Uo-Ue));//thickness of Calcite plate
   in m
10 t=t*100;// to convert in cm
11 disp(t,"thickness of Calcite plate in cm")
```

Scilab code Exa 3.7 amount of optical rotation

```
1 //Example 3.7 // Amount of optical rotation
2 clc;
3 clear;
4 //given data :
5 Ur=1.55810;// refractive index for right handed
   polarized
6 Ul=1.55821;//refractive index for left handed
   polarized
7 w=4D-7;//wavelength of light used in m
8 d=.002;// thickness of plate in m
9 R=%pi*d*(Ul-Ur)/w;// rotation in radian
10 R=R*180/%pi;// to convert in degree
11 disp(R,"Amount of optical rotation in degree")
12 // in book it is wrongly calculated
```

Scilab code Exa 3.8 phase retardation

```
1 //Example 3.8 // Phase retardation
2 clc;
3 clear;
4 //given data :
5 Uo=1.5508;//refractive index for O ray
6 Ue=1.5418;//refractive index for E ray
7 w=5D-7;// wavelength of light used in m
8 t=.000032;// thickness of plate in m
9 p=2*%pi*(Uo-Ue)*t/w;//phase retardation in radian
10 disp(p,"phase retardation in radian")
```

Scilab code Exa 3.9 specific rotation

```
1 //Example 3.9 // Specific rotation
```

```

2  clc;
3  clear;
4  //given data :
5  theta=6.5;// angle of rotation in degree
6  l=2;// length of sugar solution in decimeter
7  C=.05;// concentration of sugar solution
8  S=theta/(l*C);//specific rotation in degree
9  disp(S,"specific rotation of sugar solution in
        degree")

```

Scilab code Exa 3.10 strength of solution

```

1  //Example 3.10 // Strength of solution
2  clc;
3  clear;
4  //given data :
5  l=2;//length of solution in decimeter
6  theta=12;// angle of rotation in degree
7  S=60;//specific rotation in degree
8  C=theta/(S*l);// concentration in gm/cc
9  disp(C,"strength of solution in gm/cc")

```

Scilab code Exa 3.11 optical thickness of quarter wave plate

```

1  //Example 3.5 // Thickness of quarter wave plate
2  clc;
3  clear;
4  //given data :
5  b=.172;//bifringe of plate
6  w=6D-7;// wavelength of light used in m
7  t=w/(4*(b));//thickness of in m
8  t=t*100;// to convert in cm
9  disp(t,"thickness of quarter wave plate in cm")

```


Chapter 4

Laser

Scilab code Exa 4.1 Coherence Length

```
1 //Example 4.1 // Coherence length for laser
2 clc;
3 //given data :
4 v=3000;// bandwidth in Hz
5 c=3D8;//speed of light in m/s
6 t=1/v;//Coherence time in sec
7 l=c*t;//coherence length in m
8 l=l/1D3;// to convert in km
9 disp(l,"Coherence length for laser in km")
```

Scilab code Exa 4.2 Coherence Length

```
1 //Example 4.2 // transverse Coherence length
2 clc;
3 //given data :
4 theta=32;//angle on slit in second
5 theta=32*%pi/(60*180);// to convert in radian
6 w=5D-5;// wavelength of light used in cm
```

```
7 C=w/theta;//coherence length in cm
8 disp(C,"transverse coherence length in cm")
```

Scilab code Exa 4.3 Degree of Non monochromacity

```
1 //Example 4.3 // Degree of non-monochromacity
2 clc;
3 //given data :
4 t=1D-10;//coherence time in sec
5 c=3D8;//speed of light in m/s
6 w=54D-8;// wavelength of non-monochromacity in m
7 B=1/t;//bandwidth in Hz
8 v=c/w;//frequency of source
9 D=B/v;// degree of non-monochromacity
10 disp(D,"degree of non-monochromacity")
```

Chapter 5

Fiber Optics

Scilab code Exa 5.1 Numerical Aperture

```
1 //Example 5.1
2 clc;
3 // 1st part //critical angle
4 u1=1.48;// refractive index of cladding
5 u2=1.5;// refractive index of core
6 u=1;// refractive index of air
7 theta=asin(u1/u2);// critical angle in radian
8 theta=theta*180/%pi;// to convert in degree
9 disp(theta,"critical angle in degree")
10 // 2nd part //fractional refractive index
11 Fr=(u2-u1)/u2;// fractional refractive index
12 Fr=Fr*100;// to convert in percent
13 disp(Fr,"fractional refractive index in percentage")
14 // 3rd part // acceptance angle
15 A=asin(sqrt(u2^2-u1^2));// Acceptance angle in
    radian
16 disp(A,"Acceptance angle in radian")
17 // 4th part //numerical aperture
18 NA=sin(A);// Numerical aperture
19 disp(NA,"Numerical aperture ")
```

Scilab code Exa 5.2 Number of Modes

```
1 //Example 5.2
2 clc;
3 // 1st part // V number
4 NA=.22;// Numerical aperture
5 a=50/2;// radius of core
6 w=.850;//wavelength in um
7 V=2*%pi*a*NA/w;// V number
8 disp(V,"V number")
9 // 2nd part // number of modes
10 N=(V^2)/4;// number of modes
11 disp(N,"number of modes")
```

Scilab code Exa 5.3 Refractive Index

```
1 //Example 5.3 // refractive index
2 clc;
3 // given data
4 NA=.22;//Numerical Aperature
5 Fr=.012;//Fractional refractive index
6 u1=NA/sqrt(Fr*(2-Fr));// refractive index of core
7 u2=sqrt(u1^2-NA^2);// refractive index of clad
8 disp(u1,"Refractive index of core")
9 disp(u2,"Refractive index of clad")
```

Scilab code Exa 5.4 Numerical Aperture

```
1 //Example 8.2 // Numerical Aperture & acceptance
   angle
2 clc;
3 //given data :
4 u1=1.62;//refractive index of core
5 u2=1.52;// refractive index of clad
6 A=asin(sqrt(u1^2-u2^2));// acceptance angle in
   radian
7 NA=sin(A);// numerical aperture
8 A=A*180/%pi;// to convert in degree
9 disp(A,"Acceptance angle in degree")
10 disp(NA,"Numerical Aperture")
```

Chapter 6

oscillatory motion

Scilab code Exa 6.1 Equilibrium position time

```
1 //Example 6.1 // Equilibrium position time
2 clc;
3 clear;
4 //given data :
5 A=.05;//Amplitude of SHM in m
6 T=6;// period in sec
7 Xo=A;// equilibrium position at t=0 position in m
8 X=.025;//equilibrium position in m
9 w=2*%pi/T;// angular frequency in rad/sec
10 ph=asin(Xo/A);// phase angle in radian
11 t=(asin(X/A)-ph)/w// time for equilibrium position
    in sec
12 t=abs(t);// it take positive magnitude
13 disp(t,"time to move from Equilibrium position in
    sec")
```

Scilab code Exa 6.2 Maximum velocity in SHM

```

1 //Example 6.2 // Maximum velocity in SHM
2 clc;
3 clear;
4 //given data :
5 A=.06;// Amplitude of SHM in m
6 T=31.4;// period in sec
7 w=2*%pi/T;// angular frequency in rad/sec
8 V=A*w;// maximum velocity in m/s
9 disp(V,"Maximum velocity in m/s" )

```

Scilab code Exa 6.3 Period of Oscillation

```

1 //Example 6.3 // Period of Oscillation
2 clc;
3 clear;
4 //given data :
5 l=1;// length of pendulum in m
6 m=1;// mass of pendulum in kg
7 g=9.8;//acceleration of gravity in m/s2
8 T=2*%pi*sqrt(l/g);//time period
9 disp(T,"Period of Oscillation in sec")

```

Scilab code Exa 6.4 period of oscillation

```

1 //Example 6.4 // Period of Oscillation
2 clc;
3 clear;
4 //given data :
5 m1=8;// mass suspended in kg
6 l=.32;// length of spring stretched in m
7 m=.5;// new mass suspended in kg
8 g=9.8;//acceleration of gravity in m/s2
9 k=m1*g/l;// force constant of spring in N/m

```

```

10 disp(k)
11 T=2*%pi*sqrt(m/k); // time period of Oscillation
12 disp(T,"Time Period of Oscillation sec")
13 // in book it is wrongly calculated

```

Scilab code Exa 6.6 oscillation time

```

1 //Example 6.6 // oscillation time
2 clc;
3 clear;
4 //given data :
5 r=10; //ratio of energies
6 Q=1D4; //quality factor
7 v=250; // frequency of fork in cycles/s
8 w=2*%pi*v; //angular frequency in rad/sec
9 T=Q/w; // relaxation time in sec
10 t=T*log(r); // time in sec
11 disp(t,"time to become new energy in sec")

```

Scilab code Exa 6.7 Equilibrium position time

```

1 //Example 6.7 // Equilibrium position time
2 clc;
3 clear;
4 //given data :
5 r=exp(2); //ratio of amplitude
6 Q=2D3; //quality factor
7 v=240; // frequency of fork in cycles/s
8 w=2*%pi*v; //angular frequency in rad/sec
9 T=Q/w; // relaxation time in sec
10 t=2*T*log(r); //time for ne amplitude
11 disp(t,"time to become for new amplitude in sec")

```

Scilab code Exa 6.8 Q factor and half width of power resonance

```
1 //Example 6.8
2 clc;
3 clear;
4 //part a :
5 Ao=.1; // amplitude at minimum frequency in mm
6 A=100; //maximum amplitude
7 Q=A/Ao; //quality factor
8 disp(Q,"Quality factor")
9 //part b
10 w=100; //resonance frequency in rad/sec
11 T=Q/w; //energy decay time
12 disp(T,"energy decay time in sec")
13 //part c
14 hw=1/(2*T); // half width of power resonance curve
15 disp(hw,"half width of power resonance curve in rad/
    sec")
```

Scilab code Exa 6.9 amplitude of oscillations and relative phase

```
1 //Example 6.9 // amplitude of oscillations &
    relative phase
2 clc;
3 clear;
4 //given data :
5 m=.1; //suspended mass in kg
6 k=100; // force constant in N/m
7 Fo=2; // maximum driving force in N
8 p=1; // constant in Ns/m
9 Wo=sqrt(k/m); //angular frequency in rad/sec in
    steady state;
```

```
10 W=50; //angular frequency in rad/sec
11 f=Fo/m;
12 d=p/(2*m); //damping constant
13 B=f/sqrt(((Wo^2)-(W^2))^2+4*(d^2)*(W^2)); //amplitude
    of Oscillation in m
14 delta=atan(2*d*W/(Wo^2-W^2)); // relative phase in
    radian
15 disp(B,"amplitude of oscillations in m")
16 delta=delta*180/%pi +180; // to convert in 0 to 180
    in degree
17 disp(delta,"relative phase in degree")
```

Chapter 7

electromagnetic waves

Scilab code Exa 7.1 Energy of plane wave

```
1 //Example 7.1 // Energy of plane wave
2 clc;
3 clear;
4 //given data :
5 u=(4D-7*%pi); // permeability(free space) in H/m
6 e=8.85D-12; // permitivity(free space) in Farad/m
7 H=1; // magnetic field in amp/m
8 E=H*sqrt(u/e); // formula to calculate
9 disp(E,"magnitude of Energy of plane wave in V/m")
```

Scilab code Exa 7.2 impedance of medium and peak magnetic field

```
1 //Example 7.2
2 clc;
3 clear;
4 // 1st part //impedence of medium
5 ur=1; //relative permeability
6 er=2; //relative permitivity
```

```

7  uo=(4D-7*%pi); // permeability (free space) in H/m
8  eo=8.85D-12; // permitivity (free space) in Farad/m
9  u=ur*uo; // permeability (medium) in H/m
10 e=er*eo; // permitivity (medium) in Farad/m
11 Z=sqrt(u/e); // impedance of medium
12 disp(Z, "impedence of medium in ohm")
13 // 2nd part // peak magnetic field intensity
14 Eo=5; // peak electric field strength in V/m
15 Ho=Eo/Z; // Intensity of magnetic field in A/m
16 disp(Ho, "Intensity of magnetic field in A/m")
17 // 3rd part // velocity of electromagnetic wave
18 v=1/sqrt(u*e); // velocity in m/s
19 disp(v, "velocity of magnetic field in m/s")

```

Scilab code Exa 7.3 wavelength of wave and amplitude of magnetic field

```

1 //Example 7.3
2 clc;
3 clear;
4 // 1st part // wavelength of wave
5 f=3D11; // frequency of wave in Hz
6 c=3D8; // speed of light in m/s
7 w=c/f; // wavelength in m
8 disp(w, "wavelength of wave in m")
9 // 2nd part // amplitude of Oscillating magnetic
   field
10 Eo=50; // amplitude of electric field in V/m
11 Bo=Eo/c; // ocillating magnetic field in Tesla
12 format('e',10); Bo
13 disp(Bo, "approx amplitude of oscillating magnetic
   field in T")

```

Scilab code Exa 7.4 solar energy

```

1 //Example 7.4 // solar energy
2 clc;
3 clear;
4 //given data :
5 r=1.5D11;//distance from sun to earth
6 P=3.8D26;//power radiated by sun
7 N=P/(4*%pi*(r^2));// poyting vector (average energy)
8 N=N*60/4.2D4 ;//to convert watt/m2 into cal/cm2.min
9 N=ceil(N);
10 disp(N," average solar energy in cal/cm2.min")

```

Scilab code Exa 7.5 Dielelctric constant

```

1 //Example 7.5 // Dielelctric constant
2 clc;
3 clear;
4 //given data :
5 v=.62;// velocity factor of coaxial
6 Er=1/v^2;// relative permittivity constant
7 disp(Er," dielectric constant of insulator")

```

Chapter 8

Dielectrics

Scilab code Exa 8.1 polarisation and Energy density

```
1 //Example 8.1 // Dielectric
2 clc;
3 clear;
4 //given data :
5 k=3;// Dielectric constant
6 E=1D6;// field intensity in V/m2
7 e=8.85D-12;// permittivity in C2/N.m2
8 P=e*(k-1)*E;// polarisation in C/m2
9 disp(P,"polarisation in C/m2")
10 D=k*e*E;// displacement vector in C/m2
11 disp(D,"Displacement in C/m2")
12 ED=.5*k*e*E^2;// Energy Density in Joules/m3
13 disp(ED,"Energy density in joules/m3")
```

Scilab code Exa 8.2 Dipole moment of slab

```
1 //Example 8.2 // Dipole moment of slab
2 clc;
```

```

3 clear;
4 //given data :
5 D=5D-4; // displacement vector magnitude in m2
6 P=4D-4; // Polarisation vector magnitude in m2
7 E=D-P; // Field Intensity in m2
8 V=.5; // volume of slab in m3
9 k=D/E; // dielectric constant
10 p=P*V; //total dipole moment in m5
11 disp(k,"Dielectric constant")
12 disp(p,"total dipole constant in m5")

```

Scilab code Exa 8.3 electric susceptibility

```

1 //Example 8.3 // electric susceptibility
2 clc;
3 clear;
4 //given data :
5 k=1.000038; //dielectric constant
6 x=k-1; //electric susceptibility
7 disp(x,"electric susceptibility")

```

Scilab code Exa 8.4 Dipole moment

```

1 //Example 8.4 // Dipole moment
2 clc;
3 clear;
4 //given data :
5 E=100; // Field Intensity in V/m
6 k=1.000074; // dielectric constant
7 e=8.85D-12; // permittivity in Farad/m
8 p=22.4D-3; // dipole moment
9 N=6D23/(22.4D-3); // no. of atoms per unit volume at
   NTP

```

```
10 p=e*(k-1)*E/N; // dipole moment in C-m
11 disp(p,"total moment in C-m")
```

Chapter 14

crystal structure and x ray diffraction

Scilab code Exa 14.4 wavelength and angle

```
1 //Example 14.4 // wavelength & angle
2 clc;
3 clear;
4 //given data :
5 d=2.82; //spacing between successive planes in A
6 theta=8+35/60; //in degree
7 theta=theta*%pi/180; // to convert in radian
8 n=1; // order of reflection
9 lamda=2*d*sin(theta) /n; //de-broglie equation
10 disp(lamda,"wavelength of NaCl in A ")
11 n=2; //to find angle of reflection
12 theta=asin(n*lamda/(2*d)); //angle of reflection
    radian
13 theta=theta*180/%pi; // to convert in degree
14 disp(theta,"angle of reflection in degree")
```

Scilab code Exa 14.5 wavelength and speed of neutron

```
1 //Example 14.5 // wavelength & speed of neutron
2 clc;
3 clear;
4 //given data :
5 n=1; // given first reflection
6 d=3.84; //spacing between successive planes in A
7 m=1.67D-27; // mass of neutron in kg
8 theta=30; //in degree
9 theta=theta*%pi/180; // to convert in radian
10 lamda=2*d*sin(theta) /n; //de-broglie equation
11 disp(lamda,"wavelength of neutron in A ")
12 h=6.626D-34; // plank's constant in joules-sec
13 lamda=lamda*1D-10; // to convert in m
14 v=h/(m*lamda); // e-Broglie relation
15 disp(v,"speed of neutron in m/s")
16 // in book it is wrongly calculated
```

Scilab code Exa 14.6 spacing

```
1 //Example 14.6 // spacing d
2 clc;
3 clear;
4 // 1st part
5 theta=5+28/60; // given glancing angle in degree
6 n=1; //order of reflections
7 lamda=.586; // wavelength in A
8 theta=theta*%pi/180; //to convert in degree
9 d=n*lamda/(2*sin(theta)); // spacing
10 disp(d,"spacing in A")
11 // in question there is a mistake
12 // 2nd part
13 theta=12+1/60; // given glancing angle in degree
14 n=2; //order of reflections
```

```

15 theta=theta*%pi/180; //to convert in degree
16 d=n*lamda/(2*sin(theta)); // spacing
17 disp(d,"spacing in A")
18 //3rd part
19 theta=18+12/60; // given glancing angle in degree
20 n=3; //order of reflections
21 theta=theta*%pi/180; //to convert in degree
22 d=n*lamda/(2*sin(theta)); // spacing
23 disp(d,"spacing in A")
24
25 //The glancing angle is taken differently in the
    solution

```

Scilab code Exa 14.7 glancing angle

```

1 //Example 14.7 // glancing angle
2 clc;
3 clear;
4 //given data :
5 // 1st part
6 lamda=1.549; // wavelength in A
7 d=4.255; // in ter planer spacing in A
8 n=1; //order of reflection
9 theta=asin(n*lamda/(2*d)); // glacing angle in radian
10 theta=theta*180/%pi; // to convert in degree
11 disp(theta,"glancing angle in degree")
12 // 2nd part
13 n=2; //order of reflection
14 theta=asin(n*lamda/(2*d)); // glacing angle in radian
15 theta=theta*180/%pi; // to convert in degree
16 disp(theta,"glancing angle in degree")

```

Scilab code Exa 14.10 Energy to create defect

```

1 //Example 14.10 // Energy to create defect
2 clc;
3 clear;
4 //given data :
5 a=2.82D-10;// interionic distance in m
6 T=298;// temperture in kelvin
7 k=8.625D-5;// Boltzmann constant eV/k
8 n=5D11;// density of defects in per m3
9 V=(2*a)^3;//volume of unit cell
10 p=4;// no. of ion pairs
11 N=p/V;// no. of ion pairs per m3
12 E=2*k*T*log(N/n);// energy in eV
13 disp(E, "Energy to create defect in eV")

```

Scilab code Exa 14.11 Number of defects

```

1 //Example 14.11 // no. of defects
2 clc;
3 clear;
4 //given data :
5 k=8.625D-5;// Boltzmann constant eV/k
6 E=1.4;// energy to create defect in eV
7 T1=293;// temperature in kelvin
8 T2=573;// temperature in kelvin
9 ratio=exp((-E/k)*(1/(2*T1)-1/(2*T2)));// ratio of no
. of defects at T1 & T2
10 format('e',10);ratio;
11 disp(ratio, "ratio of number of Frenkel defect")
12 ratio=1/ratio;//
13 disp(ratio,"it can be written as")

```

Scilab code Exa 14.12 fraction of vacancy sites

```
1 //Example 14.12 // fraction of vacancy sites
2 clc;
3 clear;
4 //given data :
5 f=1D-10;// fraction of vacancy sites
6 T1=500;// temperature in degree
7 T2=2*T1;// condition given
8 T1=T1+273;// to convert in kelvin
9 T2=T2+273;// to convert in kelvin
10 f1=exp(T1*log(f)/T2);//new fraction
11 disp(f1,"new fraction at new temperature")
```

Chapter 16

difficulties of classical mechanics and development of wave mechanics

Scilab code Exa 16.1 de broglie wavelength

```
1 //Example 16.1 //de-broglie wavelength
2 clc;
3 clear;
4 //given data :
5 h=6.62D-34;// plank's constant in joules-sec
6 m=9.1D-31;// mass of electron in Kg
7 V=1.25D3;// Potential difference in kV
8 E=V*1.6D-19;// energy associated to potential in
   joule
9 lamda=h/sqrt(2*m*E);// formula to calculate
10 disp(lamda,"de broglie wavelength in m ")
11
12 //in book it is wronglly calculated
```

Scilab code Exa 16.2 Energy of Neutrons

```
1 //Example 16.2 //Energy of Neutrons
2 clc;
3 clear;
4 //given data :
5 m=1.674D-27; // mass of neutron in kg
6 h=6.60D-34; // plank's constant in joules-sec
7 lamda=1D-10; // de-broglie wavelength in m
8 E=h^2/(2*m*lamda^2); // energy of neutrons in joules
9 E=E/1.6D-19; // to convert in eV
10 disp(E,"energy of neutons in eV")
```

Scilab code Exa 16.3 frequency and energy of photon

```
1 //Example 16.3 //frequency & energy of photon
2 clc;
3 clear;
4 //given data :
5 lamda=4D-7; // de-Broglie wavelength in m
6 c=3D8; // speed of light in m/s
7 h=6.62D-34; // plank's constant in joules-sec
8 v=c/lamda; // frequency of photon in Hz
9 E=h*v; // energy in joules
10 E=E/1.6D-19; // Energy in eV
11 disp(v,"frequency of photon in Hz")
12 disp(E,"Energy of Photon in eV")
```

Scilab code Exa 16.4 de broglie wavelength of neutrons

```
1 //Example 16.4 //de-broglie wavelength of neutrons
2 clc;
3 clear;
```

```

4 //given data :
5 k=1.38D-23; // Boltzmann's Constant in joules per K
6 T=27; // temperature in degree
7 m=1.67D-27; // mass of neutron in kg
8 h=6.62D-34; // plank's constant in joules-sec
9 T=T+273; // to convert in K
10 lamda=h/sqrt(2*m*k*T); // De-broglie Wavelength in m
11 disp(lamda,"De-broglie Wavelength in m")

```

Scilab code Exa 16.5 de broglie wavelength

```

1 //Example 16.5 //de-broglie wavelength
2 clc;
3 clear;
4 //given data :
5 m=1.67D-27; // mass of proton in kg
6 h=6.62D-34; // plank's constant in joules-sec
7 V=2000; // potential Dfference
8 ma=4*m; // mass of alpha particle in kg
9 q=2*1.6D-19; // charge on alpha particle
10 lamda=h/sqrt(2*ma*q*V); // formula to calculate
11 disp(lamda,"de-broglie wavelength in m")

```

Scilab code Exa 16.6 energy of photoelectrons emitted

```

1 //Example 16.6 //energy of photoelectrons emitted
2 clc;
3 clear;
4 //given data :
5 h=6.62D-34; // plank's constant in joules-sec
6 c=3D8; //speed of ight
7 lamda=6D-7; // Threshlod wavelength in m
8 v=6D14; // frequency in Hz

```



```
9 E=h*(v-c/lamda);// energy in joules
10 E=E/1.6D-19;// to convert in eV
11 disp(E,"energy of electrons emitted in eV")
```

Chapter 17

uncertainty principle and schrodinger equation

Scilab code Exa 17.1 Uncertainty in angle of Emergence

```
1 //Example 17.1 //Uncertainty in angle of Emergence
2 clc;
3 clear;
4 //given data :
5 E=3.2D-17;//energy of enectron in J
6 m=9.1D-31;// mass of electron in kg
7 h=6.626D-34;// plank 's constant in J.sec
8 r=1D-6;//radius of circular hole in m
9 p=sqrt(2*m*E);// momentum in Kg.m/sec
10 delta_x=2*r;// uncetainty in position in m
11 delta_p=h/(delta_x);// uncertainty in momentum in Kg
    .m/sec
12 delta_theta=delta_p/p;//uncertainty in angle of
    emergence
13 disp(delta_theta," Uncertainty in angle of Emergence
    in radian");
14
15 //in book it is wrongly calculated
```

Scilab code Exa 17.2 Uncertainty in frequency and uncertainty in velocity

```
1 //Example 17.2 //Uncertainty in frequency &
   uncertainty in velocity
2 clc;
3 clear;
4 //given data :
5 ha=1.0545D-34; // average plank's constant in J.sec
6 h=6.626D-34; // plank's constant in J.sec
7 t=1D-8; //average time elapse in excitation in sec
8 E=ha/t; // uncertainty in energy in j
9 f=E/h; //Uncertainty in Energy in Hz
10 disp(E,"uncertainty in energy in j")
11 disp(f,"Uncertainty in Energy in Hz")
```

Chapter 18

free electron theory

Scilab code Exa 18.1 Fermi Energy

```
1 //Example 18.1 //Fermi Energy
2 clc;
3 clear;
4 //given data :
5 P=.971D3;// density in Kg/m3
6 N=6D26;// Avogadro number in atoms/Kg-mole
7 W=22.99;//atomic weigh of sodium
8 a=N*P/W;// electron density
9 m=9.1D-31;// mass of electron in kg
10 h=6.626D-34;// plank's constant in joules-sec
11 E=((h^2)/(2*m))*(3*a/%pi)^(2/3);// fermi energy in J
12 disp(E,"Fermi energy in J")
13 //in book formula taken wrongly
```

Scilab code Exa 18.2 Energy difference

```
1 //Example 18.2 // Energy difference
2 clc;
```

```
3 clear;
4 //given data :
5 h=1.0545D-34; // average Plank's constant in J-s
6 m=9.1D-31; // mass of electron in kg
7 a=1D-10; // dimension of box in meter
8 E1=((h^2)/(2*m))*(%pi/a)^2; //fermi energy of first
   level in j
9 E2=2*((h^2)/(m))*(%pi/a)^2; //fermi energy of second
   level in J
10 D=E2-E1; // difference of energy
11 disp(D,"energy difference in J")
```

Chapter 19

band theory of solids

Scilab code Exa 19.1 density of electrons and holes

```
1 //Example 19.1 // density of electrons and holes
2 clc;
3 clear;
4 //given data :
5 //2(2% $\pi$ km/h2)^1.5=p(assume) it is a constant
6 p=4.83D21;//constant
7 T=300;//temperature in kelvin
8 E=.7;//semiconductor with gap in eV
9 k=1.38D-23;// Boltzmann constant
10 d=k*T/1.6D-19;// to convert in eV
11 ni=p*((300)^1.5)*exp(-1*E/d);//formula for
    concentration of intrinsic charge carrier
12 disp(ni,"density of electrons and holes in per m3")
13 // in book it is wrongly calculated
```

Scilab code Exa 19.2 position of fermi level

```
1 //Example 19.2 // position of fermi level
```

```

2  clc;
3  clear;
4  //given data :
5  //2(2% $\pi$ km/h2)^1.5=p(assume) it is a constant
6  p=4.83D21;//constant
7  nd=5D22;// concentration of donor atoms in atoms/m3
8  T=300;// temperature in kelvin
9  k=1.38D-23;// Boltzmann constant
10 E=k*T*log(p*T^1.5/nd);//formula for calculation
11 E=E/1.6D-19;//to convert in eV
12 disp(E,"position of fermi level in eV")

```

Scilab code Exa 19.3 position of fermi level

```

1  //Example 19.3 // position of fermi level
2  clc;
3  clear;
4  //given data :
5  Eo=.3;// initial position in eV
6  T=300;//initially temperature in kelvin
7  T1=330;// final temperature in kelvin
8  E=Eo*T1/T;// (formula to calculate) final position
   in eV
9  disp(E,"new position of fermi level in eV")

```

Scilab code Exa 19.4 Hall coefficient and Hall voltage

```

1  //Example 19.4 // Hall coefficient Hall voltage
2  clc;
3  clear;
4  //given data :
5  p=4.83D21;//constant
6  a=.428D-9;// unil cell side in m

```

```

7 E=.15; // fermi level in eV
8 k=1.38D-23; // Boltzmann constant
9 h=6.626D-34; // plank constant in J-s
10 T=300; // temperature in kelvin
11 me=9.1D-31; // mass of electron in kg
12 me1=.014*me; // effective mass in kg
13 mh=.18*me; // effective mass of hole
14 I=.1; // current in Amp
15 B=.1; // magnetic field in tesla
16 b=1D-3; // width of speciman in m
17 n=2/a^3; // no. of atoms per unit volume
18 d=k*T/1.6D-19; // to convert in eV
19 e=1.6D-19; // charge of electron
20 R=1/(n*e); // Hall constant
21 disp(R,"Hall coefficient for sodium in m3/C")
22 // in second part InSb
23 n1=2*((2*pi*k*T/h^2)^1.5)*((me1*mh)^(3/4))*exp
    (-1*.15/(2*d));
24 // formula for concentration in per m3
25 R1=1/(n1*e); // Hall coefficient in m3/C
26 V=R*I*B/b; // Hall voltage in V
27 V1=R1*I*B/b // Hall voltage
28 disp(V,"Hall voltage of sodium")
29 disp(R1,"Hall coefficient for Insb in m3/C")
30 disp(V1,"Hall Voltage of Insb")

```

Scilab code Exa 19.5 energy of electron

```

1 //Example 19.5 // energy of electron
2 clc;
3 clear;
4 //given data :
5 h=6.626D-34; // plank constant in J-s
6 a=.3D-9; // unit cell width in m
7 p=h/(2*a); // electron momentum

```



```
8 m=9.1D-31; // mass of electron in Kg
9 E=p^2/(m*2); // formula for energy
10 disp(p,"electron momentum in Kg m/s")
11 E=E/1.6D-19; // ro convert in ev
12 disp(E,"energy of electron at this momentum in eV")
```

Chapter 21

magnetic properties of solids

Scilab code Exa 21.1 electron spin magnetic dipole moment

```
1 //Example 21.1 // electron spin magnetic dipole
  moment
2 clc;
3 clear;
4 //given data :
5 ub=5.6D-5;//electron spin magnetic moment in eV
6 kbT=1/40;//approximate value kb(constant) & at room
  temperature in eV
7 u=ub/kbT;//formula
8 if(u<1)
9     disp(u,"electron spin magnetic dipole moment &
  kbT/ub>>1")
10
11 else
12     disp(u,"kbT/ub<<1 so it is wrong")
13     end
```

Scilab code Exa 21.2 diamagnetic susceptibility

```
1 //Example 21.2 // diamagnetic susceptibility
2 clc;
3 clear;
4 //given data :
5 r=.53D-8; //(mean radius)bohr radius in cm
6 N=27D23; //atomic density in per cm2
7 k=2.8D-13 //k=e2/mc2constants e-electron m-mass c=
   speed of light in cm
8 X=-2*(N*k/6)*r^2; //formula for 2 electrons
9 disp(X,"diamagnetic susceptibility of helium atom")
```

Chapter 22

superconductivity

Scilab code Exa 22.1 critical field and transition temperature

```
1 //Example 22.1 // critical field & transition
  temperature
2 clc;
3 clear;
4 //given data :
5 T=4.2;//to calculate critical field at T (kelvin)
6 Hc1=1.4D5;// critical magnetic field in amp/m
7 Hc2=4.2D5;//critical magnetic field in amp/m
8 T1=14;//temperature in kelvin
9 T2=13;//temperature ]in kevin
10 Tc=sqrt(.5*((T2^2-T1^2)*(Hc1+Hc2)/(Hc1-Hc2)+T1^2+T2
  ^2));// transition temperature
11 H=Hc1/(1-(T1/Tc)^2);//field at 0 degree
12 Hc=H*(1-(T/Tc)^2)
13 disp(Tc,"transition temperature in kelvin")
14 disp(Hc,"Critical field at T in amp/m")
15
16 //little error due to approximations in book
```

Scilab code Exa 22.2 critical temperature

```
1 //Example 22.2 // critical temperature
2 clc;
3 clear;
4 //given data :
5 Tc1=4.185;//critical temperature in kelvin
6 M=199.5;// isotropic mass
7 M1=203.4;//isotropic mass
8 Tc2=Tc1*(M/M1)^.5;// formula
9 disp(Tc2,"critical temperature in kelvin")
```

Scilab code Exa 22.3 critical current density

```
1 //Example 22.3 // critical current density
2 clc;
3 clear;
4 //given data :
5 d=1D-3;//diameter of wire in m
6 Ho=6.5D4;//critical field at temperature at 0k
7 Tc=7.18;// critical temperature in kelvin
8 T=4.2;//temperature in kelvin
9 Hc=Ho*(1-(T/Tc)^2);//critical field at T kelvin
10 Jc=4*Hc/d;//formula
11 disp(Jc,"critical current density in A/m2")
```

Scilab code Exa 22.4 penetration depth

```
1 //Example 22.4 // penetration depth
2 clc;
3 clear;
4 //given data :
5 w=750;// penetration depth in A
```

```
6 T=3.5; // temperature in kelvin
7 Tc=4.12; // critical temperature in kelvin
8 d=13.55D3; //density of mercury
9 N=6.023D23; // avogadro number
10 M=200D-3; //molecular weight in kg
11 wo=w*(1-(T/Tc)^4)^.5; //formula
12 disp(wo, "penetration depth in A(angstrom)")
13 //n0=d*N/M; //normal electron density at 0 degree
14 //n=n0*(1-(T/Tc)^4); //electron density at T
15 //disp(n)
16
17 //according to question the answer is upto Wo only.
```
