

Scilab Textbook Companion for
Fiber Optics Communication
by H. Kolimbiris¹

Created by
Gaurav Pandey
B.tech
Electronics Engineering
Shri Mata Vaishno Devi University,Katra,J&K
College Teacher
None
Cross-Checked by
Spandana

June 7, 2016

¹Funded by a grant from the National Mission on Education through ICT,
<http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab
codes written in it can be downloaded from the "Textbook Companion Project"
section at the website <http://scilab.in>

Book Description

Title: Fiber Optics Communication

Author: H. Kolimbiris

Publisher: Pearson Education, New Delhi

Edition: 1

Year: 2001

ISBN: 9788131715888

Scilab numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

AP Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

Contents

List of Scilab Codes	4
1 Elements of Optics And Quantum Physics	5
2 Fundamental of Semi Conductor Theory	17
3 Optical Sources	24
4 Optical Detectors	30
5 Optical Amplifiers	32
6 Optical Transmittor	34
7 Optical Receivers	47
9 Optical Fibers	49
10 Optical Modulation	67
11 Multiplexing	69
12 Optical Systems	71
13 Networks	102

List of Scilab Codes

Exa 1.1	Arrival time difference between two monochromatic optical beams	5
Exa 1.2	Calculate angle of refraction velocity wavelength	6
Exa 1.3	Angle of refraction and Deviation	6
Exa 1.4	Find optical Path and angle phi	7
Exa 1.5	Find Phase velocity	8
Exa 1.6	find wavelength	9
Exa 1.7	Find wavelength of Light	9
Exa 1.8	Ratio of input output intensity	10
Exa 1.9	Compute length of Tube	10
Exa 1.10	Degree of polarisation	11
Exa 1.11	Number of refractive Plates	11
Exa 1.12	Ratio of Optical Ray	12
Exa 1.13	Angle between polariser and analyzer	12
Exa 1.14	find time difference and phase difference	13
Exa 1.15	Find wavelength	13
Exa 1.16	Compute the constant phi	14
Exa 1.17	Voltage required to accelerate an electron	15
Exa 1.18	Compute uncertainty in electron velocity	15
Exa 2.1	maximum number of electron	17
Exa 2.2	Find band gap energy	17
Exa 2.3	Find carrier velocity and current density	19
Exa 2.4	Find electron density and type of semi conductor and extrensic semiconductivity	20
Exa 2.5	Find barrier voltage	20
Exa 2.6	Calculate current	21
Exa 2.7	compute saturation current	22
Exa 2.8	calculate radiative minority	22

Exa 3.1	Determine the power coupled into fiber	24
Exa 3.2	Power Coupled into fiber	24
Exa 3.3	Bandwidth of Led Source	25
Exa 3.4	Coupling efficiency of an optical source	26
Exa 3.5	Coupling efficiency	26
Exa 3.6	MTBF of LED source	27
Exa 3.7	Calculate MTBF	28
Exa 4.1	Response time of PIN photodetector	30
Exa 4.2	MTBF of photodetector	30
Exa 4.3	Photon Lifetime	31
Exa 5.1	Input power	32
Exa 5.2	Compute pseudo random binary sequence	32
Exa 6.1	Determine whether heat sink or not	34
Exa 6.2	determine whether or not heat sink	34
Exa 6.3	Determine wheather heat sink	35
Exa 6.4	Find Junction Temperature	36
Exa 6.5	calculate value of r1 r2 r3 and c1	36
Exa 6.6	Compute required reference current	37
Exa 6.7	Find bandwidth for optical one and zero	38
Exa 6.8	compute external resistance and alarm current	39
Exa 6.9	Total power dissipation	39
Exa 6.10	find maximum power dissipation	41
Exa 6.11	Calculate differential and common mode impedance .	42
Exa 6.12	Compute differential mode and common mode impedance .	42
Exa 6.13	Compute intermediate frequency	43
Exa 6.14	Allowed parasitic cable inductance	43
Exa 6.15	Calculate high frequency component	43
Exa 6.16	compute low frequency component	44
Exa 6.17	Calculate noise bandwidth	44
Exa 6.18	Calculate effective hight frequency component	45
Exa 6.19	Calculate the effective low frequency component	45
Exa 7.1	PWD of optical receiver	47
Exa 7.2	Value of R _{adj}	47
Exa 7.3	Reference voltage and reference resistor	48
Exa 9.1	Compute angle of acceptance critical angle and NA .	49
Exa 9.2	Fiber Attenuation	49
Exa 9.3	Maximum length of optical fibre	50
Exa 9.4	Rayleigh attenuation of an optical fibre	50

Exa 9.5	SBS threshold optical power	52
Exa 9.6	SBS threshold optical power	52
Exa 9.7	SBS threshold optical power	53
Exa 9.8	SBS threshold optical power	54
Exa 9.9	SBS threshold optical power	54
Exa 9.10	Raman scattering threshold power	55
Exa 9.11	Raman scattering threshold power	55
Exa 9.12	Raman scattering threshold power	56
Exa 9.13	Maximum modal number	57
Exa 9.14	Maximum operating bandwidth	57
Exa 9.15	Maximum operating bandwidth	58
Exa 9.16	Maximum operating bandwidth	58
Exa 9.17	RMS pulse chirping	59
Exa 9.18	RMS pulse broadening	60
Exa 9.19	Channel capacity	60
Exa 9.20	Channel capacity	61
Exa 9.21	Total chromatic dispersion	61
Exa 9.22	Compute optical attenuation	62
Exa 9.23	Compute total attenuation	62
Exa 9.24	Compute the insertion loss	63
Exa 9.25	Compute insertion loss	63
Exa 9.26	Compute insertion loss	64
Exa 9.27	Compute total insertion loss	65
Exa 9.28	Compute insertion loss at the joint	65
Exa 10.1	Required Biasing voltage	67
Exa 10.2	Biasing range	67
Exa 11.1	Cross talk in reference to the number of channel	69
Exa 11.2	Capacitor value of PLL section	69
Exa 11.3	Value of damping coefficient	70
Exa 12.1	Compute power margin	71
Exa 12.2	Compute power margin	71
Exa 12.3	Calculate level of additional power launched	72
Exa 12.4	Compute link power budget	72
Exa 12.5	Calculate PIN diode required operating power and total power budget	73
Exa 12.6	Calculate maximum link distance	74
Exa 12.7	Compute chromatic dispersion	74
Exa 12.8	Compute maximum bit rate	74

Exa 12.9	Compute Maximum link span	75
Exa 12.10	Calculate chromatic dispersion	76
Exa 12.11	Calculate dispersion penalty	76
Exa 12.12	Calculate maximum length	77
Exa 12.13	Calculate the maximum length of optical link	77
Exa 12.14	Calculate maximum dispersion mean link margin sigma link margin	78
Exa 12.15	Compute maximum dispersion and nominal distribution	79
Exa 12.16	Calculate maximum dispersion and maximum distance	80
Exa 12.17	Calculate the CSO distortion	82
Exa 12.18	Calculate the required AM modulation	82
Exa 12.19	Compute the CTO distortion	83
Exa 12.20	Calculate the CSO and CTO	83
Exa 12.21	Calculate the CNR	84
Exa 12.22	Calculate the RIN	85
Exa 12.23	Calculate the required optical power	85
Exa 12.24	Calculate the percentage of optical power reflected back	86
Exa 12.25	Calculate the output voltage of an optical receiver . .	86
Exa 12.26	Determine the optical receiver responsivity	87
Exa 12.27	Calculate the modulation depth	87
Exa 12.28	Calculate the CNR	88
Exa 12.29	Total fiber span attenuation	88
Exa 12.30	Calculate the SNR	89
Exa 12.31	Calculate the optical power in fiber	90
Exa 12.32	Compute the transmission length	90
Exa 12.33	Compute the maximum bit rate	91
Exa 12.34	Compute the soliton characteristic length	91
Exa 12.35	Determine maximum dispersion	92
Exa 12.36	Calculate the soliton pulse width	92
Exa 12.37	Calculate the soliton peak pulse	93
Exa 12.38	Compute the standard deviation	94
Exa 12.39	Calculate the system BER	94
Exa 12.40	Compute the standard deviation	95
Exa 12.41	Calculate the collision length	95
Exa 12.42	Calculate the half channel length	96
Exa 12.43	Calculate the minimum number of soliton	96
Exa 12.44	Compute the maximum number of soliton	97
Exa 12.45	Compute the number of collision	98

Exa 12.46	Calculate the channel spacing	98
Exa 12.47	Compute the bit period	99
Exa 12.48	Calculate the maximum modulator spacing	99
Exa 12.49	Calculate the length of dispersion	100
Exa 12.50	Calculate the collision length	100
Exa 12.51	Compute the soliton collision length	101
Exa 13.1	Calculate R9 R7 R8 C4	102
Exa 13.2	Calculate Led If R3 C4	103
Exa 13.3	Characteristic impedance and propagation delay	104

Chapter 1

Elements of Optics And Quantum Physics

Scilab code Exa 1.1 Arrival time difference between two monochromatic optical beams

```
1
2
3
4
5
6 //Example1-1
7 //Given
8 clc;
9 clear all;
10 printf("( i )    t1=d/c \n");
11 printf(" ( ii )   t2=[(d-5)/c]+[5/v2] \n");
12 printf("           v2=c/n2 \n");
13 printf("           t2=(d+2.5)/c\n");
14 printf(" ( iii )  delta_t=t2-t1=(d+2.5-d)/c\n");
15 c=3*10^8;          //Speed of light in m/s
16 delta_t=2.5*10^-2/c;           //converted 2.5 cm
                                into meters
17 printf('The time difference %e s' ,delta_t );
```

```
18 printf("\n Arrival time difference of two
           monochromatic beams is %0.0f ps", delta_t*10^12)
19 // Answer misprinted in the book
```

Scilab code Exa 1.2 Calculate angle of refraction velocity wavelength

```
1
2
3
4
5
6 // given
7 //page no 5
8 clc;
9 clear;
10 //Applying Snell's law
11 a=1*sin(428)/1.333; //a=sin(w2)
12 printf("Angle of refraction is %0.1f\n",a)
13 printf("\n Angle of refraction is %0.0f degree \n",
           asin(a)*57.27)
14 c=3*10^8;           //speed of light in m/s
15 n2=1.333;          //refractive index of 2nd medium
16 v2=c/n2;           //velocity in second medium in m
                     /s
17 n1=1;               //refractive index of 1st medium
18 l1=620;              //in nm wavelength
19 printf("\n Velocity of optical ray through medium
           second %0.02f*10^8 m/s\n",v2/10^8);
20 l2= (n1*l1)/n2;    //wavelength in 2nd medium in nm
21 printf("\n Wavelength of optical ray through medium
           second %0.1f nm",l2);      //Result
```

Scilab code Exa 1.3 Angle of refraction and Deviation

```

1
2
3
4
5
6 // given
7 // page no 5
8 clc;
9 clear;
10 n1=1;           // refractive index of air
11 n2=1.56;        // refractive index of medium
12 w1=60;          // in deg C
13 // using snell's law
14 a= n1*sind(w1)/n2;      // a=sin(w1)
15 w2=asind(a);          // in degree
16 printf("Angle of refraction is %0.2f degree\n",w2);
17 B=w1-w2;              // in degree
18 printf("Angle of deviation is %0.1f degree\n",B)
19 // The answer doesn't match because of printing
   errors in calculation as sin(608)

```

Scilab code Exa 1.4 Find optical Path and angle phi

```

1 // given
2 // page no 6
3 clc;
4 disp('Solution ( i )');
5 w=5/12.5; // tan(w)=5/12.5;
6 printf("\n The value of tan(w2) is %0.1f \n",w);
7 w2=atan(w)*180/%pi;
8 //w2=atan(w)*180/%pi
9 printf("\n The value of w2 is %0.1f degree\n",w2);
10 printf("\n The value of sin(w2) is %0.2f \n",sin(w2*
   %pi/180));
11 disp('Solution ( ii )');

```

```

12 // Applying snell 's law
13 n1=1.05;
14 n2=1.5;
15 w1=(n2*sin(w2*pi/180))/n1; //a=sin(w1)
16 printf("\n The value of sin(w1) is %0.2f \n",w1);
17 printf("\n The value of w1 is %0.0f degree \n",asin
    (w1)*180/%pi);
18 //value of w1
19 //tan(w1)=(p-x)/12.5;
20 k=0.62*12.5;
21 d=1.05*((12.5)^2+(k)^2)^0.5 +1.5*(12.5^2+5^2)^0.5; //
    d=1.05[(h1)^2+(k)^2]^0.5 +n2(h2^2+x^2)^0.5;
22 printf("\n the optical distance is %0.2f cm\n",d);

```

Scilab code Exa 1.5 Find Phase velocity

```

1 //Ex1_5
2 //given
3 //page no 11
4 clc;
5 clear;
6 c=3*10^8;
7 disp('Solution (i) is ');
8 ri=1.5; //refractive index
9 u=830 // in nm
10 l=u/ri; //in nm
11 printf("\n Wavelength is %0.0f nm \n",l);
12 disp('Solution (ii) is ');
13 l=round(l); // rounding to nearest
    integer
14 f=c/(l*10^-9)*10^-12; //in THz
15 printf("\n frequency is %0.0f THz\n",f);
16 disp('Solution (iii) is ');
17 f=round(f); // rounding to nearest
    integer

```

```
18 v=1*10^-9*f*10^12;           //in m/s
19 mprintf("\n phase velocity is %.3e m/s\n",v); ////
    answer is getting rounding off due to larger
    calculation
```

Scilab code Exa 1.6 find wavelength

```
1 //Ex1_6
2 //given
3 //page no 12
4 clc;
5 clear;
6 disp('Solution (i) is ');
7 l=720;           //wavelength in nm
8 n=1.5;           //refractive index
9 lm=l/n;
10 disp('nm',lm,'Wavelength is ');           //result
11 disp('Solution (ii) is ');
12 c=3*10^8;        //in m/s speed of light
13 u=c/n;
14 disp('m/s ',u,' Velocity is ');           //result
```

Scilab code Exa 1.7 Find wavelength of Light

```
1 //Ex1_7
2 //given
3 //page no 12
4 clc;
5 clear;
6 disp('Solution (i)');
7 c=3*10^8;        //in m/s speed of light
8 l=640;           //in nm
9 u=2.2*10^8;       //in m/s
```

```
10 lm=u*l/c; //wavelenth in medium
11 printf("\n The wavelength is %0.1f nm\n",lm); // The
    answer in the book is misprinted
12 disp('Solution (ii)');
13 n=l/lm; //refractive index
14 printf("\n Refractive Index is %0.3f \n",n); //The
    answer in the book is misprinted
```

Scilab code Exa 1.8 Ratio of input output intensity

```
1
2
3
4
5
6 //Ex1_8
7 //given
8 //page no 12
9 clc;
10 clear;
11 //k=aa+as=6.3;
12 //Given values from research
13 k=6.3; //combined attenuation due to absorption
        and scattering
14 d=25; //in cm
15 disp('Solution (ii)');
16 //Io/Ii=exp(-(ao+ai)*d); d in m
17 j=exp(-(k)*d/100); //Io/Ii ratio
18 printf("\n Io is %0.3f of Ii \n",j); //result
```

Scilab code Exa 1.9 Compute length of Tube

```
1 //Ex1_9
```

```

2 // given
3 // page no 13
4 clc;
5 clear;
6 // Given formula Io / Ii=exp(-(ao+ai)*d);
7 // k=aa+as=63.1;
8 // Io / Ii =1.5
9 d=log(.15)/-63.1; //length of tube
10 printf("\nLength of tube , d = %0.0f cm \n",d*100);
    //Result

```

Scilab code Exa 1.10 Degree of polarisation

```

1 //Example no 1-10
2 //page no. 26
3 clc;
4 clear;
5 //p=m/{m+[2*n/(1-n)^2]^2};
6
7 m=5; //no. of reflective plates
8 n=1.33; //refractive indices
9 p=m/{m+[2*n/(1-(n)^2)]^2}; //degree of polarisation
10 printf("\n The degree of polarisation is %0.1f \n",p);

```

Scilab code Exa 1.11 Number of refractive Plates

```

1 //Example no 1-11
2 //page no. 26
3 clc;
4 clear;
5 //m= p*{m+[2*n/(1-n)^2]^2};
6

```

```

7 n=1.5;           // refractive indices
8 p=0.45;          // degree of polarisation
9 m={p*[2*n/(1-n^2)]^2}/(1-p);
10 printf("\n Thus it will require %0.0f reflective
    plate to achieve a degree of polarization equal to
    0.45",m);      // Result mis rounded off to
    nearest integer

```

Scilab code Exa 1.12 Ratio of Optical Ray

```

1
2 //Example no 1-12
3 //page no. 27
4 clc;
5 clear;
6 //I1/I0=cos(w)^2
7 //k=I1/I0 ;
8
9 w=30;           //angle bw polarizer and
    analyser in degree
10 k=cosd(w)^2;
11 disp(k,'The ratio of optical ray intensity ,I1/I0=')
    ;           //Result

```

Scilab code Exa 1.13 Angle between polariser and analyzer

```

1 //Example no 1-13
2 //page no. 27
3 clc;
4 clear;
5 //I1/I0=cos(w)^2
6 //Given I1/I0=0.55
7

```

```
8 k=sqrt(0.55); //from above formulae
9 printf("\n cos w is %0.2f ",k);
10 printf("\n The angle bw polarizer and analyser , w
      is %0.0f degree",acos(k)*180/pi); //Result
```

Scilab code Exa 1.14 find time difference and phase difference

```
1 //Example no 1-14
2 //page no. 29
3 clc;
4 clear;
5 disp('Solution ( i ) is ');
6 ne=1.4; //refractive index
7 no=1.25; //refractive index
8 c=3*10^8; //in m/s
9 T=2*10^-5; //in m
10 l=740; //in nm
11 t=[ne-no]*T/c; //time difference
12 printf("\n Time difference , t is %0.2f ps",t*10^12);
   // result
13 disp('Solution ( ii ) is ');
14 le=l/ne;
15 lo=l/no;
16 fi=2*pi*T*(1/le-1/lo)*10^9;
17 printf("\n Phase difference is %0.1f rad",fi); //
   result
18 // Answer misprinted in book
```

Scilab code Exa 1.15 Find wavelength

```
1
2
3 //page no. 31
```

```

4 //Example no 1-15
5 //E=h*v=h*c/l ;
6 clc;
7 clear;
8 E=3;           // In KeV
9 //1eV=1.6*10^-19
10 h=6.63*10^-34; //plank constant in J/s
11 c=3*10^8;      // speed of light in m/s
12 l=h*c/(E*10^3*1.6*10^-19); // wavelength in nm
13 printf("wavelength of a electromagnetic radiation is
          %0.3f nm",l*10^9); //result

```

Scilab code Exa 1.16 Compute the constant phi

```

1
2 //page no. 31
3 //Example no 1-16
4 clc;
5 clear;
6 disp('Solution (i) is ');
7 l=670 //in nm
8 h=6.63*10^-34; // plank constant in J/s
9 c=3*10^17 //speed of light in nm/sec
10 Ek=0.75 //In eV
11 phi=(h*c/l)/(1.6*10^-19) -Ek;
12 phi=round(phi*10)/10;           //round to 1 decimal
                                  point
13 printf("\n Characteristic of material = %0.1f eV\n",
        phi); //result
14 disp('Solution (ii) is ');
15 fc=phi*1.6*10^-19/h*10^-12; // frequency in THz//result
16 fc=round(fc);
17 printf("\n Cutoff frequency is = %0.0f THz\n",fc);
        //result

```

```
18 lc=c/(fc*10^12);           //in nm
19 printf("\n Cutoff wavelength is = %0.0f nm\n",lc);
   //result
```

Scilab code Exa 1.17 Voltage required to accelerate an electron

```
1
2
3 //page no. 31
4 //Example no 1-17
5 clc;
6 clear all;
7 disp('Solution (i) is ');
8 l=0.045; //wavelength in nm
9 h=6.63*10^-34;          //planks constant in J/s
10 c=3*10^8;              //speed of light in m/s
11 E=h*c/l/10^-9;         //energy of photon in eV
12 mprintf("\n E = %e J",E);
13 E1=E/(1.6*10^-19);     // energy in joule
14 mprintf("\n E = %e eV",E1);
15 e=1.6*10^-19;           // charge of electron
16 disp('Solution (ii) is ');
17 V=E/e;
18 printf("\n Required voltage is = %0.2f KV",V/1000);
   // result
19
20 // Value of wavelenght in problem is .45 but in the
   solution is .045
21 //the value considered above is .045
```

Scilab code Exa 1.18 Compute uncertainty in electron velocity

```
1 //page no. 36
```

```
2 //Example no 1-18
3 clc;
4 clear;
5
6 disp('Solution (i) is ');
7 x=620 // difference in particle momentum In nm
8 h=6.63*10^-34 // planks constant In J/s
9 //p=h/(4*pi*x);
10 //m*v=h/(4*pi*x);
11 m=9.11*10^-31 //In kg // mass of electron
12 v=h /(4*pi* x *10^-9*m); // electron velocity
13 printf("\n The uncertainty in electron velocity is
%0.0 f m/s \n",v); // result
```

Chapter 2

Fundamental of Semiconductor Theory

Scilab code Exa 2.1 maximum number of electron

```
1 //Chapter 2
2 //page no 43
3 //given
4 clc;
5 clear ;
6 n=1;
7 Ne=2*n^2;
8 printf("\n Maximum number of electron in 1st shell
      is %.0f\n",Ne); //Result
9 n2=2; // shell no
10 Ne2=2*n2^2; // shell no
11 printf("\n Maximum number of electron in 2nd shell
      is %.0f ",Ne2); //Result
```

Scilab code Exa 2.2 Find band gap energy

```

1 //Chapter 2
2 //page no 45
3 //given
4 clc;
5 clear ;
6 //Given for silicon for temp 0–400K
7 Eg0_Si=1.17;           //in eV
8 A=4.73*10^-4;          //in eV/K
9 B=636;
10 for i=1:8
11 T=50*i;               //degree/Kelvin
12 Eg_Si=Eg0_Si-(A*T^2)/(B+T);
13 printf("\n Band gap energy of silicon at %.0f K is %.
14 .3f eV ",T,Eg_Si); //result
14 end
15 //Given for Germanium for temp 0–400K
16 disp("");
17 Eg0_Ge=0.7437;         //in eV
18 A_Ge=4.774*10^-4;      //in eV/K
19 B_Ge=235;
20 for i=1:8
21 T=50*i;               //degree/Kelvin
22 Eg_Ge=Eg0_Ge-(A_Ge*T^2)/(B_Ge+T);
23 printf("\n Band gap energy of germanium at %.0f K is %
24 .3f eV ",T,Eg_Ge); //result
24 end
25
26 //Given for GaAs for temp 0–400K
27 disp("");
28 Eg0_Ga=1.519;          //in eV
29 A_Ga=5.405*10^-4;      //in eV/K
30 B_Ga=204;
31 for i=1:8
32 T=50*i;               //degree/Kelvin
33 Eg_Ga=Eg0_Ga-(A_Ga*T^2)/(B_Ga+T);
34 printf("\n Band gap energy of GaAs at %.0f K is %.3f
35 eV ",T,Eg_Ga); //result
35 end

```

Scilab code Exa 2.3 Find carrier velocity and current density

```
1 //Chapter 2
2 //page no 52
3 //given
4 clc;
5 clear ;
6 l=10*10^-3;           //in m
7 w=2*10^-3;            //in m
8 h=2*10^-3;            //in m
9 V=12;                 //in V
10 u_n=0.14;             //in m*m/V*s
11 u_p=0.05;             //in m*m/V*s
12 q_n=1.6*10^-19;       //in Columbs
13 q_p=1.6*10^-19;       //in Columbs
14 p_i=2.4*10^19;        //in columbs
15 n_i=2.4*10^19;        //in columbs
16 E=V/l;
17 v_n=E*u_n;
18 v_p=E*u_p;
19 J_n=n_i*q_n*v_n;
20 J_p=p_i*q_p*v_p;
21 J=J_n+J_p;
22 printf("\n Electron velocity :vn is %.0f m/s ",v_n)
      ;//result
23 printf("\n Hole velocity :vp is %.3f km/s ",v_p
      /1000); // result
24 printf("\n Current density : Jn %0.2f A/m^2",J);
      //Result
25 A=88*10^-6;
26 I_T=J*A;
27 printf("\n Total current :I_T is %.0f mA ",I_T
      *1000); //Result
```

Scilab code Exa 2.4 Find electron density and type of semi conductor and extrensic semiconductivity

```
1 //Chapter 2
2 //page no 53
3 //given
4 clc;
5 clear ;
6 n_i=2*10^17;           // electron /m*m*m
7 p=5.7*10^20;          // holes /m*m*m
8 u_n=0.14;              //in m*m/V*s
9 u_p=0.05;              //in m*m/V*s
10 q_n=1.6*10^-19;       //in Columbs
11 q_p=1.6*10^-19;       //in Columbs
12 n=(n_i)^2/p;
13 mprintf("\n Electron :n is %e electrons ",n); //
    result
14 n=7*10^13
15 P=(n*u_n*q_n)+(p*u_p*q_p);
16 printf("\n Conductivity :P is %.2f S/m ",P); //
    result
17 // answer misprinted
```

Scilab code Exa 2.5 Find barrier voltage

```
1 //Chapter 2
2 //page no 55
3 //given
4 clc;
5 clear ;
6 NA=10^22;               // acceptors /m*m*m
7 ND=1.2*10^21;          // donors /m*m*m
```

```

8 T=298;           //in Kelvin
9 k=1.38*10^-23;   //Boltzman Constant in J/K
10 q=1.6*10^-19;    // charge of electron in C
11 Vt=k*T/q;       //thermal voltage in V
12 printf("\n VT is %0.1f mV \n",Vt*1000);      //
   result
13 n_i=2.4*10^17;   //carrier/m^3 for silicon
14 VB=Vt*log(NA*ND/n_i^2); // barrier voltage in V
15 printf("\n Barrier Voltage of Silicon VB is %0.0f
   mV ",VB*1000);      //result

```

Scilab code Exa 2.6 Calculate current

```

1
2
3
4
5
6 //Chapter 2
7 //page no 56
8 //given
9 clc;
10 clear ;
11 Is=0.12;          //in pAmp
12 V=0.6;            //in V
13 T=293;             //in Kelvin
14 k=1.38*10^-23;    //Boltzmann's Constant in J/K
15 q=1.6*10^-19;     // charge of electron in C
16 Vt=k*T/q;         //thermal voltage
17 printf("\n VT(20 deg Cel) is %0.5f V \n",Vt); //
   result in book is misprint
18 T1=373;           //in Kelvin
19 n=1.25;
20 Vt1=k*T1/q;       //thermal voltage
21 printf("\n VT(100 deg Cel) is %0.5f V \n",Vt1);

```

```

22 I=Is*(exp(V/(n*Vt1))-1);           //forward biasing
    current in mircoA
23 printf("\n I(100 deg Cel) is %0.2f microA \n",I
    /10^6); //result

```

Scilab code Exa 2.7 compute saturation current

```

1 //Chapter 2
2 //page no 56
3 //given
4 clc;
5 clear ;
6 Is=100;           //in nAmp
7 Ts=100;           //in Kelvin
8 I_s=Is*10^-9*2^(Ts/10);      //I_s will be in nm
9 printf("\n I(100 deg Cel) is %0.2f microA \n",I_s
    *10^6); //converted to microA from nm
10 // wrong calculation in the book

```

Scilab code Exa 2.8 calculate radiative minority

```

1
2
3
4
5
6 //Chapter 2
7 //page no 59
8 //given
9 clc;
10 clear ;
11 Br_Si=1.79*10^-15;           //Recombination
    coefficient for Si

```

```

12 Br_Ge=5.25*10^-14;           //Recombination
    coefficient for Ge
13 Br_GeAs=7.21*10^-10;         //Recombination
    coefficient for GeAs
14 Br_InAs=8.5*10^-11;          //Recombination
    coefficient for InAs
15 P_N=2*10^20;                //per cubic cm
16 T_Ge=1/Br_Ge/P_N; //radiative minority carrier
    lifetime
17 printf("\n T_Ge is %0.3f micro-s \n",T_Ge/10^-6); //result
18 T_Si=1/Br_Si/P_N; //radiative minority carrier
    lifetime
19 printf("\n T_Si is %0.2f micro-s \n",T_Si/10^-6); //result
20 T_InAs=1/Br_InAs/P_N; //radiative minority carrier
    lifetime
21 printf("\n T_InAs is %0.0f ps \n",T_InAs/10^-12); //result
22 T_GeAs=1/Br_GeAs/P_N; //radiative minority carrier
    lifetime
23 printf("\n T_GeAs is %0.0f ps \n",T_GeAs/10^-12); //result

```

Chapter 3

Optical Sources

Scilab code Exa 3.1 Determine the power coupled into fiber

```
1 //Chapter 3
2 //page no 67
3 //given
4 clc;
5 clear all;
6 Pin=1;           //microW
7 W=15;            //in degree
8 NA=sin(W*%pi/180);
9 NAA=0.26;         //NA=0.2588190 which is rounded
                    off
10 C_c=(NAA)^2;
11 printf("\n Coupling coefficient is %0.4f \n",C_c);
12 Pf=C_c*Pin;
13 printf("\n Power coupled into fiber %0.1f nW\n",Pf
        *1000);
```

Scilab code Exa 3.2 Power Coupled into fiber

```

1 //Chapter 3
2 //page no 67
3 //given
4 clc;
5 clear all;
6 n=0.02;           //in percentage
7 W=20;             //in degree
8 Vf=1.5;           //in Volts
9 If=20;            //in mAmps
10 Pin=If*Vf;
11 printf("\n Power coupled into fiber ,Pin = %0.0f mW
    \n",Pin);
12 Po=n*Pin;
13 printf("\n Output Power of the optical source is
    %0.1f mW\n",Po);
14 //from nc=20 degree
15 C_c=(sin(W*pi/180))^2;
16 Pf=C_c*Po
17 printf("\n Optical power coupled into fibre is ,Pf =
    %0.0f microW\n",Pf*1000);

```

Scilab code Exa 3.3 Bandwidth of Led Source

```

1 //Chapter 3
2 //page no 68
3 //given
4 clc;
5 clear all;
6 tr=10;           //in nsec
7 BW=0.35/tr/10^-9;
8 printf("\n Maximum operating bandwidth is %0.0f MHZ
    \n",BW/10^6);      //divided by 10^6 to convert
    answer in MHZ

```

Scilab code Exa 3.4 Coupling efficiency of an optical source

```
1 //Chapter 3
2 //page no 70
3 //given
4 clc;
5 clear all;
6 T=1; //Air
7 NA=0.3;
8 n0=1;
9 //x=y;
10 disp(" for step index :A=infinite");
11 //for infinite alpha
12 //nc=T*(NA/n0)^2*(x/y)^2*(A/(A+2))
13 nc=T*(NA/n0)^2*(1)^2*1; // A/(A+2)=1 for A=
    infinite
14 printf("\n Coupling Coefficient ,nc = %0.0f percent \
    \n\n",nc*100);
15
16 disp(" for graded index :A=2");
17 A=2;
18 //n_c=(T*(NA/n0)^2*[A+[1-(y/x)^2]]/(A+2))
19 n_c=(T*(NA/n0)^2*[A+[1-(1)^2]]/(A+2)) //x/y=1
20 printf("\n Coupling Coefficient ,nc = %0.1f percent \
    \n",n_c*100);
```

Scilab code Exa 3.5 Coupling efficiency

```
1 //Chapter 3
2 //page no 71
3 //given
4 clc;
```

```

5 clear all;
6 T=1; //Air
7 NA=0.3;
8 n0=1;
9 A=2;
10 //y=0.75x;
11 disp(" for step index :");
12 //for infinite alpha
13 //nc=T*(NA/n0) ^2*(x/y) ^2*(A/(A+2))
14 nc=T*(NA/n0) ^2*(1/0.75) ^2*A/(A+2);           //      y/
15 x=0.75
16 printf("\n Coupling Coefficient ,nc = %0.0f percent \
17 \n",nc*100);
18
19 disp(" for graded index :A=2");
20 A=2;
21 //n_c=(T*(NA/n0) ^2*[A+[1-(y/x) ^2]]/(A+2))
22 n_c=(T*(NA/n0) ^2*[A+[1-(0.75) ^2]]/(A+2))      //y/x
23 =0.75
24 printf("\n Coupling Coefficient ,nc = %0.1f percent \
25 \n",n_c*100);

```

Scilab code Exa 3.6 MTBF of LED source

```

1 //Chapter 3
2 //page no 72
3 //given
4 clc;
5 clear all;
6 //calculate Tf
7 If=85;           //in mAmps
8 Vf=2.5;          //in Volts
9 Ta=25;           //in deg C
10 //calculate Tj
11 W=150;          //in C/W for hermetic led

```

```

12 Pd=If*Vf;
13 Tj=Ta+W*Pd/1000;
14 printf("\n Value of Tj is %0.1f deg C\n",Tj);
15 TF=8.01*10^12 *%e^-(8111/(Tj+273));
16 printf("\n Value of TF is %0.0f deg C\n",TF);
17 //calculate RF
18 BF=6.5*10^-4; //from table
19 QF=0.5; //from table
20 EF=1; //from table
21 RF=BF*TF*EF*QF*1/10^6;
22 disp(RF,"Value of RF")
23 printf("\n Value of MTBF is %0.0f*10^6 hours \n",1/
    RF/10^6); //Answer in book is misprint in last
    line

```

Scilab code Exa 3.7 Calculate MTBF

```

1 //Chapter 3
2 //page no 74
3 //given
4 clc;
5 clear all;
6 //calculate Tf
7 If=120; //in mAmps
8 Vf=1.8; //in Volts
9 Ta=80; //in deg C
10 //calculate Tj
11 W=150; //in C/W for hermetic led
12 Pd=0.5*If*Vf;
13 Tj=75+W*Pd/1000;
14 printf("\n Value of Tj is %0.1f degree cel \n",Tj);
15 TF=8.01*10^12 *%e^-(8111/(Tj+273));
16 printf("\n Value of TF is %0.0f \n",TF);
17 //calculate RF
18 BF=6.5*10^-4; //from table

```

```
19 QF=0.2;                      //from table
20 EF=0.75;                      //from table
21 RF=BF*TF*EF*QF*1/10^6;
22 printf("\n Value of RF is %0.3f*10^6 \n",RF*10^6);
23 printf("\n Value of MTBF is %0.0f*10^6 hours \n",1/
    RF/10^6);
```

Chapter 4

Optical Detectors

Scilab code Exa 4.1 Response time of PIN photodetector

```
1 //Chapter 4
2 //page no 99
3 //given
4 clc;
5 Tn=5;           //in micrometer
6 Vs=10^7;        //in m/s
7 tr=Tn*10^-6/Vs;
8 disp("ps",tr/10^-12,"Response time");
```

Scilab code Exa 4.2 MTBF of photodetector

```
1 //Chapter 4
2 //page no 106
3 //given
4 clc;
5 //calculate Tf
6 Pd=1.15;          //in mW
7 //calculate Tj
```

```

8 TA=25; //in deg C
9 theta_JA=200; //in C/W for hermetic led
10 TJ=TA+theta_JA*Pd/10^3;
11 TF=8.01*10^12 *%e^-(8111/(TJ+273));
12 printf("\n Value of TJ is %0.2f deg C\n",TJ);
13 printf("\n Value of TF is %0.2f deg C\n",TF);
14 // calculate RF
15 BF=1.1*10^-3; //from table
16 QF=0.5; //from table
17 EF=1; //from table
18 RF=BF*TF*EF*QF*1/10^6;
19 disp(RF," Value of RF");
20 printf("\n Value of MTBF is %0.0f*10^6 hours \n",1/
RF/10^6);

```

Scilab code Exa 4.3 Photon Lifetime

```

1 //Chapter 4
2 //page no 114
3 //given
4 clc;
5 R1=0.7;
6 R2=0.99;
7 ad=0.1;
8 //compute Ld
9 Ld=1-R1*R2*%e^-(2*ad);
10 printf("\n Decay Loss %0.4f \n",Ld);
11 trt=40; //fs
12 tph=trt/Ld;
13 printf("\n Photon lifetime %0.2f fs \n",tph);
14 BW=1/tph;
15 printf("\n Bandwidth %0.1f Thz\n",BW*1000); //Answer
in Thz

```

Chapter 5

Optical Amplifiers

Scilab code Exa 5.1 Input power

```
1 //Chapter 5
2 //page no 128
3 //given
4 clc;
5 Vrms=0.3;           // in V
6 CF=0.75;            // in V/mW
7 Pi=Vrms/CF;
8 printf("\n input power %0.1f mW\n",Pi);
```

Scilab code Exa 5.2 Compute pseudo random binary sequence

```
1 //Chapter 5
2 //page no 131
3 //given
4 clc;
5 Di=155;             // in Mb/s
6 s1=10^-3*Di*10^6;      // in bitstream
7 //PRBS=2^x-1=s1;
```

```
8 x=log(sl+1)/log(2); //equation is made to pick value  
      of x  
9 printf("\n PRBS =2^%0.0f -1 \n",x);
```

Chapter 6

Optical Transmitter

Scilab code Exa 6.1 Determine whether heat sink or not

```
1 //Chapter 6
2 //page no 139
3 //Given
4 clear;
5 clc;
6 Tj=125;           //in degree celsius
7 Tamp=60;          //n degree celsius
8 Pt=1.8;          //in W
9 RthJ_a =34;       //in k/w(Assumption)
10 Rth=(Tj-Tamp)/Pt;
11 printf("\n Rth = %0.0 f K/W" ,Rth);
12 if Rth>RthJ_a then
13     printf("\n No Heat sink is required");
14 else
15     printf("\n Yes ,Heat sink is required");
16 end ;
```

Scilab code Exa 6.2 determine whether or not heat sink

```

1 //Chapter 6
2 //page no 140
3 //Given
4
5 clear;
6 clc;
7 Tj=120; //in degree celsius
8 Tamp=80; //n degree celsius
9 Pt=2.1; //in W
10 RthJ_a =34; //in k/w(Assumption)
11 Rth=(Tj-Tamp)/Pt;
12 printf("Rth = %0.0 f K/W",Rth);
13 if Rth>RthJ_a then
14     printf("\n No Heat sink is required");
15 else
16     printf("\n Yes ,Heat sink is required");
17 end ;

```

Scilab code Exa 6.3 Determine wheather heat sink

```

1 //chapter6
2 //page no 140
3 //example 6-3
4 //given
5 clear;
6 clc;
7 //data insufficient
8 Rth=17.70; // Rth assumed minimum
9 Rthc_H=0.65; //k/w
10 Rthj_a=33; //k/w
11 Rthj_c=3; //k/w
12 RthH_a=1/(1/Rth-1/Rthj_a)-Rthj_c-Rthc_H;
13 printf("RthH-a <= %0.1 f K/W",RthH_a);
14 //disp(RthH_a," heat sink thermal resistance");

```

Scilab code Exa 6.4 Find Junction Temperature

```
1 //chapter6
2 //page no 148
3 //example 6-4
4 //given
5 clear;clc;
6 Vcc=5; //in volt
7 Icc=24; //in mA
8 Vset=0.65; //in volt
9 Vf=1.5; //in volt
10 IMOD=15;//in mA
11 TA=25; //in degree celsius
12 Pdynamic=(Vcc-Vf-Vset)*Icc;
13 disp("mW",Pdynamic,"Power dissipation under dynamic
      condition")
14 Pstatic=(Vcc*Icc);
15 disp("mW",Pstatic,"power dissipation under static
      condition")
16 PD=Pdynamic+Pstatic;
17 disp("mW",PD,"total power dissipation")
18 //Tj=TA+PD*wj_a;
19 TA=25; //in degree cel
20 wj_a=84; //degree cel/w
21 PD=188.4; //mW
22 Tj=TA+PD*10^-3*wj_a;
23 printf("\n Temp. of junction temp %0.0 f degree C",Tj
      )
```

Scilab code Exa 6.5 calculate value of r1 r2 r3 and c1

```
1 // chapter 6
```

```

2 //page no150
3 //exa 6_5Ex6_5
4 //given
5 clc;
6 clear;
7 Ifon=120;           //in mA
8 Vcc=5;             //in V
9 Vfon=2;             //in V
10 R3=(Vcc-Vfon)/Ifon/10^-3 +3.2*(Vcc-Vfon-1.4)/Ifon
    /10^-3;
11 printf("\n R3= %0.0 f ohm",R3);
12 R0=(R3-32)/3.2;
13 printf("\n R0= %0.0 f ohm",R0);
14 R1=(R0+10)/2;
15 printf("\n R1= %0.0 f ohm",R1);
16 R2=R1-10;
17 printf("\n R2= %0.0 f ohm",R2);
18 C1=2*10^-9/R1;
19 printf("\n C1= %0.0 f pF",C1*10^12);           //answer
    in book is approximately written

```

Scilab code Exa 6.6 Compute required reference current

```

1
2 //chapter 6
3 //page no155
4 //Ex6_6
5 //given
6 clear;
7 clc;
8 Impd1=250;          //in microA
9 Impd0=25;            //in microA
10 Iref=(1/16)*Impd1*10^-6;
11 printf("\n Reference current is %0.3 f microA",Iref
    *10^6)

```

```

12 Rref=1.5/Iref;
13 printf("\n External bias resistor value Rref1is %0.0
           f kohm",Rref/1000)
14 //or
15 Rref1=24/Impd1/10^-6;
16 printf("\n Also , Rref1=24/Impd \n External bias
           resistor value is %0.0 f kohm",Rref1/1000)
17 Irefz=(1/4)*Impd0;
18 printf("\n Ref0 current is %0.2 f microA",Irefz)
19 Rrefz=1.5/Irefz/10^-6;
20 printf("\n External bias resistor value Rrefz is %0
           .0 f kohm",Rrefz/1000)

```

Scilab code Exa 6.7 Find bandwidth for optical one and zero

```

1 //chapter 6
2 //page no157
3 //Ex 6_7
4 //given
5 clear;
6 clc;
7 R=400;           //in mA
8 nE0=25;          //in mW
9 nlaser=nE0*10^-3*R*10^-3;
10 printf("\n nlaser = %0.2 f ",nlaser);
11 Tone=(40*10^-12)*(80*10^3)/nlaser;
12 printf("\n Tone = %0.0 f micros ",Tone*10^6);
13 BWone=1/(2*pi*Tone);
14 printf("\n BWone = %0.0 f Hz ",BWone);
15 Tzero=(40*10^-12)*80*10^3/nlaser;
16 BWzero=1/2/pi/Tzero;           //Hz
17 printf("\n BWzero = %0.0 f Hz ",BWzero);
18 //answer misprinted

```

Scilab code Exa 6.8 compute external resistance and alarm current

```
1 //chapter 6
2 //page no159
3 //exa 6_8
4 //given
5 clear;clc;
6 iol =5;           //in mA
7 ioh=80;           //bias current in mA
8 ralarmH=(1.5*1500)/ioh/10^-3;
9 printf("\n Alarm resistor RalarmH is %0.0f kOhm",
        ralarmH/1000);
10 ralarmL=(1.5*300)/iol/10^-3;
11 printf("\n Alarm resistor RalarmL is %0.0f kOhm",
        ralarmL/1000);
12 ialarmh=80*10^-3;
13 ialarmH=ioh*10^-3/1500;
14 printf("\n Alarm current IalarmH is %0.0f microA",
        ialarmH*10^6); //unit of answer misprinted in
                      book
15 ialarml=5*10^-3;
16 ialarmL=iol*10^-3/300;
17 printf("\n Alarm current IalarmL is %0.0f microA",
        ialarmL*10^6);
```

Scilab code Exa 6.9 Total power dissipation

```
1 //chapter 6
2 //page no160
3 //exa 6_9
4 //given
5 clear;clc;
```

```

6 Ibias=15;           //in mA assumption
7 Ild=35;            //in mA
8 Rld=50;            //in ohm
9 Ildi=100;           //in mA
10 Ilde=50;           //in mA
11 Imod=(Ildi+Ilde)/Ildi*35;   //mA
12 printf("Total modulation current is \nImod=%.2f mA\n", Imod);
13 Ildq=1.2/100*10^3;      //in mA
14 printf("The current complementary output is \nIldq=%.1f mA\n", Ildq);
15 Vld=-1.2-Rld*(Ibias+Ild)*10^-3;        //optical high
16 printf("The laser voltage for optical high is \nVld=%.2f V\n", Vld);
17 Vld=-1.2-Rld*(Ibias)*10^-3;        //optical dark
18 printf("The laser voltage for optical dark is \nVld=%.2f V\n", Vld);
19 Vldq=-Ild*10^-3*Rld;
20 printf("The laser voltage at complimentary o/p is \
nVldq=%.2f V\n", Vldq);
21 Rchock=5;             //in Ohm
22 Vchock=-Rchock*Ibias*10^-3;
23 printf("\nVchock=%.3f V\n", Vchock);
24 Vbias=0.5*(-3.7+Vld)+Vchock;
25 printf("\nVbias=%.1f V\n", Vbias);
26
27 // (i) Pdvee1
28 Pdvcc=5*2.5;          //in mW
29 printf("\nPdvcc=%.1f mW\n", Pdvcc);
30 Pdvee1=4.5*80;         //in mW
31 printf("\nPdvee1=%.0f mW\n", Pdvee1);
32 // (ii) Pdvee2
33 Pdvee2=6*160;          //in mW
34 printf("\nPdvee2=%.0f mW\n", Pdvee2);
35 // (iii) PdLD
36 PdLD=0.5*(3.75*50);    //in mW
37 printf("\nPdLD=%.2f mW\n", PdLD);
38 // (iv) PdLQ

```

```

39 PdLDQ=0.5*abs(Vld)*50;           // in mW
40 printf("\nPdLDQ=%f mW\n",PdLDQ);
41 // (v) PdLDQ
42 Pdbias=abs(Vbias)*Ibias;         // in mW
43 printf("\nPdbias=%f mW\n",Pdbias);
44 //PT
45 PT=Pdvcc+Pdvee1+Pdvee2-[PdLD+PdLDQ+Pdbias];
46 printf("\nTotal power dissipation (PT)= %f mW\n",PT)
);

```

Scilab code Exa 6.10 find maximum power dissipation

```

1
2 // chapter 6
3 // page no161
4 // exa 6_10
5 // given
6 clear;
7 clc;
8 vcc=-5;           // in v
9 imod=35;          // in mA
10 ibias=18;         // in mA
11 vbias=-2;         // in v
12 vout=2;           // in v
13 tj=30;            // degree cel
14 icc=140;          // in mA
15 Pt=(-vcc*icc*10^-3)+(-vcc-vout)*imod*10^-3+(-vcc+
    vbias)*ibias*10^-3;
16 printf("Pt= %0.0 f mW",Pt*1000);
17 Tj=30; //in degree
18 Tj_a=Tj*Pt;
19 Tcase=125-Tj_a; //in degree
20 printf("\n Tcase(max)= %0.0 f degree Cel",Tcase);

```

Scilab code Exa 6.11 Calculate differential and common mode impedance

```
1 //chapter 6
2 //page no-174
3 //Ex6_11
4 //given
5 clear;clc;
6 z11=49.95;           //in ohm
7 z12=0.15;            //in ohm
8 z21=0.15;            //in ohm
9 z22=49.95;           //in ohm
10 zdiff=2*(z11-z12);
11 printf("\n Zdiff= %0.1 f ohm",zdiff);      //answer
     misprinted
12 zcm=z11+z12;
13 printf("\n Zcm= %0.1 f ohm",zcm);
```

Scilab code Exa 6.12 Compute differential mode and common mode impedance

```
1 //chapter 6
2 //page no174
3 //Ex6_11
4 //given
5 clear;clc;
6 z11=65.4; //in ohm
7 z12=8.2; //in ohm
8 z21=8.2; //in ohm
9 z22=65.4; //in ohm
10 zdiff=2*(z11-z12);
11 printf("\n Zdiff= %0.1 f ohm",zdiff);
12 zcm=z11+z12;
13 printf("\n Zcm= %0.1 f ohm",zcm);
```

Scilab code Exa 6.13 Compute intermediate frequency

```
1 //chapter 6
2 //page no181
3 //Ex6_13
4 //given
5 clear;clc;
6 dV=50;           //in mV
7 di=3;           //in Amp
8 Lcable=15;      //in nH
9 fL=dV*10^-3/di/2/%pi/Lcable/10^-9;
10 printf("fLcable = %0.0f kHz",fL/1000);
```

Scilab code Exa 6.14 Allowed parasitic cable inductance

```
1 //chapter 6
2 //page no181
3 //Ex6_14
4 //given
5 clear;clc;
6 dV=50;           //in mV
7 di=4;           //in Amp
8 fL=120;          //in kHz
9 Lcable=dV*10^-3/di/2/%pi/fL/10^3;
10 printf("\n The maximum allowed parasitic cable
           inductance (Lcable) must not exceed %0.1f nH",
           Lcable*10^9);
```

Scilab code Exa 6.15 Calculate high frequency component

```

1 //chapter 6
2 //page no182
3 //Ex6_15
4 //given
5 clear;
6 clc;
7 dV=40;           //in mV
8 di=2.5;          //in Amp
9 Lbypas=0.5;     //in nH
10 fL=dV*10^-3/di/2/%pi/Lbypas/10^-9;
11 printf("fHnoise = %0.1f MHz",fL/10^6);

```

Scilab code Exa 6.16 compute low frequency component

```

1 //chapter 6
2 //page no182
3 //Ex6_16
4 //given
5 clear;
6 clc;
7 dV=50;           //in mV
8 di=2.5;          //in Amp
9 Cbypas=220;      //in microF
10 fL=di/(dV*10^-3*2*%pi*Cbypas*10^-6);
11 printf("fLnoise = %0.0f kHz",fL/1000);    //
    Result

```

Scilab code Exa 6.17 Calculate noise bandwidth

```

1 //chapter 6
2 //page no182
3 //Ex6_17
4 //given

```

```

5  clear;
6  clc;
7  dV=50;           // in mV
8  di=4;            // in Amp
9  Cbypas=200;     // in microF
10 Lbypas=0.2;     // in nH
11 fL=di/(dV*10^-3*2*pi*Cbypas*10^-6);
12 printf("\n fLnoise = %0.0f kHz\n",fL/1000);
   //Result misprinted
13 fH=dV*10^-3/di/2/pi/Lbypas/10^-9;
14 printf("\n fHnoise = %0.0f MHz\n",fH/10^6);
15 Bw=fH-fL;
16 printf("\n Bwnoise = %0.2f MHZ",Bw/10^6);      //
   Result miscalculated

```

Scilab code Exa 6.18 Calculate effective hight frequency component

```

1 //chapter 6
2 //page no184
3 //Ex6_18
4 //given
5 clear;
6 clc;
7 dV=40;           // in mV
8 di=3;            // in Amp
9 LT=0.05;          // in nH
10 fH=dV*10^-3/di/2/pi/LT/10^-9;
11 printf("\n fCdecoupling(high) = %0.1f MHz\n",fH
   /10^6);          //Result

```

Scilab code Exa 6.19 Calculate the effective low frequency component

```
1 //chapter 6
```

```

2 //page no184
3 //Ex6_19
4 //given
5 clear;
6 clc;
7 dV=45;           //in mV
8 di=2.5;          //in Amp
9 CT=2.2;          //in microF
10 LT=0.05;         //in nH
11 fCL=di/(dV*10^-3*2*pi*CT*10^-6);
12 printf("\n fLnoise = %0.0f MHz\n",fCL/10^6);
   //Result
13 fCH=42.3;        //in MHz taken from last
   question i.e. 6.18
14 printf("\n fHnoise (from last question i.e. 6.18)=
   %0.1f MHz\n",fCH);
15 printf("\n %0.0fMHz <= B.W. noise <= %0.2fMHz",fCL
   /10^6,fCH);      //Result

```

Chapter 7

Optical Receivers

Scilab code Exa 7.1 PWD of optical receiver

```
1 //Chapter 7
2 //page no 203
3 //given
4 clc;
5 clear all;
6 Trec=54;           //in ns
7 Ttrans=40;         //in ns
8 Pwd=(Trec-Ttrans)/Ttrans*100;
9 printf("\n PWD= %0.0 f percent", Pwd)
```

Scilab code Exa 7.2 Value of R_{adj}

```
1 //Chapter 7
2 //page no 214
3 //given
4 clc;
5 clear all;
6 //Vc=Vdin-Vddinq
```

```

7 Vc=5;           //in mV  Vdin-Vdinq=Vc
8 Iset =1.8*10^-3*(Vc*10^-3);      //in A
9 printf("\n Iset %0.0f microA",Iset*10^6) ;
10 Vs=1.5;          //Voltage at signal level below
                     Vcc in V
11 Radj=Vs/Iset;        //in Ohm
12 printf("\n Radj %0.0f kohm",Radj*10^-3) ;

```

Scilab code Exa 7.3 Reference voltage and reference resistor

```

1 //Chapter 7
2 //page no 223
3 //given
4 clc;
5 clear all;
6
7 Rl=50;           //in Ohm
8 Ro=100;          //in Ohm
9 Vos=450;         //in mV
10 Vref=(Rl+Ro)/Rl*Vos/2;
11 printf("\n Vref= %0.0f mV",Vref) ;
12 Vee=3.3;         //in V
13 R1=500;          //in Ohm
14 R2=16000;        //in Ohm
15 //Rref=(Vee/Vref/10^3-1)*R1/[1-{R1/R2*(Vee/Vref
                     /10^3-1)}]
16 Rref={(Vee/Vref/10^-3-1)*R1}/[1-R1/R2*(Vee/Vref
                     /10^-3-1)]
17 printf("\n Rref= %0.0f kohm",Rref) ;
18 printf("\n Approx. Rref= %0.1f kohm",Rref*10^-3) ;

```

Chapter 9

Optical Fibers

Scilab code Exa 9.1 Compute angle of acceptance critical angle and NA

```
1 //Chapter 9
2 //page no 296
3 //given
4 clc;
5 clear all;
6 n2=1.35;           //refractive index
7 n1=1.4;           //refractive index
8 Wo=asind(n2/n1); //in radians
9 printf("\n Critical Angle ,Wo = %0.2f degree\n",Wo);
10 NA=sqrt(n1^2-n2^2);
11 printf("\n Numerical Aperture ,NA = %0.2f \n",NA);
12 Wa=asind(NA);    //in radians
13 printf("\n Angle of acceptance ,Wa = %0.2f degree\n",
Wa);
```

Scilab code Exa 9.2 Fiber Attenuation

```
1 //Chapter 9
```

```

2 //page no 300
3 //given
4 clc;
5 clear all;
6 Po=8;           //in mW
7 Pi=50;          //in mW
8 l=15;           //in km
9 TA=-10*log10(Po/Pi);
10 printf("\n Total fibre Attenuation ,L = %0.2f dB/%0.0
          fkm \n",TA,1);
11 Alpha=TA/1;
12 printf("\n Alpha is = %0.2f dB/km\n",Alpha);

```

Scilab code Exa 9.3 Maximum length of optical fibre

```

1 //Chapter 9
2 //page no 300
3 //given
4 clc;
5 clear all;
6 Po=10;           //in mW
7 Pi=150;          //in mW
8 Alpha=0.8;        //in dB/km
9 TA=-10*log10(Po/Pi);
10 printf("\n Total fibre Attenuation ,L = %0.2f dB \n",
          TA);
11 l=TA/Alpha;
12 printf("\n maximum length is ,l = %0.2f km\n",l);
13 //Round off Variations appear

```

Scilab code Exa 9.4 Rayleigh attenuation of an optical fibre

```
1 //Chapter 9
```

```

2 //page no 302
3 //given
4 clc;
5 clear all;
6 B=92*10^-12;           //in m^2/N
7 Tf=1550;               //in K
8 n=1.46;                //refractive index
9 p=0.29;
10 K=1.38*10^-23;        //in J/K
11 l=1;                   //in km
12 L1=630;                //in nm
13 L2=1330;               //in nm
14 L3=1550;               //in nm
15 disp("Rayleigh scattering coefficient");
16 Y1=8*pi^3*n^8*p^2*B*K*Tf/3/(L1*10^-9)^4;
17 Y2=8*pi^3*n^8*p^2*B*K*Tf/3/(L2*10^-9)^4;
18 Y3=8*pi^3*n^8*p^2*B*K*Tf/3/(L3*10^-9)^4;
19 fprintf(" for L1= 630nm, is %e",Y1);
20 fprintf("\n for L2= 1330nm, is %e",Y2);
21 fprintf("\n for L3= 1550nm, is %e",Y3);
22 //Misprinted answer
23
24 disp("Rayleigh scattering attenuation factor");
25 Fr1=%e^-(Y1*l*10^3);
26 Fr2=%e^-(Y2*l*10^3);
27 Fr3=%e^-(Y3*l*10^3);
28 printf("\n for Y1= 0.00179 is %0.2f",Fr1);
29 printf("\n for Y2= 0.00009 is %0.2f",Fr2);
30 printf("\n for Y3= 0.0000182 is %0.2f\n",Fr3);
31 //
32
33 disp("Rayleigh scattering attenuation ");
34 Ar1=10*log10(Fr1^-1);
35 Ar2=10*log10(Fr2^-1);
36 Ar3=10*log10(Fr3^-1);
37 printf("\n for Ar1= 0.17 is %0.2f dB/km",Ar1);
38 printf("\n for Ar2= 0.91 is %0.2f dB/km",Ar2);
39 printf("\n for Ar3= 0.98 is %0.3f dB/km",Ar3);

```

```
40 //For L3 answers in book are misprinted  
41 //Rounding off errors in answer
```

Scilab code Exa 9.5 SBS threshold optical power

```
1  
2  
3  
4  
5  
6 //Chapter 9  
7 //page no 304  
8 //given  
9 clc;  
10 clear all;  
11 L=850;           //in nm  
12 L1=0.850;        //converted L in micrometer for  
                  //using in given formula  
13 A=0.5;           //in dB/km  
14 d=5;             //in micrometer  
15 Bw=1;            //in Gz  
16 Po=4.4*10^-3*A*Bw*L1^2*d^2;  
17 printf("\n Po(Th) = %0.3f W",Po);  
18 printf("\n Therefore ,Po(Th) = %0.0f mW",Po*1000);
```

Scilab code Exa 9.6 SBS threshold optical power

```
1  
2  
3  
4  
5  
6 //Chapter 9
```

```

7 //page no 304
8 //given
9 clc;
10 clear all;
11 L=1330;           //in nm
12 L1=1.330;         //converted L in micrometer for
                     using in given formula
13 A=0.5;            //in dB/km
14 d=5;              //in micrometer
15 Bw=1;             //in Gz
16 Po=4.4*10^-3*A*Bw*L1^2*d^2;
17 printf("\n Po(Th) = %0.3f W",Po);
18 printf("\n Therefore ,Po(Th) = %0.0f mW",Po*1000);

```

Scilab code Exa 9.7 SBS threshold optical power

```

1
2
3
4
5
6 //Chapter 9
7 //page no 304
8 //given
9 clc;
10 clear all;
11 L=1550;           //in nm
12 L1=1.550;         //converted L in micrometer for
                     using in given formula
13 A=0.5;            //in dB/km
14 d=5;              //in micrometer
15 Bw=1;             //in Gz
16 Po=4.4*10^-3*A*Bw*L1^2*d^2;
17 printf("\n Po(Th) = %0.3f W",Po);
18 printf("\n Therefore ,Po(Th) = %0.0f mW",Po*1000);

```

Scilab code Exa 9.8 SBS threshold optical power

```
1
2
3
4
5
6 //Chapter 9
7 //page no 304
8 //given
9 clc;
10 clear all;
11 L=850;           //in nm
12 L1=0.850;        //converted L in micrometer for
                  using in given formula
13 A=0.5;           //in dB/km
14 d=8;             //in micrometer
15 Bw=1;            //in Gz
16 Po=4.4*10^-3*A*Bw*L1^2*d^2;
17 printf("\n Po(Th) = %0.3f W",Po);
18 printf("\n Therefore ,Po(Th) = %0.0f mW",Po*1000);
                  //answer is slightly different due to rounding
                  off
```

Scilab code Exa 9.9 SBS threshold optical power

```
1
2
3
4
5
```

```

6 //Chapter 9
7 //page no 304
8 //given
9 clc;
10 clear all;
11 L=850;           //in nm
12 L1=0.850;        //converted L in micrometer for
                  using in given formula
13 A=0.5;           //in dB/km
14 d=10;            //in micrometer
15 Bw=1;            //in Gz
16 Po=4.4*10^-3*A*Bw*L1^2*d^2;
17 printf("\n Po(Th) = %0.3f W",Po);
18 printf("\n Therefore ,Po(Th) = %0.0f mW",Po*1000);

```

Scilab code Exa 9.10 Raman scattering threshold power

```

1 //Chapter 9
2 //page no 305
3 //given
4 clc;
5 clear all;
6 L=850;           //in nm
7 L1=L/1000;        //converted L in micrometer for
                  using in given formula
8 A=0.4;           //in dB/km
9 d=5;             //in micrometer
10 Po=5.9*10^-2*A*L1*d^2;
11 printf("\n Po(Th) = %0.0f mW",Po*1000);      //
                  rounding off error

```

Scilab code Exa 9.11 Raman scattering threshold power

```
1 //Chapter 9
2 //page no 305
3 //given
4 clc;
5 clear all;
6 L=1330;           //in nm
7 L1=L/1000;        //converted L in micrometer for
                     using in given formula
8 A=0.4;            //in dB/km
9 d=5;              //in micrometer
10 Po=5.9*10^-2*A*L1*d^2;
11 printf("\n Po(Th) = %0.0f mW",Po*1000);      //
                     unit in book is wrong
```

Scilab code Exa 9.12 Raman scattering threshold power

```
1
2
3
4
5
6 //Chapter 9
7 //page no 305
8 //given
9 clc;
10 clear all;
11 L=1550;           //in nm
12 L1=L/1000;        //converted L in micrometer for
                     using in given formula
13 A=0.4;            //in dB/km
14 d=5;              //in micrometer
15 Po=5.9*10^-2*A*L1*d^2;
16 printf("\n Po(Th) = %0.0f mW",Po*1000);      //
                     unit in book is wrong
```

Scilab code Exa 9.13 Maximum modal number

```
1 //Chapter 9
2 //page no 310
3 //given
4 clc;
5 clear all;
6 R=25;           //in nm
7 R1=25*10^-6;   //in m
8 L=1000;         //in nm
9 L1=10^-6;       //in m
10 NA=0.2;
11 V=2*pi/L1*R1*NA;
12 printf("\n Normalised frequency(V) = %0.1f ",V);
13 y=2;           //for parabolic
14 Mmax=y/(y+2)*(V^2)/2;
15 printf("\n Maximum number of modes is equal to =
%0.0f ",Mmax); //answer in book is wrong
```

Scilab code Exa 9.14 Maximum operating bandwidth

```
1 //Chapter 9
2 //page no 313
3 //given
4 clc;
5 clear all;
6 Tp=0.25;        //in microsec
7 fB=0.529/Tp/10^-6; //channel bitrate
8 fBw=fB;          //channel bandwidth = channel
                   //bitrate when zero ISI and RZ input data is
                   //modulated
```

```

9 printf("\n Maximum operating bandwidth = %0.3f MHz
      ", fBw*10^-6);
10 L=50;           //in km
11 D=Tp*10^-6/L; //Dispersion
12 printf("\n Dispersion = %0.0f ns/km", D*10^9);
13 fBwL=fBw*10^-6*L; //bandwidth length
      product
14 printf("\n Bandwidth length product(fBw*L) = %0.1f
      MHz/km", fBwL);

```

Scilab code Exa 9.15 Maximum operating bandwidth

```

1 //Chapter 9
2 //page no 314
3 //given
4 clc;
5 clear all;
6 Tp=2;           //in microsec
7 fB=0.529/Tp/10^-6; //channel bit rate
8 fBw=fB;         //channel bandwidth = channel
      bitrate when zero ISI and RZ input data is
      modulated
9 printf("\n Maximum operating bandwidth = %0.2f MHz
      ", fBw*10^-6);
10 L=50;          //in km
11 D=Tp*10^-6/L; //Dispersion
12 printf("\n Dispersion = %0.0f ns/km", D*10^9);
      //unit in book is wrong
13 fBwL=fBw*10^-6*L; //bandwidth length product
14 printf("\n Bandwidth length product(fBw*L) = %0.0f
      MHz/km", fBwL);

```

Scilab code Exa 9.16 Maximum operating bandwidth

```

1 //Chapter 9
2 //page no 314
3 //given
4 clc;
5 clear all;
6 Tp=5;           //in microsec
7 fB=0.529/Tp/10^-6; //channel bit rate
8 fBw=fB;          //channel bandwidth = channel
                    bitrate when zero ISI and RZ input data is
                    modulated
9 printf("\n Maximum operating bandwidth = %0.3f MHz
         ",fB*10^-6);
10 L=50;           //in km
11 D=Tp*10^-6/L; //Dispersion
12 printf("\n Dispersion = %0.1f micro sec/km",D
         *10^6);
13 fBwL=fBw*10^-6*L; //bandwidth length product
14 printf("\n Bandwidth length product(fBw*L) = %0.1f
         MHz/km",fBwL);

```

Scilab code Exa 9.17 RMS pulse chirping

```

1 //Chapter 9
2 //page no 315
3 //given
4 clc;
5 clear all;
6 Slw=25;           //in nm
7 L=850;            //in nm      given
8 c=3*10^5;          //in km/s
9 ofmd=0.02;         //optical fiber material
                     dispersion
10 Mdp=1/L/c*ofmd; //answer mismatch due to
                     differnt value chosen for calculation
11 printf("\n Material Dispersion parameter Mdp = %0

```

```

    .0 f  ps/nm.km" ,Mdp*10^12) ;
12 l=1;           //in km
13 dmd=Slw*l*Mdp;      //pulse chirping
14 printf("\n pulse chirping dmd = %0.2f ns/km" ,dmd
    *10^9);

```

Scilab code Exa 9.18 RMS pulse broadening

```

1 //Chapter 9
2 //page no 315
3 //given
4 clc;
5 clear all;
6 Slw=2;           //in nm
7 L=850;          //in nm      given
8 c=3*10^5;        //in km/s
9 ofmd=0.02;       //optical fiber material
                    dispersion
10 Mdp=1/L/c*ofmd; //answer mismatch due to differnt
                    value chosen for calculation
11 printf("\n Material Dispersion parameter Mdp = %0
    .0 f  ps/nm.km" ,Mdp*10^12) ;
12 l=1;           //in km
13 dmd=Slw*l*Mdp;
14 printf("\n pulse chirping dmd = %0.3f ns/km" ,dmd
    *10^9);

```

Scilab code Exa 9.19 Channel capacity

```

1 //Chapter 9
2 //page no 325
3 //given
4 clc;

```

```
5 clear all;
6 fb1=2.5;           //in Gb/s
7 D1=20;             //in ps/nm.km
8 D2=5;              //in ps/nm.km
9 fb2=D1/D2*fb1;
10 printf("\n fb2 = %0.0 f Gb/s (OC-192)" ,fb2)
11 //Values of D1 and D2 are conflicted in question ,
   however solution is correct
```

Scilab code Exa 9.20 Channel capacity

```
1 //Chapter 9
2 //page no 325
3 //given
4 clc;
5 clear all;
6 fb1=2.5;           //in Gb/s
7 DV1=100;            //in GHz
8 DV2=50;             //in GHz
9 fb2=DV1/DV2*fb1;
10 printf("\n fb2 = %0.0 f Gb/s" ,fb2)
```

Scilab code Exa 9.21 Total chromatic dispersion

```
1 //Chapter 9
2 //page no 332
3 //given
4 clc;
5 clear all;
6 L=400;              //in km
7 dAV=4;               //in ps/km
8 dTL=L*dAV;           //total chromatic dispersion
9 printf("dTL =%0.0 f ps/nm.km" ,dTL);
```

```
10 printf("\n or ,dTL =%0.1f ns/nm.km" ,dTL/10^3);
```

Scilab code Exa 9.22 Compute optical attenuation

```
1 //Chapter 9
2 //page no 335
3 //given
4 clc;
5 clear all;
6 no=1;           // refractive index
7 n1=1.35;        // refractive index
8 Po=[(n1-no)/(n1+no)]^2;    // fresnal reflection
9 printf("\n Po( refl)= %0.3f" ,Po);
10 Lrefl=-10*log10(1-Po);     // attenuation loss
11 printf("\n L( refl)= %0.1f dB" ,Lrefl);
```

Scilab code Exa 9.23 Compute total attenuation

```
1 //Chapter 9
2 //page no 335
3 //given
4 clc;
5 clear all;
6 no=1;           // refractive index
7 n1=1.55;        // refractive index
8 Po=[(n1-no)/(n1+no)]^2;    // fresnal reflection
9 printf("\n Fresnel reflective coefficient ,Po( refl)=
    %0.5f\n" ,Po);
10 Lrefl=-10*log10(1-Po);     // attenuation loss
11 printf("\n Attenuation based on Fresnel reflective
    coefficient ,L( refl)= %0.1f dB\n" ,Lrefl);
12 Ltot=5*Lrefl;
```

```
13 printf("\n Total link attenuation on Fresnel  
reflections ,Ltotal = %0.1f dB",Ltot);
```

Scilab code Exa 9.24 Compute the insertion loss

```
1 //Chapter 9  
2 //page no 336  
3 //given  
4 clc;  
5 clear all;  
6 n1=1;  
7 n2=1.5;  
8 a=25;           //in micrometer  
9 y=3;           //in micrometer  
10 Csim=16*(n1/n2)^2/%pi/[1+(n1/n2)]^4*[2*acos(y/2/a)-(y/a)*[1-(y/2/a)^2]^0.5];  
11 //lateral coupling coefficient  
12 a=2*acos(y/2/a)-(y/a)*sqrt(1-(y/2/a)^2);  
13 b=16*(n1/n2)^2/%pi/[1+(n1/n2)]^4;  
14 printf("\n Lateral coupling coefficient ,Csim= %0.2f  
\n",Csim);  
15 Lsim=-10*log10(1-Csim);  
16 printf("\n Insertion Loss ,Lsim= %0.1f dB\n",Lsim);  
17 //Answer wrong in book
```

Scilab code Exa 9.25 Compute insertion loss

```
1 //Chapter 9  
2 //page no 337  
3 //given  
4 clc;  
5 clear all;  
6 Alpha=2;
```

```

7 a=25;           //in micrometer
8 y=2;           //in micrometer
9 Cgim=2/%pi*(y/a)*(Alpha+2)/(Alpha+1);      //
   lateral coupling coefficient
10 printf("\n Csim= %0.3f\n",Csim);
11 Lgim=-10*log10(1-Cgim);        //insertion loss
12 printf("\n Insertion Loss ,Lsim= %0.1f dB\n",Lsim);

```

Scilab code Exa 9.26 Compute insertion loss

```

1 //Chapter 9
2 //page no 339
3 //given
4 clc;
5 clear all;
6 n1=1.5;           //refractive index
7 n2=1.5;           //refractive index
8 W=2.5;           //in degree
9 NA1=0.3;
10 NA2=0.4;
11 Cs1=16*(n1/n2)^2/[1+(n1/n2)^4]*[1-n2*W/(180*NA1)];
   //angular coupling coefficient
12 //Answer wrong in book
13 printf("\n Cs1= %0.3f\n",Cs1);
14 Ls1=-10*log10(Cs1);
15 printf("\n Insertion Loss ,Lsim= %0.3f dB\n",Lsim);
16 Cs2=16*(n1/n2)^2/[1+(n1/n2)^4]*[1-n2*W/(180*NA2)];
   //angular coupling coefficient
17 //Answer wrong in book
18 printf("\n Cs2= %0.3f\n",Cs2);
19 Ls2=-10*log10(Cs2);
20 printf("\n Insertion Loss ,Lsim= %0.2f dB\n",Lsim);

```

Scilab code Exa 9.27 Compute total insertion loss

```
1 //Chapter 9
2 //page no 340
3 //given
4 clc;
5 clear all;
6 a=4;           //in micrometer
7 V=2.4;
8 aw=1;          //in degree
9 NA1=0.2;
10 n1=1.45;      //refractive index
11 y=1;           //in micrometer
12 omega=a*[0.65+1.62*V^-1.5+2.88*V^-6]/sqrt(2);
13 printf("\n Normalised spot view (w)= %0.2f
micrometer",omega);
14 Lsml=2.17*(y/omega)^2;
15 printf("\n Insertion loss due to lateral ,Lsm= %0.2f
dB",Lsml);    //answer is wrong in book
16 Lsmg=2.17*(aw*pi/180*omega*n1*V/a/NA1)^2;
17 printf("\n Insertion loss due to angular ,Lsm= %0.2f
dB",Lsmg);
18
19 printf("\n Total Insertion loss ,Lsmtotal= %0.2f dB"
,Lsml+Lsmg);
```

Scilab code Exa 9.28 Compute insertion loss at the joint

```
1 //Chapter 9
2 //page no 340
3 //given
4 clc;
5 clear all;
6 a1=4.5;         //in micrometer
7 a2=4;           //in micrometer
```

```

8 V=2.1;
9 aw=1;           //in degree
10 NA=0.2;
11 n1=1.45;
12 y=1;           //in micrometer
13 w1=a1*[0.65+1.62*V^-0.5+2.88*V^-6]/sqrt(2);      //
   insertion loss
14 printf("\n Wo1= %0.1f ",w1);
15 w2=a2*[0.65+1.62*V^-0.5+2.88*V^-6]/sqrt(2);      //
   insertion loss
16 printf("\n Wo2= %0.1f ",w2);
17 Lintr=-10*log10(4*[(w1/w2+w2/w1)^-2]);            //
   toatl insertion loss at joint
18 printf("\n Lintr= %0.2f dB",Lintr);                  //Answer
   wrong in book

```

Chapter 10

Optical Modulation

Scilab code Exa 10.1 Required Biasing voltage

```
1 //Chapter 10
2 //page no 354
3 //given
4 clc;
5 clear all;
6 Vpi=1;           //Assumed 1 because we can not use a
                  variable on RHS
7 //Vpi is Voltage swing
8 A=0.25;          //chirping
9 //V1=(AV1p+Vp)/2
10 V1=(A*Vpi+Vpi)/2;
11 printf("\n V1= %0.3f Vpi",V1)
12 V2=V1-Vpi;
13 printf("\n V2= %0.3f Vpi",V2)
```

Scilab code Exa 10.2 Biasing range

```
1 //Chapter 10
```

```

2 //page no 354
3 //given
4 clc;
5 clear all;
6 Vpi=1;           //Assumed 1 because we can not use a
                  variable on RHS
7 //Vpi is Voltage swing
8 disp(" for alpha=0.3");
9 A=0.3;           //chirping
10 //V1=(AV1p+Vp)/2
11 V1=(A*Vpi+Vpi)/2;
12 printf("\n V1= %0.2f Vpi",V1)
13 V2=V1-Vpi;
14 printf("\n V2= %0.2f Vpi\n",V2)
15 disp(" for alpha=0.8");
16 A=0.8;           //chirping
17 //V1=(AV1p+Vp)/2
18 V1x=(A*Vpi+Vpi)/2;
19 printf("\n V1= %0.1f Vpi",V1x)
20 V2x=V1x-Vpi;
21 printf("\n V2= %0.1f Vpi",V2x)
22 printf("\n Biasing range is %0.2f Vpi <= V1 <= %0.2f
          Vpi",V1,V1x)
23 printf("\n Biasing range is %0.1f Vpi <= V2 <= %0.2f
          Vpi",V2x,V2)

```

Chapter 11

Multiplexing

Scilab code Exa 11.1 Cross talk in refrence to the number of channel

```
1 //Chapter 11
2 //page no 386
3 //given
4 clc;
5 clear all;
6 q=4.9*10^-18;           //in m/W.GHz raman gain
    slope
7 f=100;                  //in GHz
8 A=50*10^-6;             //cross sectional area in
    micro meter square
9 P0=3.5;                 //in mW
10 Le=10*10^3;
11 G=q*f*10^6/2/A;
12 N=20;
13 mprintf ("\n G = %e ",G);
14 CT=N*(N-1)*(P0*10^-3*G*Le)/2;
15 printf ("\n CT(L) = %0.2f ",CT);
```

Scilab code Exa 11.2 Capacitor value of PLL section

```

1 //Chapter 11
2 //page no 410
3 //given
4 clc;
5 clear all;
6 K0=2*pi*625;           //in MHz/V
7 Ip=0.6;                 //in mA
8 N=64;
9 w=2.44;                 //in Mhz
10 Z=5;
11 Vout=5;                //in V
12 C=(4*K0*10^6*Ip*10^-3*Z)/(2*pi*N*w*w*10^12);
13 printf("\n The value of capacitance is %0.0 f nF",C
*10^9)

```

Scilab code Exa 11.3 Value of damping coefficient

```

1 //Chapter 11
2 //page no 410
3 //given
4 clc;
5 clear all;
6 K0=2*pi*625;           //in MHz/V
7 Ip=0.35;                //in mA
8 N=64;
9 w=2.44;                 //in MHz
10 Z=5;
11 Vout=4;                //in V
12 C=22;                  //in nF
13 Z=sqrt((2*pi*N*w^2*C)/(4*Ip*K0*0.25))
14 printf("\n Zeta is = %0.0 f",Z)

```

Chapter 12

Optical Systems

Scilab code Exa 12.1 Compute power margin

```
1 //Chapter 12
2 //page no 431
3 //given
4 clc;
5 clear all;
6 Pt=10;           //in microW
7 Pr=1;           //in microW
8 PtdBm=10*log10(Pt*10^-6/10^-3)          //
    in dBm
9 printf("\n Transmitter Power = %0.0 f dBm",PtdBm);
10 PrdBm=10*log10(Pr*10^-6/10^-3)           //
    in dBm
11 printf("\n Receiver Power = %0.0 f dBm",PrdBm);
12 Pm=PtdBm-PrdBm;
13 printf("\n Power margin= %0.0 f dBm",Pm);   //
    misprint in book
```

Scilab code Exa 12.2 Compute power margin

```
1 //Chapter 12
2 //page no 431
3 //given
4 clc;
5 clear all;
6 Pt=25;           //in microW
7 Prd=15;          //in dBm
8 Ptd=10*log10(Pt*10^-6/10^-3)           //in
                                              dBm
9 printf("\n Transmitter Power = %0.0f dBm", Ptd);
10 Pm=Ptd-Prd;
11 printf("\n Power margin= %0.0f dBm", Pm);
```

Scilab code Exa 12.3 Calculate level of additional power launched

```
1 //Chapter 12
2 //page no 432
3 //given
4 clc;
5 clear all;
6 Pt1=-18;         //in dBm for 50/125 micron fiber
7 Pt2=-10;          //in dBm for 100/125 micron
                      fiber
8 Pd=Pt1-Pt2;
9 printf("\n Additional Power = %0.0f dBm", Pd);
```

Scilab code Exa 12.4 Compute link power budget

```
1 //Chapter 12
2 //page no 432
3 //given
4 clc;
5 clear all;
```

```

6 P1b=10;           //in dBm for 50/125 micron fiber
7 Ps=3;             //in dBm for safety margin
8 Prs=-30;          //in dBm for receiver sensitivity
9 Pt=P1b+Ps+Prs;
10 printf("\n Link power budget = %0.0f dBm",Pt);
11 PtW=10^(Pt/10)*1000;
12 printf("\n Transmitter Power = %0.0f microW",PtW);

```

Scilab code Exa 12.5 Calculate PIN diode required operating power and total power budget

```

1
2
3
4
5 //Chapter 12
6 //page no 433
7 //given
8 clc;
9 clear all;
10 Is=0.5;           //in A/W
11 Ir=1.5;           //in microA
12 Xw=Ir/Is;
13 printf("\n Electrical power required by PIN diode is
           = %0.0f microW",Xw);
14 Pxw=10*log10(Xw/10^3);
15 printf("\n Therefore, Electrical power required by
           PIN diode is = %0.1f dBm",Pxw);
16
17 Ps=3;             //in dB for safety margin
18 Tp=5;             //in dB
19 Pt=Tp+Ps+Pxw;
20 printf("\n Total Power Required = %0.1f dBm",Pt);

```

Scilab code Exa 12.6 Calculate maximum link distance

```
1 //Chapter 12
2 //page no 442
3 //given
4 clc;
5 clear all;
6 fb=1.25;           //in Gb/s
7 D=17;              //in ps/nm.km
8 dL=0.5;            //in nm
9 Lmax=1/fb/10^9/dL/10^-9/D/10^-12*10^-9;
10 printf("\n Maximum Link span ,Lmax = %0.0 f km" ,Lmax);
```

Scilab code Exa 12.7 Compute chromatic dispersion

```
1 //Chapter 12
2 //page no 442
3 //given
4 clc;
5 clear all;
6 fb=2.5;           //in Gb/s
7 Lmax=50;           //in km
8 dL=0.4;            //in nm
9 D=1/fb/10^9/dL/10^-9/Lmax/10^-12*10^-9;
10 printf("\n Maximum allowable dispersion ,D = %0.0 f ps
          /nm-km" ,D);
```

Scilab code Exa 12.8 Compute maximum bit rate

```

1 //Chapter 12
2 //page no 443
3 //given
4 clc;
5 clear all;
6 Lmax=60;           //in km
7 D=17;             //in ps/nm.km
8 dL=0.5;           //in nm
9 fb=1/Lmax/10^9/dL/10^-9/D/10^-12*10^-9;
10 printf("\n Maximum system bit rate ,fb = %0.2f Gb/s" ,
fb);

```

Scilab code Exa 12.9 Compute Maximum link span

```

1 //Chapter 12
2 //page no 443
3 //given
4 clc;
5 clear all;
6 c1=4;           //channel1
7 c2=8;           //channel2
8 c3=16;          //channel3
9 fb=2.5;         //in Gb/s
10 Lmax1=6.1*10^3/(c1*fb)^2;
11 printf("\n Maximum Link span for %0.0f channel , Lmax
= %0.0f km \n",c1,Lmax1);
12 Lmax2=6.1*10^3/(c2*fb)^2;
13 printf("\n Maximum Link span for %0.0f channel , Lmax
= %0.2f km \n",c2,Lmax2);
14 Lmax3=6.1*10^3/(c3*fb)^2;
15 printf("\n Maximum Link span for %0.0f channel , Lmax
= %0.1f km \n",c3,Lmax3);

```

Scilab code Exa 12.10 Calculate chromatic dispersion

```
1 //Chapter 12
2 //page no 444
3 //given
4 clc;
5 clear all;
6 L=200;           //in km
7 dL=1550;         //in nm
8 R=10;            //in Gb/s
9 Cd=17;           //in ps/nm-km
10 w=0.1;          //Assused bandwidth
11 Cd200=Cd*L;
12 printf("\n Dispersion by 200km ofc = %0.1f*10^3 ps/
nm", Cd200/10^3);
13 TCd=w*Cd200;
14 printf("\n total chromatic dispersion = %0.2f*10^3
ps", TCd/10^3);
```

Scilab code Exa 12.11 Calculate dispersion penalty

```
1 //Chapter 12
2 //page no 480
3 //given
4 clc;
5 clear all;
6 L=1.5;           //in km
7 Ls=L/3;          //in km
8 BwF=600;          //in MHz
9 fb=1;             //in Gbps
10 Bdlsaser=0.71*BwF*L^-0.7*Ls^-0.25;
11 printf("Laser bandwidth is %0.0f MHz", Bdlsaser);
    //Answer in book is approx
12 mD=0.85*(fb*10^3/Bdlsaser)^2;
13 printf("\n Mean dispersion penalty is %0.1f dB", mD);
```

//Answer in book is approx

Scilab code Exa 12.12 Calculate maximum length

```
1 //Chapter 12
2 //page no 481
3 //given
4 clc;
5 clear all;
6 E=0.182;           //from table 12-11 for 2dB
    dispersion penalty
7 fb=622;           //in Mb/s
8 dl=4;             //in nm
9 ofdisp=3;          //in ps/km-nm
10 Dmax=E/(10^-6*fb*dl);
11 printf("\n Dmax is %0.1f ps/nm",Dmax);
12 Lmax=Dmax/ofdisp;
13 printf("\n Maximum link distance is %0.1f km",Lmax);
14 //Answer in the book is rounded
```

Scilab code Exa 12.13 Calculate the maximum length of optical link

```
1 //Chapter 12
2 //page no 481
3 //given
4 clc;
5 clear all;
6 E=0.115;           //from table 12-11 for 2dB
    dispersion penalty
7 fb=622;           //in Mb/s
8 dl=4;             //in nm
9 ofdisp=3;          //in ps/km-nm
10 Dmax=E/(10^-6*fb*dl);
```

```

11 printf("\n Dmax is %0.1f ps/nm",Dmax);
12 Lmax=Dmax/ofdisp;
13 printf("\n Maximum link distance is %0.1f km",Lmax);

```

Scilab code Exa 12.14 Calculate maximum dispersion mean link margin sigma link margin

```

1 //Chapter 12
2 //page no 481
3 //given
4 clc;
5 clear all;
6 mc=0.4;           //in dB
7 sc=0.0;           //in dB
8 dmax=2.8;         //in dB
9 mt=-4.9;          //in dBm
10 st=0.5;          //in dBm
11 mr=-38.1;         //in dBm
12 sr=0.48;          //in dBm
13 mco=0.35;         //in dB
14 sco=0.20;         //in dB
15 ms=0.2;           //in dB
16 ss=0.1;           //in dB
17 E=0.182;          //from table 12-11 for 2dB
                     dispersion penalty
18 fb=156;           //in Mb/s
19 dl=4;              //in nm
20 ofdisp=2.8;        //in ps/nm-km
21 Nco=7;
22 mD=2;
23 sD=0.1;
24 sH=2;
25 sCR=0.25;
26 Ns=4;
27 mH=0;

```

```

28 mCR=0.5;
29 L=50;
30 Ls=10;
31 Dmax=E/(10^-6*fb*d1);
32 printf("\n Dmax is %0.0f ps/nm\n",Dmax);
33 Lmax=Dmax/odisp;
34 printf("\n Maximum link distance is %0.0f km\n",Lmax
);
35 mM=mt-mr-(mc*L+mco*Nco+ms*Ns+mD+mH+mCR);
36 printf("\n Mean link margin is %0.2f dB\n",mM);
37 sM=sqrt(st^2+sr^2+sc^2*L*Ls+sco^2*Nco+sD^2*sH^2+sCR
^2);
38 printf("\n Sigma link margin is %0.3f dB\n",sM);

```

Scilab code Exa 12.15 Compute maximum dispersion and nominal distribution

```

1 //Chapter 12
2 //page no 483
3 //given
4 clc;
5 clear all;
6 E=0.115;
7 fb=622;           //in Mb/s
8 d1=4;             //in nm
9 mt=0.1;           //in dBm
10 mr=-31.5;        //in dBm
11 mc=0.41;          //in dB
12 L=25;
13 mco=0.12;         //in dB
14 Nco=2;
15 ms=0.15;          //in dB
16 Ns=4;
17 mD=1;
18 mH=0;

```

```

19 mCR=0;
20
21 sc=0.0;           //in dB
22 st=-0.15;         //in dBm
23 sr=0.3;           //in dBm
24 sco=0.08;         //in dB
25 ss=0.1;           //in dB
26 ofdisp=2.8;        //in ps/nm-km
27 sD=2;
28 sH=0;
29 sCR=0.0;
30 Ls=12;
31
32 Dmax=E/(10^-6*fb*d1);
33 printf("\n Dmax is %0.2f ps/nm\n",Dmax);
34 Lmax=Dmax/ofdisp;
35 printf("\n Maximum link distance is %0.1f km\n",Lmax
         );      //in book 4 is misprint for solving
36 mM=mt-mr-(mc*L+mco*Nco+ms*Ns+mD+mH+mCR);
37 printf("\n Mean link margin is %0.1f dB\n",mM);
               //wrong in book
38 L=60;
39 Ls=12;
40 sM=sqrt(st^2+sr^2+sc^2*L*Ls+sco^2*Nco+ss^2*Ns+sD^2*
           sH^2+sCR^2);
41 printf("\n Sigma link margin is %0.2f dB\n",sM);
42 spm=mM-2*sM-1;
43 printf("\n System power margin is %0.2f dB\n",spm);
               //answer is slightly different due to mM=19.5

```

Scilab code Exa 12.16 Calculate maximum dispersion and maximum distance

```

1 //Chapter 12
2 //page no 484

```

```

3 // given
4 clc;
5 clear all;
6 E=0.115;
7 fb=1062;           // in Mb/s
8 dl=6;             // in nm
9 mt=-8;            // in dBm
10 mr=28.7;          // in dBm
11 mc=0.4;           // in dB
12 L=5;
13 mco=0.12;         // in dB
14 Nco=8;
15 ms=0.2;           // in dB
16Ns=4;
17 mD=1;
18 mH=0;
19 mCR=1;
20
21 sc=0.0;           // in dB
22 st=0.6;           // in dBm
23 sr=0.75;          // in dBm
24 sco=0.08;          // in dB
25 ss=0.1;           // in dB
26 ofdisp=2.8;        // in ps/nm-km
27 sD=2;
28 sH=0;
29 sCR=0.25;
30 Ls=12;
31
32 Dmax=round(E/(10^-6*fb*dl));           // taking to
   nearest integer in ps/nm
33 printf("\n Dmax is %0.0 f ps/nm\n",Dmax);
34 Lmax=Dmax/ofdisp;
35 printf("\n Maximum link distance is %0.2 f km\n",Lmax
   );
36 mM=mt+mr-(mc*L+mco*Nco+ms*Ns+mD+mH+mCR);
37 printf("\n Mean link margin is %0.1 f dB\n",mM);
38 L=60;

```

```

39 Ls=12;
40 sM=sqrt(st^2+sr^2+sc^2*L*Ls+sco^2*Nco+ss^2*Ns+sD^2*
    sH^2+sCR^2);
41 printf("\n Sigma link margin is %0.2f dB\n",sM);
42 mM=round(mM*10)/10; //talking only to 1 decimal
    place and rounding of other values
43 spm=mM-2*sM-1;
44 printf("\n mM-2*sM = %0.2f\n",mM-2*sM);
45 printf("\n System power margin is %0.2f dB\n",spm);
    //answer is slightly different due to m\sM=1.03

```

Scilab code Exa 12.17 Calculate the CSO distortion

```

1 //Chapter 12
2 //page no 486
3 //given
4 clc;
5 clear all;
6 Ncs0=50;
7 a=3.6*10^-3;
8 m=0.05;
9 CS0=10*log10(Ncs0*(a*m)^2);
10 printf("\n CSO distortion for 50 channel optical
    system = %0.1f dB\n",CS0);

```

Scilab code Exa 12.18 Calculate the required AM modulation

```

1 //Chapter 12
2 //page no 486
3 //given
4 clc;
5 clear all;
6 CS0=-59.8; //in dB

```

```

7 y=10^(CSO/10);
8 mprintf("AM modulation depth (m) = %e\n",y);
9 asq=3.6*10^-3;
10 Ncs0=50;
11 msq=(y/Ncs0/asq/asq);
12 mprintf("\n m^2 = %e\n",msq);
13 printf("\n Decrease of AM modulation depth decrease
        the CSO distortion by = %0.0f percent",sqrt(msq)
        *100);

```

Scilab code Exa 12.19 Compute the CTO distortion

```

1 //Chapter 12
2 //page no 486
3 //given
4 clc;
5 clear all;
6 Ncto=50;
7 b=1.07*10^-2;
8 m=0.05;
9 CTO=10*log10(Ncto*(1.5*b*m)^2);
10 printf("\n CTO distortion for 50 channel optical
        system = %0.1f dB\n",CTO);
11 //Answer in the book is misprinted
12 //The solution in the book is calculated without
        multiplication of Ncto

```

Scilab code Exa 12.20 Calculate the CSO and CTO

```

1 //Chapter 12
2 //page no 487
3 //given
4 clc;

```

```

5 clear all;
6 Ncs0=80;
7 a=2.43*10^-3;
8 b=4.65*10^-3;
9 m=0.05;
10 //Part (i)
11 CS0=10*log10(Ncs0*(a*m)^2);
12 printf("\n CSO distortion for 50 channel optical
        system for m = 5 percent \n CSOdB = %0.1f dB\n",
        CS0);
13 //Part (ii)
14 CTO=10*log10(Ncs0*(1.5*b*m)^2);
15 printf("\n CTO distortion for 50 channel optical
        system for m = 5 percent \n CTODB = %0.1f dB\n",
        CTO);
16 //Part (iii)
17 m=0.03;
18
19 CS0=10*log10(Ncs0*(a*m)^2);
20 // Value of a in the book is considered 2.4 instead
        of 2.43
21 printf("\n CSO distortion for 50 channel optical
        system for m = 3 percent \n CSOdB = %0.1f dB\n",
        CS0);
22
23 //Part (iv)
24 CTO=10*log10(Ncs0*(1.5*b*m)^2);
25 printf("\n CTO distortion for 50 channel optical
        system for m = 3 percent \n CTODB = %0.1f dB\n",
        CTO);

```

Scilab code Exa 12.21 Calculate the CNR

```

1 //Chapter 12
2 //page no 487

```

```
3 // given
4 clc;
5 clear all;
6 RIN=-150;           // in dB
7 B=4*10^6;
8 m=0.04;
9 CNR=10*log10(m^2/(2*10^-15*B));
10 printf("\n CNR = %0.0 f dB",CNR);
```

Scilab code Exa 12.22 Calculate the RIN

```
1
2
3
4
5
6 //Chapter 12
7 //page no 488
8 //given
9 clc;
10 clear all;
11 CNR=50;           // in dB
12 Bch=4*10^6;
13 m=0.03;
14 RIN=m^2/2/Bch/10^(CNR/10)
15 mprintf("\n RIN = %e ",RIN);
16 //Miscalculated answer in the book
17 RINdB=10*log10(RIN);
18 printf("\nRIN in Db is %.2 f",RINdB)
```

Scilab code Exa 12.23 Calculate the required optical power

```
1 //Chapter 12
```

```

2 //page no 490
3 //given
4 clc;
5 clear all;
6 Ipd=0.15;           //in mA
7 n=0.75;
8 e=1.6*10^-19;      //electron charge
9 hv=1.55*10^-19;
10 Pin=hv*Ipd/n/e;
11 printf("\n Pin = %0.6f mW",Pin);    //Result
12 //answer in book is misprint

```

Scilab code Exa 12.24 Calculate the percentage of optical power reflected back

```

1 //Chapter 12
2 //page no 492
3 //given
4 clc;
5 clear all;
6 OBR=-40;           //in dB
7 //y=Pref/Pin
8 y=10^(OBR/10);
9 printf("\n Prefl = %0.2f percent Pin",y*100);

```

Scilab code Exa 12.25 Calculate the output voltage of an optical receiver

```

1 //Chapter 12
2 //page no 493
3 //given
4 clc;
5 clear all;
6 R=800;             //in V/W

```

```

7 Pin=1.5;           //in mW
8 m=0.04;
9 Voutp=R*Pin*m;
10 printf("\n Vout(peak) = %0.0f mV",Voutp);
11 Vavg=Voutp/sqrt(2);
12 printf("\n Vavg = %0.1f mV",Vavg);
13 //in dB
14 Vavgd=20*log10(Vavg*10^-3);
15 printf("\n Vavg(in dBmV) = %0.1f ",Vavgd);

```

Scilab code Exa 12.26 Determine the optical receiver responsivity

```

1 //Chapter 12
2 //page no 494
3 //given
4 clc;
5 clear all;
6 Voutp=20;           //in dB
7 Pin=1.2;           //in mW
8 m=0.035;
9 Vavg=10^(Voutp/20);          //in
10 R=Vavg*sqrt(2)/Pin/m;
11 printf("\n R = %0.1f V/W",R);

```

Scilab code Exa 12.27 Calculate the modulation depth

```

1 //Chapter 12
2 //page no 494
3 //given
4 clc;
5 clear all;
6 Voutp=28;           //in dB
7 Pin=1;             //in mW

```

```

8 R=800;           //in V/W
9 Vavg=10^(Voutp/20);           //in
10 m=Vavg*sqrt(2)/Pin/R;
11 printf("\n The modulation depth ,m = %0.1f percent" ,
      m*100);

```

Scilab code Exa 12.28 Calculate the CNR

```

1 //Chapter 12
2 //page no 495
3 //given
4 clc;
5 clear all;
6 IpD=1.2;           //in mA
7 m=0.04;
8 RIND=-160;          //in dB/Hz
9 e=1.6*10^-19;
10 nth=8;            //in pA/Hz
11 BW=4;             //in MHz
12 Rin=10^(RIND/10); //in
13
14 CNR=[0.5*(m*IpD*10^-3)^2]/[(2*e*IpD*10^-3)+(Rin*IpD
   *10^-3)^2+((nth*10^-12)^2)*BW/10^6];
15 printf("Value of CNR=%e",CNR)
16 CNRdB=10*log10(CNR)
17 printf("\nValue of CNR in dB=%.2f dB",CNRdB)
18 //Answer in the book is misprinted or wrong
   calculation performed in the book

```

Scilab code Exa 12.29 Total fiber span attenuation

```

1 //Chapter 12
2 //page no 509

```

```

3 // given
4 clc;
5 clear all;
6 L1=40;           // in km
7 L2=100;          // in km
8 A=0.2;           // in dB/Km
9 TFA1=A*L1;
10
11 printf("\n Total fibre span attenuation %0.0f dB\n",
12      TFA1);
12 TFA2=A*L2;
13 printf("\n Total fibre span attenuation %0.0f dB\n",
14      TFA2);
14 nsd=TFA2-TFA1;
15 printf("\n Noise spectral density = %0.0f dB ",nsd);
16 nsd_abs=10^(nsd/10)
17 printf("\n\n Absolute value of noise spectral
18      density = %0.0f dB ",nsd_abs);

```

Scilab code Exa 12.30 Calculate the SNR

```

1
2
3
4
5
6 //Chapter 12
7 //page no 510
8 //given
9 clc;
10 clear ;
11 P1=2.75;           // in mW
12 NFD=5;            // in dB
13 bw=5;              // in GHz
14 G=10;               // in dB

```

```

15 h=1.6*10^-19; //photon energy in J
16 N=1; //no of amplifiers
17 NF=10^(NFd/10); //amplifier noise figure
18 SNR=10*log10(P1*10^-3/[G*hv*bw*10^9*N*NF]); // signal to noise ratio
19 printf("\n Spectral Noise density = %0.0f dB ",SNR);
    // result

```

Scilab code Exa 12.31 Calculate the optical power in fiber

```

1 //Chapter 12
2 //page no 510
3 //given
4 clc;
5 clear all;
6 SNRdB=40; //in dB
7 NFd=6; //in dB
8 bw=4; //in GHz
9 Gd=8; //in dB
10 hv=1.6*10^-19; //photon energy in J
11 N=8; //no of amplifiers
12 SNR=10^(SNRdB/10);
13 NF=10^(NFd/10); //amplifier noise figure
14 G=10^(Gd/10); //amplifier gain
15 P1=10*(SNR/10)*[G*hv*bw*10^9*N*NF]/10^-3; // optical power launched into fibre
16 printf("\n Optical power required , P1 = %0.1f mW ", P1); //Result

```

Scilab code Exa 12.32 Compute the transmission length

```

1
2

```

```

3
4
5
6 //Chapter 12
7 //page no 518
8 //given
9 clc;
10 clear all ;
11 l=1550;           //wavelength in nm
12 fb=10;            //system bit rate Gb/s
13 Df=17;             //fiber dispersion in ps/nm-km
14 L=10^5/Df/fb^2;      //fiber length in km
15 printf("\n Transmission length is %0.1f km",L);
16 fb2=2.5;          //system bit rate Gb/s
17 disp("for fb=2.5 Gb/s")
18 L2=10^5/Df/fb2^2;     //fiber length in km
19 printf(" Transmission length is %0.0f km",L2); ///
               result misprint in book

```

Scilab code Exa 12.33 Compute the maximum bit rate

```

1 //Chapter 12
2 //page no 518
3 //given
4 clc;
5 clear all;
6 lembda=1550;        //wavelength in nm
7 Df=17;              //fiber dispersion in ps/nm-km
8 L=80                //fiber length in km
9 fb=sqrt(10^5/Df/L)
10 printf("\n Maximum bit rate fb = %.1f Mb/s",fb);

```

Scilab code Exa 12.34 Compute the solition characteristic length

```

1 //Chapter 12
2 //page no 530
3 //given
4 clc;
5 clear all;
6 D=0.2;                                // dispersion constant in
   ps/nm/km
7 Tfwhm=18;                            // ps
8 Zs=0.25*Tfwhm^2/D;                  // Characteristic length
9 printf("\n Zs = %0.0 f km", Zs);    // answer in book
   is miscalculated

```

Scilab code Exa 12.35 Determine maximum dispersion

```

1 //Chapter 12
2 //page no 530
3 //given
4 clc;
5 clear all;
6 lembda=1550;                         //wavelength in nm
7 c=3*10^5;                            //speed of light in km/s
8 Zs=600;                               //in km
9 Tfwhm=20;                            //in ps
10 D=1/1.763^2*[2*pi*c*Tfwhm^2/(lembda^2*Zs)]; // dispersion constant
11 printf("\n dispersion constant , D = %0.2 f ps/nm/km" ,
D);                                //result

```

Scilab code Exa 12.36 Calculate the solition pulse width

```

1
2
3

```

```

4
5
6 //Chapter 12
7 //page no 530
8 //given
9 clc;
10 clear all;
11 l=1557;           //wavelength in nm
12 c=3*10^5;         //speed of light in km/s
13 Zs=550;           //in km
14 D=0.25;           //in ps/nm/km
15 Tfwhm=sqrt(1.763^2*l^2*D*Zs/(2*pi*c)); //Soliton
    pulse width
16 printf("\n Tfwhm = %0.0 f ps",Tfwhm);      //Result

```

Scilab code Exa 12.37 Calculate the solition peak pulse

```

1 //Chapter 12
2 //page no 531
3 //given
4 clc;
5 clear ;
6 Aeff=55;           //in sq micrometer
7 l=1557;           //wavelength in nm
8 c=3*10^5;         //speed of light in km/s
9 n2=2.6*10^-16;    //in cm^2/W
10 D=0.20;           //Dispersion constant in
    ps/nm/km
11 Tfwhm=30;          //in ps
12 Zs=[2*pi*c*Tfwhm^2/l^2/D]/(1.763)^2 ; ////
    charecteric length
13 printf("\n Zs = %0.0 f km",Zs);           //result
14 Ps=(Aeff*10^-12*l*10^-9)/(2*pi*n2*10^-4*Zs*10^3); ////
    Peak pulse power
15 //Miscalculation in the book

```

```
16 printf("\n Ps = %0.2f mW",Ps*1000); // Result
```

Scilab code Exa 12.38 Compute the standard deviation

```
1
2 //Chapter 12
3 //page no 533
4 //given
5 clc;
6 clear all;
7 Z=10;           //in mm
8 Tfwhm=22;       //in ps
9 D=0.5;          //ps/nm/km
10 Aeff=55;        //in microm^2
11 A=0.05;         //in km^-1
12 nsp=1.5;        //spontaneous emission
13 F=2;            //amplifier noise
14 s=3.6*10^3*nsp*F*A*D*Z^3/(Aeff*Tfwhm);
15 printf("\n sigma = %0.0f ps",s); // Result
16
17 //answer in book is misprint
```

Scilab code Exa 12.39 Calculate the system BER

```
1 //Chapter 12
2 //page no 533
3 //given
4 clc;
5 clear ;
6 Q1=4;           //quality factor
7 Q2=6;           //quality factor
8 BER1=[2*pi*(Q1^2+2)]^-0.5*exp(-Q1*Q1/2);
9 BER2=[2*pi*(Q2^2+2)]^-0.5*exp(-Q2*Q2/2);
```

```

10 printf("\n For Q=4 ,BER = %0.0f*10^-5 ",BER1*10^5);
    //Result
11 printf("\n For Q=6 ,BER = %0.1f*10^-10 ",BER2
    *10^10);           //Result
12 //Answer second is misprinted in the book

```

Scilab code Exa 12.40 Compute the standard deviation

```

1 //Chapter 12
2 //page no 534
3 //given
4 clc;
5 clear all;
6 D=0.5;                      //Dispersion constant ps/nm/km
7 Ts=22;                       //Pulse width in ps
8 fb=10;                        //system transmission rate in Gb
    /s
9 Z1=1;                         //System total length Mm
10 Z2=10;                        //System total length Mn
11 sa1=8.6*D*D*Z1*Z1*sqrt(fb-0.99)/22/2;      //
    standard deviation based on acoustic effect
12 sa2=8.6*D*D*Z2*Z2*sqrt(fb-0.99)/22/2;      //
    standard deviation based on acoustic effect
13 printf("\n For Z=1000km ,sigma acoustic = %0.2f ps
    ",sa1);           //Result
14 printf("\n For Z=10000km ,sigma acoustic = %0.0f ps
    ",sa2);           //Result

```

Scilab code Exa 12.41 Calculate the collision length

```

1 //Chapter 12
2 //page no 535
3 //given

```

```

4 clc;
5 clear all;
6 D=0.45; //dispersion coefficient in ps/
           nm/km
7 Ts=22; //Pulse width in ps
8 l=0.5; //length in nm
9 Lcollision=2*Ts/l/D; //collision length in
           km
10 printf("\n Lcollision = %0.1f km ",Lcollision);
     //Result

```

Scilab code Exa 12.42 Calculate the half channel length

```

1 //Chapter 12
2 //page no 537
3 //given
4 clc;
5 clear all;
6 f=70; //Maximum frequencyshift in Ghz
7 Ts=22; //Pulse width in ps
8 CS=1.783*f*10^9*Ts*10^-12; //half channel
           seperation
9 printf("\n The half channel seperation %0.2f ",CS);
10 df=0.105/f/10^9/Ts/Ts/10^-24; //maximum
           frequency shift
11 printf("\n The maximum frequency shift %0.0f GHz",df
           /10^9);
12 dt=0.1786/f/10^9/f/10^9/Ts/10^-12; //time
           displacement
13 printf("\n The time displacement %0.2f ps",dt*10^12)
     ;

```

Scilab code Exa 12.43 Calculate the minimum number of soliton

```

1 //Chapter 12
2 //page no 538
3 //given
4 clc;
5 clear ;
6 M=1;
7 N=1;           //no of collision
8 S1=4;           //soliton collision
9 S2=5;           //soliton collision
10 Nc=S1*S1/4*[M*S1/2-M+N];           //minimum no of
    collision
11 printf("\n Ncollision for S=4, is %0.0f",Nc);
12 Nc2=(S2*S2-1)/4*[M*S2/2-M+N];           //minimum no of
    collision
13 printf("\n Ncollision for S=5, is %0.0f",Nc2);

```

Scilab code Exa 12.44 Compute the maximum number of soliton

```

1 //Chapter 12
2 //page no 539
3 //given
4 clc;
5 clear;
6 S=4;
7 n=5;
8 printf("\n Maximum number of solition Collisions\n")
      ;
9 for M = 1:n
10 N=M;
11 Nc=S*[M*S*S/3+S*(N/2-M)-N/2+2*M/3];           //minimum
    no of collision
12 printf("\n M=%0.0f      N=%0.0f      S=%0.0f , is      %0
.0f",M,N,S,Nc); //result
13
14

```

15 **end**

Scilab code Exa 12.45 Compute the number of collision

```
1 //Chapter 12
2 //page no 539
3 //given
4 clc;
5 clear all;
6 M=1;           //number of solition Collisions
7 N=1;           // number of solition Collisions
8 x=2;
9 y=1/2;
10 p=3;
11 p2=4;
12 Tb=100;       //ps
13 l=1;           //difference in wavelength in nm
14 D=7*10^-2;     //ps/nm^2*km
15 Zr=y*y*(Tb/l/l/D); //regeration spacing in km
16 printf("\n Zr = %0.0 f km\n",Zr);
17 P=(p-1)*N+(p-2)*(p-1)*M/2;
18 printf("\n P(%0.0 f) =%0.0 f",p,P);      //result
    number of Collisions
19 P2=(p2-1)*N+(p2-2)*(p2-1)*M/2;
20 printf("\n P(%0.0 f) =%0.0 f",p2,P2);      //result
    number of Collisions
```

Scilab code Exa 12.46 Calculate the channel spacing

```
1 //chapter 12
2 //page no 540
3 //exa 12_46
4 //given
```

```

5 clear;
6 clc;
7 Tb=100;           //bit period in ps
8 dZ=0.4;           //in ps/nm/km
9 Zr=150;           //Modulator spacing in km
10 Ta=Tb/(dZ*Zr); //channel spacing in nm
11 printf("\n Channel spacing %0.1f nm",Ta); //result

```

Scilab code Exa 12.47 Compute the bit period

```

1 //chapter 12
2 //page no 540
3 //exa 12_47
4 //given
5 clear;
6 clc;
7 Zr=200;           //Modulator spacing in km
8 D=0.6;           //in ps/nm/km
9 l=2;              //in nm
10 Tb=l*(Zr*D);   //bit period in ps
11 printf("\n Bit period Tb = %0.0f ps",Tb); //result

```

Scilab code Exa 12.48 Calculate the maximum modulator spacing

```

1 //chapter 12
2 //page no 540
3 //exa 12_48
4 //given
5 clear;
6 clc;
7 D=0.5;           //ps/nm-km
8 Tb=80;           //bit period in ps
9 l=1.5;           //in nm

```

```
10 Zr=Tb/(D*l);           //Modulator spacing in km
11 printf("\n Maximum modulator spacing Zr = %0.2f km", Zr);


---


```

Scilab code Exa 12.49 Calculate the length of dispersion

```
1 //chapter 12
2 //page no 541
3 //exa 12_49
4 //given
5 clear;
6 clc;
7 Zd=100;           //in km
8 Do=0.07;          //in ps/nm^2
9 D1=-0.3;          //in ps/nm^2
10 Ldsf=(Zd*Do)/(Do-D1);      //length of dispersion
    compensation fiber in km
11 printf("\n Length of Dispersion compensation fiber ,
    Ldsf = %0.0f km",Ldsf); //Result


---


```

Scilab code Exa 12.50 Calculate the collision length

```
1 //chapter 12
2 //page no 542
3 //ex 12_50
4 //given
5 clear;
6 clc;
7 m=3;
8 n=1;
9 Tb=100;           //ps
10 l=1;              //nm
11 D=0.07;          //ps/nm^2*km


---


```

```

12 lmn=1;           //nm
13 lmo=2;           //nm
14 Do=0.1;          //ps/nm-km
15 Lc=4*Tb/[5*D*lmn*(lmn+2*lmo)]; //Collision length in
   km
16 printf("\n Collision length without dispersion slope
   compensation = %0.1f km\n",Lc); //result
17 Lc2=2*Tb/[5*Do*lmn]; //Collision length in km
18 printf("\n Collision length with dispersion slope
   compensation = %0.0f km",Lc2); //result

```

Scilab code Exa 12.51 Compute the soliton collision length

```

1 //chapter 12
2 //page no 542
3 //ex 12_51
4 //given
5 clear;
6 clc;
7 Zr=200;           //in km
8 S=4;
9 Ltot1=2*Zr*(S-1);      //total solition colliion
   length in km
10 printf("\n Total solition Collisions length With DSC
   ,Ltotal = %0.0f km\n",Ltot1); //Result
11 Ltot2=(2/5)*Zr*(S-1);      //total solition
   colliion length in km
12 printf("\n Total solition Collisions length With non
   -DSC ,Ltotal = %0.0f km\n",Ltot2); //result

```

Chapter 13

Networks

Scilab code Exa 13.1 Calculate R9 R7 R8 C4

```
1 //Chapter 13
2 //page no 568
3 //given
4 clc;
5 clear all;
6 Vcc=5;                                //in V
7 Vf=1.5;                                //in V
8 If=60;                                 //in mA
9 B=3.97;
10 N=3;
11 R9=(Vcc-Vf)*(B+1)/If/10^-3;
12 printf("\n R9 = %0.0 f ohm\n",R9);
13 R7=R9/2/B-3/N;
14 printf("\n R7 = %0.1 f ohm\n",R7);
15 R8=R9/2/B;
16 printf("\n R8 = %0.1 f ohm\n",R8);
17 C4=2*10^-9/R8;
18 printf("\n C4 = %0.0 f pF",C4*10^12);
```

Scilab code Exa 13.2 Calculate Led If R3 C4

```
1 //Chapter 13
2 //page no 569
3 //given
4 clc;
5 clear all;
6 Vu3=1.24;           //in V
7 Vbeq3=0.7;          //in V
8 Vbeq4=0.7;          //in V
9 R5=17.5;            //in Ohm
10 R6=17.5;           //in Ohm
11 Voh=5;              //in V
12 Vol=0;              //in V
13 If=(Vu3-Vbeq3)/R5+(Vu3-Vbeq4)/R6;
14 printf("\n If= %0.1f mA\n",If*1000);
15 R3=(Voh-Vol)/If;
16 printf("\n R3= %0.0f ohm\n",R3);
17 C4=2*10^-9/R3;
18 printf("\n C4= %0.0f pF\n",C4*10^12);
19 //Chapter 13
20 //page no 581
21 //given
22 disp("Page number 581 again Example 13-2 (numbering
mistake)")
23 Er=4.9;
24 h=5;                //in mils
25 w=10;               //in mils
26 t=0.5;              //in mils
27 Z=60/sqrt(0.475*Er+0.67)*log(4*h/0.67/(0.8*w+t));
28 printf("\n Z = %0.1f ohm\n",Z);
29 tpd=1.017*sqrt(0.475*Er+0.67);
30 printf("\n tpd = %0.2f ns/ft\n",tpd);
31 Tpd=tpd*1000/12;      //converted into ps/in
32 printf("\n tpd = %0.2f ps/in\n",Tpd);
33 Co=Tpd/Z;
34 printf("\n Co = %0.1f pF/in\n",Co);
```

Scilab code Exa 13.3 Characteristic impedance and propagation delay

```
1 //Chapter 13
2 //page no 583
3 //given
4 clc;
5 clear all;
6 Er=4.7;
7 b=10;           //in mils
8 w=4;           //in mils
9 t=0.5;         //in mils
10 Z=60/sqrt(Er)*log(4*b/0.67/%pi/(0.8*w+t));
11 printf("\n Z = %0.2 f ohm\n",Z);
12 tpd=1.017*sqrt(Er);
13 printf("\n tpd = %0.1 f ns/ft \n",tpd);
14 Tpd=tpd*1000/12;      //converted into ps/in
15 printf("\n Also ,tpd = %0.0 f ps/in\n",Tpd); //answer
   is slightly different due to rounding off
```
