

Scilab Textbook Companion for  
Fluid Power With Applications  
by A. Esposito<sup>1</sup>

Created by  
Sandeep Rajendra Tripathi  
B.Tech - Final Year  
Mechanical Engineering  
Vishwakarma Institute of Technology  
College Teacher  
Prof. N. V. Sahasrabuddhe  
Cross-Checked by

August 9, 2013

<sup>1</sup>Funded by a grant from the National Mission on Education through ICT, <http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab codes written in it can be downloaded from the "Textbook Companion Project" section at the website <http://scilab.in>

# Book Description

**Title:** Fluid Power With Applications

**Author:** A. Esposito

**Publisher:** Pearson Prentice Hall

**Edition:** 6

**Year:** 2005

**ISBN:** 8177585800

Scilab numbering policy used in this document and the relation to the above book.

**Exa** Example (Solved example)

**Eqn** Equation (Particular equation of the above book)

**AP** Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

# Contents

List of Scilab Codes	4
2 PHYSICAL PROPERTIES OF HYDRAULIC FLUIDS	11
3 ENERGY AND POWER IN HYDRAULIC SYSTEMS	28
4 FRICTIONAL LOSSES IN HYDRAULIC PIPELINES	50
5 HYDRAULIC PUMPS	64
6 HYDRAULIC CYLINDERS AND CUSHIONING DEVICES	77
7 HYDRAULIC MOTORS	85
8 HYDRAULIC VALVES	95
9 HYDRAULIC CIRCUIT DESIGN AND ANALYSIS	102
10 HYDRAULIC CONDUCTORS AND FITTINGS	111
11 ANCILLARY HYDRAULIC DEVICES	118
13 PNEUMATICS AIR PREPARATION AND COMPONENTS	124
14 PNEUMATICS CIRCUITS AND APPLICATIONS	140
17 ADVANCED ELECTRICAL CONTROLS FOR FLUID POWER SYSTEMS	154

# List of Scilab Codes

Exa 2.1.a	find weight of a body . . . . .	11
Exa 2.1.b	SOLUTION weight of a body . . . . .	11
Exa 2.2.a	find specific weight of body . . . . .	12
Exa 2.2.b	SOLUTION specific weight of body . . . . .	12
Exa 2.3.a	find specific gravity of air . . . . .	13
Exa 2.3.b	SOLUTION specific gravity of air . . . . .	13
Exa 2.4.a	find density of body . . . . .	13
Exa 2.4.b	SOLUTION density of body . . . . .	14
Exa 2.5.a	find pressure on skin diver . . . . .	14
Exa 2.5.b	SOLUTION pressure on skin diver . . . . .	15
Exa 2.6.a	find height of barometer tube . . . . .	15
Exa 2.6.b	SOLUTION height of barometer tube . . . . .	16
Exa 2.7.a	convert gage to absolute pressure . . . . .	16
Exa 2.7.b	SOLUTION gage to absolute pressure . . . . .	17
Exa 2.8.a	find absolute pressure on skin diver . . . . .	17
Exa 2.8.b	SOLUTION absolute pressure on skin diver . . . . .	18
Exa 2.9.a	find specific weight in SI system . . . . .	18
Exa 2.9.b	SOLUTION specific weight in SI system . . . . .	18
Exa 2.10.a	when fahrenheit and celsius temperature equals . . . . .	19
Exa 2.10.b	SOLUTION fahrenheit and celsius temp equals . . . . .	19
Exa 2.11.a	find change in volume of oil . . . . .	20
Exa 2.11.b	SOLUTION change in volume of oil . . . . .	20
Exa 2.12.a	find viscosity of oil . . . . .	21
Exa 2.12.b	SOLUTION viscosity of oil . . . . .	21
Exa 2.13.a	find kinematic and absolute viscosities . . . . .	22
Exa 2.13.b	SOLUTION kinematic and absolute viscosities . . . . .	22
Exa 2.14.a	find viscosity of oil at 100F . . . . .	23
Exa 2.14.b	SOLUTION viscosity of oil at 100F . . . . .	23

Exa 2.15.a	find pressure on skin diver SI . . . . .	24
Exa 2.15.b	SOLUTION pressure on skin diver SI . . . . .	24
Exa 2.16.a	convert gage to absolute pressure SI . . . . .	25
Exa 2.16.b	SOLUTION gage to absolute pressure SI . . . . .	25
Exa 2.17.a	find oil volume change in SI . . . . .	25
Exa 2.17.b	SOLUTION oil volume change in SI . . . . .	26
Exa 2.18.a	find absolute viscosity in SI . . . . .	26
Exa 2.18.b	SOLUTION absolute viscosity in SI . . . . .	27
Exa 3.1.a	find work done and power delivered . . . . .	28
Exa 3.1.b	SOLUTION work done and power delivered . . . . .	28
Exa 3.2.a	find torque delivered by hydraulic motor . . . . .	29
Exa 3.2.b	SOLUTION torque delivered by hydraulic motor . . . . .	29
Exa 3.3.a	find input horsepower required by elevator . . . . .	30
Exa 3.3.b	SOLUTION input horsepower required by elevator . . . . .	30
Exa 3.4.a	find force and energy for jack . . . . .	31
Exa 3.4.b	SOLUTION force and energy for jack . . . . .	31
Exa 3.5.a	what is output horsepower . . . . .	32
Exa 3.5.b	SOLUTION output horsepower . . . . .	32
Exa 3.6.a	find load carrying capacity of system . . . . .	34
Exa 3.6.b	SOLUTION load carrying capacity of system . . . . .	34
Exa 3.7.a	find flow rate and fluid velocity . . . . .	35
Exa 3.7.b	SOLUTION flow rate and fluid velocity . . . . .	35
Exa 3.8.a	calculate output HP delivered by cylinder . . . . .	36
Exa 3.8.b	SOLUTION output HP delivered by cylinder . . . . .	36
Exa 3.9.a	calculate efficiency of cylinder assuming leakage . . . . .	37
Exa 3.9.b	SOLUTION efficiency of cylinder assuming leakage . . . . .	38
Exa 3.10.a	find pressure available at motor inlet . . . . .	39
Exa 3.10.b	SOLUTION pressure available at motor inlet . . . . .	39
Exa 3.11.a	find jet velocity and flow rate . . . . .	41
Exa 3.11.b	SOLUTION jet velocity and flow rate . . . . .	41
Exa 3.12.a	find velocity and flowrate through siphon . . . . .	42
Exa 3.12.b	SOLUTION velocity and flowrate through siphon . . . . .	43
Exa 3.13.a	determine force and displacement for piston2 . . . . .	43
Exa 3.13.b	SOLUTION force and displacement for piston2 . . . . .	44
Exa 3.14.a	find velocity of oil through pipe . . . . .	44
Exa 3.14.b	SOLUTION velocity of oil through pipe . . . . .	45
Exa 3.15.a	find hydraulic power delivered by pump . . . . .	45
Exa 3.15.b	SOLUTION hydraulic power delivered by pump . . . . .	46

Exa 3.16.a	find torque delivered by motor SI . . . . .	46
Exa 3.16.b	SOLUTION torque delivered by motor SI . . . . .	47
Exa 3.17.a	find pressure at hydraulicmotor inlet SI . . . . .	47
Exa 3.17.b	SOLUTION pressure at hydraulicmotor inlet SI . . . . .	48
Exa 4.1.a	find reynolds number of hydraulic oil . . . . .	50
Exa 4.1.b	SOLUTION reynolds number of hydraulic oil . . . . .	50
Exa 4.2.a	find reynolds number of oil SI . . . . .	51
Exa 4.2.b	SOLUTION reynolds number of oil SI . . . . .	51
Exa 4.3.a	find head loss in friction . . . . .	52
Exa 4.3.b	SOLUTION head loss in friction . . . . .	52
Exa 4.4.a	find head loss in friction SI . . . . .	53
Exa 4.4.b	SOLUTION head loss in friction SI . . . . .	53
Exa 4.5.a	find friction factor of pipe . . . . .	54
Exa 4.5.b	SOLUTION friction factor of pipe . . . . .	54
Exa 4.6.a	find head loss across globe valve . . . . .	55
Exa 4.6.b	SOLUTION head loss across globe valve . . . . .	55
Exa 4.7.a	find head loss across gate valve . . . . .	56
Exa 4.7.b	SOLUTION head loss across gate valve . . . . .	57
Exa 4.8.a	find equivalent length of globe valve . . . . .	57
Exa 4.8.b	SOLUTION equivalent length of globe valve . . . . .	58
Exa 4.9.a	find pressure at inlet of hydraulicmotor . . . . .	59
Exa 4.9.b	SOLUTION pressure at inlet of hydraulicmotor . . . . .	59
Exa 4.10.a	find pressure inlet hydraulic motor SI . . . . .	61
Exa 4.10.b	SOLUTION pressure inlet hydraulic motor SI . . . . .	61
Exa 5.1.a	find volumetric efficiency of gear pump . . . . .	64
Exa 5.1.b	SOLUTION volumetric efficiency of gear pump . . . . .	64
Exa 5.2.a	find actual flowrate of gear pump . . . . .	65
Exa 5.2.b	SOLUTION actual flowrate of gear pump . . . . .	66
Exa 5.3.a	find eccentricity of vane pump . . . . .	66
Exa 5.3.b	SOLUTION eccentricity of vane pump . . . . .	67
Exa 5.4.a	find volumetric displacement of vane pump . . . . .	67
Exa 5.4.b	SOLUTION volumetric displacement of vane pump . . . . .	68
Exa 5.5.a	find power pres compensated pump saved . . . . .	68
Exa 5.5.b	SOLUTION power pres compensated pump saved . . . . .	69
Exa 5.6.a	find offset angle of piston pump . . . . .	69
Exa 5.6.b	SOLUTION offset angle of piston pump . . . . .	70
Exa 5.7.a	find flowrate of axial piston pump . . . . .	70
Exa 5.7.b	SOLUTION flowrate of axial piston pump . . . . .	71

Exa 5.8.a	find theoretical torque required by pump . . . . .	72
Exa 5.8.b	SOLUTION theoretical torque required by pump . . . . .	72
Exa 5.9.a	find theoretical torque required in SI . . . . .	73
Exa 5.9.b	SOLUTION theoretical torque required in SI . . . . .	74
Exa 5.10.a	find yearly cost of electricity . . . . .	75
Exa 5.10.b	SOLUTION yearly cost of electricity . . . . .	75
Exa 6.1.a	find pressure velocity and horsepower . . . . .	77
Exa 6.1.b	SOLUTION pressure velocity and horsepower . . . . .	77
Exa 6.2.a	find cylinder force to move 6000lb . . . . .	79
Exa 6.2.b	SOLUTION cylinder force to move 6000lb . . . . .	79
Exa 6.3.a	find force to move inclined weight . . . . .	80
Exa 6.3.b	SOLUTION force to move inclined weight . . . . .	80
Exa 6.4.a	find cylinder force to accelerate weight . . . . .	81
Exa 6.4.b	SOLUTION cylinder force to accelerate weight . . . . .	81
Exa 6.5.a	find cylinder force using lever system . . . . .	82
Exa 6.5.b	SOLUTION cylinder force using lever system . . . . .	82
Exa 6.6.a	find maximum pressure developed by cushion . . . . .	83
Exa 6.6.b	SOLUTION maximum pressure developed by cushion . . . . .	84
Exa 7.1.a	find pressure developed to overcome load . . . . .	85
Exa 7.1.b	SOLUTION pressure developed to overcome load . . . . .	85
Exa 7.2.a	determine theoretical horsepower of hydraulic motor . . . . .	86
Exa 7.2.b	SOLUTION theoretical horsepower of hydraulic motor . . . . .	86
Exa 7.3.a	find actual horsepower delivered by motor . . . . .	87
Exa 7.3.b	SOLUTION actual horsepower delivered by motor . . . . .	87
Exa 7.4.a	find motor displacement and output torque . . . . .	88
Exa 7.4.b	SOLUTION motor displacement and output torque . . . . .	89
Exa 7.5.a	find motor theoretical power in SI . . . . .	90
Exa 7.5.b	SOLUTION motor theoretical power in SI . . . . .	90
Exa 7.6.a	find actual KW delivered by motor . . . . .	91
Exa 7.6.b	SOLUTION actual KW delivered by motor . . . . .	92
Exa 7.7.a	find motor output torque in SI . . . . .	93
Exa 7.7.b	SOLUTION motor output torque in SI . . . . .	93
Exa 8.1.a	determine cracking and full flow pressure . . . . .	95
Exa 8.1.b	SOLUTION cracking and full flow pressure . . . . .	95
Exa 8.2.a	compute horsepower across pressure relief valve . . . . .	96
Exa 8.2.b	SOLUTION horsepower across pressure relief valve . . . . .	96
Exa 8.3.a	compute horsepower across unloading valve . . . . .	97
Exa 8.3.b	SOLUTION horsepower across unloading valve . . . . .	97



Exa 8.4.a	find flow rate through the orifice . . . . .	98
Exa 8.4.b	SOLUTION flow rate through the orifice . . . . .	98
Exa 8.5.a	determine capacity coefficient of flowcontrol valve . . . . .	99
Exa 8.5.b	SOLUTION capacity coefficient of flowcontrol valve . . . . .	99
Exa 8.6.a	determine capacity coefficient of needle valve . . . . .	100
Exa 8.6.b	SOLUTION capacity coefficient of needle valve . . . . .	100
Exa 9.1.a	determine speed power for regenerative circuit . . . . .	102
Exa 9.1.b	SOLUTION speed power for regenerative circuit . . . . .	102
Exa 9.2.a	find unloading relief valve pressure settings . . . . .	103
Exa 9.2.b	SOLUTION unloading relief valve pressure settings . . . . .	104
Exa 9.3.a	find spring constant of PRV valve . . . . .	105
Exa 9.3.b	SOLUTION spring constant of PRV valve . . . . .	105
Exa 9.4.a	determine cylinder speed of meterin circuit . . . . .	106
Exa 9.4.b	SOLUTION cylinder speed of meterin circuit . . . . .	106
Exa 9.5.a	find overall efficiency of given system . . . . .	107
Exa 9.5.b	SOLUTION overall efficiency of given system . . . . .	108
Exa 10.1.a	find minimum inside diameter of pipe . . . . .	111
Exa 10.1.b	SOLUTION minimum inside diameter of pipe . . . . .	111
Exa 10.2.a	find minimum inside diameter in SI . . . . .	112
Exa 10.2.b	SOLUTION minimum inside diameter in SI . . . . .	112
Exa 10.3.a	find safe working pressure of tube . . . . .	113
Exa 10.3.b	SOLUTION safe working pressure of tube . . . . .	113
Exa 10.4.a	select proper size steel tube . . . . .	114
Exa 10.4.b	SOLUTION proper size steel tube . . . . .	114
Exa 10.5.a	select proper size steel tube SI . . . . .	115
Exa 10.5.b	SOLUTION proper size steel tube SI . . . . .	116
Exa 11.1.a	find the discharge flow and pressure . . . . .	118
Exa 11.1.b	SOLUTION the discharge flow and pressure . . . . .	118
Exa 11.2.a	determine the downstream oil temperature . . . . .	119
Exa 11.2.b	SOLUTION the downstream oil temperature . . . . .	119
Exa 11.3.a	determine downstream oil temperature in SI . . . . .	120
Exa 11.3.b	SOLUTION downstream oil temperature in SI . . . . .	120
Exa 11.4.a	find heat exchanger rating of system . . . . .	121
Exa 11.4.b	SOLUTION heat exchanger rating of system . . . . .	122
Exa 11.5.a	find heat exchanger rating in SI . . . . .	122
Exa 11.5.b	SOLUTION heat exchanger rating in SI . . . . .	123
Exa 13.1.a	find final pressure at constant temperature . . . . .	124
Exa 13.1.b	SOLUTION final pressure at constant temperature . . . . .	124

Exa 13.2.a find final volume at constant pressure . . . . .	125
Exa 13.2.b SOLUTION final volume at constant pressure . . . . .	126
Exa 13.3.a find final pressure at constant volume . . . . .	126
Exa 13.3.b SOLUTION final pressure at constant volume . . . . .	127
Exa 13.4.a find final pressure general gas law . . . . .	127
Exa 13.4.b SOLUTION final pressure general gas law . . . . .	128
Exa 13.5.a find final pressure general law SI . . . . .	128
Exa 13.5.b SOLUTION final pressure general law SI . . . . .	129
Exa 13.6.a how much air compressor must provide . . . . .	129
Exa 13.6.b SOLUTION air compressor must provide . . . . .	130
Exa 13.7.a find receiver size for pneumatic system . . . . .	130
Exa 13.7.b SOLUTION receiver size for pneumatic system . . . . .	131
Exa 13.8.a determine actual power required for compressor . . . . .	131
Exa 13.8.b SOLUTION actual power required for compressor . . . . .	132
Exa 13.9.a find moisture received by pneumatic system . . . . .	132
Exa 13.9.b SOLUTION moisture received by pneumatic system . . . . .	133
Exa 13.10.a determine air maximum flowrate in scfm . . . . .	134
Exa 13.10.b SOLUTION air maximum flowrate in scfm . . . . .	134
Exa 13.11.a determine flow capacity constant of system . . . . .	135
Exa 13.11.b SOLUTION flow capacity constant of system . . . . .	136
Exa 13.12.a determine air consumption rate in scfm . . . . .	136
Exa 13.12.b SOLUTION air consumption rate in scfm . . . . .	137
Exa 13.13.a find reciprocation rate of pneumatic cylinder . . . . .	137
Exa 13.13.b SOLUTION reciprocation rate of pneumatic cylinder . . . . .	138
Exa 14.1.a find pressure loss for given pipe . . . . .	140
Exa 14.1.b SOLUTION pressure loss for given pipe . . . . .	140
Exa 14.2.a find pressure loss with pipe valves . . . . .	141
Exa 14.2.b SOLUTION pressure loss with pipe valves . . . . .	142
Exa 14.3.a determine cost of electricity per year . . . . .	142
Exa 14.3.b SOLUTION cost of electricity per year . . . . .	143
Exa 14.4.a determine cost of leakage per year . . . . .	144
Exa 14.4.b SOLUTION cost of leakage per year . . . . .	145
Exa 14.5.a how heavy object can be lifted . . . . .	145
Exa 14.5.b SOLUTION heavy object can be lifted . . . . .	146
Exa 14.6.a determine time for achieving vacuum pressure . . . . .	146
Exa 14.6.b SOLUTION time for achieving vacuum pressure . . . . .	147
Exa 14.7.a calculate required size of the accumulator . . . . .	148
Exa 14.7.b SOLUTION required size of the accumulator . . . . .	148

Exa 14.8.a find electricity cost per year SI . . . . .	149
Exa 14.8.b SOLUTION electricity cost per year SI . . . . .	150
Exa 14.9.a what flowrate vacuum pump must deliver . . . . .	151
Exa 14.9.b SOLUTION flowrate vacuum pump must deliver . . . . .	151
Exa 14.10.a calculate required size of accumulator SI . . . . .	152
Exa 14.10.b SOLUTION required size of accumulator SI . . . . .	153
Exa 17.1.a determine system accuracy of electrohydraulic system . . . . .	154
Exa 17.1.b SOLUTION system accuracy of electrohydraulic system . . . . .	155
Exa 17.2.a determine system accuracy in SI . . . . .	155
Exa 17.2.b SOLUTION system accuracy in SI . . . . .	156
Exa 17.3.a find maximum tracking error . . . . .	157
Exa 17.3.b SOLUTION maximum tracking error . . . . .	157

## Chapter 2

# PHYSICAL PROPERTIES OF HYDRAULIC FLUIDS

Scilab code Exa 2.1.a find weight of a body

```
1 // Aim:To Find Weight of Body
2 // Given:
3 // Mass of the Body:
4 m=4; //slugs
```

---

Scilab code Exa 2.1.b SOLUTION weight of a body

```
1 clc;
2 pathname=get_absolute_file_path('2_1_soln.sce')
3 filename=pathname+filesep()+ '2_1_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // we know acceleration due to gravity,
8 g=32.2; //ft/s^2
9 W=(m*g);
```

```

10
11 // Results:
12 printf("\n Results: ")
13 printf("\n The weight of Body is %.0f lb.",W)

```

---

Scilab code Exa 2.2.a find specific weight of body

```

1 // Aim:To find the specific weight of a body
2 // Given:
3 // Weigth of the Body:
4 W=129; //lb
5 // Volume of the Body:
6 V=1.8; //ft^3

```

---

Scilab code Exa 2.2.b SOLUTION specific weight of body

```

1 clc;
2 pathname=get_absolute_file_path('2_2_soln.sce')
3 filename=pathname+filesep()+ '2_2_data.sci'
4 exec(filename)
5
6 // Solution:
7 // we know specific weight ,
8 // gamma=(Weigth of the Body/Volume of the Body)
9 gamma1=(W/V); //lb/ft^3
10 // rounding off the above answer
11 gamma1=fix(gamma1)+(fix((gamma1-fix(gamma1))*10)/10)
    ; //lb/ft^3
12
13 // Results:
14 printf("\n Results: ")
15 printf("\n The specific weight of Body is %.1f lb/ft
    ^3.",gamma1)

```

---

**Scilab code Exa 2.3.a** find specific gravity of air

```
1 // Aim:To find the specific gravity of air at 68
   degF
2 // Given:
3 // specific weight of air at 68 degF:
4 gamma_air=0.0752; //lb/ft^3
```

---

**Scilab code Exa 2.3.b** SOLUTION specific gravity of air

```
1 clc;
2 pathname=get_absolute_file_path('2_3_soln.sce')
3 filename=pathname+filesep()+ '2_3_data.sci'
4 exec(filename)
5
6 // Solution:
7 // we know,
8 // specific gravity of air=(specific weight of air/
   specific weight of water)
9 // also we know,specific weight of water at 68 degF,
10 gamma_water=62.4; //lb/ft^3
11 SG_air=gamma_air/gamma_water;
12
13 // Results:
14 printf("\\n Results: ")
15 printf("\\n The specific gravity of air %0.5f.",
   SG_air)
```

---

**Scilab code Exa 2.4.a** find density of body

```

1 // Aim:To find Density of body of Example 2-1 and
   2-2
2 // Given:
3 // mass of the Body:
4 m=4; //slugs
5 // Volume of the Body:
6 V=1.8; //ft^3

```

---

**Scilab code Exa 2.4.b SOLUTION density of body**

```

1 clc;
2 pathname=get_absolute_file_path('2_4_soln.sce')
3 filename=pathname+filesep()+ '2_4_data.sci '
4 exec(filename)
5
6 // Solution:
7 // we know density ,
8 // rho1=(mass of the Body/Volume of the Body)
9 rho1=(m/V); //slugs/ft^3
10 // also density ,rho2=(specific weight/acceleration
   due to gravity)
11 g=32.2; //ft/s^2
12 gamma1=71.6; //lb/ft^3
13 rho2=(gamma1/g); //slugs/ft^3
14
15 // Results:
16 printf("\\n Results: ")
17 printf("\\n The Density of Body is %.2f slugs/ft^3.",
   rho1)
18 printf("\\n The Density of Body is %.2f slugs/ft^3.",
   rho2)

```

---

**Scilab code Exa 2.5.a find pressure on skin diver**

```
1 // Aim:To find pressure on the skin diver
2 // Given:
3 // Depth of Water Body:
4 H=60; //ft
```

---

**Scilab code Exa 2.5.b SOLUTION** pressure on skin diver

```
1 clc;
2 pathname=get_absolute_file_path('2_5_soln.sce')
3 filename=pathname+filesep()+ '2_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // specific Weight of water ,
8 gamma1=0.0361; //lb/in^3
9 // Conversion:
10 // 1 feet = 12 inches
11 // 1 lb/in^2 = 1 psi
12 // we know pressure ,
13 // p=(specific weight of liquid * liquid column
    height)
14 p=(gamma1*H*12); //psi
15
16 // Results:
17 printf("\\n Results: ")
18 printf("\\n The pressure on skin diver is %.1f psi.",
    p)
```

---

**Scilab code Exa 2.6.a** find height of barometer tube

```
1 // Aim:To find tube height of a Barometer
2 // Given:
3 // liquid used is Water instead of Mercury.
```



---

**Scilab code Exa 2.6.b** SOLUTION height of barometer tube

```
1  clc;
2  pathname=get_absolute_file_path('2_6_soln.sce')
3  filename=pathname+filesep()+ '2_6_data.sci'
4  exec(filename)
5
6  // Solution:
7  // specific Weight of water ,
8  gamma1=0.0361; //lb/in^3
9  // We also knows Atmospheric Pressure ,
10 p=14.7; //psi
11 // Conversion:
12 // 1 feet = 12 inches
13 // 1 lb/in^2 = 1 psi
14 // we know pressure ,
15 // p=(specific weight of liquid * liquid column
    height)
16 // Therefore ,
17 H=(p/gamma1); //in
18 // He=Height in Feet.
19 He=H*0.083; //ft
20
21 // Results:
22 printf("\n Results: ")
23 printf("\n The Height of water column is %0.0f ft.",
    He)
```

---

**Scilab code Exa 2.7.a** convert gage to absolute pressure

```
1 // Aim:To convert given pressure into absolute
    pressure
```

```
2 // Given:
3 // Gage Pressure:
4 Pg=-5; //psi
```

---

**Scilab code Exa 2.7.b SOLUTION** gage to absolute pressure

```
1 clc;
2 pathname=get_absolute_file_path('2_7_soln.sce')
3 filename=pathname+filesep()+ '2_7_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Atmospheric Pressure ,
8 Po=14.7; //psi
9 // Absolute Pressure(Pa) =Gage Pressure +
   Atmospheric Pressure
10 Pa=Pg+Po;
11
12 // Results:
13 printf("\\n Results: ")
14 printf("\\n The Absolute Pressure is %0.1f psi.",Pa)
```

---

**Scilab code Exa 2.8.a** find absolute pressure on skin diver

```
1 // Aim:To find absolute pressure on skin diver of
   Example 2-5
2 // Given:
3 // Gage Pressure:
4 Pg=26; //psi
```

---

**Scilab code Exa 2.8.b SOLUTION** absolute pressure on skin diver

```
1  clc;
2  pathname=get_absolute_file_path('2_8_soln.sce')
3  filename=pathname+filesep()+ '2_8_data.sci'
4  exec(filename)
5
6  // Solution:
7  // Atmospheric Pressure ,
8  Po=14.7; //psi
9  // Absolute Pressure(Pa) =Gage Pressure +
   Atmospheric Pressure
10 Pa=Pg+Po; //psi
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The Absolute Pressure is %0.1f psi.",Pa)
```

---

**Scilab code Exa 2.9.a** find specific weight in SI system

```
1 // Aim:To Determine specific weights in N/m^3
2 // Given:
3 // specific weight:
4 gamma1=56; //lb/ft^3
```

---

**Scilab code Exa 2.9.b SOLUTION** specific weight in SI system

```
1  clc;
2  pathname=get_absolute_file_path('2_9_soln.sce')
3  filename=pathname+filesep()+ '2_9_data.sci'
4  exec(filename)
5
6  // Solution:
```

```

7 // We know ,
8 // 1 N/m^3 = 157 lb/ft^3
9 gamma2=157*gamma1; //N/m^3
10
11 // Results:
12 printf("\n Results: ")
13 printf("\n The specific weights is %0.0f N/m^3.",
    gamma2)
14 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")

```

---

**Scilab code Exa 2.10.a** when fahrenheit and celsius temperature equals

```

1 // Aim:To find Temperature at which Fahrenheit and
    Celsius values are equal
2 // Given:
3 // T(degF) = T(degC) //Eqn - 1

```

---

**Scilab code Exa 2.10.b** SOLUTION fahrenheit and celsius temp equals

```

1 clc;
2 pathname=get_absolute_file_path('2_10_soln.sce')
3 filename=pathname+filesep()+ '2_10_data.sci'
4 exec(filename)
5
6 // Solution:
7 // We know that ,
8 // T(degF) = ((1.8*T(degC)) + 32) //Eqn - 2
9 // From Eqn 1 and 2
10 // ((1.8*T(degC)) + 32) = T(degC)
11 // (1 - 1.8)*T(degC) = 32
12 // -0.8*T(degC) = 32

```

```

13 TdegC=-32/0.8;
14
15 // Results:
16 printf("\n Results: ")
17 printf("\n The temp at which Fahrenheit and Celsius
    values are equal is %0.1f deg.",TdegC)

```

---

**Scilab code Exa 2.11.a** find change in volume of oil

```

1 // Aim:To find change in volume of the oil
2 // Given:
3 // Volume of original oil:
4 V=10; //in^3
5 // Initial Pressure:
6 P1=100; //psi
7 // Final pressure:
8 P2=2000; //psi
9 // Bulk Modulus:
10 betaa=250000; //psi

```

---

**Scilab code Exa 2.11.b SOLUTION** change in volume of oil

```

1 clc;
2 pathname=get_absolute_file_path('2_11_soln.sce')
3 filename=pathname+filesep()+ '2_11_data.sci '
4 exec(filename)
5
6 // Solution:
7 // Change in pressure ,
8 delP=P2-P1; //psi
9 // Change in volume ,
10 delV=-((V*delP)/betaa); //in^3 ,- sign indicates oil
    is being compressed

```

```

11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The change in volume of oil is %.3f in^3.
    ",delV)

```

---

**Scilab code Exa 2.12.a** find viscosity of oil

```

1 // Aim:To find viscosity of oil in centistokes and
    centipoise
2 // Given:
3 // viscosity of oil:
4 nu=230; //SUS at
5 t=150; //degF.
6 // specific gravity of oil:
7 gamma1=0.9;

```

---

**Scilab code Exa 2.12.b** SOLUTION viscosity of oil

```

1 clc;
2 pathname=get_absolute_file_path('2_12_soln.sce')
3 filename=pathname+filesep()+ '2_12_data.sci'
4 exec(filename)
5
6 // Solution:
7 // kinematic viscosity of oil in centistokes ,
8 nu_cs=((0.220*nu)-(135/t)); //centistokes
9 // absolute viscosity of oil in centipoise ,
10 mu_cp=(gamma1*nu_cs); //centipoise
11
12 // Results:
13 printf("\n Results: ")

```

```
14 printf("\n The viscosity of oil in centistokes is %0
    .0f cS.",nu_cs)
15 printf("\n The viscosity of oil in centipoise is %0
    .0f cP.",mu_cp)
```

---

**Scilab code Exa 2.13.a** find kinematic and absolute viscosities

```
1 // Aim:To find kinematic and absolute viscosity of
    oil in cS and cP respectively
2 // Given:
3 // Density of oil:
4 Den=0.89; //g/cm^3
5 // Time flow:
6 t=250; //s
7 // Calibration constant:
8 cc=0.100;
```

---

**Scilab code Exa 2.13.b** SOLUTION kinematic and absolute viscosities

```
1 clc;
2 pathname=get_absolute_file_path('2_13_soln.sce')
3 filename=pathname+filesep()+ '2_13_data.sci'
4 exec(filename)
5
6
7 // Solution:
8 // kinematic viscosity of oil in centistokes ,
9 nu_cs=(t*cc); //centistokes
10 // absolute viscosity of oil in centipoise ,
11 SG=Den;
12 mu_cp=(SG*nu_cs); //centipoise
13 // rounding off the above answer
```

```

14 mu_cp=fix(mu_cp)+(fix(round((mu_cp-fix(mu_cp))*10))
    /10); //centipoise
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The viscosity of oil in centistokes is %0
    .1f cS.",nu_cs)
19 printf("\n The viscosity of oil in centipoise is %0
    .1f cP.",mu_cp)

```

---

**Scilab code Exa 2.14.a** find viscosity of oil at 100F

```

1 // Aim:To find viscosity of oil at 100 degF in SUS
2 // Given:
3 // Viscosity Index:
4 VI=80;
5 // viscosity of O-VI oil at 100 degF:
6 L=400; //SUS
7 // viscosity of 100-VI oil at 100 degF:
8 H=150; //SUS

```

---

**Scilab code Exa 2.14.b SOLUTION** viscosity of oil at 100F

```

1 clc;
2 pathname=get_absolute_file_path('2_14_soln.sce')
3 filename=pathname+filesep()+ '2_14_data.sci'
4 exec(filename)
5
6 // Solution:
7 // viscosity of sample oil at 100 degF,
8 U=L-(((L-H)*VI)/100); //SUS
9
10 // Results:

```



```
11 printf("\n Results: ")
12 printf("\n The viscosity of sample oil at 100 degF
    is %0.0f SUS.",U)
```

---

**Scilab code Exa 2.15.a** find pressure on skin diver SI

```
1 // Aim:To find pressure on the skin diver in SI
    units
2 // Given:
3 // Depth of Water Body:
4 H=18.3; //m
```

---

**Scilab code Exa 2.15.b** SOLUTION pressure on skin diver SI

```
1 clc;
2 pathname=get_absolute_file_path('2_15_soln.sce')
3 filename=pathname+filesep()+ '2_15_data.sci'
4 exec(filename)
5
6 // Solution:
7 // specific Weight of water ,
8 gamma1=9800; //N/m^3
9 // we know pressure ,
10 // p=(specific weight of liquid * liquid column
    height)
11 p=(gamma1*H); //Pa
12 pK=p/1000; //kPa
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The pressure on skin diver is %0.0f kPa.",
    pK)
```

---

**Scilab code Exa 2.16.a** convert gage to absolute pressure SI

```
1 // Aim:To convert given pressure into absolute
   pressure
2 // Given:
3 // Gage Pressure:
4 Pg=-34000; //Pa
```

---

**Scilab code Exa 2.16.b** SOLUTION gage to absolute pressure SI

```
1 clc;
2 pathname=get_absolute_file_path('2_16_soln.sce')
3 filename=pathname+filesep()+ '2_16_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Atmospheric Pressure ,
8 Po=101000; //Pa
9 // Absolute Pressure(Pa) =Gage Pressure +
   Atmospheric Pressure
10 Pa=Pg+Po; //Pa
11
12 // Results:
13 printf("\\n Results: ")
14 printf("\\n The Absolute Pressure is %0.0f Pa.",Pa)
```

---

**Scilab code Exa 2.17.a** find oil volume change in SI

```
1 // Aim:To find % change in volume of the oil
```

```

2 // Given:
3 // Volume of original oil:V=164 //cm^3
4 // Initial Pressure:
5 P1=687; //kPa
6 // Final pressure:
7 P2=13740; //kPa
8 // Bulk Modullus:
9 betaa=1718; //MPa

```

---

**Scilab code Exa 2.17.b SOLUTION** oil volume change in SI

```

1 clc;
2 pathname=get_absolute_file_path('2_17_soln.sce')
3 filename=pathname+filesep()+ '2_17_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Change in pressure ,
8 delP=P2-P1; //kPa
9 betaa=betaa*1000; //kPA
10 // % Change in volume ,
11 delV=- (delP/betaa)*100; //%, - sign indicates oil is
    being compressed
12
13 // Results:
14 printf("\n Results: ")
15 printf("\n The Percentage change in volume of oil is
    %.3f.",delV)

```

---

**Scilab code Exa 2.18.a** find absolute viscosity in SI

```

1 // Aim:To find absolute viscosity of oil in Ns/m^2
    and cP

```

```

2 // Given:
3 // Area of moving plate surface in contact with oil:
4 A=1; //m^2
5 // Force applied to the moving plate:
6 F=10; //N
7 // velocity of the moving plate:
8 v=1; //m/s
9 // oil film thickness:
10 y=5; //mm
11 y=5*0.001; //m

```

---

**Scilab code Exa 2.18.b SOLUTION** absolute viscosity in SI

```

1 clc;
2 pathname=get_absolute_file_path('2_18_soln.sce')
3 filename=pathname+filesep()+ '2_18_data.sci'
4 exec(filename)
5
6 // Solution:
7 // absolute viscosity of oil ,
8 mu=(F/A)/(v/y); //Ns/m^2
9 // absolute viscosity of oil in cP,
10 mu_P=(F*100000*y*100)/(v*100*A*10000); //poise
11 mu_cP=mu_P*100; //centipoise
12
13 // Results:
14 printf("\\n Results: ")
15 printf("\\n The viscosity of oil is %0.2f Ns/m^2.",mu
)
16 printf("\\n The viscosity of oil is %0.2f cP.",mu_cP)

```

---

## Chapter 3

# ENERGY AND POWER IN HYDRAULIC SYSTEMS

Scilab code Exa 3.1.a find work done and power delivered

```
1 // Aim:To find work done and power deliver
2 // Given:
3 // Force exerted by the person:
4 F=30; //lb
5 // Distance moved by hand truck:
6 S=100; //ft
7 // time taken:
8 t=60; //s
```

---

Scilab code Exa 3.1.b SOLUTION work done and power delivered

```
1 clc;
2 pathname=get_absolute_file_path('3_1_soln.sce')
3 filename=pathname+filesep()+ '3_1_data.sci '
4 exec(filename)
5
```

```

6 // Solution:
7 // we know, Work done=Force * Displacement,
8 W=F*S; //ft.lb
9 // Now, Power,
10 P=W/t; //(ft.lb/s)
11 P=P/550; //HP
12
13 // Results:
14 printf("\n Results: ")
15 printf("\n The work done by the person is %.1f ft.lb
    ",W)
16 printf("\n The power delivered by the person is %.3f
    HP",P)

```

---

**Scilab code Exa 3.2.a** find torque delivered by hydraulic motor

```

1 clc;
2 // Aim:To determine torque required by hydraulic
    motor
3 // Given:
4 // Power Supplied:
5 HP=2; //HP
6 // Speed of the Hydraulic motor:
7 N=1800; //rpm

```

---

**Scilab code Exa 3.2.b** SOLUTION torque delivered by hydraulic motor

```

1 clc;
2 pathname=get_absolute_file_path('3_2_soln.sce')
3 filename=pathname+filesep()+ '3_2_data.sci'
4 exec(filename)
5
6 // Solution:

```

```

7 // Power (HP)=(Torque*Speed)/63000
8 // Therefore ,Torque
9 T=(HP*63000)/N; //in.lb
10
11 // Results:
12 printf("\n Results: ")
13 printf("\n The Torque delivered by Hydraulic motor
    is %.1f in.lb",T)

```

---

**Scilab code Exa 3.3.a** find input horsepower required by elevator

```

1 // Aim: Refer Example 3–3 for Problem Description
2 // Given:
3 // Load to be raised:
4 F=3000; //lb
5 // Distance:
6 S=50; //ft
7 // time required:
8 t=10; //s
9 //efficiency of the system:
10 eta=80; //%

```

---

**Scilab code Exa 3.3.b** SOLUTION input horsepower required by elevator

```

1 clc;
2 pathname=get_absolute_file_path('3_3_soln.sce')
3 filename=pathname+filesep()+ '3_3_data.sci'
4 exec(filename)
5
6 // Solution:
7 // we know,output power=(Force * Displacement)/time,
8 outpw=(F*S)/t; //ft.lb/s
9 outpw_HP=outpw/550; //HP

```

```

10 // Efficiency=output power/input power
11 inpw=outpw_HP/(eta*0.01); //HP
12
13 // Results:
14 printf("\n Results: ")
15 printf("\n The Input Horsepower required by elevator
    hoist motor is %.1f HP",inpw)

```

---

**Scilab code Exa 3.4.a** find force and energy for jack

```

1 // Aim:Refer Example 3–4 for Problem Description
2 // Given:For the Hydraulic Jack ,
3 // Area of Piston 1:
4 A1=2; //in^2
5 // Area of Piston 2:
6 A2=20; //in^2
7 // Input force downward:
8 F1=100; //lb
9 // downward movement of piston 1:
10 S1=1; //in

```

---

**Scilab code Exa 3.4.b** SOLUTION force and energy for jack

```

1 clc;
2 pathname=get_absolute_file_path('3_4_soln.sce')
3 filename=pathname+filesep()+ '3_4_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Pascal law states , (F1*A1 = F2*A2)
8 // Similarly , (S1*A1 = S2*A2)
9 // Output force upward,
10 F2=(A2/A1)*F1; //lb

```



```

11 // upward movement of piston 2,
12 S2=(A1/A2)*S1; //in
13 // Energy Input ,
14 E1=F1*S1; //in.lb
15 // Energy Output ,
16 E2=F2*S2; //in.lb
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The Output force upward is %.1f lb",F2)
21 printf("\n The upward movement of piston 2 is %.1f
    in",S2)
22 printf("\n The Energy Input is %.1f in.lb",E1)
23 printf("\n The Energy Output is %.1f in.lb",E2)

```

---

**Scilab code Exa 3.5.a** what is output horsepower

```

1 // Aim:Refer Example 3–5 for Problem Description .
2 // Given:
3 // Diameter of piston of pump cylinder:
4 Dp=1; //in
5 // Diameter of piston of load cylinder:
6 D1=3.25; //in
7 // Average hand force:
8 Fh=25; //lb
9 // Load piston stroke:
10 S1=10; //in
11 // Pump piston stroke:
12 Sp=2; //in

```

---

**Scilab code Exa 3.5.b** SOLUTION output horsepower

```

1 clc;

```

```

2 pathname=get_absolute_file_path('3_5_soln.sce')
3 filename=pathname+filesep()+ '3_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Therefore, Force acting on rod of pump cylinder,
8 F_rod=(8/2)*Fh; //lb
9 // Area of piston of pump cylinder,
10 Ap=(%pi/4)*Dp^2; //in^2
11 // Area of piston of load cylinder,
12 Al=(%pi/4)*Dl^2; //in^2
13 // Pump cylinder discharge pressure,
14 p=round(F_rod/Ap); //psi
15 // Load carrying capacity,
16 F_load=p*Al; //lb
17 // Therefore, No.s of Cycles,
18 Noc=(Al*S1)/(Ap*Sp);
19 // Output power,
20 outpw=((F_load*(S1/12))/Noc); //ft.lb/s
21 outpw_HP=outpw/550; //HP
22 // Assuming efficiency 80 %
23 eta=0.8;
24 outpw_HP2=eta*outpw_HP; //HP
25
26 // Results:
27 printf("\n Results: ")
28 printf("\n Therefore %.0f lb of load can be lifted",
    F_load)
29 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")
30 printf("\n Therefore %.1f no.s of cycles are
    required to lift the load 10 in.",Noc)
31 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")
32 printf("\n Input power when efficiency is 100
    percent is %.3f HP",outpw_HP)

```

```
33 printf("\n Input power when efficiency is 80 percent
    is %.3f HP", outpw_HP2)
```

---

**Scilab code Exa 3.6.a** find load carrying capacity of system

```
1 // Aim:Refer Example 3-6 for Problem Description.
2 // Given:
3 // inlet air pressure:
4 p1=100; //psi
5 // air piston area:
6 A1=20; //in^2
7 // oil piston area:
8 A2=1; //in^2
9 // load piston area:
10 A3=25; //in^2
11 // load piston diameter:
12 d3=5.64; //in
```

---

**Scilab code Exa 3.6.b** SOLUTION load carrying capacity of system

```
1 clc;
2 pathname=get_absolute_file_path('3_6_soln.sce')
3 filename=pathname+filesep()+ '3_6_data.sci'
4 exec(filename)
5
6 // Solution:
7 // booster input force = booster output force
8 //  $p_1 \cdot A_1 = p_2 \cdot A_2$ 
9 p2=(A1/A2)*p1; //psi
10 // As per pascal law,
11 p3=p2; // where p3=outlet pressure
12 // Therefore load carrying capacity of system,
13 F=p3*A3; //lb
```

```

14
15 // Results:
16 printf("\n Results: ")
17 printf("\n The load carrying capacity of system is %
    .0f lb.",F)

```

---

**Scilab code Exa 3.7.a** find flow rate and fluid velocity

```

1 // Aim:Refer Example 3–7 for Problem Description.
2 // Given:
3 // inlet diameter:
4 D1=4; //in
5 // outlet diameter:
6 D2=2; //in
7 // inlet velocity:
8 v1=4; //ft/s

```

---

**Scilab code Exa 3.7.b** SOLUTION flow rate and fluid velocity

```

1 clc;
2 pathname=get_absolute_file_path('3_7_soln.sce')
3 filename=pathname+filesep()+ '3_7_data.sci'
4 exec(filename)
5
6 // Solution:
7 // we know, Discharge=Area*Velocity
8 A1=(%pi/4)*(D1/12)^2; //ft^2
9 Q=A1*v1; //ft^3/s
10 // Since, for hydraulic system, volume flow rate is
    always constant
11 // we get, outlet velocity,
12 v2=((D1/D2)^2)*v1; //ft/s
13

```

```

14 // Results:
15 printf("\n Results: ")
16 printf("\n The Volume flow rate of the system is %.3
    f ft^3/s.",Q)
17 printf("\n The fluid velocity at station 2 is %.0f
    ft/s.",v2)

```

---

**Scilab code Exa 3.8.a** calculate output HP delivered by cylinder

```

1 // Aim:Refer Example 3–8 for Problem Description.
2 // Given:
3 // Time period of operations:
4 t=10; //s
5 // Stroke of hydraulic cylinder:
6 S=10; //ft
7 // Load required to compress car:
8 F_load=8000; //lb
9 // Pump pressure:
10 p=1000; //psi
11 // Efficiency of cylinder:100 %
12 eta=1;

```

---

**Scilab code Exa 3.8.b** SOLUTION output HP delivered by cylinder

```

1 clc;
2 pathname=get_absolute_file_path('3_8_soln.sce')
3 filename=pathname+filesep()+ '3_8_data.sci'
4 exec(filename)
5
6 // Solution:
7 // The required piston area ,
8 A=round(F_load/p); //in^2
9 // The necessary pump flow rate ,

```

```

10 Q=((A/144)*S)/t; //ft ^3/s
11 Q_gpm=Q*449; //gpm
12 // The Hydraulic Horsepower delivered to cylinder ,
13 HHP=(p*Q_gpm)/1714; //HP
14 // rounding off the above answer
15 HHP=fix(HHP)+(fix(floor((HHP-fix(HHP))*10))/10); //
    HP
16 // The output horsepower delivered by cylinder to
    load ,
17 OHP=HHP*eta; //HP
18
19 // Results:
20 printf("\n Results: ")
21 printf("\n The Required piston area is %.0f in^2.",A
    )
22 printf("\n The necessary pump flow rate is %.1f gpm.
    ",Q_gpm)
23 printf("\n The Hydraulic Horsepower delivered to
    cylinder is %.1f HP.",HHP)
24 printf("\n The output horsepower delivered by
    cylinder to load is %.1f HP.",OHP)

```

---

**Scilab code Exa 3.9.a** calculate efficiency of cylinder assuming leakage

```

1 // Aim:Refer Example 3–9 for Problem Description .
2 // Given:
3 // Time period of operations:
4 t=10; //s
5 // Stroke of hydraulic cylinder:
6 S=10; //ft
7 // Load required to compress car:
8 F_load=8000; //lb
9 // Pump pressure:
10 p=1000; //psi
11 // Frictional Force:

```

```

12 F_fric=100; //lb
13 // Leakage:
14 Q_leak=0.2; //gpm

```

---

Scilab code Exa 3.9.b SOLUTION efficiency of cylinder assuming leakage

```

1  clc;
2  pathname=get_absolute_file_path('3_9_soln.sce')
3  filename=pathname+filesep()+ '3_9_data.sci'
4  exec(filename)
5
6  // Solution:
7  // The required piston area ,
8  A=(F_load+F_fric)/p; //in^2
9  // The Theoretical pump flow rate ,
10 Q_theo=((A/144)*S)/t; //ft^3/s
11 Q_gpm=(Q_theo*449); //gpm
12 // The Actual pump flow rate ,
13 Q_act=Q_gpm+Q_leak; //gpm
14 // rounding off the above answer
15 Q_act=fix(Q_act)+(fix(floor((Q_act-fix(Q_act))*10))
    /10); //gpm
16 // The Hydraulic Horsepower delivered to cylinder ,
17 HHP=(p*Q_gpm)/1714; //HP
18 // rounding off the above answer
19 HHP=fix(HHP)+(fix(ceil((HHP-fix(HHP))*10))/10); //HP
20 // The output horsepower delivered by cylinder to
    load ,
21 OHP=(F_load*(S/t))/550; //HP
22 // The Efficiency of System ,
23 eta=floor((OHP/HHP)*100); // %
24
25 // Results:
26 printf("\n Results: ")
27 printf("\n The Required piston area is %.2f in^2.",A

```

```

    )
28 printf("\n The necessary pump flow rate is %.1f gpm.
    ",Q_act)
29 printf("\n The Hydraulic Horsepower delivered to
    cylinder is %.1f HP.",HHP)
30 printf("\n The output horsepower delivered by
    cylinder to load is %.1f HP.",OHP)

```

---

**Scilab code Exa 3.10.a** find pressure available at motor inlet

```

1 // Aim:Refer Example 3-10 for Problem Description.
2 // Given:
3 // Pump Power:
4 HHP=5; //HP
5 // Pump flow:
6 Q=30; //gpm
7 // Pipe Diameter:
8 D=1; //in
9 // specific gravity of oil:
10 SG=0.9;
11 // Pressure at Station 1:
12 p1=0; //psig (It is atmospheric pressure.)
13 // Head Loss due to friction between Station 1 and 2
    of oil:
14 Hl=30; //ft

```

---

**Scilab code Exa 3.10.b SOLUTION** pressure available at motor inlet

```

1 clc;
2 pathname=get_absolute_file_path('3_10_soln.sce')
3 filename=pathname+filesep()+ '3_10_data.sci'
4 exec(filename)
5

```



```

6 // Solution:
7 // Acceleration due to gravity ,
8 g=32.2; //ft/s^2
9 // Energy Equation between Station 1 and Station 2
  is given by,
10 // (Z1+P1+K1+Hp-Hm-Hl)=(Z2+P2+K2)
11 // since , There is no Hydraulic motor between
  Station 1 and 2,
12 // Therefore Motor Head,
13 Hm=0; //ft
14 // also , cross section of oil tank is very large , as
  a result oil is at rest ,
15 v1=0; //ft/s
16 // Kinetic Energy Head at inlet ,
17 K1=(v1^2)/(2*g); //ft
18 // Height of Station 1 from Datum,
19 Z1=0; //ft
20 // Height of Station 2 from Datum,
21 Z2=20; //ft
22 // Pressure Head at inlet ,
23 P1=p1/SG; //ft
24 // Pump Head,
25 Hp=ceil((3950*HHP)/(Q*SG)); //ft
26 // Pump flow ,
27 Q_1=Q/449; //ft^3/s
28 // Area of pipe ,
29 A=((%pi)*((D/12)^2))/4; //ft^2
30 // Therefore , velocity in pipe ,
31 v2=Q_1/A; //ft/s
32 // Kinetic Energy head at Station 2,
33 K2=(v2^2)/(2*g); //ft
34 // Therefore , Pressure Head at outlet ,
35 P2=Z1+P1+K1+Hp-Hm-Hl-Z2-K2; //ft
36 // specific weight of oil ,
37 gamma1=SG*62.4; //lb/ft^3
38 // Pressure available at inlet of hydraulic motor at
  station 2,
39 p2=P2*gamma1; // lb/ft^2

```

```

40 p2=floor(p2/144); //psi
41
42 // Results:
43 printf("\n Results: ")
44 printf("\n The Pressure available at inlet of
    hydraulic motor at Station 2 is %.0f psig.",p2)

```

---

**Scilab code Exa 3.11.a** find jet velocity and flow rate

```

1 // Aim:Refer Example 3–11 for Problem Description.
2 // Given:
3 // Fluid Head:
4 h=36; //ft
5 // Diameter of opening:
6 d=2; //in
7 // Frictional Head Losses:
8 Hl=10; //ft

```

---

**Scilab code Exa 3.11.b** SOLUTION jet velocity and flow rate

```

1 clc;
2 pathname=get_absolute_file_path('3_11_soln.sce')
3 filename=pathname+filesep()+ '3_11_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Acceleration due to gravity ,
8 g=32.2; //ft/s^2
9 // Assuming ideal fluid , Jet velocity ,
10 v2=sqrt(2*g*h); //ft/s
11 // Area of the opening ,
12 A=(%pi/4)*((d/12)^2); //ft^2
13 // flow rate ,

```

```

14 Q=A*v2; //ft^3/s
15 Q_gpm=floor(449*Q); //gpm
16 // Jet velocity considering friction losses ,
17 v21=sqrt(64.4*(h-H1)); //ft/s
18 // since , flow rate is proportional to velocity ,
19 Q1=((v21/v2)*Q_gpm); //gpm
20
21 // Results:
22 printf("\n Results: ")
23 printf("\n The Jet velocity is %.1f ft/s.",v2)
24 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")
25 printf("\n The Flow rate is %.0f gpm.",Q_gpm)
26 printf("\n The Jet velocity considering friction
    losses is %.1f ft/s.",v21)
27 printf("\n The Flow rate considering friction losses
    is %.0f gpm.",Q1)
28 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")

```

---

**Scilab code Exa 3.12.a** find velocity and flowrate through siphon

```

1 // Aim:Refer Example 3–12 for Problem Description .
2 // Given:
3 // Fluid Head:
4 h=30; //ft
5 // Frictional Head Losses:
6 H1=10; //ft
7 // U-tube inside diameter:
8 d=1; //in

```

---

**Scilab code Exa 3.12.b SOLUTION** velocity and flowrate through siphon

```
1  clc;
2  pathname=get_absolute_file_path('3_12_soln.sce')
3  filename=pathname+filesep()+ '3_12_data.sci'
4  exec(filename)
5
6  // Solution:
7  // Acceleration due to gravity ,
8  g=32.2; //ft/s^2
9  // Jet velocity through siphon ,
10 v2=sqrt(2*g*(h-H1)); //ft/s
11 // rounding off the above answer
12 v2=fix(v2)+( fix(floor((v2-fix(v2))*10))/10); //ft/s
13 // Area of the U tube ,
14 A=(%pi/4)*((d/12)^2); //ft^2
15 // flow rate through siphon ,
16 Q=A*v2; //ft^3/s
17 Q_gpm=449*Q; //gpm
18 // rounding off the above answer
19 Q_gpm=fix(Q_gpm)+( fix(floor((Q_gpm-fix(Q_gpm))*10))
    /10); //gpm
20
21 // Results:
22 printf(" \n Results: ")
23 printf(" \n The velocity through siphon is %.1f ft/s.
    ",v2)
24 printf(" \n The Flow rate through siphon is %.1f gpm.
    ",Q_gpm)
```

---

**Scilab code Exa 3.13.a** determine force and displacement for piston2

```
1 // Aim: Refer Example 3-13 for Problem Description
2 // Given: For the Hydraulic Jack ,
3 // Area of Piston 1:
```

```

4 A1=25; //cm^2
5 // Area of Piston 2:
6 A2=100; //cm^2
7 // Input force downward:
8 F1=200; //N
9 // downward movement of piston 1:
10 S1=5; //cm

```

---

**Scilab code Exa 3.13.b** SOLUTION force and displacement for piston2

```

1 clc;
2 pathname=get_absolute_file_path('3_13_soln.sce')
3 filename=pathname+filesep()+ '3_13_data.sci '
4 exec(filename)
5
6 // Solution:
7 // Pascal law states , (F1*A1 = F2*A2)
8 // Similarly , (S1*A1 = S2*A2)
9 // Output force upward,
10 F2=(A2/A1)*F1; //N
11 // upward movement of piston 2,
12 S2=(A1/A2)*S1; //cm
13
14 // Results:
15 printf("\\n Results: ")
16 printf("\\n The Output force upward is %.0f N",F2)
17 printf("\\n The upward movement of piston 2 is %.2f
    cm",S2)

```

---

**Scilab code Exa 3.14.a** find velocity of oil through pipe

```

1 // Aim:To Determine velocity through pipe.
2 // Given:

```

```

3 // Diameter of pipe:
4 D=30; //mm
5 // Flow through pipe:
6 Q=60; //lpm

```

---

**Scilab code Exa 3.14.b SOLUTION** velocity of oil through pipe

```

1 clc;
2 pathname=get_absolute_file_path('3_14_soln.sce')
3 filename=pathname+filesep()+ '3_14_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Pump flow in m^3/s,
8 Q_si=0.0000167*Q; //m^3/s
9 // Diameter of pipe,
10 D_m=D/1000; //m
11 // Area of pipe,
12 A=(%pi*(D_m^2))/4; //m^2
13 // velocity,
14 v=Q_si/A; //m/s
15 // rounding off the above answer
16 v=fix(v)+(fix(floor((v-fix(v))*100))/100); //m/s
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The velocity through pipe is %.2f m/s.",v
)

```

---

**Scilab code Exa 3.15.a** find hydraulic power delivered by pump

```

1 // Aim:To Determine Hydraulic power delivered by
  pump.

```

```

2 // Given:
3 // Pump flow:
4 Q=50; //lpm
5 // Pressure delivered by pump:
6 p=10000; //kPa

```

---

**Scilab code Exa 3.15.b** SOLUTION hydraulic power delivered by pump

```

1 clc;
2 pathname=get_absolute_file_path('3_15_soln.sce')
3 filename=pathname+filesep()+ '3_15_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Pump flow in m^3/s,
8 Q_si=0.0000167*Q; //m^3/s
9 // Hydraulic Power,
10 HP=p*Q_si; //kW
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The Hydraulic power delivered by pump is
    %.2f kW.",HP)

```

---

**Scilab code Exa 3.16.a** find torque delivered by motor SI

```

1 // Aim:To determine torque delivered by hydraulic
    motor
2 // Given:
3 // Mechanical Output Power:
4 OP=10; //kW
5 // Speed of the Hydraulic motor:
6 N=1450; //rpm

```

---

**Scilab code Exa 3.16.b** SOLUTION torque delivered by motor SI

```
1 clc;
2 pathname=get_absolute_file_path('3_16_soln.sce')
3 filename=pathname+filesep()+ '3_16_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Power(kW)=(Torque*Speed)/9550
8 // Therefore ,Torque
9 T=(OP*9550)/N; //Nm
10
11 // Results:
12 printf("\n Results: ")
13 printf("\n The Torque delivered by Hydraulic motor
    is %.1 f Nm.",T)
```

---

**Scilab code Exa 3.17.a** find pressure at hydraulicmotor inlet SI

```
1 // Aim:Refer Example 3–17 for Problem Description.
2 // Given:
3 // Pump Power:
4 HHP=3.73; //kW
5 // Pump flow:
6 Q=0.001896; //m^3/s
7 // Pipe Diameter:
8 D=0.0254; //m
9 // specific gravity of oil:
10 SG=0.9;
11 // Pressure at Station 1:
12 p1=0; //Pa (It is atmospheric pressure.)
```



```

13 // Elevation Between Station 1 and 2:
14 // Z=Z1-Z2
15 Z=-6.096; //m -ve sign indicates Station 2 is
    above Station 1
16 // Head Loss due to friction between Station 1 and 2
    of oil:
17 Hl=9.144; //m

```

---

**Scilab code Exa 3.17.b SOLUTION** pressure at hydraulicmotor inlet SI

```

1  clc;
2  pathname=get_absolute_file_path('3_17_soln.sce')
3  filename=pathname+filesep()+ '3_17_data.sci'
4  exec(filename)
5
6  // Solution:
7  // Acceleration due to gravity ,
8  g=9.81; //m/s^2
9  // Energy Equation between Station 1 and Station 2
    is given by,
10 // (Z+P1+K1+Hp-Hm-Hl)=(P2+K2)
11 // since , There is no Hydraulic motor between
    Station 1 and 2,
12 // Therefore Motor Head,
13 Hm=0; //m
14 // also , cross section of oil tank is very large , as
    a result oil is at rest ,
15 v1=0; //m/s
16 // Kinetic Energy Head at inlet ,
17 K1=(v1^2)/(2*g); //m
18 // Pressure Head at inlet ,
19 P1=p1/SG; //m
20 // specific weight of oil ,
21 gamma1=round(SG*9797); //N/m^3
22 // Pump Power ,

```

```

23 W=HHP*1000; //W
24 // Pump Head,
25 Hp=(W/(Q*gamma1)); //m
26 // Area of pipe,
27 A=((%pi)*(D^2))/4; //m^2
28 // Therefore, velocity in pipe,
29 v2=Q/A; //m/s
30 // Kinetic Energy head at Station 2,
31 K2=(v2^2)/(2*g); //m
32 // Therefore, Pressure Head at outlet,
33 P2=Z+P1+K1+Hp-Hm-Hl-K2; //m
34 // Pressure available at inlet of hydraulic motor at
    station 2,
35 p2=floor((P2*gamma1)/1000); // kPa gage
36
37 // Results:
38 printf("\n Results: ")
39 printf("\n The Pressure available at inlet of
    hydraulic motor at Station 2 is %.0f kPa gage.",
    p2)

```

---

## Chapter 4

# FRICITIONAL LOSSES IN HYDRAULIC PIPELINES

Scilab code Exa 4.1.a find reynolds number of hydraulic oil

```
1 // Aim:To Find Reynolds number of oil
2 // Given:
3 // Kinematic viscosity of oil:
4 nu=100; //cS
5 // velocity of oil:
6 v=10; //ft/s
7 // Pipe diameter:
8 D=1; //in
```

---

Scilab code Exa 4.1.b SOLUTION reynolds number of hydraulic oil

```
1 clc;
2 pathname=get_absolute_file_path('4_1_soln.sce')
3 filename=pathname+filesep()+ '4_1_data.sci '
4 exec(filename)
5
```

```

6 // Solution:
7 // Reynolds Number,
8 N_R=(7740*v*D)/nu;
9
10 // Results:
11 printf("\n Results: ")
12 printf("\n The Reynolds number of given oil is %.0f.
    ",N_R)

```

---

**Scilab code Exa 4.2.a** find reynolds number of oil SI

```

1 // Aim:To Find Reynolds number of oil
2 // Given:
3 // Kinematic viscosity of oil:
4 nu=0.001; //m^2/s
5 // velocity of oil:
6 v=5; //m/s
7 // Pipe diameter:
8 D=50; //mm

```

---

**Scilab code Exa 4.2.b** SOLUTION reynolds number of oil SI

```

1 clc;
2 pathname=get_absolute_file_path('4_2_soln.sce')
3 filename=pathname+filesep()+ '4_2_data.sci '
4 exec(filename)
5
6 // Solution:
7 // Reynolds Number,
8 N_R=(v*(D/1000))/nu;
9
10 // Results:
11 printf("\n Results: ")

```

```
12 printf("\n The Reynolds number of given oil is %.0f.\n",N_R)
```

---

**Scilab code Exa 4.3.a** find head loss in friction

```
1 // Aim:Refer Example 4-3 for Problem Description
2 // Given:
3 // Kinematic viscosity of oil:
4 nu=100; //cS
5 // velocity of oil:
6 v=10; //ft/s
7 // Pipe diameter:
8 D=1; //in
9 // Length of pipe:
10 L=100; //ft
11 // specific gravity of oil:
12 SG_oil=0.9;
```

---

**Scilab code Exa 4.3.b** SOLUTION head loss in friction

```
1 clc;
2 pathname=get_absolute_file_path('4_3_soln.sce')
3 filename=pathname+filesep()+ '4_3_data.sci'
4 exec(filename)
5
6 // Solution:
7 // acceleration due to gravity ,
8 g=32.2; //ft/s^2
9 // Reynolds Number,
10 N_R=(7740*v*D)/nu;
11 // Head loss in pipe ,
12 H_L=round((64*L*(v^2))/(N_R*(D/12)*2*g)); //ft ,
    Hagen-Poiseuille Equation
```

```

13 // Head loss in terms of psi ,
14 H_L=SG_oil*0.0361*12*H_L; //psi
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The Head Loss due to friction in pipe is
    %.0f psi.",H_L)

```

---

**Scilab code Exa 4.4.a** find head loss in friction SI

```

1 // Aim:Refer Example 4-4 for Problem Description
2 // Given:
3 // Kinematic viscosity of oil:
4 nu=0.001; //m^2/s
5 // velocity of oil:
6 v=5; //m/s
7 // Pipe diameter:
8 D=50; //mm
9 // Length of pipe:
10 L=50; //m
11 // specific weigth of oil:
12 gamma1=8800; //N/m^2

```

---

**Scilab code Exa 4.4.b** SOLUTION head loss in friction SI

```

1 clc;
2 pathname=get_absolute_file_path('4_4_soln.sce')
3 filename=pathname+filesep()+'4_4_data.sci'
4 exec(filename)
5
6 // Solution:
7 // acceleration due to gravity ,
8 g=9.80; //m/s^2

```

```

9 // Reynolds Number,
10 N_R=(v*(D/1000))/nu;
11 // Head loss in pipe,
12 H_L=floor((64*L*(v^2))/(N_R*(D/1000)*2*g)); //m ,
    Hagen-Poiseuille Equation
13 // Head loss in terms of kPa,
14 H_L1=(gamma1*H_L)/1000; //kPa
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The Head Loss due to friction in pipe is
    %.0f m of oil.",H_L)

```

---

**Scilab code Exa 4.5.a** find friction factor of pipe

```

1 // Aim:Refer Example 4-5 for Problem Description
2 // Given:
3 // Kinematic viscosity of oil:
4 nu=50; //cS
5 // Pipe diameter:
6 D=1; //in
7 // velocity of oil:
8 v1=10; //ft/s
9 v2=40; //ft/s

```

---

**Scilab code Exa 4.5.b** SOLUTION friction factor of pipe

```

1 clc;
2 pathname=get_absolute_file_path('4_5_soln.sce')
3 filename=pathname+filesep()+ '4_5_data.sci '
4 exec(filename)
5
6 // Solution:

```

```

7 // Reynolds Number in 1st case ,
8 N_R1=(7740*v1*D)/nu;
9 // Using Moody diagram from fig 4-9,
10 f1=0.042 ;
11 // Reynolds Number in 2nd case ,
12 N_R2=(7740*v2*D)/nu;
13 // relative roughness ,
14 rr=0.0018/D;
15 // Using Moody diagram from fig 4-9,
16 f2=0.036;
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The friction factor in 1st case is %.3f."
    ,f1)
21 printf("\n The friction factor in 2nd case is %.3f."
    ,f2)

```

---

**Scilab code Exa 4.6.a** find head loss across globe valve

```

1 // Aim:To Find Head Loss across valve
2 // Given:
3 // Diameter of globe valve:
4 D=1; //in
5 // specific gravity of oil:
6 SG_oil=0.9;
7 // flow rate:
8 Q=30; //gpm

```

---

**Scilab code Exa 4.6.b** SOLUTION head loss across globe valve

```

1 clc;
2 pathname=get_absolute_file_path('4_6_soln.sce')

```



```

3 filename=pathname+filesep()+ '4_6_data.sci '
4 exec(filename)
5
6 // Solution:
7 // fluid velocity ,
8 v=(Q/449)/((%pi*((D/12)^2))/4); //ft/s
9 // rounding off the above answer
10 v=fix(v)+(fix(floor((v-fix(v))*10))/10); //ft/s
11 // From table of "K factors of common valves and
    fittings",
12 K=10;
13 // acceleration due to gravity ,
14 g=32.2; //ft/s^2
15 // Head Loss across globe valve ,
16 H_L=(K*(v^2))/(2*g); //ft
17 // Pressure drop across Valve ,
18 delp=SG_oil*0.0361*12*H_L; //psi
19
20 // Results:
21 printf("\n Results: ")
22 printf("\n The head loss across globe valve is %.1f
    ft of oil.",H_L)

```

---

**Scilab code Exa 4.7.a** find head loss across gate valve

```

1 // Aim:To Find Head Loss across valve
2 // Given:
3 // Diameter of gate valve:
4 D=50; //mm
5 // specific weight of oil:
6 gamma1=8800; //N/m^2
7 // kinematic viscosity of oil:
8 nu=0.001; //m^2/s
9 // flow rate:
10 Q=0.02; //m^3/s

```

---

**Scilab code Exa 4.7.b** SOLUTION head loss across gate valve

```
1 clc;
2 pathname=get_absolute_file_path('4_7_soln.sce')
3 filename=pathname+filesep()+ '4_7_data.sci'
4 exec(filename)
5
6 // Solution:
7 // fluid velocity ,
8 v=Q/((%pi*((D/1000)^2))/4); //m/s
9 // rounding off the above answer
10 v=fix(v)+(fix(round((v-fix(v))*10))/10); //m/s
11 // From table of "K factors of common valves and
    fittings",
12 K=0.19;
13 // acceleration due to gravity ,
14 g=9.80; //m/s^2
15 // Head Loss across globe valve ,
16 H_L=(K*(v^2))/(2*g); //m
17 // Pressure drop across Valve ,
18 delp=(gamma1*H_L)/1000; //kPa
19
20 // Results:
21 printf("\n Results: ")
22 printf("\n The head loss across globe valve is %.2f
    m of oil.",H_L)
```

---

**Scilab code Exa 4.8.a** find equivalent length of globe valve

```
1 // Aim: Refer Example 4–8 for Problem Description
2 // Given:
```

```

3 // Kinematic viscosity of oil:
4 nu=100; //cS
5 // Diameter of steel pipe:
6 D=1; //in
7 // flow rate:
8 Q=30; //gpm
9 // Diameter of wide open globe valve:
10 D_1=1; //in

```

---

Scilab code Exa 4.8.b SOLUTION equivalent length of globe valve

```

1 clc;
2 pathname=get_absolute_file_path('4_8_soln.sce')
3 filename=pathname+filesep()+ '4_8_data.sci'
4 exec(filename)
5
6 // Solution:
7 // velocity through steel pipes ,
8 v=(Q/449)/((%pi*((D/12)^2))/4); // ft/s
9 // rounding off the above answer
10 v=fix(v)+(fix(floor((v-fix(v))*10))/10); // ft/s
11 // Reynolds Number,
12 N_R=(7740*v*D)/nu;
13 // friction factor ,
14 f=64/N_R;
15 // From table of "K factors of common valves and
    fittings",
16 K=10;
17 // Equivalent Length,
18 Le=(K*(D_1/12))/f; //ft
19
20 // Results:
21 printf("\n Results: ")
22 printf("\n The Equivalent Length of Globe valve is %
    .1f ft.",Le)

```

---

**Scilab code Exa 4.9.a** find pressure at inlet of hydraulicmotor

```
1 // Aim:Refer Example 4-9 for Problem Description
2 // Given:
3 // Pump hydraulic power:
4 HHP=5; //HP
5 // Pump flow:
6 Q=30; //gpm
7 // Inside Diameter of pipe:
8 D=1; //in
9 // specific gravity of oil:
10 SG_oil=0.9;
11 // Kinematic viscosity of oil:
12 nu=100; //cS
13 // elevation between station 1 and 2:
14 Z=-20; //ft ,-ve sign indicates station 2 is above
    Station 1
15 // Pressure at oil top surface level in hydraulic
    tank:
16 p1=0; //psig
```

---

**Scilab code Exa 4.9.b** SOLUTION pressure at inlet of hydraulicmotor

```
1 clc;
2 pathname=get_absolute_file_path('4_9_soln.sce')
3 filename=pathname+filesep()+ '4_9_data.sci'
4 exec(filename)
5
6 // Solution:
7 // specific weight of oil,
8 gamma1=SG_oil*62.4; //lb/ft^3
```

```

9 // acceleration due to gravity ,
10 g=32.2; //ft/s^2
11 // Since , There is no hydraulic motor ,
12 Hm=0; //ft
13 // oil in tank is at rest ,
14 v1=0; //ft/s
15 // velocity head at station 1 ,
16 K1=(v1^2)/(2*g); //ft
17 // velocity through pipe ,
18 v2=(Q/449)/((%pi*((D/12)^2))/4); //ft/s
19 v2=fix(v2)+(fix(floor((v2-fix(v2))*10))/10); //ft/s
    ,rounding off the answer
20 // velocity head at station 2 ,
21 K2=(v2^2)/(2*g); //ft
22 K2=fix(K2)+(fix(ceil((K2-fix(K2))*10))/10); //ft ,
    rounding off the answer
23 // Reynolds Number ,
24 N_R=round((7740*v2*D)/nu);
25 // friction factor ,
26 f=64/N_R;
27 // From table of "K factors of common valves and
    fittings" ,
28 K=0.9;
29 // equivalent length of standard elbow ,
30 Le_std_elbow=((K*(D/12))/f); //ft
31 // Total equivalent length ,
32 Le_tot=21+Le_std_elbow; //ft
33 // head loss due to friction between Station 1 and
    2 ,
34 H_L=round((f*Le_tot*K2)/(D/12)); //ft
35 // Pump head ,
36 Hp=ceil((3950*HHP)/(Q*SG_oil)); //ft
37 // Pressure at station 2 ,
38 p2=round(Z+(p1/gamma1)+K1+Hp-Hm-H_L-K2); //ft ,
    Modified Bernoulli equation
39 p2=round((p2*gamma1)/144); //psi
40 // Pressure increase across the pump ,
41 delp=ceil((gamma1*Hp)/144);

```

```

42
43 // Results:
44 printf("\n Results: ")
45 printf("\n The Pressure available at the inlet to
    hydraulic motor is %.0f psi.",p2)

```

---

**Scilab code Exa 4.10.a** find pressure inlet hydraulic motor SI

```

1 // Aim:Refer Example 4-10 for Problem Description
2 // Given:
3 // Pump hydraulic power:
4 HHP=3.73; //kW
5 // Pump flow:
6 Q=0.00190; //m^3/s
7 // Inside Diameter of pipe:
8 D=0.0254; //m
9 // specific gravity of oil:
10 SG_oil=0.9;
11 // Kinematic viscosity of oil:
12 nu=100; //cS
13 // elevation between station 1 and 2:
14 Z=-6.10; //m ,-ve sign indicates station 2 is above
    Station 1
15 // Pressure at oil top surface level in hydraulic
    tank:
16 p1=0; //Pa
17 // Pump inlet pipe length:
18 L1=1.53; //m
19 // Pump outlet pipe length up to hydraulic motor:
20 L2=4.88; //m

```

---

**Scilab code Exa 4.10.b** SOLUTION pressure inlet hydraulic motor SI

```

1  clc;
2  pathname=get_absolute_file_path('4_10_soln.sce')
3  filename=pathname+filesep()+ '4_10_data.sci '
4  exec(filename)
5
6  // Solution:
7  // specific weight of oil ,
8  gamma1=SG_oil*9800; //N/m^3
9  // acceleration due to gravity ,
10 g=9.80; //m/s^2
11 // Since, There is no hydraulic motor ,
12 Hm=0; //m
13 // oil in tank is at rest ,
14 v1=0; //m/s
15 // velocity head at station 1,
16 K1=(v1^2)/(2*g); //m
17 // velocity through pipe ,
18 v2=Q/((%pi*(D^2))/4); //m/s
19 // velocity head at station 2,
20 K2=(v2^2)/(2*g); //m
21 // Reynolds Number,
22 N_R=((v2*D)/(nu/1000000));
23 // friction factor ,
24 f=64/N_R;
25 // From table of "K factors of common valves and
    fittings",
26 K=0.9;
27 // equivalent length of standard elbow ,
28 Le_std_elbow=((K*(D/12))/f); //m
29 // Total equivalent length ,
30 Le_tot=L1+L2+Le_std_elbow; //m
31 // head loss due to friction between Station 1 and
    2,
32 H_L=((f*Le_tot*K2)/D); //m
33 // Pump head ,
34 Hp=((1000*HHP)/(Q*gamma1)); //m
35 // Pressure at station 2,
36 p2=(Z+(p1/gamma1)+K1+Hp-Hm-H_L-K2); //m ,Modified

```

```
    Bernoulli equation
37 p2=((p2*gamma1)/1000); //kPa
38
39 // Results:
40 printf("\n Results: ")
41 printf("\n The Pressure available at the inlet to
    hydraulic motor is %.0f kPa.",p2)
42 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")
```

---



# Chapter 5

## HYDRAULIC PUMPS

Scilab code Exa 5.1.a find volumetric efficiency of gear pump

```
1 // Aim:To Find volumetric efficiency of Gear Pump
2 // Given:
3 // outside diameter of gear pump:
4 Do=3; //in
5 // inside diameter of gear pump:
6 Di=2; //in
7 // width of gear pump:
8 L=1; //in
9 // Actual flow rate of pump:
10 Qa=28; //gpm
11 // Speed of gear pump:
12 N=1800; //rpm
```

---

Scilab code Exa 5.1.b SOLUTION volumetric efficiency of gear pump

```
1 clc;
2 pathname=get_absolute_file_path('5_1_soln.sce')
3 filename=pathname+filesep()+ '5_1_data.sci'
```

```

4  exec(filename)
5
6  // Solutions:
7  // Volumetric Displacement is given by,
8  Vd=(%pi/4)*((Do^2)-(Di^2))*L; //in^3
9  // Theoretical Flow rate ,
10 Qt=(Vd*N)/231; //gpm
11 // Volumetric efficiency ,
12 eta_v=(Qa/Qt)*100; //%
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The volumetric efficiency of Gear Pump
    is %.1f percent.",eta_v)
17 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")

```

---

**Scilab code Exa 5.2.a** find actual flowrate of gear pump

```

1  // Aim:To Find actual flow-rate of Gear Pump
2  // Given:
3  // outside diameter of gear pump:
4  Do=75; //mm
5  // inside diameter of gear pump:
6  Di=50; //mm
7  // width of gear pump:
8  L=25; //mm
9  // Volumetric efficiency ,
10 eta_v=90; //%
11 // Speed of gear pump:
12 N=1000; //rpm

```

---

**Scilab code Exa 5.2.b SOLUTION actual flowrate of gear pump**

```
1  clc;
2  pathname=get_absolute_file_path('5_2_soln.sce')
3  filename=pathname+filesep()+ '5_2_data.sci'
4  exec(filename)
5
6  // Solutions:
7  // Volumetric Displacement is given by,
8  Vd=(%pi/4)*(((Do/1000)^2)-((Di/1000)^2))*(L/1000);
   //m^3/rev
9  // Actual Flow-rate ,
10 Qa=Vd*N*(eta_v/100); //m^3/min
11 Qa_lpm=Qa*1000; //Lpm
12 // rounding off the above answer
13 Qa_lpm=fix(Qa_lpm)+(fix(ceil((Qa_lpm-fix(Qa_lpm))
   *10))/10); //m^3/min
14
15 // Results:
16 printf("\n Results: ")
17 printf("\n The volumetric efficiency of Gear Pump
   is %.1f Lpm.",Qa_lpm)
```

---

**Scilab code Exa 5.3.a find eccentricity of vane pump**

```
1 // Aim:To Find eccentricity of Vane Pump
2 // Given:
3 // volumetric displacement of vane pump:
4 Vd=5; //in^3
5 // rotor diameter of vane pump:
6 Dr=2; //in
7 // cam ring diameter of vane pump:
8 Dc=3; //in
9 // width of vane:
10 L=2; //in
```

---

**Scilab code Exa 5.3.b SOLUTION** eccentricity of vane pump

```
1  clc;
2  pathname=get_absolute_file_path('5_3_soln.sce')
3  filename=pathname+filesep()+ '5_3_data.sci '
4  exec(filename)
5
6  // Solutions:
7  // eccentricity for vane pump,
8  e=2*Vd/(%pi*(Dc+Dr)*L); //in
9
10 // Results:
11 printf("\n Results: ")
12 printf("\n The eccentricity of vane pump is %.3f in
    .",e)
```

---

**Scilab code Exa 5.4.a** find volumetric displacement of vane pump

```
1 // Aim:To Find volumetric displacement of Vane Pump
2 // Given:
3 // rotor diameter of vane pump:
4 Dr=50; //mm
5 // cam ring diameter of vane pump:
6 Dc=75; //mm
7 // width of vane:
8 L=50; //mm
9 // eccentricity:
10 e=8; //mm
```

---

**Scilab code Exa 5.4.b SOLUTION** volumetric displacement of vane pump

```
1  clc;
2  pathname=get_absolute_file_path('5_4_soln.sce')
3  filename=pathname+filesep()+ '5_4_data.sci'
4  exec(filename)
5
6  // Solutions:
7  // volumetric displacement of pump,
8  Vd=(%pi*((Dc/1000)+(Dr/1000))*(e/1000)*(L/1000))/2;
   //m^3
9  // since ,1m^3 = 1000L
10 Vd=1000*Vd; //L
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The volumetric displacement of vane pump
   is %.4f L.",Vd)
```

---

**Scilab code Exa 5.5.a** find power pres compensated pump saved

```
1 // Aim:Refer Example 5–5 for Problem Description
2 // Given:
3 // for Fixed Displacement pump:
4 // pump delivery pressure:
5 Pd_f=1000; //psi
6 // pump flow rate:
7 Q_f=20; //gpm
8 // oil leakage after cylinder is fully extended:
9 Ql_f=0.7; //gpm
10 // pressure relief valve setting:
11 p=1200; //psi
12
13 // for Pressure Compensated pump:
14 // pump flow rate:
```

```
15 Q_p=0.7; //gpm
16 // pressure relief valve setting:
17 P=1200; //psi
```

---

**Scilab code Exa 5.5.b** SOLUTION power pres compensated pump saved

```
1 clc;
2 pathname=get_absolute_file_path('5_5_soln.sce')
3 filename=pathname+filesep()+ '5_5_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // Hydraulic Power lost in Fixed Displacemnt pump,
8 HP_f=(p*Q_f)/1714; //HP
9 // Hydraulic Power lost in Pressure Compensated pump
10 HP_p=(P*Q_p)/1714; //HP
11 // Therefore, Hydraulic Power saved,
12 HP=HP_f-HP_p; //HP
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The Hydraulic Power saved after cylinder
    is fully extended is %.2f HP.",HP)
```

---

**Scilab code Exa 5.6.a** find offset angle of piston pump

```
1 // Aim:To Find offset angle of axial piston pump
2 // Given:
3 // pump flow rate:
4 Qa=16; //gpm
5 // speed of pump:
6 N=3000; //rpm
```

```

7 // number of pistons:
8 Y=9;
9 // piston diameter:
10 d=0.5; //in
11 // piston circle diameter:
12 D=5; //in
13 // volumetric efficiency:
14 eta_v=95; //%
```

---

**Scilab code Exa 5.6.b SOLUTION** offset angle of piston pump

```

1 clc;
2 pathname=get_absolute_file_path('5_6_soln.sce')
3 filename=pathname+filesep()+ '5_6_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // Theoretical flow rate ,
8 Qt=Qa/(eta_v/100); //gpm
9 // Area of piston ,
10 A=(%pi/4)*(d^2); //in^2
11 // tan of offset angle ,
12 T_theta=(231*Qt)/(D*A*N*Y);
13 // offset angle ,
14 theta=atand(T_theta); //deg
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The offset angle of axial piston pump is
    %.1f deg.",theta)
```

---

**Scilab code Exa 5.7.a** find flowrate of axial piston pump

```

1 // Aim:To Find flow rate of axial piston pump in L/s
2 // Given:
3 // speed of pump:
4 N=1000; //rpm
5 // number of pistons:
6 Y=9;
7 // piston diameter:
8 d=15; //mm
9 // piston circle diameter:
10 D=125; //mm
11 // offset angle:
12 theta=10; //deg
13 // volumetric efficiency:
14 eta_v=94; //%
```

---

**Scilab code Exa 5.7.b SOLUTION** flowrate of axial piston pump

```

1 clc;
2 pathname=get_absolute_file_path('5_7_soln.sce')
3 filename=pathname+filesep()+ '5_7_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // Area of piston ,
8 A=(%pi/4)*((d/1000)^2); //m^2
9 // offset angle ,
10 theta=(theta*%pi)/180; //rad
11 // Theoretical flow rate ,
12 Qt=(D/1000)*A*N*Y*tan(theta); //m^3/min
13 // Actual flow rate ,
14 Qa=Qt*(eta_v/100); //m^3/min
15 // rounding off the above answer
16 Qa=fix(Qa)+(fix(round((Qa-fix(Qa))*1000))/1000); //m
    ^3/min
17 // Actual flow rate in L/s,
```



```

18 Qa=Qa/(60*0.001); //L/s
19
20 // Results:
21 printf("\n Results: ")
22 printf("\n The flow rate of axial piston pump in L/s
    is %.3f L/s.",Qa)

```

---

**Scilab code Exa 5.8.a** find theoretical torque required by pump

```

1 // Aim:Refer Example 5–8 for Problem Description
2 // Given:
3 // Displacement volume:
4 Vd=5; //in^3
5 // Actual pump flow rate:
6 Qa=20; //gpm
7 // Speed of the pump:
8 N=1000; //rpm
9 // Pressure delivered by pump:
10 p=1000; //psi
11 // Prime mover input torque:
12 Ta=900; //in.lb

```

---

**Scilab code Exa 5.8.b** SOLUTION theoretical torque required by pump

```

1 clc;
2 pathname=get_absolute_file_path('5_8_soln.sce')
3 filename=pathname+filesep()+ '5_8_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // Theoretical pump flow rate ,
8 Qt=(Vd*N)/231; //gpm
9 // rounding off the above answer

```

```

10 Qt=fix(Qt)+(fix(floor((Qt-fix(Qt))*10))/10); //gpm
11 // Therefore, volumetric efficiency,
12 eta_v=(Qa/Qt);
13 // Now, mechanical efficiency,
14 eta_m=((p*Qt)/1714)/((Ta*N)/63000);
15 // overall Efficiency,
16 eta_o=eta_v*eta_m*100; //%
17 // rounding off the above answer
18 eta_o=fix(eta_o)+(fix(floor((eta_o-fix(eta_o))*10))
    /10); //%
19 // Theoretical torque required to operate the pump,
20 Tt=floor(eta_m*Ta); //in.lb
21
22 // Results:
23 printf("\n Results: ")
24 printf("\n The overall efficiency of pump is %.1f
    percent.",eta_o)
25 printf("\n The Theoretical torque required to
    operate the pump is %.0f in.lb.",Tt)

```

---

**Scilab code Exa 5.9.a** find theoretical torque required in SI

```

1 // Aim: Refer Example 5–9 for Problem Description
2 // Given:
3 // Displacement volume:
4 Vd=100; //cm^3
5 // Actual pump flow rate:
6 Qa=0.0015; //m^3/s
7 // Speed of the pump:
8 N=1000; //rpm
9 // Pressure delivered by pump:
10 p=70; //bars
11 // Prime mover input torque:
12 Ta=120; //N.m

```

---

Scilab code Exa 5.9.b SOLUTION theoretical torque required in SI

```
1  clc;
2  pathname=get_absolute_file_path('5_9_soln.sce')
3  filename=pathname+filesep()+ '5_9_data.sci'
4  exec(filename)
5
6  // Solutions:
7  // volumetric displacement in m^3/rev,
8  Vd=100/(10^6); //m^3/rev
9  // Speed of pump in rps,
10 N=N/60; //rps
11 // Theoretical pump flow rate,
12 Qt=Vd*N; //m^3/s
13 // Therefore, volumetric efficiency,
14 eta_v=(Qa/Qt);
15 // Now, mechanical efficiency,
16 eta_m=(p*10^5*Qt)/(Ta*N*2*(%pi));
17 // overall Efficiency,
18 eta_o=eta_v*eta_m*100; //%
19 // rounding off the above answer
20 eta_o=fix(eta_o)+(fix(floor((eta_o-fix(eta_o))*10))
    /10); //%
21 // Theoretical torque required to operate the pump,
22 Tt=ceil(eta_m*Ta); //N.m
23
24 // Results:
25 printf("\n Results: ")
26 printf("\n The overall efficiency of pump is %.1f
    percent.",eta_o)
27 printf("\n The Theoretical torque required to
    operate the pump is %.0f N.m.",Tt)
```

---

Scilab code Exa 5.10.a find yearly cost of electricity

```
1 // Aim: Refer Example 5-10 for Problem Description
2 // Given:
3 // Speed of the pump:
4 N=1000; //rpm
5 // Prime mover input torque:
6 Ta=120; //N.m
7 // overall efficiency:
8 eta_o=85; //%
9 // operation time= 12 hrs/day for 250 days/year:
10 OT=12*250; //hrs/yr
11 // cost of electricity:
12 coe=0.11; //$/kW.hr
13 // overall efficiency for pump:
14 eta_l=83.5; //%
```

---

Scilab code Exa 5.10.b SOLUTION yearly cost of electricity

```
1 clc;
2 pathname=get_absolute_file_path('5_10_soln.sce')
3 filename=pathname+filesep()+ '5_10_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // Pump input power,
8 IP=Ta*N/9550; //kW
9 // Electric motor input power,
10 EIP=IP/(eta_o/100); //kW
11 // rounding off the above answer
12 EIP=fix(EIP)+(fix(round((EIP-fix(EIP))*10))/10); //
    kW
```

```

13 // Yearly cost of electricity ,
14 Yce=EIP*OT*coe; //$/yr
15 // Total kW loss ,
16 kWL=((1-(eta_o/100))*EIP)+((1-(eta_l/100))*IP); //kW
17 // rounding off the above answer
18 kWL=fix(kWL)+(fix(round((kWL-fix(kWL))*10))/10); //
    kW
19 // Yearly cost due to inefficiencies ,
20 Yci=(kWL/EIP)*Yce; //$/yr
21
22 // Results:
23 printf("\n Results: ")
24 printf("\n The yearly cost of electricity is %.0f $/
    yr.",Yce)
25 printf("\n The yearly cost of electricity due to
    inefficiencies is %.0f $/yr.",Yci)

```

---

## Chapter 6

# HYDRAULIC CYLINDERS AND CUSHIONING DEVICES

Scilab code Exa 6.1.a find pressure velocity and horsepower

```
1 // Aim: Refer Example 6-1 for Problem Description
2 // Given:
3 // Flow rate of pump:
4 Q_in=20; //gpm
5 // Bore diameter of Cylinder:
6 D=2; //in
7 // Load during extending and retracting:
8 F_ext=1000; //lb
9 F_ret=1000; //lb
10 // Rod diameter of cylinder:
11 d=1; //in
```

---

Scilab code Exa 6.1.b SOLUTION pressure velocity and horsepower

```

1  clc;
2  pathname=get_absolute_file_path('6_1_soln.sce')
3  filename=pathname+filesep()+'6_1_data.sci'
4  exec(filename)
5
6  // Solution:
7  // Area of blank end of piston ,
8  Ap=(%pi/4)*(D^2); //in^2
9  // Area of rod end of piston ,
10 Ar=(%pi/4)*(d^2); //in^2
11 // hydraulic pressure during the extending stroke ,
12 p_ext=F_ext/Ap; //psi
13 // piston velocity during the extending stroke ,
14 v_ext=(Q_in/449)/(Ap/144); //ft/s
15 // rounding off the above answer
16 v_ext=fix(v_ext)+(fix(ceil((v_ext-fix(v_ext))*100))
    /100); //ft/s
17 // cylinder horsepower during the extending stroke ,
18 HP_ext=(v_ext*F_ext)/550; //HP
19 // rounding off the above answer
20 HP_ext=fix(HP_ext)+(fix(floor((HP_ext-fix(HP_ext))
    *100))/100); //HP
21 // hydraulic pressure during the retraction stroke ,
22 p_ret=ceil(F_ret/(Ap-Ar)); //psi
23 // piston velocity during the retraction stroke ,
24 v_ret=(Q_in/449)/((Ap-Ar)/144); //ft/s;
25 // rounding off the above answer
26 v_ret=fix(v_ret)+(fix(ceil((v_ret-fix(v_ret))*100))
    /100); //ft/s
27 // cylinder horsepower during the retraction stroke ,
28 HP_ret=(v_ret*F_ret)/550; //HP
29
30 // Results:
31 printf("\\n Results: ")
32 printf("\\n The hydraulic pressure during the
    extending stroke is %.0f psi.",p_ext)
33 printf("\\n The piston velocity during the extending
    stroke is %.2f ft/s.",v_ext)

```

```

34 printf("\n The cylinder horsepower during the
    extending stroke is %.2f HP.",HP_ext)
35 printf("\n The hydraulic pressure during the
    retraction stroke is %.0f psi.",p_ret)
36 printf("\n The piston velocity during the retraction
    stroke is %.2f ft/s.",v_ret)
37 printf("\n The cylinder horsepower during the
    retraction stroke is %.2f HP.",HP_ret)

```

---

**Scilab code Exa 6.2.a** find cylinder force to move 6000lb

```

1 // Aim: Refer Example 6–2 for Problem Description
2 // Given:
3 // Weight of Body:
4 W=6000; //lb
5 // coefficient of friction between weight and
    horizontal support:
6 CF=0.14;

```

---

**Scilab code Exa 6.2.b** SOLUTION cylinder force to move 6000lb

```

1 clc;
2 pathname=get_absolute_file_path('6_2_soln.sce')
3 filename=pathname+filesep()+ '6_2_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Cylinder Force ,
8 F=CF*W; //lb
9
10 // Results:
11 printf("\n Results: ")

```



```
12 printf("\n The Cylinder Force at constant velocity
    is %.0f lb.",F)
```

---

**Scilab code Exa 6.3.a** find force to move inclined weight

```
1 // Aim: Refer Example 6-3 for Problem Description
2 // Given:
3 // Weight of Body:
4 W=6000; //lb
5 // Inclination of Weight:
6 theta=30; //deg
```

---

**Scilab code Exa 6.3.b** SOLUTION force to move inclined weight

```
1 clc;
2 pathname=get_absolute_file_path('6_3_soln.sce')
3 filename=pathname+filesep()+ '6_3_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Inclination of Weight,
8 theta=(theta*%pi)/180; //rad
9 // Cylinder Force,
10 F=W*sin(theta); //lb
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The Cylinder Force at constant velocity
    is %.0f lb.",F)
```

---

**Scilab code Exa 6.4.a** find cylinder force to accelerate weight

```
1 // Aim: Refer Example 6-4 for Problem Description
2 // Given:
3 // Weight of Body:
4 W=6000; //lb
5 // initial velocity:
6 u=0; //ft/s
7 // final velocity:
8 v=8; //ft/s
9 // Time taken:
10 t=0.5; //s
```

---

**Scilab code Exa 6.4.b** SOLUTION cylinder force to accelerate weight

```
1 clc;
2 pathname=get_absolute_file_path('6_4_soln.sce')
3 filename=pathname+filesep()+ '6_4_data.sci'
4 exec(filename)
5
6 // Solution:
7 // For constant velocity, Cylinder Force,
8 F=W; //lb
9 // Rate of change of velocity,
10 a=(v-u)/t; //ft/s^2
11 // Force required to accelerate the weight,
12 F_acc=(F/32.2)*a; //lb
13 // Therefore, Cylinder Force,
14 F_cyl=(F+F_acc); //lb
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The Cylinder Force at constant velocity
19 is %.0f lb.",F)
19 printf("\n The Cylinder Force required to accelerate
```

```
    the Body is %.0f lb.",F_cyl)
20 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")
```

---

**Scilab code Exa 6.5.a** find cylinder force using lever system

```
1 // Aim:Refer Example 6–5 for Problem Description
2 // Given:
3 L1=10; //in
4 L2=10; //in
5 // Inclination of cylinder axis with vertical axis:
6 phi=0; //deg
7 // cylinder load:
8 F_load=1000; //lb
```

---

**Scilab code Exa 6.5.b** SOLUTION cylinder force using lever system

```
1 clc;
2 pathname=get_absolute_file_path('6_5_soln.sce')
3 filename=pathname+filesep()+'6_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Inclination of cylinder axis with vertical axis,
8 phi=(phi*%pi)/180; //rad
9 // cylinder force required to overcome load using
    First Class Lever Sytem,
10 F_cyl_1=(L2*F_load)/(L1*cos(phi)); //lb
11 // cylinder force required to overcome load using
    Second Class Lever Sytem,
12 F_cyl_2=(L2*F_load)/((L1+L2)*cos(phi)); //lb
```

```

13 // cylinder force required to overcome load using
    Third Class Lever Sytem,
14 F_cyl_3=((L1+L2)*F_load)/(L2*cos(phi)); //lb
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The Cylinder Force using First Class
    lever System is %.0f lb.",F_cyl_1)
19 printf("\n The Cylinder Force using Second Class
    lever System is %.0f lb.",F_cyl_2)
20 printf("\n The Cylinder Force using Third Class
    lever System is %.0f lb.",F_cyl_3)

```

---

**Scilab code Exa 6.6.a** find maximum pressure developed by cushion

```

1 // Aim: Refer Example 6–6 for Problem Description
2 // Given:
3 // Flow rate of pump:
4 Q_pump=18.2; //gpm
5 // Diameter of blank end of piston:
6 D=3; //in
7 // Diameter of cushion plunger:
8 D_cush=1; //in
9 // Stroke of cushion plunger:
10 L_cush=0.75; //in
11 // Distance Piston decelerates at the end of
    extending stroke:
12 L=0.75; //in
13 // Weight of Body:
14 W=1500; //lb
15 // coefficient of friction:
16 CF=0.12;
17 // Pressure relief valve settings:
18 p_relf=750; //psi
19 // maximum pressure at the Blank end:

```

```
20 p1=750; //psi
```

---

**Scilab code Exa 6.6.b** SOLUTION maximum pressure developed by cushion

```
1 clc;
2 pathname=get_absolute_file_path('6_6_soln.sce')
3 filename=pathname+filesep()+ '6_6_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Area of blank end of piston ,
8 A_piston=(%pi/4)*(D^2); //in^2
9 // piston velocity prior to deceleration ,
10 v=(Q_pump/449)/(A_piston/144); //ft/s
11 // deceleration of piston at the end of extending
    stroke ,
12 a=(v^2)/(2*(L/12)); //ft/s^2
13 // Area of cushion plunger ,
14 A_cush=(%pi/4)*(D_cush^2); //in^2
15 // maximum pressure developed by the cushion ,
16 p2=((W*a)/32.2)+(p1*A_piston)-(CF*W)/(A_piston-
    A_cush); //psi
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The maximum pressure developed by the
    cushion is %.0f psi.",p2)
```

---

# Chapter 7

## HYDRAULIC MOTORS

Scilab code Exa 7.1.a find pressure developed to overcome load

```
1 // Aim:To determine pressure developed to overcome
  load
2 // Given:
3 // outer radius of rotor:
4 R_R=0.5; //in
5 // outer radius of vane:
6 R_V=1.5; //in
7 // width of vane:
8 L=1; //in
9 // Torque Load:
10 T=1000; //in.lb
```

---

Scilab code Exa 7.1.b SOLUTION pressure developed to overcome load

```
1 clc;
2 pathname=get_absolute_file_path('7_1_soln.sce')
3 filename=pathname+filesep()+'7_1_data.sci'
4 exec(filename)
```

```

5
6 // Solution:
7 // volumetric displacement,
8 V_D=%pi*((R_V^2)-(R_R^2))*L; //in^3
9 // pressure developed to overcome load,
10 p=2*%pi*T/V_D; //psi
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The pressure developed to overcome load
    is %.0f psi.",p)

```

---

**Scilab code Exa 7.2.a** determine theoretical horsepower of hydraulic motor

```

1 // Aim:Refer Example 7-2 for Problem Description
2 // Given:
3 // volumetric displacement:
4 V_D=5; //in^3
5 // pressure rating:
6 p=1000; //psi
7 // theoretical flow-rate of pump:
8 Q_T=10; //gpm

```

---

**Scilab code Exa 7.2.b SOLUTION** theoretical horsepower of hydraulic motor

```

1 clc;
2 pathname=get_absolute_file_path('7_2_soln.sce')
3 filename=pathname+filesep()+'7_2_data.sci'
4 exec(filename)
5
6 // Solution:

```

```

7 // motor speed ,
8 N=231*Q_T/V_D; //rpm
9 // Theoretical torque ,
10 T_T=floor(V_D*p/(2*pi)); //in.lb
11 // Theoretical horsepower ,
12 HP_T=T_T*N/63000; //HP
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The motor Speed is %.0f rpm.",N)
17 printf("\n The motor Theoretical torque is %.0f in.
    lb.",T_T)
18 printf("\n The motor Theoretical horsepower is %.2f
    HP.",HP_T)

```

---

**Scilab code Exa 7.3.a** find actual horsepower delivered by motor

```

1 // Aim:Refer Example 7-3 for Problem Description
2 // Given:
3 // volumetric displacement:
4 V_D=10; //in^3
5 // pressure rating:
6 p=1000; //psi
7 // speed of motor:
8 N=2000; //rpm
9 // actual flow-rate of motor:
10 Q_A=95; //gpm
11 // actual torque delivered by motor:
12 T_A=1500; //in.lb

```

---

**Scilab code Exa 7.3.b SOLUTION** actual horsepower delivered by motor

```

1 clc;

```



```

2 pathname=get_absolute_file_path('7_3_soln.sce')
3 filename=pathname+filesep()+ '7_3_data.sci'
4 exec(filename)
5
6 // Solution:
7 // theoretical flow-rate,
8 Q_T=V_D*N/231; //gpm
9 // volumetric efficiency,
10 eta_v=(Q_T/Q_A)*100; //%
11 // theoretical torque,
12 T_T=(V_D*p/(2*pi)); //in.lb
13 // mechanical efficiency,
14 eta_m=(T_A/T_T)*100; //%
15 // overall efficiency,
16 eta_o=(eta_v/100)*(eta_m/100)*100; //%
17 eta_o=fix(eta_o)+(fix(floor((eta_o-fix(eta_o))*10))
    /10); //%, rounding off the answer
18 // actual horsepower delivered by motor,
19 HP_A=T_A*N/63000; //HP
20
21 // Results:
22 printf("\n Results: ")
23 printf("\n The volumetric efficiency is %.1f percent
    .",eta_v)
24 printf("\n The mechanical efficiency is %.1f percent
    .",eta_m)
25 printf("\n The overall efficiency is %.1f percent.",
    eta_o)
26 printf("\n The actual horsepower delivered by the
    motor is %.1f HP.",HP_A)

```

---

**Scilab code Exa 7.4.a** find motor displacement and output torque

```

1 // Aim: Refer Example 7-4 for Problem Description
2 // Given:

```

```

3 // operating pressure:
4 p=1000; //psi
5 // volumetric displacement of pump:
6 V_D_pump=5; //in^3
7 // speed of pump:
8 N_pump=500; //rpm
9 // volumetric efficiency of pump:
10 eta_v_pump=82; //%
11 // mechanical efficiency of pump:
12 eta_m_pump=88; //%
13 // speed of motor:
14 N_motor=400; //rpm
15 // volumetric efficiency of motor:
16 eta_v_motor=92; //%
17 // mechanical efficiency of motor:
18 eta_m_motor=90; //%

```

---

**Scilab code Exa 7.4.b SOLUTION** motor displacement and output torque

```

1 clc;
2 pathname=get_absolute_file_path('7_4_soln.sce')
3 filename=pathname+filesep()+'7_4_data.sci'
4 exec(filename)
5
6 // Solution:
7 // pump theoretical flow-rate,
8 Q_T_pump=V_D_pump*N_pump/231; //gpm
9 // pump actual flow rate,
10 Q_A_pump=Q_T_pump*(eta_v_pump/100); //gpm
11 // motor theoretical flow-rate,
12 Q_T_motor=Q_A_pump*(eta_v_motor/100); //gpm ,motor
    actual flow-rate = pump actual flow rate
13 // motor displacement,
14 V_D_motor=Q_T_motor*231/N_motor; //in^3
15 // hydraulic HP delivered to motor,

```

```

16 HHP_motor=p*Q_A_pump/1714; //HP
17 // brake HP delivered by motor,
18 BHP_motor=HHP_motor*(eta_v_motor/100)*(eta_m_motor
    /100); //HP
19 BHP_motor=fix(BHP_motor)+(fix(floor((BHP_motor-fix(
    BHP_motor))*100))/100); //HP ,rounding off the
    answer
20 // torque delivered by motor,
21 T_motor=(BHP_motor*63000/N_motor); //in.lb
22
23 // Results:
24 printf("\n Results: ")
25 printf("\n The Displacement of motor is %.2f in^3.",
    V_D_motor)
26 printf("\n The Motor output torque is %.0f in.lb.",
    T_motor)

```

---

**Scilab code Exa 7.5.a** find motor theoretical power in SI

```

1 // Aim:Refer Example 7–5 for Problem Description
2 // Given:
3 // volumetric displacement:
4 V_D=0.082; //L
5 // pressure rating:
6 p=70; //bar
7 // theoretical flow–rate of pump:
8 Q_T=0.0006; //m^3/s

```

---

**Scilab code Exa 7.5.b** SOLUTION motor theoretical power in SI

```

1 clc;
2 pathname=get_absolute_file_path('7_5_soln.sce')
3 filename=pathname+filesep()+ '7_5_data.sci'

```

```

4  exec(filename)
5
6  // Solution:
7  // motor speed,
8  N=(Q_T*60)/(V_D*10^-3); //rpm
9  // Theoretical torque,
10 T_T=((V_D*10^-3)*(p*10^5))/(2*pi); //Nm
11 // Theoretical power,
12 HP_T=T_T*N*2*pi/(60*1000); //kW
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The motor Speed is %.0f rpm.",N)
17 printf("\n The motor Theoretical torque is %.1f Nm.",
18        ,T_T)
18 printf("\n The motor Theoretical power is %.2f kW.",
19        HP_T)

```

---

**Scilab code Exa 7.6.a** find actual KW delivered by motor

```

1  // Aim: Refer Example 7-6 for Problem Description
2  // Given:
3  // volumetric displacement:
4  V_D=164; //cm^3
5  // pressure rating:
6  p=70; //bar
7  // speed of motor:
8  N=2000; //rpm
9  // actual flow-rate of motor:
10 Q_A=0.006; //m^3/s
11 // actual torque delivered by motor:
12 T_A=170; //Nm

```

---

Scilab code Exa 7.6.b SOLUTION actual KW delivered by motor

```
1  clc;
2  pathname=get_absolute_file_path('7_6_soln.sce')
3  filename=pathname+filesep()+ '7_6_data.sci'
4  exec(filename)
5
6  // Solution:
7  // theoretical flow-rate,
8  Q_T=(V_D*10^-6)*(N/60); //m^3/s
9  Q_T=fix(Q_T)+(fix(ceil((Q_T-fix(Q_T))*10^5))/10^5);
   //m^3/s ,rounding off the answer
10 // volumetric efficiency,
11 eta_v=(Q_T/Q_A)*100; //%
12 // theoretical torque,
13 T_T=((V_D*10^-6)*(p*10^5))/(2*pi); //Nm
14 // mechanical efficiency,
15 eta_m=(T_A/T_T)*100; //%
16 // overall efficiency,
17 eta_o=(eta_v/100)*(eta_m/100)*100; //%
18 eta_o=fix(eta_o)+(fix(floor((eta_o-fix(eta_o))*10))
   /10); //%,rounding off the answer
19 // actual horsepower delivered by motor,
20 HP_A=(T_A*N*2*pi)/(60*1000); //kW
21
22 // Results:
23 printf("\n Results: ")
24 printf("\n The volumetric efficiency is %.1f percent
   .",eta_v)
25 printf("\n The mechanical efficiency is %.1f percent
   .",eta_m)
26 printf("\n The overall efficiency is %.1f percent.",
   eta_o)
27 printf("\n The actual horsepower delivered by the
   motor is %.1f kW.",HP_A)
```

---

Scilab code Exa 7.7.a find motor output torque in SI

```
1 // Aim:Refer Example 7-7 for Problem Description
2 // Given:
3 // operating pressure:
4 p=70; //bar
5 // volumetric displacement of pump:
6 V_D_pump=82; //cm^3
7 // speed of pump:
8 N_pump=500; //rpm
9 // volumetric efficiency of pump:
10 eta_v_pump=82; //%
11 // mechanical efficiency of pump:
12 eta_m_pump=88; //%
13 // speed of motor:
14 N_motor=400; //rpm
15 // volumetric efficiency of motor:
16 eta_v_motor=92; //%
17 // mechanical efficiency of motor:
18 eta_m_motor=90; //%
```

---

Scilab code Exa 7.7.b SOLUTION motor output torque in SI

```
1 clc;
2 pathname=get_absolute_file_path('7_7_soln.sce')
3 filename=pathname+filesep()+ '7_7_data.sci'
4 exec(filename)
5
6 // Solution:
7 // pump theoretical flow-rate,
8 Q_T_pump=(V_D_pump*10^-6)*(N_pump/60); //m^3/s
9 // pump actual flow rate,
```

```

10 Q_A_pump=Q_T_pump*(eta_v_pump/100); //m^3/s
11 // motor theoretical flow-rate,
12 Q_T_motor=Q_A_pump*(eta_v_motor/100); //m^3/s ,motor
    actual flow-rate = pump actual-flow rate
13 // motor displacement,
14 V_D_motor=(Q_T_motor/(N_motor/60))*10^6; //cm^3
15 // hydraulic HP delivered to motor,
16 HHP_motor=(p*10^5)*Q_A_pump; //W
17 // brake HP delivered by motor,
18 BHP_motor=HHP_motor*(eta_v_motor/100)*(eta_m_motor
    /100); //W
19 BHP_motor=fix(BHP_motor)+(fix(floor((BHP_motor-fix(
    BHP_motor))*100))/100); //W ,rounding off the
    answer
20 // torque delivered by motor,
21 T_motor=(BHP_motor/N_motor)*(60/(2*pi)); //Nm
22
23 // Results:
24 printf("\n Results: ")
25 printf("\n The Displacement of motor is %.1f cm^3.",
    V_D_motor)
26 printf("\n The Motor output torque is %.1f Nm.",
    T_motor)

```

---

# Chapter 8

## HYDRAULIC VALVES

Scilab code Exa 8.1.a determine cracking and full flow pressure

```
1 // Aim: Refer Example 8-1 for Problem Description
2 // Given:
3 // area of relief valve:
4 A=0.75; //in^2
5 // spring constant:
6 k=2500; //lb/in
7 // initial compressed length of spring:
8 S=0.20; //in
9 // poppet displacement to pass full pump flow:
10 L=0.10; //in
```

---

Scilab code Exa 8.1.b SOLUTION cracking and full flow pressure

```
1 clc;
2 pathname=get_absolute_file_path('8_1_soln.sce')
3 filename=pathname+filesep()+ '8_1_data.sci'
4 exec(filename)
5
```



```

6 // Solution:
7 // spring force exerted on poppet when it is fully
  closed,
8 F=k*S; //lb
9 // Cracking pressure,
10 p_crack=F/A; //psi
11 // spring force when poppet moves 0.10 in from its
  fully closed position,
12 F_new=k*(L+S); //lb
13 // Full pump flow pressure,
14 p_ful_pump_flow=F_new/A; //psi
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The Cracking pressure is %.0f psi.",
  p_crack)
19 printf("\n The Full pump flow pressure is %.0f psi.
  ",p_ful_pump_flow)

```

---

**Scilab code Exa 8.2.a** compute horsepower across pressure relief valve

```

1 // Aim:To compute horsepower across the pressure
  relief valve
2 // Given:
3 // pressure relief valve setting:
4 p=1000; //psi
5 // pump flow to the tank:
6 Q=20; //gpm

```

---

**Scilab code Exa 8.2.b** SOLUTION horsepower across pressure relief valve

```

1 clc;
2 pathname=get_absolute_file_path('8_2_soln.sce')

```

```

3 filename=pathname+filesep()+ '8_2_data.sci '
4 exec(filename)
5
6 // Solution:
7 // Horsepower across the valve ,
8 HP=((p*Q)/1714); //HP
9
10 // Results:
11 printf("\n Results: ")
12 printf("\n The Horsepower across the pressure relief
    valve is %.1f HP.",HP)

```

---

**Scilab code Exa 8.3.a** compute horsepower across unloading valve

```

1 // Aim:To compute horsepower across the unloading
    valve
2 // Given:
3 // pump pressure during unloading:
4 p=25; //psi
5 // pump flow to the tank:
6 Q=20; //gpm

```

---

**Scilab code Exa 8.3.b** SOLUTION horsepower across unloading valve

```

1 clc;
2 pathname=get_absolute_file_path('8_3_soln.sce')
3 filename=pathname+filesep()+ '8_3_data.sci '
4 exec(filename)
5
6 // Solution:
7 // Horsepower across the valve ,
8 HP=((p*Q)/1714); //HP
9

```

```

10 // Results:
11 printf("\n Results: ")
12 printf("\n The Horsepower across the unloading valve
    is %.2f HP.",HP)

```

---

**Scilab code Exa 8.4.a** find flow rate through the orifice

```

1 // Aim:To find flow-rate through given orifice
2 // Given:
3 // pressure drop across orifice:
4 del_p=100; //psi
5 // orifice diameter:
6 D=1; //in
7 // specific gravity of oil:
8 SG_oil=0.9;
9 // flow coefficient for sharp edge orifice:
10 C=0.80;

```

---

**Scilab code Exa 8.4.b** SOLUTION flow rate through the orifice

```

1 clc;
2 pathname=get_absolute_file_path('8_4_soln.sce')
3 filename=pathname+filesep()+ '8_4_data.sci '
4 exec(filename)
5
6 // Solution:
7 // flow-rate through orifice ,
8 Q=38.1*C*((%pi*(D^2))/4)*sqrt(del_p/SG_oil); //gpm
9
10 // Results:
11 printf("\n Results: ")
12 printf("\n The flow-rate through orifice is %.0f gpm
    .",Q)

```

---

**Scilab code Exa 8.5.a** determine capacity coefficient of flowcontrol valve

```
1 // Aim:To determine the capacity coefficient of flow
   control valve
2 // Given:
3 // pressure drop across flow control valve:
4 del_p=100; //psi
5 del_p1=687; //kPa
6 // flow-rate across valve:
7 Q=25; //gpm
8 Q1=94.8; //Lpm
9 // specific gravity of oil:
10 SG_oil=0.9;
```

---

**Scilab code Exa 8.5.b** SOLUTION capacity coefficient of flowcontrol valve

```
1 clc;
2 pathname=get_absolute_file_path('8_5_soln.sce')
3 filename=pathname+filesep()+ '8_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // capacity coefficient in English Units,
8 Cv=Q/sqrt(del_p/SG_oil); //gpm/sqrt(psi)
9 // capacity coefficient in Metric Units,
10 Cv1=Q1/sqrt(del_p1/SG_oil); //Lpm/sqrt(kPA)
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The capacity coefficient in English unit
   is %.2f gpm/sqrt(psi).",Cv)
```

```
15 printf("\n The capacity coefficient in Metric unit
    is %.2f Lpm/sqrt(kPa).", Cv1)
```

---

**Scilab code Exa 8.6.a** determine capacity coefficient of needle valve

```
1 // Aim:To determine the capacity coefficient of
    needle valve
2 // Given:
3 // Desired cylinder speed:
4 v2=10; //in/s
5 // Cylinder piston area:
6 A1=3.14; //in^2
7 // Cylinder rod area:
8 Ar=0.79; //in^2
9 // Cylinder load:
10 F_load=1000; //lb
11 // Specific gravity of oil:
12 SG_oil=0.9;
13 // Pressure relief valve setting:
14 p1=500; //psi
```

---

**Scilab code Exa 8.6.b SOLUTION** capacity coefficient of needle valve

```
1 clc;
2 pathname=get_absolute_file_path('8_6_soln.sce')
3 filename=pathname+filesep()+'8_6_data.sci'
4 exec(filename)
5
6 // Solution:
7 // annular area of cylinder ,
8 A2=A1-Ar; //in^2
9 // back pressure in the rod end,
10 p2=((p1*A1)-F_load)/A2; //psi
```

```
11 // flow rate through needle valve based on desired
    cylinder speed ,
12 Q=(A2*v2*60)/231; //gpm
13 // capacity coefficient of needle valve ,
14 Cv=Q/sqrt(p2/SG_oil); //gpm/sqrt(psi)
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The capacity coefficient of needle valve
    is %.2f gpm/sqrt(psi).",Cv)
```

---

## Chapter 9

# HYDRAULIC CIRCUIT DESIGN AND ANALYSIS

Scilab code Exa 9.1.a determine speed power for regenerative circuit

```
1 // Aim: Refer Example 9–1 for Problem Description
2 // Given:
3 // cracking pressure of relief valve:
4 p=1000; //psi
5 // piston area:
6 Ap=25; //in^2
7 // rod area:
8 Ar=7; //in^2
9 // pump flow:
10 Qp=20; //gpm
```

---

Scilab code Exa 9.1.b SOLUTION speed power for regenerative circuit

```
1 clc;
2 pathname=get_absolute_file_path('9_1_soln.sce')
3 filename=pathname+filesep()+ '9_1_data.sci'
```

```

4  exec(filename)
5
6  // Solution:
7  // cylinder speed during extending stroke ,
8  vp_ext=(Qp*231)/(Ar*60); //in/s
9  // load carrying capacity during extending stroke ,
10 Fload_ext=p*Ar; //lb
11 // power delivered to load during extending stroke ,
12 Power_ext=(Fload_ext*vp_ext)/(550*12); //HP
13 // cylinder speed during retracting stroke ,
14 vp_ret=(Qp*231)/((Ap-Ar)*60); //in/s
15 // load carrying capacity during retracting stroke ,
16 Fload_ret=p*(Ap-Ar); //lb
17 // power delivered to load during retracting stroke ,
18 Power_ret=(Fload_ext*vp_ext)/(550*12); //HP
19
20 // Results:
21 printf("\n Results: ")
22 printf("\n The cylinder speed during extending
    stroke is %.1f in/s.",vp_ext)
23 printf("\n The load carrying capacity during
    extending stroke is %.0f lb.",Fload_ext)
24 printf("\n The power delivered to load during
    extending stroke is %.1f HP.",Power_ext)
25 printf("\n The cylinder speed during retracting
    stroke is %.2f in/s.",vp_ret)
26 printf("\n The load carrying capacity during
    retracting stroke is %.0f lb.",Fload_ret)
27 printf("\n The power delivered to load during
    retracting stroke is %.1f HP.",Power_ret)

```

---

**Scilab code Exa 9.2.a** find unloading relief valve pressure settings

```

1 // Aim: Refer Example 9–2 for Problem Description
2 // Given:

```



```

3 // force required for sheet metal punching
  operations:
4 F_load=2000; //lb
5 // piston diameter:
6 Dp=1.5; //in
7 // rod diameter:
8 Dr=0.5; //in
9 // frictional pressure loss in line from high-flow
  pump to blank end during rapid extension:
10 p_loss1=100; //psi
11 // frictional pressure loss in return line from rod
  end to oil tank during rapid extension:
12 p_loss2=50; //psi

```

---

Scilab code Exa 9.2.b SOLUTION unloading relief valve pressure settings

```

1 clc;
2 pathname=get_absolute_file_path('9_2_soln.sce')
3 filename=pathname+filesep()+ '9_2_data.sci'
4 exec(filename)
5
6 // Solution:
7 // Unloading Valve:
8 // load due to back pressure force on cylinder ,
9 F_back_pressure=(p_loss2*%pi*((Dp^2)-(Dr^2)))/4; //
  psi
10 // back pressure force on cylinder ,
11 P_cyl_blank_end=F_back_pressure/((%pi*(Dp^2))/4); //
  psi
12 // pressure setting of the unloading valve ,
13 p_unload=1.5*(P_cyl_blank_end+p_loss1); //psi
14
15 // Pressure Relief Valve:
16 // pressure to overcome punching operations ,
17 P_punching=F_load/((%pi*(Dp^2))/4); //psi

```

```

18 // pressure setting of the pressure relief valve ,
19 p_prv=1.5*P_punching; //psi
20
21 // Results:
22 printf("\n Results: ")
23 printf("\n The pressure setting of unloading valve
    is %.0f psi.",p_unload)
24 printf("\n The pressure setting of pressure relief
    valve is %.0f psi.",p_prv)

```

---

**Scilab code Exa 9.3.a** find spring constant of PRV valve

```

1 // Aim:Refer Example 9–3 for Problem Description
2 // Given:
3 // poppet area:
4 A_poppet=0.75; //in^2
5 // hydraulic pressure:
6 p_hydraulic=1698; //psi
7 // full poppet stroke:
8 l_stroke=0.10; //in
9 // cracking pressure:
10 p_cracking=1.1*1132; //psi

```

---

**Scilab code Exa 9.3.b** SOLUTION spring constant of PRV valve

```

1 clc;
2 pathname=get_absolute_file_path('9_3_soln.sce')
3 filename=pathname+filesep()+'9_3_data.sci'
4 exec(filename)
5
6 // Solution:
7 // spring force at full pump flow pressure ,
8 F_spr_full=round(p_hydraulic*A_poppet); //lb

```

```

 9 // spring force at cracking pressure ,
10 F_spr_crack=round(p_cracking*A_poppet); //lb
11 // spring constant of compression spring ,
12 k=(F_spr_full-F_spr_crack)/l_stroke; //lb/in
13 // initial compression of spring ,
14 l=F_spr_crack/k; //in
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The spring constant of compression spring
    is %.0f lb/in.",k)
19 printf("\n The initial compression of spring is %.3f
    in.",l)

```

---

**Scilab code Exa 9.4.a** determine cylinder speed of meterin circuit

```

1 // Aim:To determine cylinder speed for given meter-
    in circuit
2 // Given:
3 // valve capacity coefficient:
4 Cv=1.0; //gpm/sqrt(psi)
5 // cylinder piston diameter and area:
6 D=2; //in
7 A_piston=3.14; //in^2
8 // cylinder load:
9 F_load=4000; //lb
10 // specific gravity of oil:
11 SG=0.9;
12 // pressure relief valve setting:
13 p_PRV=1400; //psi

```

---

**Scilab code Exa 9.4.b** SOLUTION cylinder speed of meterin circuit

```

1  clc;
2  pathname=get_absolute_file_path('9_4_soln.sce')
3  filename=pathname+filesep()+ '9_4_data.sci '
4  exec(filename)
5
6  // Solution:
7  // flow-rate through valve ,
8  Q=Cv*sqrt((p_PRV-(F_load/A_piston))/SG); //gpm
9  // flow-rate through valve in in^3/s,
10 Q=(Q*231)/60; //in^3/s
11 // cylinder speed,
12 v_cyl=Q/A_piston; //in/s
13
14 // Results:
15 printf("\\n Results: ")
16 printf("\\n The cylinder speed is %.1f in/s.",v_cyl)

```

---

**Scilab code Exa 9.5.a** find overall efficiency of given system

```

1  // Aim:Refer Example 9-5 for Problem Description
2  // Given:
3  // Pump:
4  // mechanical efficiency:
5  eff_m_pump=92; //%
6  // volumetric efficiency:
7  eff_v_pump=94; //%
8  // volumetric displacement:
9  V_D_pump=10; //in^3
10 // speed of pump:
11 Np=1000; //rpm
12 // inlet pressure:
13 pi=-4; //psi
14
15 // Hydraulic Motor:
16 // mechanical efficiency:

```

```

17 eff_m_motor=92; %%
18 // volumetric efficiency:
19 eff_v_motor=90; %%
20 // volumetric displacement:
21 V_D_motor=8; //in^3
22 // inlet pressure required to drive load:
23 p2=500; //psi
24 // motor discharge pressure:
25 po=5; //psi
26
27 // Pipe and Fittings:
28 // inside diameter of pipe:
29 D=1.040; //in
30 // Length of pipe between station 1 and 2:
31 L_pipe=50; //ft
32 // K factor of standard 90 deg elbow:
33 K_elbow=0.75;
34 // K factor of check valve:
35 K_check=4.0;
36
37 // Oil:
38 // kinematic viscosity of oil:
39 nu=125; //cS
40 // specific gravity of oil:
41 SG=0.9;

```

---

**Scilab code Exa 9.5.b SOLUTION** overall efficiency of given system

```

1 clc;
2 pathname=get_absolute_file_path('9_5_soln.sce')
3 filename=pathname+filesep()+ '9_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // acceleration due to gravity,

```

```

8 g=32.2; //ft/s^2
9 // pump's theoretical flow-rate,
10 Q_T_pump=(V_D_pump*Np)/231; //gpm
11 // pump's actual flow-rate,
12 Q_A_pump=(Q_T_pump*eff_v_pump)/100; //gpm
13 // velocity of oil,
14 v=((Q_A_pump)/449)/((%pi*((D/12)^2))/4); //ft/s
15 // Reynolds number,
16 N_R=(7740*v*D)/nu;
17 // friction factor,
18 f=64/N_R;
19 // equivalent length of 90 deg standard elbow,
20 Le_elbow=(K_elbow*(D/12))/f; //ft
21 // equivalent length of check valve,
22 Le_check_valve=(K_check*(D/12))/f; //ft
23 // total length of pipe,
24 LeTOT=L_pipe+(2*Le_elbow)+Le_check_valve; //ft
25 // head loss due to friction,
26 H_L=(f*LeTOT*(v^2))/(2*g*(D/12)); //ft
27 // head developed due to hydraulic motor and pump,
28 Hp=0; //ft
29 Hm=0; //ft
30 // height difference between station 1 and station
    2,
31 Z=20; //ft
32 // pump discharge pressure,
33 p1=((Z+H_L+Hm+Hp)*SG*62.4)/144+p2; //psi
34 // input HP required to drive pump,
35 HP_pump=((p1-pi)*Q_A_pump)/(1714*(eff_m_pump/100)*(
    eff_v_pump/100)); //Hp
36 // motor theoretical power,
37 Q_T_motor=Q_A_pump*(eff_v_motor/100); //gpm
38 // speed of motor,
39 N_motor=floor((Q_T_motor*231)/V_D_motor); //rpm
40 // motor input horsepower,
41 HP_input_motor=((p2-po)*Q_A_pump)/1714; //HP
42 // rounding off the above answer
43 HP_input_motor=fix(HP_input_motor)+(fix(ceil((

```

```

        HP_input_motor-fix(HP_input_motor)*10))/10); //
    HP
44 // motor output horsepower ,
45 HP_output_motor=(HP_input_motor*(eff_m_motor/100)*(
    eff_v_motor/100)); //HP
46 // motor output torque ,
47 T_output_motor=(HP_output_motor*63000)/N_motor; //in
    .lb
48 // overall efficiency of system ,
49 eff_overall=(HP_output_motor/HP_pump)*100; //%
50 // rounding off the above answer
51 eff_overall=fix(eff_overall)+(fix(ceil((eff_overall-
    fix(eff_overall))*10))/10); //%
52
53 // Results:
54 printf("\n Results: ")
55 printf("\n The Pump flow-rate is %.1f gpm.",Q_A_pump
    )
56 printf("\n The Pump discharge pressure is %.0f psi."
    ,p1)
57 printf("\n The Input HP required to drive the pump
    is %.1f HP.",HP_pump)
58 printf("\n The Motor Speed is %.0f rpm.",N_motor)
59 printf("\n The Motor output torque is %.0f in.lb.",
    T_output_motor)
60 printf("\n The Overall efficiency of system is %.1f
    percent.",eff_overall)

```

---

## Chapter 10

# HYDRAULIC CONDUCTORS AND FITTINGS

Scilab code Exa 10.1.a find minimum inside diameter of pipe

```
1 // Aim:To find minimum inside diameter of pipe
2 // Given:
3 // flow-rate through pipe:
4 Q=30; //gpm
5 // average fluid velocity:
6 v=20; //ft/s
```

---

Scilab code Exa 10.1.b SOLUTION minimum inside diameter of pipe

```
1 clc;
2 pathname=get_absolute_file_path('10_1_soln.sce')
3 filename=pathname+filesep()+ '10_1_data.sci '
4 exec(filename)
5
6 // Solution:
7 // flow-rate in ft3/s,
```



```

8 Q_fps=Q/449; //ft^3/s
9 // minimum required pipe flow area ,
10 A=(Q_fps/v)*144; //in^2
11 // minimum inside diameter ,
12 D=sqrt((4*A)/(%pi)); //in
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The minimum inside diameter of pipe is %
    .3f in.",D)

```

---

**Scilab code Exa 10.2.a** find minimum inside diameter in SI

```

1 // Aim:To find minimum inside diameter of pipe in
    Metric units
2 // Given:
3 // flow-rate through pipe:
4 Q=0.002; //m^3/s
5 // average fluid velocity:
6 v=6.1; //m/s

```

---

**Scilab code Exa 10.2.b SOLUTION** minimum inside diameter in SI

```

1 clc;
2 pathname=get_absolute_file_path('10_2_soln.sce')
3 filename=pathname+filesep()+ '10_2_data.sci'
4 exec(filename)
5
6 // Solution:
7 // minimum required pipe flow area ,
8 A=(Q/v); //m^2
9 // minimum inside diameter ,
10 D=sqrt((4*A)/(%pi))*1000; //mm

```

```

11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The minimum inside diameter of pipe is %
    .1 f mm.",D)

```

---

**Scilab code Exa 10.3.a** find safe working pressure of tube

```

1 // Aim:To find safe working pressure for the tube
2 // Given:
3 // outside diameter of steel tube:
4 Do=1.250; //in
5 // inside diameter of steel tube:
6 Di=1.060; //in
7 // tensile strength of steel tube:
8 S=55000; //psi
9 // factor of safety:
10 FS=8;

```

---

**Scilab code Exa 10.3.b SOLUTION** safe working pressure of tube

```

1 clc;
2 pathname=get_absolute_file_path('10_3_soln.sce')
3 filename=pathname+filesep()+ '10_3_data.sci'
4 exec(filename)
5
6 // Solution:
7 // wall thickness ,
8 t=(Do-Di)/2; //in
9 // burst pressure ,
10 BP=(2*t*S)/Di; //psi
11 // working pressure ,
12 WP=BP/FS; //psi

```

```

13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The working pressure of steel tube is %.0
    f psi.",WP)
17 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")

```

---

**Scilab code Exa 10.4.a** select proper size steel tube

```

1 // Aim: Refer Example 10-4 for Problem Description
2 // Given:
3 // flow-rate:
4 Q=30; //gpm
5 // operating pressure:
6 p=1000; //psi
7 // maximum velocity:
8 v=20; //ft/s
9 // tensile strength of material:
10 S=55000; //psi
11 // factor of safety:
12 FS=8;

```

---

**Scilab code Exa 10.4.b** SOLUTION proper size steel tube

```

1 clc;
2 pathname=get_absolute_file_path('10_4_soln.sce')
3 filename=pathname+filesep()+ '10_4_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // flow-rate,

```

```

 8 Q=Q/449; //ft^3/s
 9 // minimum required pipe flow area ,
10 Ai=(Q/v)*144; //in^2
11 // minimum inside diameter ,
12 Di=sqrt((4*Ai)/(%pi)); //in
13 // wall thickness ,
14 t1=0.049; t2=0.065; //in
15 // tube inside diameter ,
16 D1=0.902; D2=0.870; //in
17 // burst pressure ,
18 BP1=(2*t1*S)/D1; //psi
19 // working pressure ,
20 WP1=BP1/FS; //psi
21 printf(" \n The working pressure %.0f psi is not
        adequate (less than %.0f psi) so next case is
        considered ,",WP1,p)
22 // burst pressure ,
23 BP2=(2*t2*S)/D2; //psi
24 // working pressure ,
25 WP2=BP2/FS; //psi
26 // ratio of inner diameter to thickness ,
27 r2=D2/t2;
28 printf(" \n The working pressure %.0f psi is greater
        than %.0f psi) ,",WP2,p)
29
30 // Results:
31 printf("\n Results: ")
32 printf("\n The ratio of inner diameter to length is
        %.1f.",r2)
33 printf("\n The answer in the program is different
        than that in textbook. It may be due to no.s of
        significant digit in data and calculation")

```

---

Scilab code Exa 10.5.a select proper size steel tube SI

```

1 // Aim:Refer Example 10-5 for Problem Description
2 // Given:
3 // flow-rate:
4 Q=0.00190; //m^3/s
5 // operating pressure:
6 p=70; //bars
7 // maximum velocity:
8 v=6.1; //m/s
9 // tensile strength of material:
10 S=379; //MPa
11 // factor of safety:
12 FS=8;

```

---

**Scilab code Exa 10.5.b SOLUTION** proper size steel tube SI

```

1 clc;
2 pathname=get_absolute_file_path('10_5_soln.sce')
3 filename=pathname+filesep()+ '10_5_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // minimum required pipe flow area ,
8 A=(Q/v); //m^2
9 // minimum inside diameter ,
10 ID=sqrt((4*A)/(%pi))*1000; //mm
11 // wall thickness ,
12 t1=1; t2=2; //mm
13 // tube inside diameter ,
14 D1=20; D2=24; //mm
15 // burst pressure ,
16 BP1=(2*(t1/1000)*S)/(D1/1000); //MPa
17 // working pressure ,
18 WP1=(BP1/FS)*10; //bars
19 printf(" \n The working pressure %.0f bars is not
        adequate (less than %.0f bars) so next case is

```

```

        considered ,",WP1,p)
20 // burst pressure ,
21 BP2=(2*(t2/1000)*S)/(D2/1000); //MPa
22 // working pressure ,
23 WP2=(BP2/FS)*10;; //MPa
24 // ratio of inner diameter to thickness ,
25 r2=D2/t2;
26 printf(" \n The working pressure %.0f bars is
        greater than %.0f bars) ,",WP2,p)
27
28
29 // Results:
30 printf("\n Results: ")
31 printf("\n The ratio of inner diameter to length is
        %.1f.",r2)

```

---

# Chapter 11

## ANCILLARY HYDRAULIC DEVICES

Scilab code Exa 11.1.a find the discharge flow and pressure

```
1 // Aim:To find the discharge flow and pressure
2 // Given:
3 // high inlet flow-rate:
4 Q_high_inlet=20; //gpm
5 // low inlet pressure:
6 p_low_inlet=500; //psi
7 // Ratio of piston area to rod area:
8 Ratio=5/1;
```

---

Scilab code Exa 11.1.b SOLUTION the discharge flow and pressure

```
1 clc;
2 pathname=get_absolute_file_path('11_1_soln.sce')
3 filename=pathname+filesep()+ '11_1_data.sci '
4 exec(filename)
5
```

```

6 // Solution:
7 // high discharge pressure ,
8 p_high_discharge=Ratio*p_low_inlet; //psi
9 // low discharge flow-rate ,
10 Q_low_discharge=Q_high_inlet/Ratio; //gpm
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The high discharge pressure is %.0f psi."
        ,p_high_discharge)
15 printf("\n The low discharge flow-rate is %.0f gpm."
        ,Q_low_discharge)

```

---

**Scilab code Exa 11.2.a** determine the downstream oil temperature

```

1 // Aim:To find the downstream oil temperature
2 // Given:
3 // temperature of oil flowing through pressure
  relief valve:
4 T_oil=120; //deg F
5 // pressure of oil flowing through pressure relief
  valve:
6 p=1000; //psi
7 // oil flow through pressure relief valve:
8 Q_gpm=10; //gpm

```

---

**Scilab code Exa 11.2.b SOLUTION** the downstream oil temperature

```

1 clc;
2 pathname=get_absolute_file_path('11_2_soln.sce')
3 filename=pathname+filesep()+ '11_2_data.sci'
4 exec(filename)
5

```



```

6 // Solution:
7 // heat generation rate,
8 HP=(p*Q_gpm)/1714; //HP
9 // heat generation rate in Btu/min,
10 HP_btu=HP*42.4; //Btu/min
11 // oil flow-rate in lb/min,
12 Q_lb=7.42*Q_gpm; //lb/min
13 // temperature increase,
14 T_increase=HP_btu/(0.42*Q_lb); //deg F
15 // downward oil temperature,
16 T_downward=T_oil+T_increase; //deg F
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The downstream oil temperature is %.1f
    deg F.",T_downward)

```

---

**Scilab code Exa 11.3.a** determine downstream oil temperature in SI

```

1 // Aim:To find the downstream oil temperature in SI
    Unit
2 // Given:
3 // temperature of oil flowing through pressure
    relief valve:
4 T_oil=50; //deg C
5 // pressure of oil flowing through pressure relief
    valve:
6 p=70; //bar
7 // oil flow through pressure relief valve:
8 Q=0.000632; //m^3/s

```

---

**Scilab code Exa 11.3.b** SOLUTION downstream oil temperature in SI

```

1  clc;
2  pathname=get_absolute_file_path('11_3_soln.sce')
3  filename=pathname+filesep()+ '11_3_data.sci '
4  exec(filename)
5
6  // Solution:
7  // heat generation rate ,
8  kW=((p*10^5)*Q)/1000; //kW
9  // oil flow-rate ,
10 Q_kg_s=895*Q; //kg/s
11 // temperature increase ,
12 T_increase=kW/(1.8*Q_kg_s); //deg C
13 // downward oil temperature ,
14 T_downward=T_oil+T_increase; //deg C
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The downstream oil temperature is %.1f
    deg C.",T_downward)

```

---

**Scilab code Exa 11.4.a** find heat exchanger rating of system

```

1  // Aim:To find the rating of heat exchanger required
    to dissipate generated heat
2  // Given:
3  // oil flow-rate:
4  Q=20; //gpm
5  // operating pressure:
6  p=1000; //psi
7  // overall efficiency of pump:
8  eff_overall=85; //%
9  // power lost due to friction:
10 HP_frict=10; //%

```

---

**Scilab code Exa 11.4.b SOLUTION** heat exchanger rating of system

```
1  clc;
2  pathname=get_absolute_file_path('11_4_soln.sce')
3  filename=pathname+filesep()+ '11_4_data.sci '
4  exec(filename)
5
6  // Solution:
7  // pump power loss ,
8  pump_HP_loss=((1/(eff_overall/100))-1)*((p*Q)/1714);
   //HP
9  // PRV average HP loss ,
10 PRV_loss=0.5*((p*Q)/1714); //HP
11 // line average HP loss ,
12 line_loss=(HP_frict/100)*PRV_loss; //HP
13 // total average loss ,
14 total_loss=pump_HP_loss+PRV_loss+line_loss; //HP
15 // heat exchanger rating ,
16 HEx_rating=total_loss*2544; //Btu/hr
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The heat exchanger rating is %.0f Btu/hr.
   ",HEx_rating)
21 printf("\n The answer in the program does not match
   with that in the textbook due to roundoff error (
   standard ratings) in textbook")
```

---

**Scilab code Exa 11.5.a** find heat exchanger rating in SI

```
1 // Aim:To find the rating of heat exchanger required
   to dissipate generated heat in SI unit
```

```

2 // Given:
3 // oil flow-rate:
4 Q=0.00126; //m^3/s
5 // operating pressure:
6 p=70; //bar
7 // overall efficiency of pump:
8 eff_overall=85; //%
9 // power lost due to friction:
10 HP_frict=10; //%

```

---

**Scilab code Exa 11.5.b SOLUTION** heat exchanger rating in SI

```

1 clc;
2 pathname=get_absolute_file_path('11_5_soln.sce')
3 filename=pathname+filesep()+ '11_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // pump power loss ,
8 pump_loss=((1/(eff_overall/100))-1)*((p*10^5*Q)
   /1000); //kW
9 // PRV average HP loss ,
10 PRV_loss=0.5*((p*10^5*Q)/1000); //kW
11 // line average HP loss ,
12 line_loss=(HP_frict/100)*PRV_loss; //kW
13 // total average loss ,
14 HEx_rating=pump_loss+PRV_loss+line_loss; //kW
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The heat exchanger rating is %.2f kW.",
   HEx_rating)

```

---

## Chapter 13

# PNEUMATICS AIR PREPARATION AND COMPONENTS

Scilab code Exa 13.1.a find final pressure at constant temperature

```
1 // Aim:To find new pressure in cylinder when its  
   blank end is blocked  
2 // Given:  
3 // diameter of pneumatic piston:  
4 D=2; //in  
5 // length of retraction of piston:  
6 l_ret=4; //in  
7 // blank side pressure:  
8 p1=20; //psig  
9 // volume of cylinder for extension stroke:  
10 V1=20; //in^3
```

---

Scilab code Exa 13.1.b SOLUTION final pressure at constant temperature

```

1  clc;
2  pathname=get_absolute_file_path('13_1_soln.sce')
3  filename=pathname+filesep()+ '13_1_data.sci '
4  exec(filename)
5
6  // Solution:
7  // volume of cylinder during retraction stroke ,
8  V2=(V1-((%pi * D^2 * l_ret)/4)); //in^3
9  // absolute pressure on blank side ,
10 p1=p1+14.7; //psia
11 // new pressure when blank side port is blocked ,
12 // Boyle 's Law,
13 p2=(p1*V1)/V2; //psia
14 p2=p2-14.7; //psig
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The new pressure when blank side port is
    blocked is %.1f psig.",p2)

```

---

**Scilab code Exa 13.2.a** find final volume at constant pressure

```

1  // Aim:To find new volume of air at the blank end of
    cylinder
2  // Given:
3  // initial volume:
4  V1=20; //in^3
5  // constant load:
6  p=20; //psi
7  // initial temperature of air:
8  T1=60; //deg F
9  // final temperature of air:
10 T2=120; //degF

```

---

**Scilab code Exa 13.2.b SOLUTION** final volume at constant pressure

```
1  clc;
2  pathname=get_absolute_file_path('13_2_soln.sce')
3  filename=pathname+filesep()+ '13_2_data.sci'
4  exec(filename)
5
6  // Solution:
7  // initial temperature of air in Rankine,
8  T1=T1+460; //deg R
9  // final temperature of air in Rankine,
10 T2=T2+460; //deg R
11 // final volume of air,
12 // Charle's Law,
13 V2=(T2/T1)*V1; //in^3
14
15 // Results:
16 printf("\n Results: ")
17 printf("\n The final volume of air is %.1f in^3.",V2
    )
```

---

**Scilab code Exa 13.3.a** find final pressure at constant volume

```
1 // Aim:To find new pressure in cylinder when it is
   at locked position
2 // Given:
3 // initial pressure:
4 p1=20; //psig
5 // initial temperature of air:
6 T1=60; //deg F
7 // final temperature of air:
8 T2=160; //degF
```

---

**Scilab code Exa 13.3.b** SOLUTION final pressure at constant volume

```
1  clc;
2  pathname=get_absolute_file_path('13_3_soln.sce')
3  filename=pathname+filesep()+ '13_3_data.sci'
4  exec(filename)
5
6  // Solution:
7  // initial temperature of air in Rankine,
8  T1=T1+460; //deg R
9  // final temperature of air in Rankine,
10 T2=T2+460; //deg R
11 // absolute initial pressure ,
12 p1=p1+14.7; //psia
13 // final pressure of air ,
14 // Gay-Lussac 's Law,
15 p2=(T2/T1)*p1; //psia
16 p2=p2-14.7; //psig
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The final pressure of air at constant
    volume is %.1f psig.",p2)
```

---

**Scilab code Exa 13.4.a** find final pressure general gas law

```
1 // Aim:To find final pressure in the cylinder
2 // Given:
3 // initial gas pressure:
4 p1=1000; //psig
5 // initial volume of cylinder:
```



```

6 V1=2000; //in^3
7 // initial temperature of cylinder:
8 T1=100; //deg F
9 // final volume of cylinder:
10 V2=1500; //in^3
11 // final temperature of cylinder:
12 T2=200; //deg F

```

---

**Scilab code Exa 13.4.b SOLUTION** final pressure general gas law

```

1 clc;
2 pathname=get_absolute_file_path('13_4_soln.sce')
3 filename=pathname+filesep()+ '13_4_data.sci '
4 exec(filename)
5
6 // Solution:
7 // final pressure in the cylinder ,
8 // General Gas Law,
9 p2=((p1+14.7)*V1*(T2+460))/(V2*(T1+460))-14.7; //
   psig
10
11 // Results:
12 printf("\\n Results: ")
13 printf("\\n The final pressure in the cylinder is %.1
   f psig.",p2)

```

---

**Scilab code Exa 13.5.a** find final pressure general law SI

```

1 // Aim:To find final pressure in the cylinder in SI
   units
2 // Given:
3 // initial gas pressure:
4 p1=70; //bar

```

```

5 // initial volume of cylinder:
6 V1=12900; //cm^3
7 // initial temperature of cylinder:
8 T1=37.8; //deg C
9 // final volume of cylinder:
10 V2=9680; //cm^3
11 // final temperature of cylinder:
12 T2=93.3; //deg C

```

---

**Scilab code Exa 13.5.b SOLUTION final pressure general law SI**

```

1 clc;
2 pathname=get_absolute_file_path('13_5_soln.sce')
3 filename=pathname+filesep()+ '13_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // final pressure in the cylinder in absolute units,
8 // General Gas Law,
9 p2=(((p1+1)*10^5*V1*(T2+273))/(V2*(T1+273)))/10^5;
   //bars
10
11 // Results:
12 printf("\n Results: ")
13 printf("\n The final pressure in the cylinder is %.1
   f bars absolute.",p2)

```

---

**Scilab code Exa 13.6.a** how much air compressor must provide

```

1 // Aim:To find how many cfm of free air compressor
   must be provided
2 // Given:
3 // flow-rate of air from receiver:

```

```

4 Q2=30; //cfm
5 // temperature of air from receiver:
6 T2=90; //deg F
7 // pressure of air coming from receiver:
8 p2=125; //psig
9 // atmospheric temperature:
10 T1=70; //deg F
11 // atmospheric pressure:
12 p1=14.7; //psig

```

---

**Scilab code Exa 13.6.b SOLUTION** air compressor must provide

```

1 clc;
2 pathname=get_absolute_file_path('13_6_soln.sce')
3 filename=pathname+filesep()+ '13_6_data.sci'
4 exec(filename)
5
6 // Solution:
7 // cfm of free air compressor must be provided,
8 Q1=Q2*((p2+14.7)/14.7)*((T1+460)/(T2+460)); //cfm
9
10 // Results:
11 printf("\\n Results: ")
12 printf("\\n The cfm of free air compressor must be
    provided is %.0f cfm of free air.",Q1)

```

---

**Scilab code Exa 13.7.a** find receiver size for pneumatic system

```

1 // Aim: Refer Example 13-7 for Problem Description
2 // Given:
3 // maximum pressure level in receiver:
4 p_max=100; //psi
5 // minimum pressure level in receiver:

```

```

6 p_min=80; //psi
7 // time that receiver can supply required amount of
  air:
8 t=6; //min
9 // consumption rate of pneumatic system:
10 Qr=20; //scfm
11 // output flow-rate of compressor:
12 Qc=5; //scfm

```

---

Scilab code Exa 13.7.b SOLUTION receiver size for pneumatic system

```

1 clc;
2 pathname=get_absolute_file_path('13_7_soln.sce')
3 filename=pathname+filesep()+ '13_7_data.sci'
4 exec(filename)
5
6 // Solution:
7 // required size of a receiver before compressor
  resumes operation ,
8 Vr=((14.7*t*(Qr-0))/(p_max-p_min))*7.48; //gal
9 // required size of a receiver when compressor is
  running ,
10 Vr_run=((14.7*t*(Qr-Qc))/(p_max-p_min))*7.48; //gal
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The required size of a receiver before
  compressor resumes operation is %.0f gal.",Vr)
15 printf("\n The required size of a receiver when
  compressor is running %.0f gal.",Vr_run)

```

---

Scilab code Exa 13.8.a determine actual power required for compressor

```

1 // Aim:To determine actual power required to drive a
    compressor
2 // Given:
3 // input flow-rate of air through compressor:
4 Q=100; //scfm
5 // inlet atmospheric pressure:
6 p_in=14.7; //psig
7 // outlet pressure:
8 p_out=114.7; //psig
9 // overall efficiency of compressor:
10 eff=75; //%
```

---

**Scilab code Exa 13.8.b SOLUTION** actual power required for compressor

```

1 clc;
2 pathname=get_absolute_file_path('13_8_soln.sce')
3 filename=pathname+filesep()+ '13_8_data.sci '
4 exec(filename)
5
6 // Solution:
7 // theoretical horsepower ,
8 HP_theo=((p_in*Q)/65.4)*((p_out/p_in)^0.286-1); //HP
9 // actual horsepower ,
10 HP_act=HP_theo/(eff/100); //HP
11
12
13 // Results:
14 printf("\\n Results: ")
15 printf("\\n The actual power required to drive a
    compressor is %.0f HP.",HP_act)
```

---

**Scilab code Exa 13.9.a** find moisture received by pneumatic system

```

1 // Aim:Refer Example 13-9 for Problem Description
2 // Given:
3 // output flow-rate of compressor:
4 Qc=100; //scfm
5 // pressure at compressor outlet:
6 p_out=100; //psig
7 // temperature of saturated air at compressor inlet:
8 T_in=80; //deg F
9 // operation time of compressor per day:
10 t=8; //hr/day

```

---

**Scilab code Exa 13.9.b SOLUTION** moisture received by pneumatic system

```

1 clc;
2 pathname=get_absolute_file_path('13_9_soln.sce')
3 filename=pathname+filesep()+ '13_9_data.sci'
4 exec(filename)
5
6 // Solution:
7 // from fig 13-29,
8 // entering moisture content at 80 deg F,
9 moist_in=1.58/1000; //lb/ft^3
10 // moisture rate which enters the compressor,
11 moist_rate=moist_in*Qc; //lb/min
12 // number of gallons/day received by pneumatic
    system,
13 gal_per_day=(moist_rate*60*t)/8.34; //gal/day
14 // moisture received by pneumatic system if
    aftercooler is installed,
15 // from fig 13-29,
16 moist_after=(1-((1.58-0.2)/1.58))*gal_per_day; //gal
    /day
17 // moisture received by pneumatic system if air
    dryer is installed,

```

```

18 // from fig 13-29,
19 moist_air_dryer=(1-((1.58-0.05)/1.58))*gal_per_day;
    //gal/day
20
21 // Results:
22 printf("\n Results: ")
23 printf("\n The number of gallons/day received by
    pneumatic system is %.2f gal/day.",gal_per_day)
24 printf("\n The moisture received by pneumatic system
    if aftercooler is installed is %.2f gal/day.",
    moist_after)
25 printf("\n The moisture received by pneumatic system
    if air dryer is installed is %.2f gal/day.",
    moist_air_dryer)

```

---

**Scilab code Exa 13.10.a** determine air maximum flowrate in scfm

```

1 // Aim:To determine maximum flow-rate in units of
    scfm of air
2 // Given:
3 // upstream temperature:
4 T1=80; //deg F
5 // upstream pressure:
6 p1=80; //psi
7 // flow capacity constant:
8 Cv=7.4;
9 // diameter of orifice:
10 d=0.5; //in

```

---

**Scilab code Exa 13.10.b** SOLUTION air maximum flowrate in scfm

```

1 clc;
2 pathname=get_absolute_file_path('13_10_soln.sce')

```

```

3 filename=pathname+filesep()+ '13_10_data . sci '
4 exec(filename)
5
6 // Solution:
7 // upstream temperature in Rankine ,
8 T1=T1+460; //deg R
9 // absolute upstream pressure ,
10 p1=p1+14.7; //psia
11 // for maximum flow-rate ,
12 // absolute downstream pressure ,
13 p2=0.53*p1; //psia
14 // volume flow-rate ,
15 Q=floor(22.7*Cv*sqrt(((p1-p2)*p2)/T1)); //scfm
16
17 // Results:
18 printf("\n Results: ")
19 printf("\n The maximum flow-rate is %.0f scfm of air
    .",Q)

```

---

**Scilab code Exa 13.11.a** determine flow capacity constant of system

```

1 // Aim:To determine size valve (Cv) for
    pneumatically powered impact tool
2 // Given:
3 // volume flow-rate of air:
4 Q=50; //scfm
5 // downstream pressure:
6 p2=100; //psi
7 // pressure drop across valve:
8 del_p=12; //psi
9 // upstream air temperature:
10 T1=80; //deg F

```

---



Scilab code Exa 13.11.b SOLUTION flow capacity constant of system

```
1 clc;
2 pathname=get_absolute_file_path('13_11_soln.sce')
3 filename=pathname+filesep()+ '13_11_data.sci'
4 exec(filename)
5
6 // Solution:
7 // upstream temperature in Rankine,
8 T1=T1+460; //deg R
9 // absolute downstream pressure,
10 p2=p2+14.7; //psia
11 // flow capacity constant,
12 Cv=(Q/22.7)*sqrt(T1/(p2*del_p));
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The flow capacity constant is %.2f.",Cv)
```

---

Scilab code Exa 13.12.a determine air consumption rate in scfm

```
1 // Aim:To determine the air-consumption rate in scfm
2 // Given:
3 // piston diameter of pneumatic cylinder:
4 d=1.75; //in
5 // stroke length of cylinder:
6 L=6; //in
7 // number of cycles per minute:
8 N=30; //cycles/min
9 // atmospheric temperature:
10 T1=68; //deg F
11 // atmospheric pressure:
12 p1=14.7; //psia
13 // temperature of air in pneumatic cylinder:
14 T2=80; //deg F
```

```
15 // pneumatic cylinder pressure:
16 p2=100; //psig
```

---

**Scilab code Exa 13.12.b** SOLUTION air consumption rate in scfm

```
1  clc;
2  pathname=get_absolute_file_path('13_12_soln.sce')
3  filename=pathname+filesep()+ '13_12_data.sci'
4  exec(filename)
5
6  // Solution:
7  // atmospheric temperature in deg Rankine,
8  T1=T1+460; //deg R
9  // temperature of air in deg Rankine in pneumatic
   cylinder ,
10 T2=T2+460; //deg R
11 // absolute pneumatic cylinder pressure ,
12 p2=p2+14.7; //psia
13 // the volume per minute of air consumed by cylinder
   ,
14 Q2=(%pi/4)*(d/12)^2*(L/12)*N; //ft^3/min
15 // air consumption rate ,
16 Q1=Q2*(p2/p1)*(T1/T2); //scfm
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The air consumption rate in scfm is %.2f.
   ",Q1)
```

---

**Scilab code Exa 13.13.a** find reciprocation rate of pneumatic cylinder

```
1 // Aim:To determine the piston reciprocation rate
2 // Given:
```

```

3 // piston diameter of pneumatic cylinder:
4 d=44.5; //mm
5 // stroke length of cylinder:
6 L=152; //mm
7 // atmospheric temperature:
8 T1=20; //deg C
9 // atmospheric pressure:
10 p1=101; //kPa
11 // temperature of air in pneumatic cylinder:
12 T2=27; //deg C
13 // pneumatic cylinder pressure:
14 p2=687; //kPa
15 // air consumption rate:
16 Q1=0.0555; //m^3/min

```

---

**Scilab code Exa 13.13.b** SOLUTION reciprocation rate of pneumatic cylinder

```

1 clc;
2 pathname=get_absolute_file_path('13_13_soln.sce')
3 filename=pathname+filesep()+ '13_13_data.sci'
4 exec(filename)
5
6 // Solution:
7 // atmospheric temperature in kelvin ,
8 T1=T1+273; //K
9 // temperature of air in kelvin in pneumatic
   cylinder ,
10 T2=T2+273; //K
11 // absolute pneumatic cylinder pressure ,
12 p2=p2+101; //kPa abs
13 // flow-rate of air consumed by cylinder ,
14 Q2=Q1*(p1/p2)*(T2/T1); //m^3/min
15 // reciprocation rate of piston ,
16 N=floor(Q2/((%pi/4)*(d/1000)^2*(L/1000))); //cycles/

```

```
    min
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The reciprocation rate of piston is %.0f
    cycles/min.",N)
```

---

# Chapter 14

## PNEUMATICS CIRCUITS AND APPLICATIONS

Scilab code Exa 14.1.a find pressure loss for given pipe

```
1 // Aim:To find pressure loss for a 250 ft length of
   pipe
2 // Given:
3 // flow-rate:
4 Q=100; //scfm
5 // receiver pressure:
6 p2=150; //psi
7 // atmospheric pressure:
8 p1=14.7; //psi
9 // length of pipe:
10 L=250; //ft
```

---

Scilab code Exa 14.1.b SOLUTION pressure loss for given pipe

```
1 clc;
2 pathname=get_absolute_file_path('14_1_soln.sce')
```

```

3 filename=pathname+filesep()+ '14_1_data . sci '
4 exec(filename)
5
6 // Solution:
7 // compression ratio ,
8 CR=(p2+p1)/p1;
9 // from fig 14-3,
10 // inside diameter raised to 5.31,
11 k=1.2892; //in
12 // experimentally determined coefficient ,
13 c=0.1025/(1)^0.31;
14 // pressure loss ,
15 p_f=(c*L*Q^2)/(3600*CR*k); //psi
16
17 // Results:
18 printf("\n Results: ")
19 printf("\n The pressure loss for a 250 ft length of
    pipe is %.2f psi.",p_f)

```

---

**Scilab code Exa 14.2.a** find pressure loss with pipe valves

```

1 // Aim:To find pressure loss for a pipe with valves
2 // Given:
3 // experimentally determined coefficient:
4 c=0.1025;
5 // compression ratio:
6 CR=11.2;
7 // receiver pressure:
8 p2=150; //psi
9 // atmospheric pressure:
10 p1=14.7; //psi
11 // length of pipe:
12 L=250; //ft

```

---

**Scilab code Exa 14.2.b SOLUTION** pressure loss with pipe valves

```
1  clc;
2  pathname=get_absolute_file_path('14_2_soln.sce')
3  filename=pathname+filesep()+ '14_2_data.sci'
4  exec(filename)
5
6  // Solution:
7  // from fig 14-3,
8  // inside diameter raised to 5.31,
9  k=1.2892; //in
10 // length of pipe along with valves ,
11 L=L+(2*0.56)+(3*29.4)+(5*1.5)+(4*2.6)+(6*1.23); //ft
12 // pressure loss ,
13 p_f=(c*L*Q^2)/(3600*CR*k); //psi
14
15 // Results:
16 printf("\n Results: ")
17 printf("\n The pressure loss for a 250 ft length of
    pipe is %.2f psi.",p_f)
```

---

**Scilab code Exa 14.3.a** determine cost of electricity per year

```
1 // Aim:Refer Example 14-3 for Problem Description
2 // Given:
3 // air flow-rate:
4 Q=270; //scfm
5 // pressure at which compressor delivers air:
6 p_out=100; //psig
7 // overall efficiency of compressor:
8 eff_o=75; //%
```

```

9 // pressure at which compressor delivers air taking
  friction in account:
10 p_out1=115; //psig
11 // efficiency of electric motor driving compressor:
12 eff_mot=92; %%
13 // operating time of compressor:
14 t=3000; //hr/year
15 // cost of electricity per watt:
16 cost_per_wat=0.11; //$/kWh

```

---

**Scilab code Exa 14.3.b SOLUTION** cost of electricity per year

```

1 clc;
2 pathname=get_absolute_file_path('14_3_soln.sce')
3 filename=pathname+filesep()+ '14_3_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // inlet pressure ,
8 p_in=14.7; //psi
9 // actual horsepower at 100 psig ,
10 act_HP=((p_in*Q)/(65.4*(eff_o/100)))*(((p_out+14.7)/
  p_in)^0.286-1); //HP
11 // actual horsepower at 115 psig ,
12 act_HP1=((p_in*Q)/(65.4*(eff_o/100)))*(((p_out1
  +14.7)/p_in)^0.286-1); //HP
13 // actual power at 100 psig in kW,
14 act_kW=act_HP*0.746; //kW
15 // electric power required to drive electric motor
  at 100 psig ,
16 elect_kW=act_kW/(eff_mot/100); //kW
17 // cost of electricity per year at 100 psig ,
18 yearly_cost=elect_kW*t*cost_per_wat; //$/yr
19 // actual power at 115 psig in kW,
20 act_kW1=act_HP1*0.746; //kW

```



```

21 // electric power required to drive electric motor
    at 115 psig ,
22 elect_kW1=act_kW1/(eff_mot/100); //kW
23 // cost of electricity per year at 115 psig ,
24 yearly_cost1=elect_kW1*t*cost_per_wat; //$/yr
25
26 // Results:
27 printf("\n Results: ")
28 printf("\n The actual HP required to drive the
    compressor at 100 psig is %.1f HP.",act_HP)
29 printf("\n The actual HP required to drive the
    compressor at 115 psig is %.1f HP.",act_HP1)
30 printf("\n The cost of electricity per year at 100
    psig is %.0f $.",yearly_cost)
31 printf("\n The cost of electricity per year at 115
    psig is %.0f $.",yearly_cost1)
32 printf("\n The answer in the program does not match
    with that in the textbook due to roundoff error (
    standard electric ratings)")

```

---

**Scilab code Exa 14.4.a** determine cost of leakage per year

```

1 // Aim:To determine the yearly cost of leakage of
    pneumatic system
2 // Given:
3 // air flow-rate:
4 Q=270; //scfm
5 // air flow-rate leakage:
6 Q_leak=70; //scfm
7 // // electric power required to drive electric
    motor at 100 psig:
8 elect_kW=52.3; //kW
9 // cost of electricity per watt:
10 cost_per_wat=0.11; //$/kWh

```

---

**Scilab code Exa 14.4.b SOLUTION** cost of leakage per year

```
1  clc;
2  pathname=get_absolute_file_path('14_4_soln.sce')
3  filename=pathname+filesep()+ '14_4_data.sci '
4  exec(filename)
5
6  // Solutions:
7  // electric power required to compensate for leakage
8  power_rate=(Q_leak/Q)*elect_kW; //kW
9  // rounding off the above answer
10 power_rate=fix(power_rate)+(fix(round((power_rate -
    fix(power_rate))*10))/10); //kW
11 // cost of electricity per year at 100 psig ,
12 yearly_leak=power_rate*24*365*cost_per_wat; //$/yr
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The cost of electricity for leakage per
    year at 100 psig is %.0f $.",yearly_leak)
17 printf("\n The answer in the program does not match
    with that in the textbook due to roundoff error(
    standard electric ratings)")
```

---

**Scilab code Exa 14.5.a** how heavy object can be lifted

```
1 // Aim: Refer Example 14–5 for Problem Description
2 // Given:
3 // diameter of suction cup lip outer circle:
4 Do=6; //in
5 // diameter of suction cup inner lip circle:
```

```

6 Di=5; //in
7 // atmospheric pressure:
8 p_atm=14.7; //psi
9 // suction pressure:
10 p_suc=-10; //psi

```

---

**Scilab code Exa 14.5.b** SOLUTION heavy object can be lifted

```

1 clc;
2 pathname=get_absolute_file_path('14_5_soln.sce')
3 filename=pathname+filesep()+ '14_5_data.sci'
4 exec(filename)
5
6 // Solution:
7 // suction pressure in absolute ,
8 p_suc_abs=p_suc+p_atm; //psia
9 // maximum weight that suction cup can lift ,
10 F=ceil((p_atm*(%pi/4)*Do^2)-(p_suc_abs*(%pi/4)*Di^2)
); //lb
11 // maximum weight suction cup can lift with perfect
    vaccum ,
12 W=p_atm*(%pi/4)*Do^2; //lb
13
14 // Results:
15 printf("\n Results: ")
16 printf("\n The maximum weight that suction cup can
    lift is %.0f lb.",F)
17 printf("\n The maximum weight that suction cup can
    lift with perfect vacuum is %.0f lb.",W)

```

---

**Scilab code Exa 14.6.a** determine time for achieving vacuum pressure

```

1 // Aim:To determine the time required to achieve the
    desired vacuum pressure
2 // Given:
3 // total volume of space in the suction cup:
4 V=6; //ft^3
5 // flow-rate produced by vacuum pump:
6 Q=4; //scfm
7 // desired suction pressure:
8 p_vacuum=6; //in Hg abs
9 // atmospheric pressure:
10 p_atm=30; //in Hg abs

```

---

**Scilab code Exa 14.6.b SOLUTION** time for achieving vacuum pressure

```

1 clc;
2 pathname=get_absolute_file_path('14_6_soln.sce')
3 filename=pathname+filesep()+ '14_6_data.sci '
4 exec(filename)
5
6 // Solutions:
7 // time required to achieve the desired vacuum
    pressure ,
8 t=(V/Q)*log(p_atm/p_vacuum); //min
9 // time required to achieve perfect vacuum pressure ,
10 t1=(V/Q)*log(p_atm/0.5); //min
11
12 // Results:
13 printf("\\n Results: ")
14 printf("\\n The time required to achieve the desired
    vacuum pressure is %.2f min.",t)
15 printf("\\n The time required to achieve perfect
    vacuum pressure is %.2f min.",t1)

```

---

Scilab code Exa 14.7.a calculate required size of the accumulator

```
1 // Aim: Refer Example 14-7 for Problem Description
2 // Given:
3 // diamter of hydraulic cylinder:
4 D=6; //in
5 // cylinder extension:
6 L=100; //in
7 // duration of cylinder extension:
8 t=10; //s
9 // time between crushing stroke:
10 t_crush=5; //min
11 // gas precharge pressure:
12 p1=1200; //psia
13 // gas charge pressure when pump is turned on:
14 p2=3000; //psia
15 // minimum pressure required to actuate load:
16 p3=1800; //psia
```

---

Scilab code Exa 14.7.b SOLUTION required size of the accumulator

```
1 clc;
2 pathname=get_absolute_file_path('14_7_soln.sce')
3 filename=pathname+filesep()+ '14_7_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // volume of hydraulic cylinder ,
8 V=(%pi/4)*L*(D^2); //in^3
9 // volume of cylinder in charged position ,
10 V2=V/((p2/p3)-1); //in^3
11 // volume of cylinder in final position ,
12 V3=(p2/p3)*V2; //in^3
13 // required size of accumulator ,
14 V1=((p2*V2)/p1)/231; //gal
```

```

15 // rounding off the above answer ,
16 V1=fix(V1)+(fix(floor((V1-fix(V1))*10))/10); //gal
17 // pump flow-rate with accumulator ,
18 Q_pump_acc=((2*V)/231)/t_crush; //gpm
19 // rounding off the above answer
20 Q_pump_acc=fix(Q_pump_acc)+(fix(ceil((Q_pump_acc-fix
    (Q_pump_acc))*100))/100); //gpm
21 // pump hydraulic power with accumulator ,
22 HP_pump_acc=(Q_pump_acc*p2)/1714; //HP
23 // pump flow-rate without accumulator ,
24 Q_pump_no_acc=(V/231)/(t/60); //gpm
25 // pump hydraulic power without accumulator ,
26 HP_pump_no_acc=(Q_pump_no_acc*p3)/1714; //HP
27
28 // Results:
29 printf("\n Results: ")
30 printf("\n The required size of accumulator is %.1f
    gal.",V1)
31 printf("\n The pump hydraulic horsepower with
    accumulator is %.2f HP.",HP_pump_acc)
32 printf("\n The pump hydraulic horsepower without
    accumulator is %.1f HP.",HP_pump_no_acc)
33 printf("\n The answer in the program is different
    than that in textbook. It may be due to no.s of
    significant digit in data and calculation")

```

---

**Scilab code Exa 14.8.a** find electricity cost per year SI

```

1 // Aim:To calculate the cost of electricity per year
    in Metric Unit
2 // Given:
3 // air flow-rate:
4 Q=7.65; //m3/min
5 // pressure at which compressor delivers air:
6 p_out=687; //kPa gage

```

```

7 // efficiency of compressor:
8 eff_o=75; //%
9 // efficiency of electric motor driving compressor:
10 eff_mot=92; //%
11 // operating time of compressor per year:
12 t=3000; //hr
13 // cost of electricity:
14 cost_per_wat=0.11; //$/kWh

```

---

Scilab code Exa 14.8.b SOLUTION electricity cost per year SI

```

1 clc;
2 pathname=get_absolute_file_path('14_8_soln.sce')
3 filename=pathname+filesep()+ '14_8_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // inlet pressure ,
8 p_in=101; //kPa
9 // actual power ,
10 act_kW=((p_in*Q)/(17.1*(eff_o/100)))*(((p_out+101)/
    p_in)^0.286-1); //kW
11 // electric power required to drive electric motor,
12 elect_kW=act_kW/(eff_mot/100); //kW
13 // rounding off the above answer
14 elect_kW=fix(elect_kW)+(fix(round((elect_kW-fix(
    elect_kW))*10))/10); //kW
15 // cost of electricity ,
16 yearly_cost=elect_kW*t*cost_per_wat; //$/yr
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The cost of electricity per year is %.0f
    $.",yearly_cost)
21 printf("\n The answer in the program does not match

```

with that in the textbook due to roundoff error (standard electric ratings)”)

---

**Scilab code Exa 14.9.a** what flowrate vacuum pump must deliver

```
1 // Aim:To find the flow-rate to be delivered by
   vacuum pump
2 // Given:
3 // lip outside diameter of suction cup:
4 Do=100; //mm
5 // lip inside diameter of suction cup:
6 Di=80; //mm
7 // weight of steel sheets:
8 F=1000; //N
9 // numbers of suction cups:
10 N=4;
11 // total volume of space inside the suction cup:
12 V=0.15; //m^3
13 // factor of safety:
14 f=2;
15 // time required to produce desired vacuum pressure:
16 t=1; //min
```

---

**Scilab code Exa 14.9.b** SOLUTION flowrate vacuum pump must deliver

```
1 clc;
2 pathname=get_absolute_file_path('14_9_soln.sce')
3 filename=pathname+filesep()+ '14_9_data.sci '
4 exec(filename)
5
6 // Solutions:
7 // atmospheric pressure ,
8 p_atm=101000; //Pa
```



```

 9 // lip outside area of suction cup,
10 Ao=(%pi/4)*(Do/1000)^2; //m^2
11 // lip inside area of suction cup,
12 Ai=(%pi/4)*(Di/1000)^2; //m^2
13 // required vacuum pressure,
14 p=((p_atm*Ao)-((F*f)/N))/Ai; //Pa abs
15 // flow-rate to be delivered by vacuum pump,
16 Q=(V/t)*log(p_atm/p); //m^3/min
17 // rounding off the above answer
18 Q=fix(Q)+(fix(ceil((Q-fix(Q))*10000))/10000); //m^3/
  min
19
20 // Results:
21 printf("\n Results: ")
22 printf("\n The flow-rate of air to be delivered by
  vacuum pump is %.4f m^3/min.",Q)

```

---

**Scilab code Exa 14.10.a** calculate required size of accumulator SI

```

1 // Aim:Refer Example 14-7 for Problem Description
2 // Given:
3 // diamter of hydraulic cylinder:
4 D=152; //mm
5 // cylinder extension:
6 L=2.54; //m
7 // duration of cylinder extension:
8 t=10; //s
9 // time between crushing stroke:
10 t_crush=5; //min
11 // gas precharge pressure:
12 p1=84; //bars abs
13 // gas charge pressure when pump is turned on:
14 p2=210; //bars abs
15 // minimum pressure required to actuate load:
16 p3=126; //bars abs

```

---

Scilab code Exa 14.10.b SOLUTION required size of accumulator SI

```
1  clc;
2  pathname=get_absolute_file_path('14_10_soln.sce')
3  filename=pathname+filesep()+ '14_10_data.sci'
4  exec(filename)
5
6  // Solutions:
7  // volume of hydraulic cylinder ,
8  V=(%pi/4)*L*((D/1000)^2); //m^3
9  // volume of cylinder in charged position ,
10 V2=V/((p2/p3)-1); //m^3
11 // volume of cylinder in final position ,
12 V3=(p2/p3)*V2; //m^3
13 // required size of accumulator ,
14 V1=floor(((p2*V2)/p1)*1000); //L
15 // pump flow-rate with accumulator ,
16 Q_pump_acc=(2*V*1000)/(t_crush*60); //L/s
17 // pump hydraulic power with accumulator ,
18 kW_pump_acc=(Q_pump_acc*10^-3*p2*10^5)/1000; //kW
19 // pump flow-rate without accumulator ,
20 Q_pump_no_acc=V/t; //L/s
21 // pump hydraulic power without accumulator ,
22 kW_pump_no_acc=(Q_pump_no_acc*10^-3*p3*10^5); //kW
23
24 // Results:
25 printf("\n Results: ")
26 printf("\n The required size of accumulator is %.0f
    L.",V1)
27 printf("\n The pump hydraulic horsepower with
    accumulator is %.2 f kW.",kW_pump_acc)
28 printf("\n The pump hydraulic horsepower without
    accumulator is %.1 f kW.",kW_pump_no_acc)
```

---

## Chapter 17

# ADVANCED ELECTRICAL CONTROLS FOR FLUID POWER SYSTEMS

Scilab code Exa 17.1.a determine system accuracy of electrohydraulic system

```
1 // Aim:To determine the system accuracy of
   // electrohydraulic servo system
2 // Given:
3 // servo valve gain:
4 G_SV=0.15; //(in^3/s)/mA
5 // cylinder gain:
6 G_cyl=0.20; //in/in^3
7 // feedback transducer gain:
8 H=4; //V/in
9 // weight of load:
10 W=1000; //lb
11 // mass of load:
12 M=2.59; //lb.(s^2)/in
13 // volume of oil under compression:
14 V=50; //in^3
15 // system deadband:
```

```

16 SD=4; //mA
17 // bulk modulus of oil:
18 beta1=175000; //lb/in^2
19 // cylinder piston area:
20 A=5; //in^2

```

---

**Scilab code Exa 17.1.b** SOLUTION system accuracy of electrohydraulic system

```

1  clc;
2  pathname=get_absolute_file_path('17_1_soln.sce')
3  filename=pathname+filesep()+ '17_1_data.sci'
4  exec(filename)
5
6  // Solutions:
7  // natural frequency of the oil ,
8  om_H=A*sqrt((2*beta1)/(V*M)); //rad/s
9  // value of open-loop gain ,
10 open_loop=om_H/3; ///s
11 // amplifier gain ,
12 G_A=open_loop/(G_SV*G_cyl*H); //mA/V
13 // repeatable error ,
14 RE=SD/(G_A*H); //in
15
16 // Results:
17 printf("\n Results: ")
18 printf("\n The repeatable error of system is %.5f in
    .",RE)

```

---

**Scilab code Exa 17.2.a** determine system accuracy in SI

```

1 // Aim:To determine the system accuracy of in SI
  units

```

```

2 // Given:
3 // servo valve gain:
4 G_SV=2.46; //(cm^3/s)/mA
5 // cylinder gain:
6 G_cyl=0.031; //cm/cm^3
7 // feedback transducer gain:
8 H=4; //V/cm
9 // mass of load:
10 M=450; //kg
11 // volume of oil:
12 V=819; //cm^3
13 // system deadband:
14 SD=4; //mA
15 // bulk modulus of oil:
16 beta1=1200; //MPa
17 // cylinder piston area:
18 A=32.3; //cm^2

```

---

### Scilab code Exa 17.2.b SOLUTION system accuracy in SI

```

1 clc;
2 pathname=get_absolute_file_path('17_2_soln.sce')
3 filename=pathname+filesep()+ '17_2_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // natural frequency of the oil ,
8 om_H=(A*10^-4)*sqrt((2*beta1*10^6)/(V*10^-6*M)); //
   rad/s
9 // value of open-loop gain ,
10 open_loop=om_H/3; ///s
11 // amplifier gain ,
12 G_A=open_loop/(G_SV*G_cyl*H); //mA/V
13 // repeatable error ,
14 RE=SD/(G_A*H); //cm

```

```

15 // rounding off the above answer ,
16 RE=fix(RE)+(fix(ceil((RE-fix(RE))*100000))/100000);
    //cm
17
18 // Results:
19 printf("\n Results: ")
20 printf("\n The repeatable error of system is %.5f cm
    .",RE)

```

---

**Scilab code Exa 17.3.a** find maximum tracking error

```

1 // Aim:Refer Example 14-3 for Problem Description
2 // Given:
3 // servo valve current saturation:
4 I=300; //mA
5 // amplifier gain:
6 G_A=724; //mA/V
7 // feedback transducer gain:
8 H=4; //V/in
9 // feedback transducer gain in metric units
10 H1=1.57; //V/cm

```

---

**Scilab code Exa 17.3.b SOLUTION** maximum tracking error

```

1 clc;
2 pathname=get_absolute_file_path('17_3_soln.sce')
3 filename=pathname+filesep()+ '17_3_data.sci'
4 exec(filename)
5
6 // Solutions:
7 // tracking error ,
8 TE=I/(G_A*H); //in
9 // tracking error ,

```

```
10 TE1=I/(G_A*H1); //cm
11
12 // Results:
13 printf("\n Results: ")
14 printf("\n The tracking error of system is %.3f in."
    ,TE)
15 printf("\n The tracking error of system in SI Unit
    is %.3f cm.",TE1)
```

---