

Scilab Textbook Companion for
Introduction To Fluid Mechanics
by R. W. Fox And A. T. McDonald¹

Created by
Eswar Prasad
B.Tech
Mechanical Engineering
National Institute of Technology
College Teacher
Prof. Shivraj Deshmukh
Cross-Checked by
Prof. Shivraj Deshmukh

August 16, 2016

¹Funded by a grant from the National Mission on Education through ICT, <http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and Scilab codes written in it can be downloaded from the "Textbook Companion Project" section at the website <http://scilab.in>

Book Description

Title: Introduction To Fluid Mechanics

Author: R. W. Fox And A. T. McDonald

Publisher: Wiley India, New Delhi

Edition: 5

Year: 2001

ISBN: 9971-51-355-2

Scilab numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

AP Appendix to Example(Scilab Code that is an Appednix to a particular Example of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means a scilab code whose theory is explained in Section 2.3 of the book.

Contents

List of Scilab Codes	4
1 Introduction	5
2 Fundamental Concepts	7
3 Fluid Statics	9
4 Basic Equations in Integral form for a Control Volume	15
5 Introducton to Differential Analysis of Fluid Motion	25
6 Incompressible Inviscid Flow	29
7 Dimensional Analysis and Similitude	34
8 Internal Incompressible Viscous Flow	38
9 External Incompressible Viscous Flow	46
10 Fluid Machinery	53
11 Introduction to Compressible Flow	65
12 Steady One Dimensional Compressible Flow	68

List of Scilab Codes

Exa 1.01	Heat added during the process	5
Exa 1.02	speed and actual speed	5
Exa 2.02	Viscosity and stress	7
Exa 3.01	liquid level	9
Exa 3.03	pressure difference	10
Exa 3.04	temperature and pressure	10
Exa 3.05	force and pressure	12
Exa 3.06	force	13
Exa 3.07	force at equilibrium	13
Exa 4.01	Velocity	15
Exa 4.02	Mass flow	16
Exa 4.03	density	17
Exa 4.04	Horizontal force	17
Exa 4.05	Scale	18
Exa 4.06	force exerted per unt	19
Exa 4.07	Force to hold	19
Exa 4.08	Tension	20
Exa 4.09	pressure required	20
Exa 4.10	Net force	21
Exa 4.11	PLOTTING	22
Exa 4.12	Velocity of rocket	22
Exa 4.14	Relative speed and friction	23
Exa 4.16	Rate of heat	24
Exa 4.17	Mass flow rate	24
Exa 5.02	Rate of change	25
Exa 5.07	angular and rotation	26
Exa 5.08	Rates and area	26
Exa 5.09	Volume flow rate	27

Exa 6.01	Volume flow rate	29
Exa 6.02	Velocity of flow	30
Exa 6.03	prssure required	30
Exa 6.04	Speed and pressure	30
Exa 6.05	flow	31
Exa 6.06	pressure	32
Exa 6.08	temperature	32
Exa 6.09	Streamline flow	33
Exa 7.04	speed and force	34
Exa 7.05	speed force and power	35
Exa 7.06	power and speed	36
Exa 8.01	Leakage flow rate	38
Exa 8.02	Torque and power	39
Exa 8.04	Viscosity of fluid	39
Exa 8.05	required	40
Exa 8.06	Maximum and power	40
Exa 8.07	Volume low	41
Exa 8.08	Minimum diameter	42
Exa 8.09	Loss Coefficient	42
Exa 8.10	Volume and increase	43
Exa 8.11	Diameter and head	44
Exa 9.01	static pressure	46
Exa 9.04	Displacement thickness and stress	47
Exa 9.05	force and power	48
Exa 9.06	Bending moment	49
Exa 9.07	Time required	49
Exa 9.08	Optimum cruise speed	50
Exa 9.09	Aerodynamic and Radius	51
Exa 10.01	input and power	53
Exa 10.1	Performance curves	54
Exa 10.02	volume and power	55
Exa 10.03	Pump Power	56
Exa 10.06	Specific and relation	57
Exa 10.07	Comparison of head	58
Exa 10.08	NPSHA and NPSHR	59
Exa 10.12	Power required	61
Exa 10.14	propeller	62
Exa 10.16	Actual	63

Exa 11.01	Change	65
Exa 11.03	Speed of sound	66
Exa 11.04	pressure and change	67
Exa 12.01	pressure and area	68
Exa 12.02	Mass flow	69
Exa 12.03	mass and area	70
Exa 12.04	throat	71
Exa 12.05	number and flow	72
Exa 12.06	mass and volume	73
Exa 12.07	length	74
Exa 12.08	velocity and entropy	75
Exa 12.09	Temperature and entropy	77
Exa 12.10	Temperature	78
AP 1	data	81
AP 2	data	81
AP 3	data	82
AP 4	data	82
AP 5	data	83
AP 6	data	83
AP 7	data	84
AP 8	data	84
AP 9	data	85
AP 10	data	85
AP 11	data	86
AP 12	data	86
AP 13	data	87
AP 14	data	87
AP 15	data	88
AP 16	data	88
AP 17	data	89
AP 18	data	89
AP 19	data	90
AP 20	data	91
AP 21	data	91
AP 22	data	92
AP 23	data	92
AP 24	data	93
AP 25	data	93

AP 26	data	94
AP 27	data	94
AP 28	data	94
AP 29	data	95
AP 30	data	95
AP 31	data	95
AP 32	data	96
AP 33	data	96
AP 34	data	97
AP 35	data	97
AP 36	data	97
AP 37	data	98
AP 38	data	99
AP 39	data	99
AP 40	data	99
AP 41	data	100
AP 42	data	101
AP 43	data	101
AP 44	data	102
AP 45	data	102
AP 46	data	102
AP 47	data	103
AP 48	data	103
AP 49	data	103
AP 50	data	104
AP 51	data	104
AP 52	data	104
AP 53	data	105
AP 54	data	105
AP 55	data	105
AP 56	data	105
AP 57	data	106
AP 58	data	107
AP 59	data	107
AP 60	data	107
AP 61	data	108
AP 62	data	108
AP 63	data	108

AP 64	data	109
AP 65	data	109
AP 66	data	109
AP 67	data	110
AP 68	data	110
AP 69	data	111
AP 70	data	111
AP 71	data	111
AP 72	data	112
AP 73	data	112
AP 74	data	113
AP 75	data	113
AP 76	data	114
AP 77	data	114
AP 78	data	114
AP 79	data	115

Chapter 1

Introduction

check Appendix [AP 79](#) for dependency:

1_01.sci

Scilab code Exa 1.01 Heat added during the process

```
1 //Heat addition//
2 filename=pathname+filesep()+ '1.01 - data . sci '
3 exec(filename)
4 //Heat added during the process(in kJ):
5 Q12=m*cp*(T2-T1)
6 printf("\n\nRESULTS\n\n")
7 printf("\n\nHeat added during the process: %f kJ\n\n",Q12/1000)
```

check Appendix [AP 78](#) for dependency:

1_02.sci

Scilab code Exa 1.02 speed and actual speed

```

1 //speed and actual speed//
2 pathname=get_absolute_file_path('1.02.sce')
3 filename=pathname+filesep()+ '1.02-data.sci'
4 exec(filename)
5 //Speed at which the ball hits the ground(in m/sec):
6 V=sqrt(m*g/k*(1-%e^(2*k/m*(-y0))))
7 //Terminal speed(in m/sec):
8 Vt=sqrt(m*g/k)
9 //Ratio of actual speed to the terminal speed:
10 r=V/Vt;
11 printf("\n\nRESULTS\n\n")
12 printf("\n\nSpeed at which the ball hits he ground:
    %f m/sec\n\n",V)
13 printf("\n\nRatio of actual speed to the terminal
    speed: %f\n\n",r)

```

Chapter 2

Fundamental Concepts

check Appendix [AP 77](#) for dependency:

2_02.sci

Scilab code Exa 2.02 Viscosity and stress

```
1 //Viscosity and stress//
2 pathname=get_absolute_file_path('2.02.sce')
3 filename=pathname+filesep()+ '2.02-data.sci'
4 exec(filename)
5
6 //Viscosity in units of lbf-s/ft^2:
7 u1=u/100/454/32.2*30.5
8 //Kinematic viscosity (in m/sec^2):
9 v=u1/SG/d*(0.305)^2
10 //Shear stress on the upper plate(lbf/ft^2):
11 tu=u1*U/D*1000
12 //Shear stress on the lower plate(in Pa)
13 t1=tu*4.45/0.305^2
14 printf("\n\nRESULTS\n\n")
15 printf("\n\nViscosity in units of lbf-s/ft^2: %1.8f
    $lbf-s/ft^2\n\n",u1)
```

```
16 printf("\n\nKinematic viscosity: %1.8f m/sec^2\n\n",
    v)
17 printf("\n\nShear stres on the upeer plate: %f lbf/
    ft^2\n\n",tu)
18 printf("\n\nSear stress on the lower plate: %f Pa\n\n",t1)
```

Chapter 3

Fluid Statics

check Appendix [AP 76](#) for dependency:

3_01.sci

Scilab code Exa 3.01 liquid level

```
1 //liquid level//
2 pathname=get_absolute_file_path('3.01.sce')
3 filename=pathname+filesep()+ '3.01-data.sci'
4 exec(filename)
5 //Tube diameter (in mm):
6 D=1:25;
7 D1=D/1000
8 [m n]=size(D1)
9 for i=1:n
10 //Change in liquid level for water (in mm):
11 dhw(i)=4*STw*cosd(thetaw)/dw/g/D1(i);
12 //Change in liquid level for mercury (in mm):
13 dhm(i)=4*STm*cosd(thetam)/dm/g/D1(i);
14 end;
15
16 //Plotting tube diameter and water level:
17 plot(D1*1000,dhw,'-o')
```

```

18 //Plotting tube diameter and mercury level:
19 plot(D1*1000,dhm,'-*')
20 legend(['Water';'Mercury']);
21 xtitle('Liquid level vs Tube diameter','Liquid level
(in mm)','Tube diameter(in mm)')

```

check Appendix [AP 75](#) for dependency:

3_03.sci

Scilab code Exa 3.03 pressure difference

```

1 //pressure difference//
2 pathname=get_absolute_file_path('3.03.sce')
3 filename=pathname+filesep()+ '3.03-data.sci'
4 exec(filename)
5 //Pressure difference(in lbf/in^2):
6 dp=g*d*(-d1+SGm*d2-SGo*d3+SGm*d4+d5)/12/144
7 printf("\n\nRESULTS\n\n")
8 printf("\n\nPressure difference between A and B: %f
lbf/in^2\n\n",dp)

```

check Appendix [AP 74](#) for dependency:

3_04.sci

Scilab code Exa 3.04 temperature and pressure

```

1 //temperature and pressure//
2 pathname=get_absolute_file_path('3.04.sce')
3 filename=pathname+filesep()+ '3.04-data.sci'
4 exec(filename)
5 //Assuming temperature varies linearly with altitude
:

```

```

6 //Temperature gradient(in F/ft):
7 m=(T1-T2)/(z2-z1)
8 //Value of g/(m*R):
9 v=g/m/R/32.2
10 //Pressure at Vail Pass(in inches of Hg):
11 p12=p1*((T2+460)/(T1+460))^v
12 //Percentage change in density:
13 pc1=(p12/p1*(T1+460)/(T2+460)-1)*100
14 //Assuming density is constant:
15 //Pressure at Vail Pass(in inches of Hg):
16 p22=p1*(1-(g*(z2-z1)/(R*32.2)/(T1+460)))
17 //Percentage change in density:
18 pc2=0;
19 //Assuming temperature is constant:
20 //Pressure at Vail Pass(in inches of Hg):
21 p32=p1*e^(-g*(z2-z1)/(R*32.2)/(T2+460))
22 //Percentage change in density:
23 pc3=(p32/p1*(T1+460)/(T2+460)-1)*100
24 //For an adiabatic atmosphere:
25 p42=p1*((62+460)/(80+460))^(k/(k-1))
26 //Percentage change in density:
27 pc4=(p42/p1*(T1+460)/(T2+460)-1)*100
28 printf("\n\nRESULTS\n\n")
29 printf("\n\n1) If temperature varies linearly with
    altitude\n\n")
30 printf("\n\n\tAtmospheric pressure at Vail Pass: %f
    inches of Hg\n\n",p12)
31 printf("\n\n\tPercentage change in density wrt
    Denver: %f percent\n\n",pc1)
32 printf("\n\n2) If density is constant\n\n")
33 printf("\n\n\tAtmospheric pressure at Vail Pass: %f
    inches of Hg\n\n",p22)
34 printf("\n\n\tPercentage change in density wrt
    Denver: %f percent\n\n",pc2)
35 printf("\n\n3) If temperature is constant\n\n")
36 printf("\n\n\tAtmospheric pressure at Vail Pass: %f
    inches of Hg\n\n",p32)
37 printf("\n\n\tPercentage change in density wrt

```



```

    Denver: %f percent\n\n",pc3)
38 printf("\n\n4) For an adiabatic atmosphere\n\n")
39 printf("\n\n\tAtmospheric pressure at Vail Pass: %f
    inches of Hg\n\n",p42)
40 printf("\n\n\tPercentage change in density wrt
    Denver: %f percent\n\n",pc4)

```

check Appendix [AP 73](#) for dependency:

3_05.sci

Scilab code Exa 3.05 force and pressure

```

1 //force and pressure//
2 pathname=get_absolute_file_path('3.05.sce')
3 filename=pathname+filesep()+ '3.05-data.sci'
4 exec(filename)
5 //Net force on the gate(in kN):
6 Fr=d*g*w*(D*L+L^2/2*sind(theta))
7 //Centre of pressure:
8 //Calculation for y coordinate:
9   yc=D/sind(theta)+L/2
10   //Area(in m^2):
11   A=L*w
12   //Moment of inertia of rectangular gate(in m^4):
13   Ixx=w*L^3/12
14   //y coordinate(in m):
15   y=yc+Ixx/A/yc
16 //Calculation for x coordinate:
17   Ixy=0
18   xc=w/2
19   //x coordinate(in m):
20   x=xc+Ixy/A/xc
21 printf("\n\nRESULTS\n\n")
22 printf("\n\nNet force on the gate: %f kN\n\n",Fr
    /1000)

```

```
23 printf("\n\nCoordinate of centre of pressure:(%0.1f,
    %0.1f)\n\n",x,y)
```

check Appendix [AP 72](#) for dependency:

3_06.sci

Scilab code Exa 3.06 force

```
1 //force//
2 pathname=get_absolute_file_path('3.06.sce')
3 filename=pathname+filesep()+ '3.06-data.sci'
4 exec(filename)
5 //Force required to keep the door shut(in lbf):
6 function y=f(z),y=b/L*p0*z+d*b/L*(L*z-z^2),
    endfunction
7 Ft=intg(0,L,f)
8 printf("\n\nRESULTS\n\n")
9 printf("\n\nForce requiredto kep the door shut: %0.1f
    lbf\n\n",Ft)
```

check Appendix [AP 71](#) for dependency:

3_07.sci

Scilab code Exa 3.07 force at equilibrium

```
1 //force at equilibrium//
2 pathname=get_absolute_file_path('3.07.sce')
3 filename=pathname+filesep()+ '3.07-data.sci'
4 exec(filename)
5 //Horizontal component of resultant force(in kN):
6 Frh=0.5*d*g*w*D^2
7 //Line of action of Frh(in m):
```

```

8 y1=0.5*D+w*D^3/12/(0.5*D)/(w*D)
9 //Vertical component of resultant force(in kN):
10 function y=q(x), y=d*g*w*(D-sqrt(a*x)),endfunction
11 Frv=intg(0,D^2/a,q)
12 //Line of action of Frv(in m):
13 function k=f(x), k=d*g*w/Frv*x*(D-sqrt(a*x)),
    endfunction
14 xa=intg(0,D^2/a,f)
15 //Force required to keep the gate in equilibrium(in
    kN):
16 Fa=1/l*(xa*Frv+(D-y1)*Frh)
17 printf("\n\nRESULTS\n\n")
18 printf("\n\nForce required to keep the gate at
    equilibrium: %f kN\n\n",Fa/1000)

```

Chapter 4

Basic Equations in Integral form for a Control Volume

check Appendix [AP 70](#) for dependency:

4_01.sci

Scilab code Exa 4.01 Velocity

```
1 //Velocity//
2 pathname=get_absolute_file_path('4.01.sce')
3 filename=pathname+filesep()+ '4.01-data.sci'
4 exec(filename)
5 //If I=integral of(pV.dA):
6 //For system: Ics=IA1+IA2+IA3+IA4.
7 //For area 1
8 IA1=-d*V1*A1
9 //For area 3: IA2=d*V3*A3=m3
10 IA3=m3
11 //For area 4: IA4=-d*V4*A4=-d*Q4
12 IA4=-d*Q4
13 //For area 2:
14 IA2=-IA1-IA3-IA4
15 //Velocity at section 2(in ft/sec):
```

```

16 V2=IA2/d/A2
17 //V2 is in the negative y direction
18 printf("\n\nRESULTS\n\n")
19 printf("\n\nVelocity at section 2: -%.0fj ft/sec\n\n",V2)

```

check Appendix [AP 69](#) for dependency:

4_02.sci

Scilab code Exa 4.02 Mass flow

```

1 //Mass flow//
2 pathname=get_absolute_file_path('4.02.sce')
3 filename=pathname+filesep()+ '4.02-data.sci'
4 exec(filename)
5 //If I=integral of(pV.dA):
6 //For system: ICS=Iab+Ibc+Icd+Ida
7 //But ICS=0
8
9 //For Aab:
10 function p=f(y),p=-d*U*w*y^0, endfunction
11 IAab=intg(0,t,f)
12
13 //For Acd:
14 function q=g(y),q=d*U*w*(2*y/t-(y/t)^2), endfunction
15 IAcd=intg(0,t,g)
16
17 //Mass flow rate across surface bc(in kg/sec):
18 mbc=(-IAab-IAcd)/1000
19 printf("\n\nRESULTS\n\n")
20 printf("\n\nMass flow rate across surface bc: %.4f
kg/sec\n\n",mbc)

```

check Appendix [AP 68](#) for dependency:

4_03.sci

Scilab code Exa 4.03 density

```
1 //density//
2 pathname=get_absolute_file_path('4.03.sce')
3 filename=pathname+filesep()+ '4.03-data.sci'
4 exec(filename)
5 //Rate of change of air density in tank(in (kg/m^3)/
   s):
6 r=-d*v*A/V/10^6
7 printf("\n\nRESULTS\n\n")
8 printf("\n\nRate of change of air density in tank: %
   .3f kg/m^3\n\n",r)
9 printf("\n\nThe density decreases as is indicated by
   the negative sign\n\n")
```

check Appendix [AP 67](#) for dependency:

4_04.sci

Scilab code Exa 4.04 Horizontal force

```
1 //Horizontal force//
2 pathname=get_absolute_file_path('4.04.sce')
3 filename=pathname+filesep()+ '4.04-data.sci'
4 exec(filename)
5 //1) Control Volume selected so that area of left
   surface is equal to the area of the right surface
6 u1=15;
7 //Force of support on control volum(in kN):
8 function y=f(A),y=-u1*d*V, endfunction
9 Rx1=intg(0,0.01,f)
10 //Horizontal force on support(in kN):
```

```

11 Kx=-Rx1
12 //2) Control volumes are selected do that the area
    of the left and right surfaces are equal to the
    area of the plate
13
14 function z=g(A),z=-u1*d*V, endfunction
15 Fsx=intg(0,0.01,g)
16 //Net force on plate:Fx=0=-Bx-pa*Ap+Rx
17 //                               Rx=pa*Ap+Bx
18 //From the above, it is obtained that:
19 Rx2=-2.25
20 //Horizontal force on support(in kN):
21 Kx2=-Rx2
22 printf("\n\nRESULTS\n\n")
23 printf("\n\nHorizontal force on support: %.3f kN\n\n
    ",Kx/1000)

```

check Appendix [AP 66](#) for dependency:

4_05.sci

Scilab code Exa 4.05 Scale

```

1 //Scale//
2 pathname=get_absolute_file_path('4.05.sce')
3 filename=pathname+filesep()+ '4.05-data.sci'
4 exec(filename)
5 //Weight of water in the tank(in lbf):
6 d1=62.4;
7 WH20=d1*A*h
8 v=-5;
9 //Total body force in negative y direction(lbf):
10 function y=f(A),y=-v*d2*V1, endfunction
11 F=intg(0,A1,f)
12 //Force of scale on control volume(in kN):
13 Ry=W+WH20-F

```

```
14 printf("\n\nRESULTS\n\n")
15 printf("\n\nScale Reading: %.3f lbf\n\n",Ry)
```

check Appendix [AP 65](#) for dependency:

4_06.sci

Scilab code Exa 4.06 force exerted per unit

```
1 //force exerted per unit//
2 pathname=get_absolute_file_path('4.06.sce')
3 filename=pathname+filesep()+ '4.06-data.sci'
4 exec(filename)
5 //X-component of reaction force per unit width of
   the gate(in N/m):
6 Rxw=(d*(V2^2*D2-V1^2*D1))-(d*g/2*(D1^2-D2^2))
7 //Horizontal force exerted per unit width on the gate
   (in N/m):
8 Kxw=-Rxw
9 printf("\n\nRESULTS\n\n")
10 printf("\n\nHorizontal force exerted per unit width
   on the gate: %.3f kN/m\n\n",Kxw/1000)
```

check Appendix [AP 64](#) for dependency:

4_07.sci

Scilab code Exa 4.07 Force to hold

```
1 //Force to hold//
2 pathname=get_absolute_file_path('4.07.sce')
3 filename=pathname+filesep()+ '4.07-data.sci'
4 exec(filename)
5 //Velocity at section 1(in m/sec):
```



```

6 V1=V2*A2/A1
7 //Gauge pressure(in kPa):
8 p1g=p1-patm
9 u1=V1;u2=-V2;
10 //Reaction force component in the x direction(in N):
11 Rx=-p1g*A1-u1*d*V1*A1
12 //Reaction force component in the y direction(in N):
13 Ry=u2*d*V2*A2
14 printf("\n\nRESULTS\n\n")
15 printf("\n\nForce to hold elbow acting to the left:
    %.3f kN\n\n",Rx/1000)
16 printf("\n\nForce to hold elbow acting downwards: %
    .3f N\n\n",Ry)

```

check Appendix [AP 63](#) for dependency:

4_08.sci

Scilab code Exa 4.08 Tension

```

1 //Tension//
2 filename=pathname+filesep()+ '4.08-data.sci '
3 exec(filename)
4 //Tension required to pull the belt(in lbf):
5 T=Vbelt*m/32.2
6 printf("\n\nRESULTS\n\n")
7 printf("\n\nTension required to pull the belt: %.3f
    lbf\n\n",T)

```

check Appendix [AP 62](#) for dependency:

4_09.sci

Scilab code Exa 4.09 pressure required

```

1 //pressure required//
2 pathname=get_absolute_file_path('4.09.sce')
3 filename=pathname+filesep()+ '4.09-data.sci'
4 exec(filename)
5 //Minimum gauge pressure required(in lbf/in^2):
6 pg=8/%pi^2*d/D1^4*Q^2*((D1/D2)^4-1)*144
7 printf("\n\nRESULTS\n\n")
8 printf("Minimum gauge pressure required: %.3f lbf/in
    ^2",pg)

```

check Appendix [AP 61](#) for dependency:

4_10.sci

Scilab code Exa 4.10 Net force

```

1 //Net force//
2 pathname=get_absolute_file_path('4.10.sce')
3 filename=pathname+filesep()+ '4.10-data.sci'
4 exec(filename)
5 u1=V-U
6 u2=(V-U)*cosd(theta)
7 v2=(V-U)*sind(theta)
8 V1=V-U
9 V2=V1
10 //X component of moment equation(in N):
11 function y=f(A),y=u1*-(d*V1),endfunction
12 function z=g(A),z=u2*d*V2,endfunction
13 Rx=intg(0,A,f)+intg(0,A,g)
14
15 //Y component of moment equation(in N):
16 function a=h(A),a=v2*d*V1,endfunction
17 Ry=intg(0,A,h) //This is after neglecting weight of
    vane and the water.
18 printf("\n\nRESULTS\n\n")
19 printf("\n\nNet force on the vane: %.3f i+%.2f j kN\
    n\n",Rx/1000,Ry/1000)

```

check Appendix [AP 60](#) for dependency:

4_11.sci

Scilab code Exa 4.11 PLOTTING

```
1 //PLOTTING//
2 pathname=get_absolute_file_path('4.11.sce')
3 filename=pathname+filesep()+ '4.11-data.sci'
4 exec(filename)
5 //Evaluating the value of Vb:
6 Vb=V*(1-cosd(theta))*d*A/M
7 //Value of U/V for various values of t
8 t=0:20;
9 [m n]=size(t)
10 for i=1:n
11     U_V(i)=Vb*t(i)/(1+Vb*t(i));
12 end
13
14 //Plotting U/V vs t:
15 plot(t,U_V)
16 xtitle('U/V vs t','t (in sec)','U/V')
```

check Appendix [AP 59](#) for dependency:

4_12.sci

Scilab code Exa 4.12 Velocity of rocket

```
1 //Velocity of rocket//
2 pathname=get_absolute_file_path('4.12.sce')
3 filename=pathname+filesep()+ '4.12-data.sci'
4 exec(filename)
```

```

5 //Acceleration of rocket at t=0(in m/sec^2):
6 Ve*me/M0-g
7 //Velocity of rocket at t=10 (in m/sec):
8 function y=f(t),y=Ve*me/(M0-me*t)-g, endfunction
9 Vcv=intg(0,t,f)
10 printf("\n\nRESULTS\n\n")
11 printf("\n\nVelocity of rocket at t=10: %.1f m/sec\n\n",Vcv)

```

check Appendix [AP 58](#) for dependency:

4_14.sci

Scilab code Exa 4.14 Relative speed and friction

```

1 //Relative speed and friction//
2 pathname=get_absolute_file_path('4.14.sce')
3 filename=pathname+filesep()+ '4.14-data.sci'
4 exec(filename)
5 //Area of jet(in mm^2):
6 Ajet=%pi/4*D^2
7 //Jet speed relative to the nozzle(in m/sec):
8 Vrel=Q/2/Ajet*10^6/60/1000
9 //Value of w*R in m/sec:
10 wR=w*R*2*%pi/60/1000
11 //Friction torque at pivot(in N-m):
12 Tf=R*(Vrel*cosd(alpha)-wR)*d*Q/1000/60/1000
13 printf("\n\nRESULTS\n\n")
14 printf("\n\nJet speed relative to each nozzle: %.2f\n\n",Vrel)
15 printf("\n\nFriction torque at pivot: %.5f N-m\n\n",Tf)

```

check Appendix [AP 57](#) for dependency:

4_16.sci

Scilab code Exa 4.16 Rate of heat

```
1 //Rate of heat//
2 pathname=get_absolute_file_path('4.16.sce')
3 filename=pathname+filesep()+ '4.16-data.sci'
4 exec(filename)
5 //Velocity at exit(in ft/sec):
6 V2=m*R*(T2+460)/A2/p2/144
7 //As power input is to CV, Ws=-600
8 //Rate of heat transfer(in Btu/sec):
9 Q=Ws*550/778+m*cp*(T2-T1)+m*V2^2/2/32.2/778
10 printf("\n\nRESULTS\n\n")
11 printf("\n\nRate of heat transfer: %.3f Btu/sec\n\n",Q)
```

check Appendix [AP 56](#) for dependency:

4_17.sci

Scilab code Exa 4.17 Mass flow rate

```
1 //Mass flow rate//
2 pathname=get_absolute_file_path('4.17.sce')
3 filename=pathname+filesep()+ '4.17-data.sci'
4 exec(filename)
5 //Density of tank(in kg/m^3):
6 d=(p1+patm)/R/T
7 //Mass flow rate of air into the tank(in kg/sec):
8 m=d*V*cv*r/R/T*1000
9 printf("\n\nRESULTS\n\n")
10 printf("\n\nMass flow rate of air into the tank: %.3f g/sec\n\n",m)
```

Chapter 5

Introduction to Differential Analysis of Fluid Motion

check Appendix [AP 55](#) for dependency:

5_02.sci

Scilab code Exa 5.02 Rate of change

```
1 //Rate of change//
2 pathname=get_absolute_file_path('5.02.sce')
3 filename=pathname+filesep()+ '5.02-data.sci '
4 exec(filename)
5 //Rate of change of density with time(in kg/m^3-s):
6 r=-d*V/L
7 printf("\n\nRESULTS\n\n")
8 printf("\n\nRate of change of density with time: %.1
   f kg/m^3-s\n\n",r)
```

check Appendix [AP 54](#) for dependency:

5_07.sci

Scilab code Exa 5.07 angular and rotation

```
1 //angular and rotation//
2 pathname=get_absolute_file_path('5.07.sce')
3 filename=pathname+filesep()+ '5.07-data.sci'
4 exec(filename)
5 //At point b, u=3 mm/sec
6 u=3;
7 //Displacemet of b(in mm):
8 xb=u*t
9 //Rate of angular deformation(in s-1):
10 def=U/h
11 //Rate of rotation(in s-1):
12 rot=-0.5*U/h
13 printf("\n\nRESULTS\n\n")
14 printf("\n\nRate of angular deformation: %.1f /sec\n\n",def)
15 printf("\n\nRate of rotation: %.1f /sec\n\n",rot)
```

check Appendix [AP 53](#) for dependency:

5_08.sci

Scilab code Exa 5.08 Rates and area

```
1 //Rates and area//
2 pathname=get_absolute_file_path('5.08.sce')
3 filename=pathname+filesep()+ '5.08-data.sci'
4 exec(filename)
5 //Value of T:
6 T=log(3/2)/A
7 x0=1:2;
8 y0=1:2;
9 for i=1:2
10     for j=1:2
11         //For X coordinate:
```

```

12   X(i)(j)=x0(i)*%e^(A*T)
13   //For Y coordinate:
14   Y(i)(j)=y0(j)*%e^(-A*T)
15   end
16 end
17 plot(X,Y)
18 //Rates of linear deformation in X direction:
19 Ax=0.3;
20 //Rate of linear deformation in the y direction:
21 Ay=-0.3;
22 //Rate of volume dilation(s^-1):
23 v=A-A
24 //Area of abcd:
25 A1=1;
26 //Area of a'b'c'd':
27 A2=(3-3/2)*(4/3-2/3)
28 printf("\n\nRESULTS\n\n")
29 printf("\n\nRates of linear deformation in X and Y
        direction: %.1f /s , %.1f /s\n\n",Ax,Ay)
30 printf("\n\nRate of volume dilation: %.0f /sec\n\n",
        v)
31 printf("\n\nArea of abcd and a,b,c,d:%.1f m^2, %.1f
        m^\n\n",A1,A2)

```

check Appendix [AP 52](#) for dependency:

5_09.sci

Scilab code Exa 5.09 Volume flow rate

```

1 //Volume flow rate//
2 pathname=get_absolute_file_path('5.09.sce')
3 filename=pathname+filesep()+ '5.09-data.sci'
4 exec(filename)
5 //Volume flow rate(in m^3/sec):
6 Q=d*g*sind(theta)*b*(h/1000)^3*1000/u/3

```



```
7 printf("RESULTS")
8 printf("\n\nVolume flow rate: %.4f m^3/sec\n\n",Q)
```

Chapter 6

Incompressible Inviscid Flow

check Appendix [AP 51](#) for dependency:

6_01.sci

Scilab code Exa 6.01 Volume flow rate

```
1 //Volume flow rate//
2 pathname=get_absolute_file_path('06.01.sce')
3 filename=pathname+filesep()+ '06.01-data.sci'
4 exec(filename)
5 //Velocity of flow(in m/sec):
6 V=sqrt(dw/log((r+w)/r)*g/da*p/1000)
7 //Volume flow rate(in m^3/sec):
8 Q=V*(d*w)
9 printf("\n\nRESULTS\n\n")
10 printf("\n\nVolume flow rate: %.3f m^3/sec\n\n",Q)
```

check Appendix [AP 50](#) for dependency:

6_02.sci

Scilab code Exa 6.02 Velocity of flow

```
1 //Velocity of flow//
2 pathname=get_absolute_file_path('06.02.sce')
3 filename=pathname+filesep()+ '06.02-data.sci'
4 exec(filename)
5 //Velocity of flow(in m/sec):
6 V=sqrt(2*dw*g*p/1000*SG/da)
7 printf("\n\nRESULTS\n\n")
8 printf("\n\nVelocity of flow: %.3f m/sec\n\n",V)
```

check Appendix [AP 49](#) for dependency:

6_03.sci

Scilab code Exa 6.03 prssure required

```
1 //prssure required//
2 filename=pathname+filesep()+ '06.03-data.sci'
3 exec(filename)
4 //Velocity of flwat the inlet(in m/sec):
5 V1=Ae/Ai*V2
6 //Gauge pressure required at the inlet(in kPa):
7 p=0.5*da*(V2^2-V1^2)
8 printf("\n\nRESULTS\n\n")
9 printf("\n\nGauge prssure required at the inlet: %.3
   f kPa\n\n",p/1000)
```

check Appendix [AP 48](#) for dependency:

6_04.sci

Scilab code Exa 6.04 Speed and pressure

```

1 //Speed and pressure//
2 pathname=get_absolute_file_path('06.04.sce')
3 filename=pathname+filesep()+ '06.04-data.sci'
4 exec(filename)
5 //Speed of water at exit(in m/sec):
6 V2=sqrt(2*g*z)
7 //Pressure at point A in the flow(kPa):
8 pA=p1+d*g*(0-l)-0.5*d*V2^2
9 printf("\n\nRESULTS\n\n")
10 printf("\n\nSpeed of water at exit: %.3f m/sec\n\n",
    V2)
11 printf("\n\nPressure at point A in the flow: %3f kPa
    \n\n",pA/1000)

```

check Appendix [AP 47](#) for dependency:

6_05.sci

Scilab code Exa 6.05 flow

```

1 //flow//
2 pathname=get_absolute_file_path('06.05.sce')
3 filename=pathname+filesep()+ '06.05-data.sci'
4 exec(filename)
5 //Velocity of flow at the exit(in ft/sec):
6 V2=sqrt(2*g*(Du-Dd/12))
7 //Volume flow rate/width(ft^2/sec):
8 Q=V2*Dd/12
9 printf("\n\nRESULTS\n\n")
10 printf("\n\nVelocity of flow at the exit: %.3f ft/
    sec\n\n",V2)
11 printf("\n\nVolume flow rate/width: %.3f ft^2/sec\n\n",
    Q)

```

check Appendix [AP 46](#) for dependency:

6_06.sci

Scilab code Exa 6.06 pressure

```
1 //pressure//
2 pathname=get_absolute_file_path('06.06.sce')
3 filename=pathname+filesep()+ '06.06-data.sci'
4 exec(filename)
5 //Pressure of air at 1000 m(in N/m^2):
6 p=P1*pa
7 //Density of air at 1000m(in kg/m^3):
8 d=D1*da
9 //Stagnation pressure at A(in kPa):
10 p0A=p+0.5*d*(V*1000/3600)^2
11 //Static pressure at B(in kPa):
12 pB=p+d/2*((V*1000/3600)^2-Vb^2)
13 printf("\n\nRESULTS\n\n")
14 printf("\n\nStagnation pressure at A: %.3f kPa\n\n",
        p0A/1000)
15 printf("\n\nStatic pressure at B: %.3f kPa\n\n",pB
        /1000)
```

check Appendix [AP 45](#) for dependency:

6_08.sci

Scilab code Exa 6.08 temperature

```
1 //temperature//
2 pathname=get_absolute_file_path('06.08.sce')
3 filename=pathname+filesep()+ '06.08-data.sci'
4 exec(filename)
5 //Velocity of flow at exit(in ft/sec):
6 V4=sqrt(2*g*(z3-0))
```

```

7 //Mass flow rate of water(in slug/sec):
8 m=d*V4*A4/144
9 //Rise in temperature between points 1 and 2(in R):
10 T=Q*3413/3600/m/32.2
11 printf("\n\nRESULTS\n\n")
12 printf("\n\nRise in temperature between points 1 and
      2: %.3 f R\n\n",T)

```

check Appendix [AP 44](#) for dependency:

6_09.sci

Scilab code Exa 6.09 Streamline flow

```

1 //Streamline flow//
2 pathname=get_absolute_file_path('06.09.sce')
3 filename=pathname+filesep()+ '06.09-data.sci'
4 exec(filename)
5 t=0:5
6 //Value of sqrt(2gh):
7 x=sqrt(2*g*h)
8 //Value of 1/2L*sqrt(2gh):
9 y=1/2/L*x
10 [m n]=size(t)
11 i=1:n;
12 //Velocity(in m/sec):
13 V2=x*tanh(y*t(i))
14 plot(t,V2);
15 xtitle('Streamline flow from 1 to 2','Time(in s)',
      V2('in m/sec'))

```

Chapter 7

Dimensional Analysis and Similitude

check Appendix [AP 43](#) for dependency:

7_04.sci

Scilab code Exa 7.04 speed and force

```
1 //speed and force//
2 pathname=get_absolute_file_path('7.04.sce')
3 filename=pathname+filesep()+ '7.04-data.sci'
4 exec(filename)
5 //Velocity of prototype in ft/sec
6 Vp1=Vp*6080/3600
7 //Reynolds number of prototype:
8 Rep=Vp1*Dp/vp
9 //Rep=Rem
10 //Therefore:
11 Rem=Rep;
12 //Velocity of air for wind tunnel(in ft/sec):
13 Vm=Rem*vm/(Dm/12)
14 //Drag force on prototype(in lbf):
15 Fp=Fm*(dp/dm)*(Vp1/Vm)^2*(Dp/(Dm/12))^2
```

```

16 printf("\n\nRESULTS\n\n")
17 printf("\n\nTest speed in air: %.3f ft/sec\n\n",Vm)
18 printf("\n\nDrag force on prototype: %.3f lbf\n\n",
    Fp)

```

check Appendix [AP 42](#) for dependency:

7_05.sci

Scilab code Exa 7.05 speed force and power

```

1 //speed force and power//
2 pathname=get_absolute_file_path('7.05.sce')
3 filename=pathname+filesep()+ '7.05-data.sci'
4 exec(filename)
5 //Width of the model(in m):
6 wm=S*wp*0.3048
7 //Area of model (in m^2):
8 Am=S^2*Ap*0.305^2
9 [m n]=size(V)
10 i=1:n
11 //Aerodynamic drag coefficient():
12 Cd=2.*Fd(i)/d./(V(i))^2/0.0305
13 //Reynolds number:
14 Re=V(i)*wm/v
15 plot(Re,Cd);
16 a=gca()
17 a.data_bounds=[100000,0.4;500000,0.6]
18 xtitle('Aerodynamic drag coefficient vs drag force',
    'Reynolds number','Model Drag Coeff.')
19 //It is seen that drag coefficient becomes constant
    at CD=0.46above Re=4*10^5 at which speed of air
    is 40m/s
20 CDc=0.46;
21 Va=40;
22 //Drag force (in N):

```



```

23 FDp=CDc/2*d*(Vp*5/18)^2*Ap*0.305^2
24 //Power required to pull prototype at 100 kmph(in W)
25 Pp=FDp*Vp*5/18
26 printf("\n\nRESULTS\n\n")
27 printf("\n\nSpeed above which Cd is constant: %.3f m
    /sec\n\n",Va)
28 printf("\n\nDrag Force: %.3f kN\n\n",FDp/1000)
29 printf("\n\nPower required to pull prototype at 100
    kmph: %.3f kW\n\n",Pp/1000)

```

check Appendix [AP 41](#) for dependency:

7_06.sci

Scilab code Exa 7.06 power and speed

```

1 //power and speed//
2 pathname=get_absolute_file_path('7.06.sce')
3 filename=pathname+filesep()+ '7.06-data.sci'
4 exec(filename)
5 //The same pump is used for both the conditions.
    Hence:
6 D2=D1;
7 //The same water is used for both the conditions.
    Hence:
8 d2=d1;
9 //Flow rate at condition 2(in gpm):
10 Q2=Q1*N2/N1*(D2/D1)^3
11 //Head at condition 1(in ft):
12 H1=(N1*sqrt(Q1)/Nscu1)^(4/3)
13 //Head at condition 1(in ft):
14 H2=H1*(N2/N1)^2*(D2/D1)^2
15 //Pump output power at condition 1(in hp):
16 P1=d1*g*Q1*H1/7.48/60/550
17 //Pump output power at condition 2(in hp):
18 P2=P1*(d2/d1)*(N2/N1)^3*(D2/D1)^5

```

```

19 //Required input power(in hp):
20 Pin=P2/Effp
21 //Specific speed at condition 2:
22 Nscu2=N2*sqrt(Q2)/H2^(3/4)
23 printf("\n\nRESULTS\n\n\n")
24 printf("\n\nVolume flow rate at condition 2: %.3f
    gpm\n\n\n",Q2)
25 printf("\n\nHead at condition: %.3f ft\n\n\n",H2)
26 printf("\n\nPump output power at condition: %.3f hp\
    n\n\n",P2)
27 printf("\n\nRequired input power: %.3f hp\n\n\n",Pin
    )
28 printf("\n\nSpecific speed at condition 2: %.3f\n\n\
    n",Nscu2)

```

Chapter 8

Internal Incompressible Viscous Flow

check Appendix [AP 40](#) for dependency:

8_01.sci

Scilab code Exa 8.01 Leakage flow rate

```
1 //Leakage flow rate//
2 pathname=get_absolute_file_path('8.01.sce')
3 filename=pathname+filesep()+ '8.01-data.sci'
4 exec(filename)
5 //Leakage flow rate (in mm3/sec):
6 Q=%pi/12*D*a3*(p1-p2)*103/u/L
7 //Velocity of flow(in m/sec):
8 V=Q/%pi/D/a/1000
9 //Specific gravity of SAE 10W oil:
10 SG=0.92;
11 //Reynolds Number:
12 Re=SG*dw*V*a/u/1000
13 //As Re<1400, flow is laminar.
14 printf("\n\nRESULTS\n\n")
15 printf("\n\nLeakage flow rate: %.3f mm3/sec\n\n",Q)
```

check Appendix [AP 39](#) for dependency:

8_02.sci

Scilab code Exa 8.02 Torque and power

```
1 //Torque and power//
2 pathname=get_absolute_file_path('8.02.sce')
3 filename=pathname+filesep()+ '8.02-data.sci'
4 exec(filename)
5 //Shear stres (in lbf/ft^2):
6 Tyx=u*N*2*%pi/60*D/2/(a/2)
7 //Torque(in inches-lbf):
8 T=%pi/2*Tyx*D^2*L/144
9 //Power dissipated in the bearing(in hp):
10 P=T*N/60*2*%pi/12/550
11 //Reynolds number:
12 Re=SG*p*N*2*%pi/60*1.5*a/2/u/144
13 printf("\n\nRESULTS\n\n")
14 printf("\n\nTorque: %.3f inches-lbf\n\n",T)
15 printf("\n\nPower dissipated in the bearing: %.3f hp
    \n\n",P)
```

check Appendix [AP 38](#) for dependency:

8_04.sci

Scilab code Exa 8.04 Viscosity of fluid

```
1 //Viscosity of fluid//
2 pathname=get_absolute_file_path('8.04.sce')
3 filename=pathname+filesep()+ '8.04-data.sci'
4 exec(filename)
```

```

5 //Viscosity of the liquid(in N-s/m^2):
6 u=%pi/128*p*1000*D^4/Q/L/1000
7 //Velocity(in m/sec)
8 V=Q/(%pi/4*D^2)/1000
9 //Reynolds number:
10 Re=d*V*D/u/1000
11 printf("\n\nRESULTS\n\n")
12 printf("\n\nViscosity of fluid %.3f N-s/m^2\n\n",u)

```

check Appendix [AP 37](#) for dependency:

8_05.sci

Scilab code Exa 8.05 required

```

1 //required//
2 pathname=get_absolute_file_path('8.05.sce')
3 filename=pathname+filesep()+ '8.05-data.sci'
4 exec(filename)
5 //Reservoir depth required to maintain flow(in m):
6 D1=8*Q^2/(%pi)^2/D^4/g*(f*L/D+K+1)
7 //Reynolds number:
8 Re=4*d*Q/((%pi)*u*D)
9 printf("\n\nRESULTS\n\n")
10 printf("\n\nReservoir depth required to maintain
    flow: %.3f m\n\n",D1)

```

check Appendix [AP 36](#) for dependency:

8_06.sci

Scilab code Exa 8.06 Maximum and power

```

1 //Maximum and power//
2 pathname=get_absolute_file_path('8.06.sce')
3 filename=pathname+filesep()+ '8.06-data.sci'
4 exec(filename)
5 //Velocity of flow(in ft/sec):
6 V=Q/24/3600/(%pi/4*(D/12)^2)*42/7.48
7 //Maximum spacing(in ft):
8 L=2/f*D/12*(p2-p1)/(SG*d)/V^2*144
9 //Power needed at each pump(in hp):
10 Win=1/Effp*V*%pi/4*(D/12)^2*(p2-p1)/550*144
11 printf("\n\nRESULTS\n\n")
12 printf("\n\nMaximum spacing: %.3f feet\n\n",L)
13 printf("\n\nPower needed at each pump: %.3f hp\n\n",
    Win)

```

check Appendix [AP 35](#) for dependency:

8_07.sci

Scilab code Exa 8.07 Volume low

```

1 //Volume low//
2 pathname=get_absolute_file_path('8.07.sce')
3 filename=pathname+filesep()+ '8.07-data.sci'
4 exec(filename)
5 //Velocity(in ft/sec):
6 V2=sqrt(2*g*1/(f*((L+1)/D*12+8)+1))
7 //Volume flow rate(in gpm):
8 Q=V2*%pi*(D/12)^2/4*7.48*60
9 printf("\n\nRESULTS\n\n")
10 printf("\n\nVolume low rate: %.3f\n\n",Q)

```

check Appendix [AP 34](#) for dependency:

8_08.sci

Scilab code Exa 8.08 Minimum diameter

```
1 //Minimum diameter//
2 pathname=get_absolute_file_path('8.08.sce')
3 filename=pathname+filesep()+ '8.08-data.sci'
4 exec(filename)
5 //Value of dPmax(in psi):
6 dPmax=p1-p2
7 //Q in cubic feet/sec:
8 Q1=1500/60/7.48;
9 //Initially assume diameter to be 4inches:
10 D=4;
11 //Reynolds number:
12 Re=4*Q1/%pi/v/D*12
13 //For this value ,
14 f=0.012;
15 dP=8*f*L*p*Q1^2/(%pi)^2/D^5*1728;
16 while(dP>dPmax)
17     dP=8*f*L*p*Q1^2/(%pi)^2/D^5*1728;
18     if(dP<dPmax)
19         break
20     else
21         D=D+1;
22     end
23 end
24 printf("\n\nRESULTS\n\n")
25 printf("Minimum diameter that can be used:%.1f
    inches\n\n",D)
```

check Appendix [AP 33](#) for dependency:

8_09.sci

Scilab code Exa 8.09 Loss Coefficient

```
1 //Loss Coefficient//
```

```

2 pathname=get_absolute_file_path('8.09.sce')
3 filename=pathname+filesep()+ '8.09-data.sci'
4 exec(filename)
5 //Average velocity (in ft/s):
6 V2=4/%pi*Q/D^2*144
7 //Reynolds number:
8 Re=V2*D/v/12
9 //For this value ,
10 f=0.013;
11 //Power law exponent:
12 n=-1.7+1.8*log10(Re)
13 //Value of V/U:
14 v_u=2*n^2/(n+1)/(2*n+1)
15 //Value of alpha:
16 alpha=(1/v_u)^3*2*n^2/(3+n)/(3+2*n)
17 //Loss Coefficient for a square edged entrance:
18 K=2*g*h/V2^2-f*L/D*12-alpha;
19 printf("\n\nRESULTS\n\n")
20 printf("\n\nLoss Coefficient for a square edged
    entrance: %.3f \n\n",K)

```

check Appendix [AP 32](#) for dependency:

8_10.sci

Scilab code Exa 8.10 Volume and increase

```

1 //Volume and increase//
2 pathname=get_absolute_file_path('8.10.sce')
3 filename=pathname+filesep()+ '8.10-data.sci'
4 exec(filename)
5 //Velocity V1(in m/s):
6 V1=sqrt(2*g*z0/1.04)
7 //Volume flow rate(in m^3/sec):
8 Q=V1*%pi*D^2/4
9 Kdiff=1-1/A_R^2-Cp

```



```

10 //For 2nd case:
11 //Velocity(in m/s):
12 V1=sqrt(2*g*z0/0.59)
13 //Volume flow rate(in m^3/s):
14 Qd=V1*pi*D^2/4
15 //Increase in discharge after addition of diffuser
    is:
16 dQ=(Qd-Q)/Q*100
17 printf("\n\nRESULTS\n\n")
18 printf("\n\nVolume flow rate in case1: %.3f m^3/sec\n
    n\n",Q)
19 printf("\n\nVolume flow rate in case 2: %.3f m^3/sec
    \n\n",Qd)
20 printf("\n\nIncrease in discharge after addition of
    diffuser is: %.3f percent\n\n",dQ)

```

check Appendix [AP 31](#) for dependency:

8_11.sci

Scilab code Exa 8.11 Diameter and head

```

1 //Diameter and head//
2 pathname=get_absolute_file_path('8.11.sce')
3 filename=pathname+filesep()+ '8.11-data.sci'
4 exec(filename)
5
6 //Value of K*B^2:
7 K_B=Q/(%pi/4*D^2)*sqrt(0.5*d1/g/d2/h)
8 //Reynods number:
9 ReD1=4/%pi*Q/D/v
10 //By trial and error method, the value of beta is
    fixed at:
11 beta=0.66;
12 //K is then:
13 K=K_B/betta^2

```

```

14 //Diameter of orifice plate(in m):
15 Dt=beta*D
16 //Value of p3-p2(in N/m^2):
17 P1=d1*Q^2/(%pi/4*D^2)^2*(1/0.65/betta^2-1)
18 //Value of p1-p2(in N/m^2):
19 P2=d2*g*h
20 //Head loss between sections 1 and 3(in N-m/kg):
21 hLT=(P2-P1)/d1
22 //Expressing the permanent pressure as a fractio of
    the meter differential:
23 C=(P2-P1)/P2
24 printf("\n\n\nRESULTS\n\n\n")
25 printf("\n\nDiameter of the orifice: %.3f m\n\n",Dt)
26 printf("\n\nHead loss between seicions 1 and 3: %.3f
    N-m/kg\n\n",hLT)

```

Chapter 9

External Incompressible Viscous Flow

check Appendix [AP 30](#) for dependency:

9_01.sci

Scilab code Exa 9.01 static pressure

```
1 //static pressure//
2 pathname=get_absolute_file_path('9.01.sce')
3 filename=pathname+filesep()+ '9.01-data.sci'
4 exec(filename)
5 //Change in static pressure between sections 1 and
   2:
6 C=(((L-2*d1)/(L-2*d2))^4-1)*100;
7 printf("\n\nRESULTS\n\n")
8 printf("\n\nChange in static pressure between the
   sections 1 and 2: %.3f percent \n\n",C)
```

check Appendix [AP 29](#) for dependency:

9_04.sci

Scilab code Exa 9.04 Displacement thickness and stress

```
1 //Displacement thickness and stress//
2 pathname=get_absolute_file_path('9.04.sce')
3 filename=pathname+filesep()+ '9.04-data.sci'
4 exec(filename)
5 //Reynolds number:
6 ReL=U*L/v
7 //FOR TURBULENT FLOW
8 //Disturbance thickness(in m):
9 dL1=0.382/ReL^0.2*L
10 //Displacement thickness(in m):
11 function y=f(n),y=dL1*(1-n^(1/7))
12 endfunction
13 dl1=intg(0,1,f)
14 //Skin friction coefficient:
15 Cf1=0.0594/ReL^0.2
16 //Wall shear stress(in N/m^2):
17 tw1=Cf1*0.5*d*U^2
18 //For LAMINAR FLOW:
19 //Disturbance thickness(in m)
20 dL2=5/sqrt(ReL)*L
21 //Displacement thickness(in m):
22 dl2=0.344*dL2
23 //Skin friction coefficient:
24 Cf2=0.664/sqrt(ReL)
25 //Wall shear stress(in N/m^2):
26 tw2=Cf2*0.5*d*U^2
27 //COMPARISON OF VALUES WITH LAMINAR FLOW
28 //Disturbance thickness
29 D=dL1/dL2
30 //Displacement thickness
31 DS=dl1/dl2
32 //Wall shear stress
33 WSS=tw1/tw2
34 printf("\n\nRESULTS\n\n")
35 printf("\n\nDisturbace thickness: %.3f m\n\n",dL1)
36 printf("\n\nDisplacement thickness: %.3f m\n\n",dl1)
```

```

37 printf("\n\nWall shear stress: %f N/m^2\n\n",tw1)
38 printf("\n\nCOMPARISON WIH LAMINAR FLOW\n\n\n")
39 printf("\n\n Disturbance thicknes: %.3f \n\n",D)
40 printf("\n\nDisplacement thickness: %.3f\n\n",DS)
41 printf("\n\nWall shear stress: %.3f \n\n",WSS)

```

check Appendix [AP 28](#) for dependency:

9_05.sci

Scilab code Exa 9.05 force and power

```

1 //force and power//
2 pathname=get_absolute_file_path('9.05.sce')
3 filename=pathname+filesep()+ '9.05-data.sci'
4 exec(filename)
5 //Speed in m/s:
6 U=s*6076*0.305/3600
7 //Reynolds number:
8 Re=U*L/v
9 //Drag coefficient:
10 Cd=0.455/log10(Re)^2.58-1610/Re
11 //Area(in m^2):
12 A=L*(W+D)
13 //Drag force(in N)
14 Fd=Cd*A*0.5*d*U^2
15 //Power required to overcome skin friction drag(in W
   ):
16 P=Fd*U
17 printf("\n\nRESULTS\n\n\n")
18 printf("\n\nDrag force: %f N\n\n",Fd)
19 printf("\n\nPower required to overcome skin friction
   drag: %.3f W\n\n",P)

```

check Appendix [AP 27](#) for dependency:

9_06.sci

Scilab code Exa 9.06 Bending moment

```
1 //Bending moment//
2 pathname=get_absolute_file_path('9.06.sce')
3 filename=pathname+filesep()+ '9.06-data.sci'
4 exec(filename)
5 //Velocity in m/sec:
6 V=s*5/18
7 //Reynolds number:
8 Re=d*V*D/u
9 //Value of Cd is obtained as:
10 Cd=0.35;
11 //Area(in m^2):
12 A=L^2;
13 //Moment about the chimney base(in N-m):
14 M0=Cd*A*D/4*d*V^2
15 printf("\n\nRESULTS\n\n")
16 printf("\n\nBending moment at the bottom of the
    chimney: %.3f N-m\n\n",M0)
```

check Appendix [AP 26](#) for dependency:

9_07.sci

Scilab code Exa 9.07 Time required

```
1 //Time required//
2 pathname=get_absolute_file_path('9.07.sce')
3 filename=pathname+filesep()+ '9.07-data.sci'
4 exec(filename)
5 //Time required to decelerate to 100 mph(in seconds)
  :
```

```

6 t=(s1-s2)*2*w/(s1*s2)/Cd/d/A/g*3600/5280
7 printf("\n\nRESULTS\n\n")
8 printf("\n\nTime required to decelerate to 100 mph:
   %.3f seconds\n\n",t)

```

check Appendix [AP 25](#) for dependency:

9_08.sci

Scilab code Exa 9.08 Optimum cruise speed

```

1 //Optimum cruise speed//
2 pathname=get_absolute_file_path('9.08.sce')
3 filename=pathname+filesep()+ '9.08-data.sci'
4 exec(filename)
5 //Plotting velocity with drag force
6 V=175:25:455;
7
8 [m n]=size(V);
9 for i=1:n
10   CL(i)=2*W/p*(3600/V(i)/5280)^2/A;
11   Cd(i)=Cd0+CL(i)^2/%pi/ar;
12   Fd(i)=Cd(i)/CL(i)*W;
13   FD(i)=Fd(i)/1000;
14 end
15 plot(V,FD)
16 xtitle('Flight speed vs thrust','Flight Speed(in mph
   )','Drag Force(in 1000lbf)')
17 //Optimum cruise speed at speed level is obtained to
   be 320 mph from the graph.
18 Vosl=320;
19 //Ratio of speeds at 30000 ft and at sea level is
   given by:
20 r=sqrt(1/0.375);
21 //Stall speed at 30000 ft is (in mph):
22 Vs3=Vssl*r;

```

```

23 //Optimum Cruise speed at 30000 ft (in mph):
24 Vo3=Vos1*r;
25 printf("\n\nRESULTS\n\n")
26 printf("\n\nOptimum cruise speed at sea level: %.3f
    mph\n\n", Vos1)
27 printf("\n\nStall speed at 30000 ft: %.3f mph\n\n",
    Vs3)
28 printf("\n\nOptimum cruise speed at 30000 ft: %.3f\n
    \n", Vo3)

```

check Appendix [AP 24](#) for dependency:

9_09.sci

Scilab code Exa 9.09 Aerodynamic and Radius

```

1 //Aerodynamic and Radius//
2 pathname=get_absolute_file_path('9.09.sce')
3 filename=pathname+filesep()+ '9.09-data.sci'
4 exec(filename)
5 //Reynolds number:
6 //Value of wD/2V:
7 W=0.5*N*D/1000/V*2*pi/60
8 Red=V*D/v;
9 //For this value, CL is obtained as:
10 CL=0.3;
11 //Aerodynamic lift(in N):
12 FL=pi/8*CL*(D/1000)^2*d*V^2;
13 //Radius of curvature of the path in the vertical
    plane(in m) with topspin:
14 Rts=V^2/(g+FL/(m/1000));
15 //Radius of curvature without topspin(in m):
16 Rwts=V^2/g;
17 printf("\n\nRESULTS\n\n")
18 printf("\n\nAerodynamic lift acting on the ball: %.3f
    N\n\n", FL)

```



```
19 printf("\n\nRadius of curvature of the path when
    ball has topspin: %.3f m\n\n", Rts)
20 printf("\n\nRadius of curvature of the path when
    ball has topspin: %.3f m\n\n", Rwts)
```

Chapter 10

Fluid Machinery

check Appendix [AP 23](#) for dependency:

10_01.sci

check Appendix [AP 17](#) for dependency:

10_11.sci

Scilab code Exa 10.01 input and power

```
1 //input and power//
2 pathname=get_absolute_file_path('10.01.sce')
3 filename=pathname+filesep()+ '10.01-data.sci'
4 exec(filename)
5 //Impeller exit width b2(in feet):
6 b2=Q*12/(2*pi*R2*Vrb2*7.48*60)
7 //Torque of the Shaft, Tshaft(in ft-lbf):
8 Tshaft=w*R2^2*p*Q*2*pi/3600/7.48/144
9 //Power, Wm(in hp):
10 Wm=w*Tshaft*2*pi/60/550
11 printf("\n\nRESULTS\n\n")
12 printf("\n\nImpeller exit width: %.3f feet\n\n",b2)
13 printf("\n\nTorque input: %.3f ft-lbf\n\n",Tshaft)
14 printf("\n\nPower: %.3f hp\n\n",Wm)
```

Scilab code Exa 10.1 Performance curves

```
1 //Performance curves//
2 pathname=get_absolute_file_path('10.11.sce')
3 filename=pathname+filesep()+ '10.11-data.sci'
4 exec(filename)
5 [nQ mQ]= size(Q1);
6 [np mp]= size(p1);
7 [nP mP]= size(P1);
8 //Volume flow rate for fan 2(in cfm):
9 j=1:mQ;
10 Q2=Q1(j)*(N2/N1)*(D2/D1)^3
11 //Pressure values for fan 2(in inches of H2O):
12 j=1:mp;
13 p2=p1(j)*(d2/d1)*((N2/N1)^2)*((D2/D1)^2)
14 //Power values for fan 2(in hp):
15 j=1:mP;
16 P2=P1(j)*(d2/d1)*((N2/N1)^3)*((D2/D1)^5)
17 plot(Q2,p2)
18 xtitle('Performance curves','Volume flow rate(in cfm
    )','Pressure head(in inches of water)')
19 printf("\n\nType (resume) to continue or (abort) to
    exit\n\n")
20 pause
21 clf
22 plot(Q2,P2)
23 xtitle('Performance curves','Volume flow rate(in cfm
    )','Power(in hp)')
24 printf("\n\nType (resume) to continue or (abort) to
    exit\n\n")
25 pause
26 clf
27 plot(Q2,Eff)
28 xtitle('Performance curves','Volume flow rate(in cfm
```

```

    )', 'Efficiency (in percentage)')
29 // Specific speed of fan (in US customary units) at
    operating point:
30 Nscu= 1150*110000^0.50*0.045^0.75/7.4^0.75
31 // Specific speed of fan (in SI units) at operating
    point:
32 Nssi=120*3110^0.5*0.721^0.75/1.84e3^0.75

```

check Appendix [AP 22](#) for dependency:

10_02.sci

Scilab code Exa 10.02 volume and power

```

1 //volume and power//
2 pathname=get_absolute_file_path('10.02.sce')
3 filename=pathname+filesep()+ '10.02-data.sci'
4 exec(filename)
5 U=0.5*(Dh+Dt)/2*1200*2*%pi/60
6 k=tand(alpha1)+cotd(betta1)
7 Vn1=U/k
8 V1=Vn1/cosd(alpha1)
9 Vt1=V1*sind(alpha1)
10 Vrb1=Vn1/sind(betta1)
11 //Volume flow rate (in m^3/sec):
12 Q=%pi/4*Vn1*(Dt^2-Dh^2)
13 k=(U-Vn1*cotd(betta2))/Vn1
14 alpha2= atand(k)
15 V2=Vn1/cosd(alpha2)
16 Vt2=V2*sind(alpha2)
17 //Rotor Torque (in N-m):
18 Tz=p*Q*(Dh+Dt)/4*(Vt2-Vt1)
19 //Power required (in W):
20 Wm=w*2*%pi/60*Tz
21 printf("\n\nRESULTS\n\n")
22 printf("\n\nVolume flow rate: %.3f m^3/sec\n\n",Q)

```

```

23 printf("\n\nRotor Torque: %.3 f N-m\n\n",Tz)
24 printf("\n\nPower required: %.3 f W\n\n",Wm)

```

check Appendix [AP 21](#) for dependency:

10_03.sci

Scilab code Exa 10.03 Pump Power

```

1 //Pump Power//
2 pathname=get_absolute_file_path('10.03.sce')
3 filename=pathname+filesep()+ '10.03-data.sci'
4 exec(filename)
5 [nQ mQ]= size(Q);
6 [nps mps]=size(ps);
7 [npd mpd]= size(pd);
8 [nI mI]= size(I);
9 //Correct measured static pressures to the pump
  centreline p1, p2(in psig):
10 j=1:mps;
11 p1=ps(j)+px*g*zs/144
12 j=1:mpd;
13 p2=pd(j)+px*g*zd/144
14 //The value of Pump head(in feet):
15 j=1:mps;
16 Hp=(p2(j)-p1(j))/(px*g)*144
17 //Values of Hydraulic Power delivered(in hp):
18 j=1:mps;
19 Wh=Q(j).*(p2(j)-p1(j))/7.48/60*144/550
20 //Values of motor power output(in hp):
21 j=1:mI;
22 Pin=Effm*sqrt(3)*PF*E*I(j)/746
23 //Values of Pump Efficiency:
24 j=1:mI;
25 Effp= Wh(j)./Pin(j)*100
26 //Plotting pump characteristics:

```

```

27     plot(Q, Hp, "-o")
28     plot(Q, Pin, "-+")
29     plot(Q, Effp, "-*")
30     xtitle('Pump Characteristics ', 'Volume flow rate (in
           gpm) ', ['Pump Efficiency (%) ', ' Pump Head (
           in feet) ', ' Pump Power input (in hp) '])
31     legend('Hp', 'Pin', 'Effp')

```

check Appendix [AP 20](#) for dependency:

10_06.sci

Scilab code Exa 10.06 Specific and relation

```

1 //Specific and relation//
2 pathname=get_absolute_file_path('10.06.sce')
3 filename=pathname+filesep()+ '10.06-data.sci'
4 exec(filename)
5 //Specific speed in Us customary units:
6 Nscu=N*Qus^0.5/Hus^0.75
7 //Conversion to SI units:
8 w=1170*2*%pi/60;
9 Qsi=Qus/7.48/60*0.305^3;
10 Hsi=Hus*0.305;
11 //Energy per unit mass is:
12 h=g*Hsi;
13 //Specific speed in SI units:
14 Nssi=w*Qsi^0.5/h^0.75
15 //Conversion to hertz:
16 whz=N/60;
17 //Specific speed in European units:
18 Nseu=whz*Qsi^0.5/65.5^0.75
19 //Relation between specific speeds in Us customary
    units and European units:
20 Conversionfactor1=Nscu/Nseu

```

```

21 //Relation between specific speeds in Us customary
    units and SI units:
22 Conversionfactor2=Nscu/Nssi
23 printf("\n\nRESULTS\n\n")
24 printf("\n\nSpecific speed in US customary units: %
    .3f \n\n",Nscu)
25 printf("\n\nSpecific speed in SI units: %.3f \n\n",
    Nssi)
26 printf("\n\nSpecific speed in European units: %.3f \n
    \n",Nseu)
27 printf("\n\nRelation between specific speeds in Us
    customary units and European units: %.3f \n\n",
    Conversionfactor1)
28 printf("\n\nRelation between specific speeds in Us
    customary units and SI units: %.3f \n\n",
    Conversionfactor2)

```

check Appendix [AP 19](#) for dependency:

10_07.sci

Scilab code Exa 10.07 Comparison of head

```

1 //Comparison of head//
2 pathname=get_absolute_file_path('10.07.sce')
3 filename=pathname+filesep()+ '10.07-data.sci'
4 exec(filename)
5 //Volume flow rate(in gpm) at shut off condition for
    N2:
6 Q2so=N2/N1*Q1so
7 //Volume flow(in gpm) rate at best efficiency for N2
    :
8 Q2be=N2/N1*Q1be
9 //Relation between pump heads:
10 head_relation=(N2/N1)^2
11 //Head(in feet) at shut off condition for N2:

```

```

12 H2so=(N2/N1)^2*H1so
13 //Head(in feet) at best efficiency condition for N2:
14 H2be=(N2/N1)^2*H1be
15 Q1=[Q1so Q1be];
16 Q2=[Q2so Q2be];
17 H1=[H1so H1be];
18 H2=[H2so H2be];
19 plot(Q1,H1,"-o")
20 plot(Q2,H2,"-*")
21 xtitle('Comparison of head for both conditions','
    Volume Flow Rate','Head')
22 legend('1170','1750')

```

check Appendix [AP 18](#) for dependency:

10_08.sci

Scilab code Exa 10.08 NPSHA and NPSHR

```

1 //NPSHA and NPSHR//
2 pathname=get_absolute_file_path('10.08.sce')
3 filename=pathname+filesep()+ '10.08-data.sci'
4 exec(filename)
5 //Diameter of pipe (in feet):
6 Df= Di/12
7 //Area of crossection of pipe(in ft^2):
8 A=%pi/4*Df^2
9 //Velocity of flow(in ft/sec):
10 V=Q/7.48/A/60
11 //For water at T=80F, viscosity=0.927e-5 ft^2/sec,
    Reynolds number:
12 Re=V*Df/v
13 //Friction loss Coefficient for this value of Re:
14 f=0.0237;
15 //For cast iron, roughness(in feet):
16 e=0.00085

```



```

17 //e/D is :
18 e/Df
19 //Total head loss(in feet):
20 HL=K+f*(SE+OGV)+f*(L/Df)+1
21 //The heads are(in feet):
22 H1=patm*144/(p*g)
23 Vh=V^2/2/g
24 //Suction head(in feet):
25 Hs=H1+h-HL*Vh
26 //NPSHA(in feet):
27 NPSHA=Hs+Vh-Hv1
28 //For a flow rate of 1000 gpm,NPSHR(in feet) for
    water at 80 F
29 NPSHR=10
30 //PLOTTING NPSHA AND NPSHR VERSUS VOLUME FLOW RATE:
31 //For 80 F
32 Qp=0:100:1500;
33 [nQp mQp]=size(Qp);
34 for j=1:mQp;
35 Vp(j)=Qp(j)/(7.48*A*60);
36 Vhp(j)=(Vp(j))^2/2/g;
37 Hs(j)=H1+h-HL*Vhp(j);
38 end
39
40 for j=1:mQp;
41 NPSHAp1(j)=Hs(j)+(Vhp(j))-Hv1;
42 end
43
44 plot(Qp,NPSHAp1,"-+")
45 plot(Qh,NPSHRp,"-o")
46 xtitle('Suction head vs Flow rate','Volume flow rate
    (gpm)','Suction Head(feet)');
47 printf("\n\nType (Resume) to continue or (abort) to
    end\n\n")
48 legend('NPSHA','NPSHR')
49 pause
50 clf
51

```

```

52 //For 180 F
53 for j=1:mQp;
54     NPSHAp2(j)=Hs(j)+(Vhp(j))-Hv2;
55 end
56 plot(Qp,NPSHAp2,"-+")
57 plot(Qh,NPSHRp,"-o")
58 xtitle('Suction head vs Flow rate','Volume flow rate
        (gpm)','Suction Head(feet)');
59 legend('NPSHA','NPSHR')
60 printf("\n\nRESULTS\n\n")
61 printf("\n\nNPSHA at Q=1000 gpm of water at 80 F: %
        .2 f ft\n\n",NPSHA)
62 printf("\n\nNPSHR at Q=1000 gpm of water at 80 F: %
        .1 f ft\n\n",NPSHR)

```

check Appendix [AP 16](#) for dependency:

10_12.sci

Scilab code Exa 10.12 Power required

```

1 //Power required//
2 pathname=get_absolute_file_path('10.12.sce')
3 filename=pathname+filesep()+ '10.12-data.sci'
4 exec(filename)
5 //From given graph, for maximum delivery condition,
   Q=48.5gpm.
6 //Volume of oil per revolution delivered by the pump
   (in in3/rev):
7 vc=Qe/N*231
8 //Volumetric Efficiency of pump at max flow:
9 Effv=vc/va
10 //Operating point of the pump is found to be at 1500
    psig ,Q=46.5gpm

```

```

11 //Power delivered by the fluid(in hp):
12 Pf=Qo*po1/7.48/60*144/550
13 //Input power(in hp):
14 Pi=Pf/Effp
15 //The power delivered to the load(in hp):
16 P1=Q*(po1)/7.48/60*144/550
17 //Power dissipated by throttling(in hp):
18 Pd=Pf-P1
19 //The dissipation with the variable displacement
    pump(in hp):
20 Pvd=Q*(po2-po1)/7.48/60*144/550
21 //Power required for te load sensing pump if pump
    pressure is 100psi above that required by the
    load(in hp):
22 P1s=Q*100/7.48/60*144/550
23 printf("\n\nRESULTS\n\n")
24 printf("\n\nVolume of oil per revolution delivered
    by the pump: %.3f in^3/rev\n\n",vc)
25 printf("\n\nRequired pump power input: %.3f hp\n\n",
    Pi)
26 printf("\n\nPower deliverd to the load: %.3f hp\n\n"
    ,P1)
27 printf("\n\nPower dissipated by throttling: %.3f hp\
n\n",Pd)
28 printf("\n\nThe dissipation with the variable
    displacement pump: %.3f hp\n\n",Pvd)
29 printf("\n\nPower required for te load sensing pump
    if pump pressure is 100psi above that required by
    the load: %.3f hp\n\n",P1s)

```

check Appendix [AP 15](#) for dependency:

10_14.sci

Scilab code Exa 10.14 propeller

```

1 //propeller//
2 pathname=get_absolute_file_path('10.14.sce')
3 filename=pathname+filesep()+ '10.14-data.sci'
4 exec(filename)
5 //Propeller Thrust(in MN) :
6 Ft=P/V
7 //Required power input to the propeller(in MW):
8 Pin=P/Eff
9 //Calculating value of D(in m):
10 nD=V/J
11 D=(Ft*10^6/p/(nD)^2/Cf)^0.5
12 //Operating speed (in rpm) is given by:
13 n=nD/D*60
14 printf("\n\nRESULTS\n\n")
15 printf("\n\nDiameter of the single propeller
    required to pwer the ship: %.3f m\n\n",D)
16 printf("\n\nOperating speed of the propeller: %.3f
    rpm\n\n",n)

```

check Appendix [AP 14](#) for dependency:

10_16.sci

Scilab code Exa 10.16 Actual

```

1 //Actual//
2 pathname=get_absolute_file_path('10.16.sce')
3 filename=pathname+filesep()+ '10.16-data.sci'
4 exec(filename)
5 //Tip speed ratio of windmill:
6 X=N*2*%pi/60*D/2/(V*5/18)
7 //Accounting for whirl,max attainable efficiency is:
8 Efw=0.53;
9 //Kinetic energy flux(in W) is given by:
10 KEF=0.5*p*(V*5/18)^3*%pi*(D/2)^2
11 //Actual Efficiency:

```

```
12 Effa=Po/KEF
13 //The maximum possible thrust occurs for an
    interference factor of:
14 amax=0.5;
15 //Thrust(in W):
16 Kx=p*(V*5/18)^2*pi*(D/2)^2*2*amax*(1-amax)
17 printf("\n\nRESULTS\n\n")
18 printf("\n\nTip speed ratio of windmill:%.3f\n\n",X)
19 printf("\n\nActual Efficiency: %.3f\n\n",Effa)
20 printf("\n\nActual Thrust: %.3f W\n\n",Kx)
```

Chapter 11

Introduction to Compressible Flow

check Appendix [AP 13](#) for dependency:

11_01.sci

Scilab code Exa 11.01 Change

```
1 //Change//
2 pathname=get_absolute_file_path('11.01.sce')
3 filename=pathname+filesep()+ '11.01-data.sci'
4 exec(filename)
5 //Density of air at entry:
6 d1=p1*10^3/R/T1
7 //Area(in m^2):
8 A=m/d1/V1
9 //Change in enthalpy of air(in kJ/kg):
10 dh=cp*(T2-T1)
11 //Change in internal energy of air(in kJ/kg):
12 du=cv*(T2-T1)
13 //Change in entropy(in kJ/(kg-K)):
14 ds=cp*log(T2/T1)-R/1000*log(p2/p1)
15 printf("\n\nRESULTS\n\n")
```

```

16 printf("\n\nDuct Area: %.3f m^2\n\n",A)
17 printf("\n\nChange in enthalpy of air: %.3f kJ/kg\n\n",dh)
18 printf("\n\nChange in internal energy of air: %.3f kJ/kg\n\n",du)
19 printf("\n\nChange in entropy: %.3f kg-K\n\n",ds)

```

check Appendix [AP 12](#) for dependency:

11_03.sci

Scilab code Exa 11.03 Speed of sound

```

1 //Speed of sound//
2 pathname=get_absolute_file_path('11.03.sce')
3 filename=pathname+filesep()+ '11.03-data.sci'
4 exec(filename)
5 //Values of altitude(in m):
6 A1=0:1000:15000
7 [nA1 mA1]=size(A1);
8 //Values of temperature at given altitudes(in K):
9 T=[288.2 281.7 275.2 268.7 262.2 255.7 249.2 242.7
    236.2 229.7 223.3 216.8 216.7 216.7 216.7 216.7];
10 [nT mT]=size(T);
11 //Values of speed of sound at these altitudes(in m/sec):
12 j=1:mT;
13 c=sqrt(k*R*T(j))
14 //Speed of sound at sea level(in m/sec):
15 c1=sqrt(k*R*T(1))
16 plot(c,A1)
17 xtitle('Variation of sound speed with altitude','Speed of sound(m/sec)','Altitude(m)')
18 printf("\n\nRESULTS\n\n")
19 printf("\n\nSpeed of sound at sea level: %.3f m/sec\n\n",c1)

```

check Appendix [AP 11](#) for dependency:

11_04.sci

Scilab code Exa 11.04 pressure and change

```
1 //pressure and change//
2 pathname=get_absolute_file_path('11.04.sce')
3 filename=pathname+filesep()+ '11.04-data.sci'
4 exec(filename)
5 //Mach number at entry:
6 M1=V1/sqrt(k*R*T1)
7 //Stagnation pressure at entry(in kPa):
8 p01=p1*(1+(k-1)/2*M1^2)^(k/(k-1))
9 //Stagnation temperature at entry(in K):
10 T01=T1*(1+(k-1)/2*M1^2)
11 //Static pressure at exit(in kPa):
12 p2=p02/(1+(k-1)/2*M2^2)^(k/(k-1))
13 //Temperature at exit(in K):
14 T2=T02/(1+(k-1)/2*M2^2)
15 //Change in entropy(in kJ/kg-K):
16 ds=cp*log(T2/T1)-R/1000*log(p2/p1)
17 printf("\n\nRESULTS\n\n")
18 printf("\n\nStagnation pressure at entry: %.3f kPa\n\n", p01)
19 printf("\n\nStagnation temperature at entry: %.3f K\n\n", T01)
20 printf("\n\nStatic pressure at exit: %.3f kPa\n\n", p2)
21 printf("\n\nTemperature at exit: %.3f K\n\n", T2)
22 printf("\n\nChange in entropy: %.3f kJ/kg-K\n\n", ds)
```

Chapter 12

Steady One Dimensional Compressible Flow

check Appendix [AP 10](#) for dependency:

12_01.sci

Scilab code Exa 12.01 pressure and area

```
1 //pressure and area//
2 pathname=get_absolute_file_path('12.01.sce')
3 filename=pathname+filesep()+ '12.01-data.sci'
4 exec(filename)
5 //Here the stagnation quantities are constant.
6 // Stagnation temperature(in K):
7 T0=T1*(1+(k-1)/2*M1^2)
8 //Stagnation pressure(in kPa):
9 p0=p1*((1+(k-1)/2*M1^2)^(k/(k-1)))
10 //Finding T2/T1:
11 T=t2/t1
12 //Temperature at exit(in K):
13 T2=T*T1
14 //Finding p2/p1:
15 P=P2/P1
```

```

16 //Pressure at exit(in kPa):
17 p2=P2*p1
18 //Density of air at exit(in kg/m^3):
19 d2=p2*10^3/R/T2
20 //Velocity of air at exit(in m/sec):
21 V2=M2*sqrt(k*R*T2)
22 //Finding A2/A1:
23 a=a2/a1
24 //Area at exit(in m^2):
25 A2=a*A1
26 printf("\n\nRESULTS\n\n")
27 printf("\n\nStagnation temperature: %.3f K\n\n",T0)
28 printf("\n\nStagantion pressure: %.3f kPa\n\n",p0)
29 printf("\n\nTemperature a exit %.3f K\n\n",T2)
30 printf("\n\nPressure at exit: %.3f kPa\n\n",p2)
31 printf("\n\nDensity of air at exit: %.3f kg/m^3\n\n"
    ,d2)
32 printf("\n\nVelocity of air at exit: %.3f m/sec\n\n"
    ,V2)
33 printf("\n\nArea at exit: %.3f \n\n",A2)

```

check Appendix [AP 9](#) for dependency:

12_02.sci

Scilab code Exa 12.02 Mass flow

```

1 //Mass flow//
2 pathname=get_absolute_file_path('12.02.sce')
3 filename=pathname+filesep()+ '12.02-data.sci'
4 exec(filename)
5 //Checking for chocking:
6 c=pb/p0;
7 if(c<=0.528)
8     //choked
9 else

```

```

10 //Not choked
11 //Therefore pressure at exit = back pressure
12 pe=pb;
13 //Mach number at exit:
14 Me=((p0/pe)^((k-1)/k)-1)*(2/(k-1))^0.5
15 //Temperature at exit(in K):
16 Te=T0/(1+(k-1)/2*Me^2)
17 //Velocity at exit(in m/sec):
18 Ve=Me*sqrt(k*R*Te)
19 //Density at exit(in kg/m^3):
20 de=pe*10^3/R/Te
21 //Mass flow rate of air(kg/sec):
22 m=de*Ve*Ae
23 end;
24 printf("\n\nRESULTS\n\n")
25 printf("\n\nMach number at exit: %.3f\n\n",Me)
26 printf("\n\nMass flow rate of air: %.3f kg/sec\n\n",
    m)

```

check Appendix [AP 8](#) for dependency:

12_03.sci

Scilab code Exa 12.03 mass and area

```

1 //mass and area//
2 pathname=get_absolute_file_path('12.03.sce')
3 filename=pathname+filesep()+ '12.03-data.sci'
4 exec(filename)
5 //Saturation pressure(in psia):
6 p0=p1*(1+(k-1)/2*M1^2)^(k/(k-1))
7 //Checking for choking:
8 x=pb/p0;
9 if(x>0.528)
10 //Not choked
11 else

```

```

12 //choked
13 end
14 //As there is choking:
15 Mt=1;
16 //Velocity at entry:
17 V1=M1*sqrt(k*R*(T1+460)*32.2)
18 //Density at the entry(in lbm/ft^3):
19 d1=p1/(R*(T1+460))*144
20 //Mass flow rate(in lbm/sec):
21 m=d1*V1*A1
22 //Finding the valueof A1/A*;
23 A=1/M1*((1+(k-1)/2*M1^2)/(1+(k-1)/2))^(k+1)/(2*(k
    -1))
24 //For choked flow , At=A*
25 At=A1/A
26 printf("\n\nRESULTS\n\n")
27 printf("\n\nMach number at throat: %.3f\n\n",Mt)
28 printf("\n\nMass flow rate: %.3f lbm/sec\n\n",m)
29 printf("\n\nArea at throat: %.3f ft^2\n\n",At)

```

check Appendix [AP 7](#) for dependency:

12_04.sci

Scilab code Exa 12.04 throat

```

1 //throat//
2 pathname=get_absolute_file_path('12.04.sce')
3 filename=pathname+filesep()+ '12.04-data.sci'
4 exec(filename)
5 //Temperature at the throat(in K):
6 Tt=T0/(1+(k-1)/2*Mt^2)
7 //Pressure at throat(in kPa):
8 pt=p0*(Tt/T0)^(k/(k-1))
9 //Density at throat(in kg/m^3):
10 dt=pt*1000/R/Tt

```

```

11 //Velocity at the throat(in m/s):
12 Vt=Mt*sqrt(k*R*Tt)
13 //Value of At/A*:
14 Ax=1/Mt*((1+(k-1)/2*Mt^2)/(1+(k-1)/2))^(k+1)/(2*(k
    -1))
15 //Stagnation properties are constant
16 //As a result pressure at exit ,
17 pe=pb;
18 //The Mach number at the exit is therefore given by
19 Me=sqrt(((p0/pe)^((k-1)/k)-1)*2/(k-1))
20 //Calculating the value of Ae/A*:
21 Ay=1/Me*((1+(k-1)/2*Me^2)/(1+(k-1)/2))^(k+1)/(2*(k
    -1))
22 //Value of A*(in m^2):
23 A_star=Ae/Ay
24 //Area at throat(in m^2):
25 At=Ax*A_star
26 printf("\n\nRESULTS\n\n")
27 printf("\n\nTemperature at the throat: %.3f K\n\n",
    Tt)
28 printf("\n\nPressure at throat: %.3f kPa\n\n",pt)
29 printf("\n\nDensity at throat: %.3f kg/m^3\n\n",dt)
30 printf("\n\nVelocity at the throat: %.3f m/sec\n\n",
    Vt)
31 printf("\n\nMach number at the exit: %.3f\n\n",Me)
32 printf("\n\nArea at throat: %.3f m^2\n\n",At)

```

check Appendix [AP 6](#) for dependency:

12_05.sci

Scilab code Exa 12.05 number and flow

```

1 //number and flow//
2 pathname=get_absolute_file_path('12.05.sce')
3 filename=pathname+filesep()+ '12.05-data.sci'

```

```

4 exec(filename)
5 //Mach number at the exit:
6 Me=sqrt((p0/pe)^((k-1)/k)-1)*2/(k-1))
7 //Temperature at exit(in K):
8 Te=T0/(1+(k-1)/2*Me^2)
9 //Mass flow rate(in kg/s):
10 m=pe*1000*Me*sqrt(k/R/Te)*Ae
11 printf("\\n\\nRESULTS\\n\\n")
12 printf("\\n\\nMach number at the exit: %.3f \\n\\n",Me)
13 printf("\\n\\nMass flow rate: %.3f kg/sec\\n\\n",m)

```

check Appendix [AP 5](#) for dependency:

12_06.sci

Scilab code Exa 12.06 mass and volume

```

1 //mass and volume//
2 pathname=get_absolute_file_path('12.06.sce')
3 filename=pathname+filesep()+ '12.06-data.sci'
4 exec(filename)
5 //Mach umber at section 1:
6 M1=sqrt((2/(k-1)*((p0/p1)^((k-1)/k)-1)))
7 //Temperature at section 1(in K):
8 T1=T0/(1+(k-1)/2*M1^2)
9 //Density at section 1(in kg/m^3):
10 d1=p1*1000/R/T1
11 //Velocity at section1(in m/sec):
12 V1=M1*sqrt(k*R*T1)
13 //Area at section 1(in m^2):
14 A1=%pi/4*D^2
15 //Mass flow rate(in kg/sec):
16 m=d1*A1*V1
17 //Mach number at section 2:
18 M2=sqrt((2/(k-1))*((T0/T2)-1))
19 //Velocity at section 2(in m/sec):

```

```

20 V2=M2*sqrt(k*R*T2)
21 //Density at section 2(in kg/m^3):
22 d2=d1*V1/V2
23 //Pressure at section 2(in kPa):
24 p2=d2/1000*R*T2
25 //Stagnation pressure at section 2(in kPa):
26 p02=p2*(1+(k-1)/2*M2^2)^(k/(k-1))
27 //Force exerted on control volume by duct wall(in N)
   :
28 F=(p2-p1)*1000*A1+m*(V2-V1)
29 printf("\n\nRESULTS\n\n")
30 printf("\n\nMass flow rate: %.3f kg/sec\n\n",m)
31 printf("\n\nLocal isentropic stagnation pressure at
   section 2:%.3f kPa\n\n",p02)
32 printf("\n\nForce exerted on control volume by duct
   wall:%.3f N\n\n",F)

```

check Appendix [AP 4](#) for dependency:

12_07.sci

Scilab code Exa 12.07 length

```

1 //length//
2 pathname=get_absolute_file_path('12.07.sce')
3 filename=pathname+filesep()+ '12.07-data.sci'
4 exec(filename)
5 //Mach number at section 1:
6 M1= sqrt(2/(k-1)*((p0/(p0+p1)))^((k-1)/k)-1))
7 //Temperature at section 1(in K):
8 T1=T0/(1+(k-1)/2*(M1)^2)
9 V1=M1*sqrt(k*R*T1)
10 //Pressure at section 1(in kPa):
11 p1=g*dHg*(760-18.9)*10^-3
12 //Density at section 1(in kg/m^3):
13 d1=p1/R/T1

```

```

14 //At M1=0.190,
15 //(p/p*) 1:
16 P1=5.745
17 // (fLmax/Dh) 1:
18 F1=16.38
19 //Value of L13(in m):
20 L13=F1*D/f
21 //Value of (p/p*) 2:
22 P2=p2/p1*P1
23 //For this value, Value of M2 is obtained as 0.4
24 M2=0.4;
25 //For M=0.4, fLmX/D=2.309
26 F2=2.309
27 //Value of L23(in m):
28 L23=F2*D/f
29 //Length of duct between section 1 and 2(in m):
30 L12=L13-L23
31 printf("\n\nRESULTS\n\n")
32 printf("\n\nLength of duct required for choking from
    section 1: %3f m\n\n",L13)
33 printf("\n\nMach number section 2: %.3f \n\n",M2)
34 printf("\n\nLength of duct between section 1 and 2: %
    .3f m\n\n",L12)

```

check Appendix [AP 3](#) for dependency:

12_08.sci

Scilab code Exa 12.08 velocity and entropy

```

1 //velocity and entropy//
2 pathname=get_absolute_file_path('12.08.sce')
3 filename=pathname+filesep()+ '12.08-data.sci'
4 exec(filename)
5 //Density at section 1(in lbm/ft^3):
6 d1=p1*144/R/T1

```



```

7 //Velocity at section 2(in ft/sec):
8 V2=(p1-p2)*144/d1/V1*32.2+V1
9 //Density at section 2(in lbm/ft3):
10 d2=d1*V1/V2
11 //Temperature at section 2(in R):
12 T2=p2/d2/R*144
13 //Mach number at section 2:
14 M2=V2/sqrt(k*R*32.16*T2)
15 //Stagnation Temperature at section 2(in R):
16 T02=T2*(1+(k-1)/2*M2^2)
17 //Stagnation pressure at section 2 (in psia):
18 p02=p2*(T02/T2)^(k/(k-1))
19 //Mach Number at section 1:
20 M1=V1/sqrt(k*R*32.16*T1)
21 //Stagnation temperature at section 1(in R):
22 T01=T1*(1+(k-1)/2*M1^2)
23 //Energy added(in Btu/lbm):
24 E=Cp*(T02-T01)
25 //Change in entropy(in Btu/(lbm-R)):
26 dS=Cp*log(T2/T1)-(Cp-Cv)*log(p2/p1)
27 printf("\n\nRESULTS\n\n")
28 printf("\n\nVelocity at section 2: %.3f ft/sec\n\n",
    V2)
29 printf("\n\nDensity at section 2: %.3f lbm/ft^3\n\n"
    ,d2)
30 printf("\n\nTemperature at section 2: %.3f R\n\n",T2
    )
31 printf("\n\nStagnation Temperature at section 2: %.3
    f R\n\n",T02)
32 printf("\n\nStagnation pressure at section 2: %.3f
    psia\n\n",p02)
33 printf("\n\nEnergy added: %.3f Btu/lbm\n\n",E)
34 printf("\n\nChange in entropy: %.3f Btu/(lbm-R)\n\n"
    ,dS)

```

check Appendix [AP 2](#) for dependency:

12_09.sci

Scilab code Exa 12.09 Temperature and entropy

```
1 //Temperature and entropy//
2 pathname=get_absolute_file_path('12.09.sce')
3 filename=pathname+filesep()+ '12.09-data.sci'
4 exec(filename)
5 //Mach nuber at section 1:
6 M1=V1/sqrt(k*R*T1)
7 //For these value of M1 and M2,the following values
   are obtained:
8 //(To/T0*) 1:
9 t01=0.7934;
10 //(T0/T0*) 2:
11 t02=0.9787;
12 //(p0/p0*) 1:
13 P01=1.503;
14 //(p0/p0*) 2:
15 P02=1.019;
16 //(T/T*) 1:
17 t1=0.5289;
18 //(T/T*) 2:
19 t2=0.9119;
20 //(p/p*) 1:
21 P1=0.3636;
22 //(p/p*) 2:
23 P2=0.7958;
24 //(V/V*) 1:
25 v1=1.455;
26 //(V/V*) 2:
27 v2=1.146;
28 //Value of T2/T1:
29 t=t2/t1
30 //Temperature at section 2(in K):
31 T2=t*T1
```

```

32 //Value of p2/p1:
33 p=P2/P1
34 //Pressure at section 2(in kPa):
35 p2=p*p1
36 //Value of V2/V1:
37 v=v2/v1
38 //Velocity at section 2(in m/sec):
39 V2=v*V1
40 //Density at section 2(in kg/m^3):
41 d2=p2*1000/R/T2
42 //At M1, T/T0=0.5556
43 T01=T1/0.5556
44 //At M2, T/T0=0.7764
45 T02=T2/0.7764
46 //Heat added(in kJ/kg):
47 E=Cp*(T02-T01)
48 //Change in entropy(kJ/kg-K):
49 dS=Cp*log(T2/T1)-R*log(p2/p1)/1000
50 printf("\n\nRESULTS\n\n")
51 printf("\n\nTemperature at section 2: %.3f K\n\n",T2
)
52 printf("\n\nPressure at section 2: %.3f kPa\n\n",p2)
53 printf("\n\nVelocity at section 2: %.3f m/sec\n\n",
V2)
54 printf("\n\nDensity at section 2: %.3f kg/m^3\n\n",
d2)
55 printf("\n\nStagnation temperature at section 2: %.3
f K\n\n",T02)
56 printf("\n\nHeat added: %.3f kJ/kg\n\n",E)
57 printf("\n\nChange in entropy: %.3f kJ/kg\n\n",dS)

```

check Appendix [AP 1](#) for dependency:

12_10.sci

Scilab code Exa 12.10 Temperature

```

1 //Temperature//
2 pathname=get_absolute_file_path('12.10.sce')
3 filename=pathname+filesep()+ '12.10-data.sci'
4 exec(filename)
5 //Density at section 1(in kg/m^3):
6 d1=p1*1000/R/T1
7 //Mach number at section 1:
8 M1=V1/sqrt(k*R*T1)
9 //Stagnation temperature at section 1(in K):
10 T01=T1*(1+(k-1)/2*M1^2)
11 //Stagnation pressure at section 1(in kPa):
12 p01=p1*(1+(k-1)/2*M1^2)^(k/(k-1))
13 //The following values are obtained from the
    appendix:
14 //p02/p01:
15 p0=0.7209;
16 //T2/T1:
17 T=1.687;
18 //p2/p1:
19 p=4.5;
20 //V2/V1:
21 V=0.3750;
22 //Temperature at section 2 (in K):
23 T2=T*T1
24 //Pressure at section 2(in kPa):
25 p2=p*p1
26 //Velocity at section 2(in m/sec):
27 V2=V*V1
28 //Density at section 2 (in kg/m^3):
29 d2=p2*1000/R/T2
30 //Stagnation pressure at section 2(in kPa):
31 p02=p0*p01
32 //Stagnation temperature at section 2(in K):
33 T02=T01;
34 //Change in entropy(in kJ/(kg-K)):
35 dS=-R/1000*log(p0)
36 printf("\n\nRESULTS\n\n")
37 printf("\n\nTemperature at section 2 : %.3f K\n\n",

```

```
    T2)
38 printf("\n\nPressure at section 2: %.3f kPa\n\n",p2)
39 printf("\n\nVelocity at section 2: %.3f m/sec\n\n",
    V2)
40 printf("\n\nDensity at section 2 : %.3f kg/m^3\n\n",
    d2)
41 printf("\n\nStagnation pressure at section 2: %.3f
    kPa\n\n",p02)
42 printf("\n\nChange in entropy: %.3f kg-K\n\n",dS)
43 printf("\n\nStagnation temperature at section 2: %.3
    f K\n\n",T02)
```

Appendix

Scilab code AP 1 data

```
1 //Temperature at section 1(in K):
2 T1=278;
3 //Pressure at section 1(in kPa):
4 p1=65;
5 //Velocity at section 1(in m/sec):
6 V1=668;
7 //Value of gas constant(in N-m/kg-K):
8 R=287;
9 //Value of k:
10 k=1.4;
```

Scilab code AP 2 data

```
1 //Temperature at section 1(in K):
2 T1=333;
3 //Pressure at section 1(in kPa):
4 p1=135;
5 //Velocity at section 1(in m/sec):
6 V1=732;
7 //Mach number at section 2:
8 M2=1.2;
9 //Gas constant(in N-m/kg-K):
10 R=287;
11 //Value of k:
12 k=1.4;
13 //Specific heat at constant pressure(in N-m/kg-K):
```

14 Cp=1;

Scilab code AP 3 data

```
1 //Temperature at section 1(in R):
2 T1=600;
3 //Pressure at section 1(in psia):
4 p1=20;
5 //Pressure at section 2(in psia):
6 p2=10;
7 //Velocity at section 1(in ft/s):
8 V1=360;
9 //Cross-sectional area of the duct(in ft^2):
10 A=0.25;
11 //Gas Constant(in ft-lbf/lbm-R):
12 R=53.3;
13 //Value of k:
14 k=1.4;
15 //Specific heat at constant pressure(in Btu/lbm-R):
16 Cp=0.24;
17 //Specific heat at constant volume(in Btu/lbm-R):
18 Cv=0.171;
```

Scilab code AP 4 data

```
1 //Stagnation temperature(in K):
2 T0=296;
3 //Stagnation pressure(in mm of Hg):
4 p0=760;
5 //Gauge pressure at section 1(in mm of Hg):
6 p1=-18.9;
7 //Gauge pressure at section2(in mm of Hg):
8 p2=-412;
9 //Mach number at 3:
10 M3=1;
11 //Gas constant:
12 R=287;
13 //Density of mercury(kg/m^3):
```

```
14 dHg=13500;
15 // Acceleration due to gravity(in m/sec ^2):
16 g=9.8;
17 //Friction factor:
18 f=0.0235;
19 //Diameter of tube(in m):
20 D=7.16*10^-3;
21 //Value of k:
22 k=1.4;
```

Scilab code AP 5 data

```
1 //Diameter of pipe(in m):
2 D=7.16*10^-3;
3 //Stagnation pressure(in kPa):
4 p0=101;
5 //Stagnation temperature(in K):
6 T0=296;
7 //Pressure at section 1(in kPa):
8 p1=98.5;
9 //Temperature at section 2(in K):
10 T2=287;
11 //Gas constant(in N-m/kg-K):
12 R=287;
13 //Value of k:
14 k=1.4;
```

Scilab code AP 6 data

```
1 //Stagnation temperature(in K):
2 T0=350;
3 //Stagnation pressure(in kPa)\
4 p0=1000;
5 //Pressure at exit(in kPa)
6 pe=87.5;
7 //Back Pressure(in kPa):
8 pb=50;
9 //Area at exit(in m^2):
```



```
10 Ae=0.001;
11 //Gas Constant(in N-m/kg-K)
12 R=287;
13 //Value of k:
14 k=1.4;
```

Scilab code AP 7 data

```
1 //Stagnation temperature(in K):
2 T0=350;
3 //Stagnation pressure(in kPa):
4 p0=1000;
5 //Back Pressure(in kPa):
6 pb=954;
7 //Mach number at throat:
8 Mt=0.68;
9 //Area at exit(in m^2):
10 Ae=0.001;
11 //Value of k:
12 k=1.4;
13 //Gas Constant(in N-m/kg-K):
14 R=287;
```

Scilab code AP 8 data

```
1 //Mach number at entry:
2 M1=0.52;
3 //Temperature at entry(in F):
4 T1=40;
5 //Pressure at entry(in psia):
6 p1=60;
7 //Area at entry(in ft^2):
8 A1=0.013;
9 //Back pressure(in psia):
10 pb=30;
11 //Gas Constant(in ft-lbf/lbm-R)
12 R=53.3;
13 //Value of k:
```

14 k=1.4;

Scilab code AP 9 data

```
1 //Throat area of nozzle(in m^2):
2 Ae=0.001;
3 //Back pressure of air(in kPa):
4 pb=591;
5 //Stagnation pressure(in kPa):
6 p0=1000;
7 //Stagnation temperature(in K):
8 T0=333;
9 //Gas Constant(in N-m/kg-K):
10 R=287;
11 //Value of k:
12 k=1.4;
```

Scilab code AP 10 data

```
1 //Mach number at entry:
2 M1=0.3;
3 //Temperature at entry(in K):
4 T1=335;
5 //Pressure at entry(in kPa):
6 p1=650;
7 //Area at entry(in m^2):
8 A1=0.001;
9 //Mach number at exit:
10 M2=0.8;
11 ///Value of k:
12 k=1.4;
13 //For the Mach no:0.3:
14 //T/T0:
15 t1=0.9823,
16 //p/p0:
17 P1=0.9395;
18 //d/d0:
19 den1=0.9564;
```

```

20 //A/A*:
21 a1=2.035;
22 //For the Mach no:0.8:
23 // T/T0:
24 t2=0.8865;
25 //p/p0:
26 P2=0.6560;
27 //d/d0:
28 den2=0.7400;
29 //A/A*:
30 a2=1.038;
31 //Gas Constant (in N-m/kg-K):
32 R=287;

```

Scilab code AP 11 data

```

1 //Pressure at entry (in kPa):
2 p1=350;
3 //Temperature at entry (in K)
4 T1=333;
5 //Velocity at entry (in m/s):
6 V1=183;
7 //Mach no. at exit:
8 M2=1.3;
9 //Stagnation pressure at exit (in kPa):
10 p02=385;
11 //Stagnation temperature at exit (in K):
12 T02=350;
13 //Value of k:
14 k=1.4;
15 //Gas constant (in N-m/kg-K)
16 R=287;
17 //Specific heat at constant pressure (kJ/(kg-K)):
18 cp=1;

```

Scilab code AP 12 data

```

1 //Value of k:

```

```
2 k=1.4;
3 //Gas Constant(in Kj/(kg-K)):
4 R=287;
```

Scilab code AP 13 data

```
1 //Temperature of air entering the cold section(in K)
  :
2 T1=440;
3 //Absolute pressure of air entering the cold section
  (in kPa):
4 p1=188;
5 //Velocity of air entering the cold section(in m/sec
  ):
6 V1=210;
7 //Temperature of air at outlet:(in K)
8 T2=351;
9 //Absolute pressure of air at outlet(in kPa):
10 p2=213;
11 //Rate of heat loss in the section(in kJ/sec):
12 //Gas Constant(in N-m):
13 R= 287;
14 //Mass flow rate of air(in kg/sec):
15 m=0.15;
16 //Specific heat at constant pressue(in kJ/(kg-K)):
17 cp=1;
18 //Specific energy at constant volume(in kJ/(kg-K)):
19 cv=0.717;
```

Scilab code AP 14 data

```
1 //Diameter of windmill(in m):
2 D=26;
3 //Operating speed(in rpm):
4 N=20;
5 //Wind speed(in km/hr):
6 V=36;
7 //Power Output(in W):
```

```

8 Po=41000;
9 //Maximum efficiency occurs in following conditions:
10 //Efficiency:
11 Eff=0.593;
12 //Inteference Factor:
13 a=1/3;
14 //Density of air(in kg/m^3):
15 p=1.23;

```

Scilab code AP 15 data

```

1 //Total propulsion power requirement(in MW):
2 P=11.4;
3 //From the given curves,Value of coefficients
  atoptimum efficiency are as follows:
4 //Speed of advance coefficient:
5 J=0.85;
6 //Thrust Coefficient:
7 Cf=0.1;
8 //Torque Coefficint:
9 Ct=0.02;
10 //Efficiency:
11 Eff=0.66;
12 //Velocity of ship(in m/sec):
13 V=6.69;
14 //Density of water(in kg/m^3):
15 p=1025;

```

Scilab code AP 16 data

```

1 //Operation speed(in rpm):
2 N=2000;
3 //Volume flow rate(in gpm):
4 Q=20;
5 //Pressure(in psig):
6 p=1500;
7 //Actual Pump Displacement(in ^3/rev):
8 va=5.9;

```

```

9 //Volume flow rate at operating condition(in gpm):
10 Qo=46.5;
11 //Volume flow rate at maximum delivery(in gpm):
12 Qe=48.5;
13 //Pressure at operation condition(in psi):
14 po1=1500;
15 //Efficiency of pump at operating condition:
16 Effp=0.84;
17 //Pressure at operating condition case 2(in psig):
18 po2=3000;

```

Scilab code AP 17 data

```

1 //Diameter of fan 1 (in inches):
2 D1=36;
3 //Operating speed of fan 1(in rpm):
4 N1=600
5 //Density of air used in fan 1(in lbm/ft^3):
6 d1=0.075;
7 //Diameter of fan 2(in inches):
8 D2=42;
9 //Operating speed of fan 2(in rpm):
10 N2=1150;
11 //Density of air used in fan 2(in lbm/ft^3):
12 d2= 0.045;
13 //The following values are obtained from the given
    graph
14 //Values of volume flow rate(in cfm) through fan 1:
15 Q1= [0 10000 20000 30000 40000 50000 60000];
16 //Values of pressure( in inches of H2O):
17 p1=[ 3.68 3.75 3.50 2.96 2.12 1.02 0];
18 //Values of power(in hp):
19 P1=[ 11.1 15.1 18.6 21.4 23.1 23.1 21.0];
20 //Efficiency (in %):
21 Eff=[0 37 59 65 57 34 0];

```

Scilab code AP 18 data

```

1 //For 5 inch nominal pipe line , diameter D:
2 Di=5.047;
3 //Length of pipeline(in feet):
4 L=6;
5 //Operatng spped (in rpm):
6 N=1750;
7 //Water level abovepump centreline(in feet):
8 h=3.5;
9 //Temperature 1 of water(in Farenheit):
10 T1=80;
11 //Temperature 2 of water (in Farenheit):
12 T2=180;
13 //Volume flow rate of water(in gpm):
14 Q=1000;
15 //Minor loss Coefficients:
16 K=0.5; SE=30; OGV=8;
17 //Atmospheric pressure(in lbf/in^2):
18 patm=14.7;
19 //Density of air(slug/ft^3):
20 p=1.93;
21 //Acceleration due to gravity(in ft/sec^2):
22 g=32.2;
23 //Head(in feet) due to vapor pressure of water for T
    =80F:
24 Hv1=1.17;
25 //Head(in feet) due to vapor pressure of water for T
    =180F:
26 Hv2=17.3;
27 //Kinematic viscosity of water at 80F:
28 v=0.927e-5;
29 //Value of discharges for plotting NPSHR(in gpm):
30 Qh=[500 700 900 1100 1300]
31 //Values of NPSHR obtained from Fig. D3 of appendix
    D:
32 NPSHRp=[7 8 9.5 12 16]

```

Scilab code AP 19 data

```

1 //Volume flow rate(in gpm) at shut off condition for
  N1:
2 Q1so=0;
3 //Volume flow(in gpm) rate at best efficiency for N1
  :
4 Q1be=300;
5 //Head(in feet) at shut off condition for N1:
6 H1so=25;
7 //Head(in feet) at best efficiency condition for N1:
8 H1be=21.9
9 //Operation Speed 1:
10 N1=1170;
11 //Operation speed 2:
12 N2=1750;

```

Scilab code AP 20 data

```

1 //Head in Us customary units:
2 Hus=21.9;
3 //Volume flow rate in US customary units:
4 Qus=300;
5 //Working seed in rpm:
6 N=1170;
7 //Aceleration due to graviy in m/s^2
8 g=9.81;

```

Scilab code AP 21 data

```

1 //Rate of flow in gm:
2 Q=[0 500 800 1000 1100 1200 1400 1500];
3 //Suction pressure in psig:
4 ps=[ 0.65 0.25 -0.35 -0.92 -1.24 -1.62 -2.42 -2.89];
5 //Discharge pressure in psig:
6 pd=[53.3 48.3 42.3 36.9 33 27.8 15.3 7.3];
7 //Motor Current in amps:
8 I=[18 26.2 31 33.9 35.2 36.3 38 39];
9 //Acceleration due to gravity in ft/s^2:
10 g=32.2;

```



```

11 //Value of Zs in feet
12 zs=1;
13 //Density of air in slug/ft^3:
14 px=1.94;
15 //Value of ZD in feet:
16 zd=3;
17 //Density of fluid in slug/ft^3:
18 py=1000;
19 //Motor Efficiency:
20 Effm=0.9;
21 //Motor Supply in volts:
22 E=460;
23 //Power Factor:
24 PF=0.875;

```

Scilab code AP 22 data

```

1 //Tip Diameter in metres:
2 Dt=1.1;
3 //Hub Diameter in metres:
4 Dh=0.8;
5 //Operating Speed in rpm:
6 w=1200;
7 //Absolute inlet angle in degrees:
8 alpha1=30;
9 //Blade inlet angle in degrees:
10 betta1=30;
11 //Blade outlet angle in degrees:
12 betta2=60;
13 //Density of air in kg/m^3
14 p=1.23;

```

Scilab code AP 23 data

```

1 //Volume flow rate in gpm:
2 Q= 150;
3 //Value of Vrb2 in ft/sec:
4 Vrb2=10;

```

```

5 //Radius of outter impeller in inches:
6 R2=2;
7 //Impeller Speed in rpm:
8 w=3450;
9 //Density of air in slug/ft^3
10 p=1.94;

```

Scilab code AP 24 data

```

1 //Mass of the tennis ball(in grams):
2 m=57;
3 //Diameter ofthe ball (in mm):
4 D=64;
5 //Velocity with which te ball is hit(in m/s):\
6 V=25;
7 //Topspin given on the ball(in rpm):
8 N=7500;
9 //Acceleration due to gravity(in m/s^2):
10 g=9.81;
11 //Kinematic viscosity(in m^2/s):
12 v=1.46*10^-5
13 //Desity of air(in kg/m^3):
14 d=1.23;

```

Scilab code AP 25 data

```

1 //Wing area(in ft^2):
2 A=1600;
3 //Aspect ratio:
4 ar=6.5;
5 //Groos weight of aircraft(in lbf):
6 W=150000;
7 //Coefficient of drag at zero lift :
8 Cd0=0.0182;
9 //Sonic speed at sea level(in mph):
10 c=759;
11 //Density of air(in slug/ft^3):
12 p=0.00238;

```

```
13 //Sroll speed at sea level(in mph):
14 Vssl=175;
```

Scilab code AP 26 data

```
1 //Weight of the dragster(in lbf):
2 w=1600;
3 //Speed of dragster(in mph):
4 s1=270;
5 //Area of drag chute(in ft^2):
6 A=25;
7 //Speed of dragster after deceleraton(in mph):
8 s2=100;
9 //Acceleration due to gravity(in ft/sec^2):
10 g=32.2;
11 //Density of air(in slug/ft^3):
12 d=0.00238;
13 //Value of coefficient of drag:
14 Cd=1.42;
```

Scilab code AP 27 data

```
1 //Diameter of chimney(in m):
2 D=1;
3 //Height of chimney(in m):
4 L=25;
5 //Speed of wind(in kmph):
6 s=50;
7 //Density of air(in kg/m^3):
8 d=1.23;
9 //Viscosity of air(in kg/(m-s)):
10 u=1.79*10^-5;
11 //Pressure(in kPa):
12 p=101;
```

Scilab code AP 28 data

```

1 //Length of the supertanker(in m):
2 L=360;
3 //Width of supertanker(in m):
4 W=70;
5 //Draft of the supertanker(in m):
6 D=50;
7 //Cruising speed in water(in knots):
8 s=13;
9 //Kinematic viscosity at 10 C
10 v=1.37*10^-6;
11 //Density of sea water(in kg/m^3):
12 d=1020;

```

Scilab code AP 29 data

```

1 //Velocity of flow(in m/sec):
2 U=1;
3 //Length of flat plate(in m):
4 L=1;
5 //Density of water(in kg/m^3):
6 d=999;
7 //Kinematic viscosity of water(in m^2/sec):
8 v=10^-6;

```

Scilab code AP 30 data

```

1 //Lengh of side of the test section(in mm):
2 L=305;
3 //Freesteam speed at section 1(in m/sec):
4 U1=26;
5 //Displacement thickness at section 1(in mm):
6 d1=1.5;
7 //Displacment thickness at section 2(in mm):
8 d2=2.1;

```

Scilab code AP 31 data

```

1 //Volume flw rate of ai(in m^3/sec):
2 Q=1;
3 //Diameter of pipe(in m):
4 D=0.25;
5 //Density of air (in kg/m^3):
6 d1=1.23;
7 //Acceleration due to gravity(in m/s^2):
8 g=9.8;
9 //Density of water(in kg/m^3):
10 d2=999;
11 //Maxmum range of manometer(in m):
12 h=0.3;
13 //Kinematic viscosity (in m^2/s):
14 v=1.46*10^-5;

```

Scilab code AP 32 data

```

1 //Nozzle exit diameter(in mm):
2 D=25;
3 //N/R1 value value:
4 N_R=3;
5 //AR value:
6 A_R=2;
7 //Static head available from the main(in m):
8 z0=1.5;
9 //Acceleration due to gravity(in m/sec^2):
10 g=9.8;
11 //Value of Cp:
12 Cp=0.45;

```

Scilab code AP 33 data

```

1 //Length of copper wire(in ft):
2 L=10;
3 //Inner diameer of pipe(in inches):
4 D=1.5;
5 //Dischare(in ft^3/sec):
6 Q=0.566;

```

```

7 //Level of reservoir above pipe centreline(inn feet)
  :
8 h=85.1;
9 //Kinematic viscosity at 70 F(in ft^2/s):
10 v=1.05*10^-5;
11 //Acceleration due to gravity(in ft/sec^2):
12 g=32.2;

```

Scilab code AP 34 data

```

1 //Length of Al tubing (in ft):
2 L=500;
3 //Volume flow rate of pump output(in gpm):
4 Q=1500;
5 //Discharge pressure(in psig):
6 p1=65;
7 //Sprinkler pressure(in psig):
8 p2=30;
9 //Kinematic viscosity (in ft^2/sec):
10 v=1.21*10^-5;
11 //Density (in slug/ft^3):
12 p=1.94;

```

Scilab code AP 35 data

```

1 //Height of standpipe(in ft):
2 l=80;
3 //Length of longest pipe(in ft):
4 L=600;
5 //Diameter of pipe(in inches):
6 D=4;
7 //Friction factor:
8 f=0.031;
9 //Acceleration due to gravityin ft/sec^2):
10 g=32.2;

```

Scilab code AP 36 data

```

1 //Flow rate of crude oil(in bbl):
2 Q=1.6*10^6;
3 //Inside diamete of pipe(i inches):
4 D=48;
5 //Maximum allowable pressure(in psi):
6 p2=1200;
7 //Minimum pressure required to keep gases dissolves(
   in psi):
8 p1=50;
9 //Specific gravity of crde oil:
10 SG=0.93;
11 //Viscosity at 140 F(in lbf-s/ft^2):
12 u=3.5*10^-4;
13 //Efficency of pump:
14 Effp=0.85;
15 //Density(in slug/ft^3):
16 d=1.94;
17 //Viscosity (in lbf-sec):
18 u=3.5*10^-4;
19 //Friction factor:
20 f=0.017;

```

Scilab code AP 37 data

```

1 //Volme flow rate of water(in m^3/sec):
2 Q=0.0084;
3 //Length of horizontal pipe(in m):
4 L=100;
5 //Diameter of pipe(in m):
6 D=0.075;
7 //Density of water(in kg/m^3):
8 d=999;
9 //Friction factor:
10 f=0.017;
11 //Minor loss coefficient:
12 K=0.5;
13 //Viscosity(in kg/m-s):
14 u=10^-3;

```

```
15 //Acceleration due to gravity(in /sec^2):
16 g=9.8;
```

Scilab code AP 38 data

```
1 //Flow rate through capillary viscometer(in mm^3/sec
  ):
2 Q=880;
3 //Tube length(in m):
4 L=1;
5 //Tube diameter(in mm):
6 D=0.5;
7 //Pressure drop(in kPa):
8 p=1000;
9 //Density of oil(in kg/m^3):
10 d=999;
```

Scilab code AP 39 data

```
1 //temperature fo operation(in F):
2 T=210;
3 //Diameter of te bearing(in inches):
4 D=3;
5 //Diametral clearance(in inches):
6 a=0.0025;
7 //Length of shaft(in inches):
8 L=1.25;
9 //Speed of rotation of the shaft(in rpm):
10 N=3600;
11 //Viscosity of the oil(in lbf-s/ft^2):
12 u=2.01*10^-4;
13 //Specific gravity of SAE 10W:
14 SG=0.92;
15 //Density of water (in slug/ft^3)
16 p=1.94;
```

Scilab code AP 40 data


```

1 //Operation pressure of hydraulic system(in kPa):
2 p1=20000;
3 //Operation temperature of hydraulic system(in C):
4 T=55;
5 //Piston diameter(in mm):
6 D=25;
7 //Viscosity of SAE 10W at 55C(in kg/(m-s):
8 u=0.018;
9 //Mean radial clearance of a cylinder(in mm):
10 a=0.005;
11 //Gauge pressure on lower pressure side of piston(in
    kPa):
12 p2=1000;
13 //Lenth of piston(in mm):
14 L=15;
15 //Denity of water(in kg/m^3):
16 dw=1000;

```

Scilab code AP 41 data

```

1 //Efficinc of pump:
2 Effp=0.8;
3 //Design specific speed(in rpm):
4 Nscu1=2000;
5 //Impeller diameter(in inches):
6 D1=8;
7 //Opertion sped at esign point flow condition(in rpm
    ):
8 N1=1170;
9 //Flow rate at design point flow condition(in gpm):
10 Q1=300;
11 //Density of water (in slug/ft^3):
12 d1=1.94;
13 //Acceleration due to gravity(in ft^2/sec):
14 g=32.2;
15 //Working speed 2(in rpm):
16 N2=1750;

```

Scilab code AP 42 data

```
1 //Width of the prototype(in ft):
2 wp=8;
3 //Frontal area of the prototype(in ft^2):
4 Ap=84;
5 //Model Scale:
6 S=1/16;
7 //Density of air(in kg/m^3):
8 d=1.23;
9 //Air speed in wind tunnel(in m/sec):
10 V=[18 21.8 26 30.1 35 38.5 40.9 44.1 46.7];
11 //Drag force(in N):
12 Fd=[3.1 4.41 6.09 7.97 10.7 12.9 14.7 16.9 18.9];
13 //Kinematic viscosity(in m^2/sec):
14 v=1.46*10^-5;
15 //Density of air(in kg/m^3):
16 d=1.23;
17 //Speed of prototype(in km/hr):\
18 Vp=100;
```

Scilab code AP 43 data

```
1 //Diameter of the prototype(in ft):
2 Dp=1;
3 //Speed of towing of prototype(in knots):
4 Vp=5;
5 //Diameter of model(in inches):
6 Dm=6;
7 //Drag for model at test condition(in lbf):
8 Fm=5.58;
9 //Density of seawater at 5 C for prototype(in slug/
  ft^3):
10 dp=1.99;
11 //Kinematic viscosity at 5 C for prototype(in ft^2/
  sec):
12 vp=1.69*10^-5;
13 //Density of air at STP for model(in slug/ft^3):
```

```
14 dm=0.00238;
15 //Kinematic viscosity of air at STP for model(in ft
    ^2/sec):
16 vm=1.57*10^-4;
```

Scilab code AP 44 data

```
1 //Depth to which water is filled(in m):
2 h=3;
3 //Length of pipe(in m):
4 L=6;
5 //Diameter of pipe (in mm):
6 D=150;
7 //Acceleration due to gravity(in m/sec^2):
8 g=9.81;
```

Scilab code AP 45 data

```
1 //Area of cross section of the nozzle(in in^2):
2 A4=0.864;
3 //Capacity of heater(in kW):
4 Q=10
5 //Acceleration due to gravity(in ft/sec^2):
6 g=32.2;
7 //Water level in reservoir above datum line(in ft):
8 z3=10;
9 //Density of water(In slug/ft^3):
10 d=1.94;
```

Scilab code AP 46 data

```
1 //Speed of plane(in km/hr):
2 V=150;
3 //Speed at point B relative to the wing(in m/sec):
4 Vb=60;
5 //Density of air(in kg/m^3):
6 da=1.23;
```

```
7 //Atmospheric pressure (in N/m^2):
8 pa=1.01*10^5;
9 //At 1000m,
10 //p/pSL:
11 P1=0.8870;
12 //d/dSL:
13 D1=0.9075;
```

Scilab code AP 47 data

```
1 //Depth of water at the upstream (on feet):
2 Du=1.5;
3 //Depth of water at the vena contracta downstream
  from the gate (in inches):
4 Dd=2;
5 //Acceleration due to gravity (in ft/sec^2):
6 g=32.2;
```

Scilab code AP 48 data

```
1 //Length of tube above surface (in m):
2 l=1;
3 //Depth of exit below water surface (in m):
4 z=7;
5 //Acceleration due to gravity (in m/sec^2):
6 g=9.81;
7 //Density of water (in kg/m^3):
8 d=999;
9 //Atmospheric pressure (in N/m^2):
10 p1=1.01*10^5;
```

Scilab code AP 49 data

```
1 //Area of nozzle at input (in m^2):
2 Ai=0.1;
3 //Area of nozzle at exit (in m^2):
4 Ae=0.02;
```

```
5 //Outlet velocity of flow(in m/sec):
6 V2=50;
7 //Density of air(in kg/m^3):
8 da=1.23;
```

Scilab code AP 50 data

```
1 //Pressure diference(in mm of mecury):
2 p=30;
3 //Density of water(in kg/m^3):
4 dw=1000;
5 //Aceleration due to gravity(in m/sec^2):
6 g=9.81;
7 //Density of air(in kg/m^3):
8 da=1.23;
9 //Specific gravity of mercury:
10 SG=13.6;
```

Scilab code AP 51 data

```
1 //Depth of the duct(in m):
2 d=0.3;
3 //Width of the duct(in m):
4 w=0.1;
5 //Inner radius of the bend(in m):
6 r=0.25;
7 //Pressure difference between the taps(in mm of Hg):
8 p=40;
9 //Density of water(in kg/m^3):
10 dw=999;
11 //Acceleration due to gravity(in m/sec^2):
12 g=9.8;
13 //Density of air(in kg/m^3):
14 da=1.23;
```

Scilab code AP 52 data

```

1 //Thickness of water film(in mm):
2 h=1;
3 //Width of surface(in m):
4 b=1;
5 //Angle of inclination of surface:
6 theta=15;
7 //Density of water(in kg/m^3):
8 d=999;
9 //Acceleration du to gravity(in m/sec^2):
10 g=9.81;
11 //Viscosity(kg/m-s):
12 u=10^-3;

```

Scilab code AP 53 data

```

1 //Value of A(in sec^-1):
2 A=0.3;

```

Scilab code AP 54 data

```

1 //Value of (in mm/sec):
2 U=4;
3 //Value of h(in mm):
4 h=4;
5 //Tme at which to find position(in sec):
6 t=1.5;

```

Scilab code AP 55 data

```

1 //Distance f piston from closed end of the cylinder
  at the give instant(in m):
2 L=0.15;
3 //Density of gas(in kg/m^3):
4 d=18;
5 //Velocity of piston(in m/sec):
6 V=12;

```

Scilab code AP 56 data

```

1 //Volume of tank(in m^3):
2 V=0.1;
3 //Temperature of line and tank(in K):
4 T=293;
5 //Initial tank gauge pressure(in N/m^2):
6 p1=1*10^5;
7 //Absolute line pressure(in N/m^2):
8 p=2*10^6;
9 //Rate of rise of temperature after opening of the
  valve(in C/sec):
10 r=0.05;
11 //Atmospheric pressure(in N/m^2):
12 patm=1.01*10^5;
13 //Gas Constant(in N-m/(kg-K)):
14 R=287;
15 //Value of cv(in N-m/kg-K):
16 cv=717;

```

Scilab code AP 57 data

```

1 //Pressure at entry(in psia):
2 p1=14.7;
3 //Temperature at entry(in F):
4 T1=70;
5 //Pressure at exit(in psia):
6 p2=50;
7 //Temperature a exit(in F):
8 T2=100;
9 //Cross sectional area of the pipe at exit(in ft^2):
10 A2=1;
11 //Mass flow rate(in lbf/sec):
12 m=20;
13 //Power input to the compressor(in hp):
14 Ws=-600;
15 //Value of cp(in Btu/lbm-R):
16 cp=0.24;
17 //Value of gas constant(in ft-lbf/(lbm-R))
18 R=53.3;

```

Scilab code AP 58 data

```
1 //Inlet gauge pressure(in kPa):
2 p=20;
3 //Volume flow rate of water through the sprinkler(in
  l/min):
4 Q=7.5;
5 //Speed of rotation of sprinkler(in rpm):
6 w=30;
7 //Diameter of jet of sprinkler(in mm):
8 D=4;
9 //Radius of sprinkler(in mm):
10 R=150;
11 //Supply pressure to sprinkler(in kPa):
12 p=20;
13 //Angle at which jet is sprayed wrt horizontal:
14 alpha=30;
15 //Density of water(in kg/m^):
16 d=999;
```

Scilab code AP 59 data

```
1 //Initial mass of the rocket(in kg):
2 M0=400;
3 //Rate of fuel consumption(in kg/sec):
4 me=5;
5 //Exhaust velocity(in m/sec):
6 Ve=3500;
7 //Acceleration due to gravity(in m/sec^2):
8 g=9.81;
9 //Time after which velocity is to be calculated(in
  sec):
10 t=10;
```

Scilab code AP 60 data


```

1 //Mass of vane and cart(in kg):
2 M=75;
3 //Turning angle of vane:
4 theta=60;
5 //Speed of water leaving nozzle horizontally(in m/
  sec):
6 V=35;
7 //Exit area of nozzle(in m^):
8 A=0.003;
9 //Density of water(in kg/m^3):
10 d=999;

```

Scilab code AP 61 data

```

1 //Vane turning angle:
2 theta=60;
3 //Speed of vane(in m/sec):
4 U=10;
5 //Area of nozzle(in m2):
6 A=0.003;
7 //Flow velocity of water(in m/sec):
8 V=30;
9 //Density of water(in kg/m^3):
10 d=999;

```

Scilab code AP 62 data

```

1 //Nozzle inlet diameter(in inchess):
2 D1=3;
3 //Nozzle exit diameter(in inches):
4 D2=1;
5 //Desired volume flow rate(in ft^3/sec):
6 Q=0.7;
7 //Density of water(in slug/ft^3):
8 d=1.94;

```

Scilab code AP 63 data

```
1 //Velocity of conveyer belt(in ft/sec):
2 Vbelt=3;
3 //Velocity of sand alling onto belt(in ft/sec):
4 Vsand=5;
5 //Flow rate(in lbm/sec):
6 m=500;
```

Scilab code AP 64 data

```
1 //Pressure at inlet tothe elbow(in N/m^2):
2 p1=2.21*10^5;
3 //Area of crossection(in m^2):
4 A1=0.01;
5 //Velocity at secton 2(in m/sec):
6 V2=16;
7 //Area of cross section of section 2(in m^2):
8 A2=0.0025;
9 //Atmospheric pressure(in kPa):
10 patm=1.012*10^5;
```

Scilab code AP 65 data

```
1 //Diameter of channel(in m):
2 D1=1.5;
3 //Velcity of flow in channel(in m/sec):
4 V1=0.2;
5 //Diameter at section 2(in m):
6 D2=0.0563;
7 //Velocity a section 2(in m/sec):
8 V2=5.33;
9 //Density of water(in kg/m^3):
10 d=999;
11 //Acceleration due to gravity(in m/sec2):
12 g=9.81;
```

Scilab code AP 66 data

```

1 //Height of the container(in ft):
2 l=2;
3 //Area of cross section(in ft^2):
4 A=1;
5 //Weight of container(in lbf):
6 W=5;
7 //Water depth (in ft):
8 h=1.9;
9 //Area of opening 1(in ft^2):
10 A1=0.1;
11 //Velocity at opening 1(in ft/sec):
12 V1=-5;
13 //Area of opening 2(in ft^2):
14 A2=0.1;
15 //Area of opening 1(in ft^2):
16 A3=0.1;
17 //Density of water(in slug/f^3):
18 d2=1.94;

```

Scilab code AP 67 data

```

1 //Velocity of water leaving the nozzle(in m/sec):
2 V=15;
3 //Area of nozzle(in m^2):
4 A=0.01;
5 //Density of water(in kg/m^3):
6 d=999;

```

Scilab code AP 68 data

```

1 //Volume of tank(in m^3):
2 V=0.05;
3 //Pressure of air(In kPa):
4 p=800;
5 //Temperature of tank(in C):
6 T=15;
7 //Velocity of leavig air(in m/sec):
8 v=311;

```

```
9 //Density of air(in kg/m^3):
10 d=6.13;
11 //Area ofvalve exit(in mm^2):
12 A=65;
```

Scilab code AP 69 data

```
1 //Flow velocity ahead of the plate(in m/sec):
2 U=30;
3 //Boundary layer tckness at location d(in mm):
4 t=5;
5 //Density of fluid air(in k/m^3):
6 d=1.24;
7 //Plate wdth perpendicular to the plate(in m):
8 w=0.6;
```

Scilab code AP 70 data

```
1 //Area of 1 (in ft^2):
2 A1=0.2;
3 //Area of 2 (in ft^2):
4 A2=0.5;
5 //Area of 3 (in ft^2):
6 A3=0.4;
7 //Area of 4 (in ft^2):
8 A4=0.4;
9 //Density of water (in slug/ft^3):
10 d=1.94;
11 //Mass flow rate out of section 3(in slug/sec):
12 m3=3.88;
13 //Volme flow rate in section 4 (in ft^3/sec):
14 Q4=1;
15 //Velocity at 1(in ft/sec):
16 V1=10;
```

Scilab code AP 71 data

```

1 //Width of gate(in m):
2 w=5;
3 //Depth of water(in m):
4 D=4;
5 //Density of water(in kg/m^3);
6 d=999;
7 //Accelration deto gravity(in m/sec^2):
8 g=9.81;
9 //Value of a (in m):
10 a=4;
11 //Point where force acts(in m):
12 l=5;

```

Scilab code AP 72 data

```

1 //Pressure apllied on the door(in psfg):
2 p0=100;
3 //Length of door(in feet):
4 L=3;
5 //Breadth of the door(in feet):
6 b=2;
7 //Density of liquiuid(in lbf/ft^3):
8 d=100;

```

Scilab code AP 73 data

```

1 //Length of gate(in m):
2 L=4;
3 //Width of gate(in m):
4 w=5;
5 //Depth of gate under water(in m):
6 D=2;
7 //Density of water(in kg/m^3:
8 d=999;
9 //Acceleration due to gravity(in m/sec^2):
10 g=9.81;
11 //Angle of gate with horizontal:
12 theta=30;

```

Scilab code AP 74 data

```
1 //Elevation of Denver(in ft):
2 z1=5280;
3 //Pressure at Denver(in mm of Hg):
4 p1=24.8;
5 //Temperature at Denver(in F):
6 T1=80;
7 //Elevation at Vail Pass(in ft):
8 z2=10600;
9 //Temperature at Vail Pass(in F):
10 T2=62;
11 //Value of R in ft-lbf/lbm-R):
12 R=53.3;
13 //Acceleration due to gravity(in ft/sec^2):
14 g=32.2;
15 //Value of adiabatic constant:
16 k=1.4;
```

Scilab code AP 75 data

```
1 //Acceleration due to gravity(in ft/sec^2):
2 g=32.2;
3 //Specific gravity of mercury:
4 SGm=13.6;
5 //Specific gravity of oil:
6 SGo=0.88;
7 //Specific gravity of water:
8 SGw=1;
9 //Density of water(in slug/ft^3):
10 d=1.94;
11 //Heights of liquid in various tubes(in inches):
12 d1=10;
13 d2=3;
14 d3=4;
15 d4=5;
```

16 d5=8;

Scilab code AP 76 data

```
1 //Surface tension of water(in mN/m):
2 STw=72.8*10^-3;
3 //Surface Tension of mercury(in mN/m):
4 STm=375*10^-3;
5 //Contact angle for water:
6 thetaw=0;
7 //COntact angle for mercury:
8 thetam=140;
9 //Density of water(in kg/m^3):
10 dw=1;
11 //Density of mercury(in kg/m^3):
12 dm=13.6;
13 //Acceleration de to gravity(in m/sec):
14 g=9.81;
```

Scilab code AP 77 data

```
1 //Liquid Viscosity(in cp):
2 u=0.65;
3 //Specific gravity:
4 SG=0.88;
5 //Density of water(in slug/ft^3):
6 d=1.94;
7 //Velocity with which plate is moved(in m/sec):
8 U=0.3;
9 //Distance between the plates(in mm):
10 D=0.3;
```

Scilab code AP 78 data

```
1 //Mass of ball(in kg):
2 m=0.2;
3 //Height fom which ball is dropped(in m):
```

```
4 y0=500;
5 //Value of k:
6 k=2*10^-4;
7 //Accleration due to gravity(in m/sec^2):
8 g=9.81;
```

Scilab code AP 79 data

```
1 //Mass of oxygen present(in kg):
2 m=0.95;
3 //Initial temperatur(in K):
4 T1=300;
5 //Final temperature of oxygen(in K):
6 T2=900;
7 //Pressure of oxygen(in kPa):
8 p=150;
9 //Specific heat at constant pressure(in J/kg-K):
10 cp=909.4;
```
